

# FCC Radio Test Report

## FCC ID: 2AH4HATD600

This report concerns: Original Grant

**Project No.** : 2107C193  
**Equipment** : LTE Cat-M1 Tracker  
**Brand Name** : Mobilogix  
**Test Model** : ATD600S  
**Series Model** : N/A  
**Applicant** : Mobilogix, Inc.  
**Address** : 5500 Trabuco Rd Suite 150 Irvine, CA, USA  
**Manufacturer** : Mobilogix, Inc.  
**Address** : 5500 Trabuco Rd Suite 150 Irvine, CA, USA  
**Factory** : Suga Electronics (Dongguan) Co., Ltd.  
**Address** : No.8 Fulong Road, Qingxi Town, Dongguan City  
**Date of Receipt** : Jul. 29, 2021  
**Date of Test** : Jul. 30, 2021 ~ Sep. 10, 2021  
**Issued Date** : Sep. 18, 2021  
**Report Version** : R00  
**Test Sample** : Engineering Sample No.: DG2021081225 for radiated, DG2021081224 for conducted.  
**Standard(s)** : 47 CFR FCC Part 90 Subpart S  
                   47 CFR FCC Part 2  
                   ANSI/TIA/EIA-603-E-2016  
                   FCC KDB 971168 D01 Power Meas License Digital Systems v03r01

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

*Vegeta Li*

Prepared by : Vegeta Li

*Steven Lu*

Approved by : Steven Lu



TESTING CERT #5123.02

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China

Tel: +86-769-8318-3000

Web: www.newbtl.com

**Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

**BTL** is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

**Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and is not use in determining the Pass/Fail results.

<b>Table of Contents</b>	<b>Page</b>
<b>REPORT ISSUED HISTORY</b>	<b>5</b>
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>6</b>
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST ENVIRONMENT CONDITIONS	7
<b>2 . GENERAL INFORMATION</b>	<b>8</b>
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATIONOFSYSTEMTESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS	10
<b>3 . TEST RESULT</b>	<b>11</b>
3.1 OUTPUT POWER MEASUREMENT	11
3.1.1 LIMIT	11
3.1.2 TEST PROCEDURE	11
3.1.3 TEST SETUP LAYOUT	11
3.1.4 TEST DEVIATION	11
3.1.5 TEST RESULTS	11
3.2 OCCUPIED BANDWIDTH MEASUREMENT	12
3.2.1 TEST PROCEDURE	12
3.2.2 TEST SETUP LAYOUT	12
3.2.3 TEST DEVIATION	12
3.2.4 TEST RESULTS	12
3.3 CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	13
3.3.1 LIMIT	13
3.3.2 TEST PROCEDURES	13
3.3.3 TEST SETUP LAYOUT	13
3.3.4 TEST DEVIATION	13
3.3.5 TEST RESULTS	13
3.4 RADIATED SPURIOUS EMISSIONS MEASUREMENT	14
3.4.1 LIMIT	14
3.4.2 TEST PROCEDURES	14
3.4.3 TEST SETUP LAYOUT	15
3.4.4 TEST DEVIATION	16
3.4.5 TEST RESULTS (9KHZ TO 30MHZ)	16
3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)	16
3.4.7 TEST RESULTS (ABOVE 1000MHZ)	16
3.5 MASK MEASUREMENTS	17
3.5.1 LIMIT	17

<b>Table of Contents</b>	<b>Page</b>
3.5.2 TEST PROCEDURES	17
3.5.3 TEST SETUP LAYOUT	17
3.5.4 TEST DEVIATION	17
3.5.5 TEST RESULTS	17
3.6 PEAK TO AVERAGE RATIO MEASUREMENT	18
3.6.1 LIMIT	18
3.6.2 TEST PROCEDURES	18
3.6.3 TEST SETUP LAYOUT	18
3.6.4 TEST DEVIATION	18
3.6.5 TEST RESULTS	18
3.7 FREQUENCY STABILITY MEASUREMENT	19
3.7.1 LIMIT	19
3.7.2 TEST PROCEDURES	19
3.7.3 TEST SETUP LAYOUT	19
3.7.4 TEST DEVIATION	19
3.7.5 TEST RESULTS	19
4 . LIST OF MEASUREMENT EQUIPMENTS	20
APPENDIX A - OUTPUT POWER	22
APPENDIX B - OCCUPIED BANDWIDTH	25
APPENDIX C - CONDUCTED SPURIOUS EMISSIONS	33
APPENDIX D - RADIATED SPURIOUS EMISSIONS (9KHZ TO 30MHZ)	37
APPENDIX E - RADIATED SPURIOUS EMISSIONS (30MHZ TO 1000MHZ)	42
APPENDIX F - RADIATED SPURIOUS EMISSIONS (ABOVE 1000MHZ)	49
APPENDIX G - MASK	56
APPENDIX H - PEAK TO AVERAGE RATIO	61
APPENDIX I - FREQUENCY STABILITY	66

**REPORT ISSUED HISTORY**

Report Version	Description	Issued Date
R00	Original Issue.	Sep. 18, 2021

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part 90 Subpart S & Part 2			
Standard(s) Section	Test Item	Judgment	Remark
2.1046 & 90.635 (b)	Output Power & Effective Radiated Power	PASS	-----
2.1049 & 90.209	Occupied Bandwidth	PASS	-----
2.1053 & 90.669	Conducted Spurious Emissions	PASS	-----
2.1053 & 90.669	Radiated Spurious Emissions	PASS	-----
2.1053 & 90.691	Mask Measurements	PASS	-----
-	Peak To Average Ratio	PASS	Record Only
2.1055 & 90.213	Frequency Stability	PASS	-----

Note:

(1) "N/A" denotes test is not applicable in this test report.

## 1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China.

BTL's Test Firm Registration Number for FCC: 357015

BTL's Designation Number for FCC: CN1240

## 1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

The BTL measurement uncertainty as below table:

### A. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
DG-CB03	CISPR	9kHz ~ 30MHz	-	2.36
		30MHz ~ 200MHz	V	4.36
		30MHz ~ 200MHz	H	3.32
		200MHz ~ 1,000MHz	V	4.08
		200MHz ~ 1,000MHz	H	3.96
		1GHz ~ 6GHz	-	3.80
		6GHz ~ 18GHz	-	4.82

### B. Other Measurement:

Parameter	Uncertainty
Spectrum Bandwidth	±3.8 %
Maximum Output Power	±0.95 dB
Power Spectral Density	±0.86 dB
Frequency Stability	±0.16 dB
Temperature	±0.08 °C
Time	±0.58 %
Supply voltages	±0.3 %

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

## 1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
Output Power & ERP	23.5°C	43%	DC 3.6 V	Tate Liu
Occupied Bandwidth	23.5°C	43%	DC 3.6 V	Tate Liu
Conducted Spurious Emissions	23.5°C	43%	DC 3.6 V	Tim Yang
Radiated Spurious Emissions	26°C	52%	DC 3.6 V	Kwok Guo
Band Edge	23.5°C	43%	DC 3.6 V	Tate Liu
Peak to Average Ratio	23.5°C	43%	DC 3.6 V	Tate Liu
Frequency Stability	Normal & Extreme	43%	Normal & Extreme	Tate Liu

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	LTE Cat-M1 Tracker			
Brand Name	Mobilogix			
Test Model	ATD600S			
Series Model	N/A			
Model Difference(s)	N/A			
Hardware Version	1.1			
Software Version	1.1.45			
Power Source	Supplied from battery.			
Power Rating	DC 3.6V			
IEMI No.	Conducted	867730051961021		
	Radiated	867730051961708		
LTE Category	M1			
Modulation Type	UL: QPSK,16QAM DL: QPSK,16QAM			
Max. ERP	LTE	Channel Bandwidth (MHz)	QPSK (dBm)	16QAM (dBm)
	Band 26	1.4	19.43	18.50
		3	19.16	18.24
		5	19.49	18.90
		10	19.08	19.39

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

#### 2. Channel List:

LTE Band 26					
Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink (MHz)	N <sub>DL</sub>	Frequency of Downlink (MHz)
Low Range	1.4	26697	814.7	8697	859.7
	3	26705	815.5	8705	860.5
	5	26715	816.5	8715	861.5
Mid Range	1.4/3/5/10	26740	819	8740	864
High Range	1.4	26783	823.3	8783	868.3
	3	26775	822.5	8775	867.5
	5	26765	821.5	8765	866.5

#### 3. Table for Filed Antenna:

Brand	P/N	Antenna Type	Connector	Gain (dBi)	Note
Ethertronics	1004795	Chip	N/A	1.6	LTE Band 26

Note: The antenna gain is provided by the manufacturer.



## 2.2 DESCRIPTION OF TEST MODES

Following mode(s) is (were) found to be the worst case(s) and selected for the final test.

LTE BAND 26 MODE					
Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
Output Power & ERP	26697 to 26783	26697, 26740, 26783	1.4MHz	QPSK, 16QAM	1RB/6RB
	26705 to 26775	26705, 26740, 26775	3MHz	QPSK, 16QAM	1RB/6RB
	26715 to 26765	26715, 26740, 26765	5MHz	QPSK, 16QAM	1RB/6RB
	26740	26740	10MHz	QPSK, 16QAM	1RB/4RB
Occupied Bandwidth	26697 to 26783	26697, 26740, 26783	1.4MHz	QPSK, 16QAM	6RB
	26705 to 26775	26705, 26740, 26775	3MHz	QPSK, 16QAM	6RB
	26715 to 26765	26715, 26740, 26765	5MHz	QPSK, 16QAM	6RB
	26740	26740	10MHz	QPSK, 16QAM	6RB
Conducted Spurious Emissions	26697 to 26783	26740	1.4MHz	QPSK	1RB
	26705 to 26775	26740	5MHz	QPSK	1RB
	26715 to 26765	26740	10MHz	QPSK	1RB
Radiated Spurious Emissions	26697 to 26783	26740	1.4MHz	QPSK	1RB
	26705 to 26775	26740	5MHz	QPSK	1RB
	26715 to 26765	26740	10MHz	QPSK	1RB
Mask	26697 to 26783	26697, 26783	1.4MHz	QPSK	1RB/6RB
	26705 to 26775	26705, 26775	3MHz	QPSK	1RB/6RB
	26715 to 26765	26715, 26765	5MHz	QPSK	1RB/6RB
	26740	26740	10MHz	QPSK	1RB/6RB
Peak To Average Ratio	26697 to 26783	26697, 26740, 26783	1.4MHz	QPSK, 16QAM	1RB
	26705 to 26775	26705, 26740, 26775	3MHz	QPSK, 16QAM	1RB
	26715 to 26765	26715, 26740, 26765	5MHz	QPSK, 16QAM	1RB
	26740	26740	10MHz	QPSK, 16QAM,	1RB
Frequency Stability	26697 to 26783	26740	1.4MHz	QPSK	1RB
	26705 to 26775	26740	3MHz	QPSK	1RB
	26715 to 26765	26740	5MHz	QPSK	1RB
	26740	26740	10MHz	QPSK	1RB

## 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATIONOFSYSTEMTESTED



## 2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model No.	Series No.
-	-	-	-	-

Item	Cable Type	Shielded Type	Ferrite Core	Length
-	-	-	-	-

### 3. TEST RESULT

#### 3.1 OUTPUT POWER MEASUREMENT

##### 3.1.1 LIMIT

Mobile / Portable station are limited to 100 watts e.r.p.

##### 3.1.2 TEST PROCEDURE

The testing follows FCC KDB 971168 v03r01 Section 5.0.

##### ERP:

$EIRP = \text{Output Power} + \text{Antenan gain}$


$ERP = EIPR - 2.15dBi$ .

##### Output Power:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA, CDMA, and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

##### 3.1.3 TEST SETUP LAYOUT

##### Output Power Measurement



##### 3.1.4 TEST DEVIATION

No deviation

##### 3.1.5 TEST RESULTS

Please refer to the APPENDIX A.


## 3.2 OCCUPIED BANDWIDTH MEASUREMENT

### 3.2.1 TEST PROCEDURE

The testing follows FCC KDB 971168 v03r01 Section 4.0.

1. The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth and 26dB bandwidth.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3.  $RBW = (1\% \sim 5\%) * EBW$   
 $VBW \geq 3 * RBW$
4. Set spectrum analyzer with RMS detector.

### 3.2.2 TEST SETUP LAYOUT



### 3.2.3 TEST DEVIATION

No deviation

### 3.2.4 TEST RESULTS

Please refer to the APPENDIX B.

### 3.3 CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

#### 3.3.1 LIMIT


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to -13dBm.

#### 3.3.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 6.0.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Set RBW  $\geq 1\%$  EBW in the 1MHz band immediately outside and adjacent to the band edge.
3. Set spectrum analyzer with RMS detector.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### 3.3.3 TEST SETUP LAYOUT



#### 3.3.4 TEST DEVIATION

No deviation

#### 3.3.5 TEST RESULTS

Please refer to the APPENDIX C.

### **3.4 RADIATED SPURIOUS EMISSIONS MEASUREMENT**

#### **3.4.1 LIMIT**

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to -13dBm.


#### **3.4.2 TEST PROCEDURES**

The testing follows FCC KDB 971168 v03r01 Section 5.8.


1. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
2. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
3.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
4. ERP can be calculated form EIRP by subtracting the gain of dipole,  $ERP = EIPR - 2.15\text{dBi}.$
5. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.


### 3.4.3 TEST SETUP LAYOUT

#### Below 30MHz



#### 30MHz to 1000MHz





### 3.4.4 TEST DEVIATION

No deviation

### 3.4.5 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the APPENDIX D.

### 3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the APPENDIX E.

### 3.4.7 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the APPENDIX F.



## 3.5 MASK MEASUREMENTS

### 3.5.1 LIMIT


According to FCC part 90.691 shall be tested the emission mask. For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $116 \log_{10}(f/6.1)$  decibels or  $50 + 10 \log_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz. For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

### 3.5.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 6.0.

1. All measurements were done at low and high operational frequency range.
2. Set RBW=1% of 26dBc bandwidth, VBW=3 X RBW, detector=RMS, Sweep time = Auto. For Section 90.691(a) compliance testing, use RBW = 300 Hz for offsets less than 37.5 kHz from a channel edge; RBW = 100 kHz for offsets greater than 37.5 kHz is allowed.
3. Record the max trace plot into the test report.

### 3.5.3 TEST SETUP LAYOUT



### 3.5.4 TEST DEVIATION

No deviation

### 3.5.5 TEST RESULTS

Please refer to the APPENDIX G.

### 3.6 PEAK TO AVERAGE RATIO MEASUREMENT

#### 3.6.1 LIMIT


In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

#### 3.6.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 5.7.

1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

#### 3.6.3 TEST SETUP LAYOUT



#### 3.6.4 TEST DEVIATION

No deviation

#### 3.6.5 TEST RESULTS

Please refer to the APPENDIX H.

### 3.7 FREQUENCY STABILITY MEASUREMENT

#### 3.7.1 LIMIT


$\pm 1.5$  ppm is for base and fixed station.  $\pm 2.5$  ppm is for mobile station.

#### 3.7.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 9.0.

1. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
2. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
3. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^{\circ}\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.
4. The frequency error was recorded frequency error from the communication simulator.

#### 3.7.3 TEST SETUP LAYOUT



#### 3.7.4 TEST DEVIATION

No deviation

#### 3.7.5 TEST RESULTS

Please refer to the APPENDIX I.

#### 4. LIST OF MEASUREMENT EQUIPMENTS

Radiated Spurious Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarzbeck	VULB9160	9160-3232	Mar. 15, 2022
2	Amplifier	Agilent	8449B	3008A02334	Feb. 27, 2022
3	High Pass Filter	Wairwright Instruments Gmbh	WHK 1.5/15G-10ST	11	Feb. 27, 2022
4	Band Reject Filter	Wairwright Instruments Gmbh	WRCG 1710/1785-1690/1805-60/ 12SS	38	Feb. 27, 2022
5	Band Reject Filter	Wairwright Instruments Gmbh	WRCG 824/849-810/863-60/9SS	7	Feb. 27, 2022
6	Band Reject Filter	Wairwright Instruments Gmbh	WRCG 880/915-860/935-60/9SS	14	Feb. 27, 2022
7	Band Reject Filter	Wairwright Instruments Gmbh	WRCG 1850/1910-1830/1930-60/ 10SS	17	Feb. 27, 2022
8	High Pass Filter	Wairwright Instruments Gmbh	WHK3.1/18G-10SS	24	Feb. 27, 2022
9	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Feb. 28, 2022
10	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Feb. 28, 2022
11	Receiver	Agilent	N9038A	MY52130039	Mar. 19, 2022
12	wideband radio communication tester	R&S	CMW500	152372	Feb. 27, 2022
13	High pass filter	KANGMAIWEI	ZHPF-M3-12.75G-3869	B2015073763	Feb. 07, 2022
14	High pass filter	KANGMAIWEI	ZHPF-M1000-4000-1	B2015073762	Feb. 07, 2022
15	High pass filter	KANGMAIWEI	ZHPF-M6-186-1727	B2015073764	Feb. 07, 2022
16	Cable	emci	LMR-400(30MHz-1GHz) (8m+5m)	N/A	May 20, 2022
17	Cable	mitron	RWLP50-4.0A-KJ-SMSM-12M	N/A	Nov. 23, 2021
18	Controller	ETS-Lindgren	2090	N/A	N/A
19	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
20	Loop Antenna	EM	EM-6876-1	230	Apr. 28, 2022
21	Double Ridged Guide Antenna	ETS	3115	75846	Mar. 17, 2022
22	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Jun. 30, 2022

Conducted Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Feb. 28, 2022
2	EXA Spectrum Analyzer	Agilent	N9010A	MY50520044	Feb. 28, 2022
3	POWER SPLITTER	Mini-Circuits	ZFRSC-123-S+	331000910-1	Feb. 27, 2022
4	wideband radio communication tester	R&S	CMW500	152372	Feb. 27, 2022

Frequency Stability Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Feb. 28, 2022
2*	Multi-output DC Power Supply	GW Instek	GPC-3030DN	EK880675	Jul. 25, 2023
3	POWER SPLITTER	Mini-Circuits	ZFRSC-123-S+	331000910-1	Feb. 27, 2022
4	wideband radio communication tester	R&S	CMW500	152372	Feb. 27, 2022
5	Const Temp,& Humidity Chamber	Bell	BTH-50C	20170306001	Feb. 27, 2022

Remark: "N/A" denotes no model name, serial no. or calibration specified.

"\*\*" calibration period of equipment list is three year.

Except \* item, all calibration period of equipment list is one year.

## **APPENDIX A - OUTPUT POWER**

**Output Power (dBm):**

LTE Band / BW	Channel / Frequency (MHz)	RB Size	RB Offset	Index	Conducted Power (dBm)	
					QPSK	16QAM
26 / 1.4M	26697 / 814.7	1	0	0	19.63	19.05
		6	0	0	18.33	18.26
	26740 / 819	1	0	0	19.80	18.58
		6	0	0	18.35	18.20
	26783 / 823.3	1	5	0	19.98	18.82
		6	0	0	18.35	18.39
26 / 3M	26705 / 815.5	1	0	0	19.71	18.79
		6	0	0	18.31	18.07
	26740 / 819	1	0	0	19.68	18.55
		6	0	0	18.34	18.19
	26775 / 822.5	1	5	1	19.61	18.45
		6	0	1	18.35	18.19
26 / 5M	26715 / 816.5	1	0	3	20.04	19.45
		6	0	0	18.49	18.60
	26740 / 819	1	0	0	19.98	19.43
		6	0	0	18.56	18.67
	26765 / 821.5	1	5	0	19.81	19.40
		6	0	3	18.46	18.65
26 / 10M	26740 / 819	1	0	0	19.49	19.94
		4	0	0	19.63	19.58

**ERP (dBm):**


LTE Band / BW	Channel / Frequency (MHz)	RB Size	RB Offset	Index	Conducted Power (dBm)	
					QPSK	16QAM
26 / 1.4M	26797 / 824.7	1	0	0	19.08	18.50
		6	0	0	17.78	17.71
	26915 / 836.5	1	0	0	19.25	18.03
		6	0	0	17.80	17.65
	27033 / 848.3	1	5	0	19.43	18.27
		6	0	0	17.80	17.84
26 / 3M	26805 / 825.5	1	0	0	19.16	18.24
		6	0	0	17.76	17.52
	26915 / 836.5	1	0	0	19.13	18.00
		6	0	0	17.79	17.64
	27025 / 847.5	1	5	1	19.06	17.90
		6	0	1	17.80	17.64
26 / 5M	26815 / 826.5	1	0	3	19.49	18.90
		6	0	0	17.94	18.05
	26915 / 836.5	1	0	0	19.43	18.88
		6	0	0	18.01	18.12
	27015 / 846.5	1	5	0	19.26	18.85
		6	0	3	17.91	18.10
26 / 10M	26840 / 829	1	0	0	18.94	19.39
		4	0	0	19.08	19.03
	26915 / 836.5	1	0	0	19.08	18.50
		6	0	0	17.78	17.71
	26990 / 844	1	0	0	19.25	18.03
		6	0	0	17.80	17.65
26 / 15M	26865 / 831.5	1	5	0	19.43	18.27
		6	0	0	17.80	17.84



## **APPENDIX B - OCCUPIED BANDWIDTH**


LTE Band 26_1.4M					
QPSK					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
26697	814.7	1.0900	26697	814.7	1.276
26740	819	1.0918	26740	819	1.285
26783	823.3	1.0908	26783	823.3	1.292
16QAM					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
26697	814.7	0.9190	26697	814.7	1.100
26740	819	1.0928	26740	819	1.172
26783	823.3	0.9143	26783	823.3	1.096

## Spectrum Plot



LTE Band 26_3M					
QPSK					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
26705	815.5	1.1275	26705	815.5	1.256
26740	819	1.1143	26740	819	1.550
26775	822.5	1.1108	26775	822.5	1.332
16QAM					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
26705	815.5	0.9635	26705	815.5	1.192
26740	819	0.9481	26740	819	1.157
26775	822.5	0.9700	26775	822.5	1.329

## Spectrum Plot




LTE Band 26_5M					
QPSK					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
26715	816.5	1.1708	26715	816.5	1.471
26740	819	1.1737	26740	819	1.498
26765	821.5	1.1751	26765	821.5	1.479
16QAM					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
26715	816.5	1.0160	26715	816.5	1.281
26740	819	1.0251	26740	819	1.324
26765	821.5	1.0238	26765	821.5	1.293

## Spectrum Plot





LTE Band 26_10M					
QPSK					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
26740	819	1.3299	26740	819	2.226
16QAM					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
26740	819	1.1792	26740	819	1.624






## **APPENDIX C - CONDUCTED SPURIOUS EMISSIONS**








## **APPENDIX D - RADIATED SPURIOUS EMISSIONS (9KHZ TO 30MHZ)**

Test Mode	TX Mode
-----------	---------


Ant 0°



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	0.0180	45.65	13.84	59.49	122.50	-63.01	AVG		
2		0.0900	27.48	12.66	40.14	108.52	-68.38	AVG		
3		0.1263	29.68	12.73	42.41	105.58	-63.17	AVG		

Test Mode	TX Mode
-----------	---------


Ant 0°



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.4374	48.25	12.17	60.42	94.79	-34.37	AVG		
2	*	2.2367	36.79	11.19	47.98	69.54	-21.56	QP		
3		4.3606	34.85	11.00	45.85	69.54	-23.69	QP		

Test Mode	TX Mode
-----------	---------

Ant 90°




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	0.0177	44.51	13.93	58.44	122.65	-64.21	AVG		
2		0.0780	26.89	12.59	39.48	109.76	-70.28	AVG		
3		0.1344	26.43	12.73	39.16	105.04	-65.88	AVG		



Test Mode	TX Mode
-----------	---------


Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.4468	43.83	12.14	55.97	94.60	-38.63	AVG		
2	*	1.9906	32.57	11.31	43.88	69.54	-25.66	QP		
3		3.7198	30.49	10.91	41.40	69.54	-28.14	QP		


## **APPENDIX E - RADIATED SPURIOUS EMISSIONS (30MHZ TO 1000MHZ)**

Test Mode	LTE Band 26_TX CH26740_1.4M
-----------	-----------------------------



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1		106.630	-63.71	-15.60	-79.31	-13.00	-66.31	peak	
2		169.680	-64.76	-12.64	-77.40	-13.00	-64.40	peak	
3		334.580	-64.59	-10.38	-74.97	-13.00	-61.97	peak	
4		574.170	-63.18	-5.54	-68.72	-13.00	-55.72	peak	
5		740.040	-63.17	-2.36	-65.53	-13.00	-52.53	peak	
6	*	876.810	-63.50	-0.27	-63.77	-13.00	-50.77	peak	


Test Mode	LTE Band 26_TX CH26740_1.4M
-----------	-----------------------------



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		MHz	Level	Factor	ment			Detector	Comment
			dBm	dB	dBm	dBm	dB		
1		62.980	-62.50	-14.92	-77.42	-13.00	-64.42	peak	
2		175.500	-64.20	-13.23	-77.43	-13.00	-64.43	peak	
3		267.650	-63.31	-12.36	-75.67	-13.00	-62.67	peak	
4		466.500	-63.35	-7.34	-70.69	-13.00	-57.69	peak	
5		722.580	-61.95	-2.77	-64.72	-13.00	-51.72	peak	
6	*	930.160	-63.73	1.09	-62.64	-13.00	-49.64	peak	

Test Mode	LTE Band 26_TX CH26740_5M
-----------	---------------------------


## Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		76.560	-59.02	-17.67	-76.69	-13.00	-63.69	peak	
2		249.220	-64.52	-13.06	-77.58	-13.00	-64.58	peak	
3		377.260	-63.54	-9.47	-73.01	-13.00	-60.01	peak	
4		564.470	-62.51	-5.79	-68.30	-13.00	-55.30	peak	
5		801.150	-63.43	-0.84	-64.27	-13.00	-51.27	peak	
6	*	996.120	-63.45	1.76	-61.69	-13.00	-48.69	peak	

Test Mode	LTE Band 26_TX CH26740_5M
-----------	---------------------------


## Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1		45.520	-62.36	-13.92	-76.28	-13.00	-63.28	peak	
2		167.740	-62.84	-12.60	-75.44	-13.00	-62.44	peak	
3		248.250	-64.07	-13.10	-77.17	-13.00	-64.17	peak	
4		433.520	-63.08	-8.05	-71.13	-13.00	-58.13	peak	
5		660.500	-62.32	-3.85	-66.17	-13.00	-53.17	peak	
6	*	836.070	-63.31	-0.79	-64.10	-13.00	-51.10	peak	


Test Mode	LTE Band 26_TX CH26740_10M
-----------	----------------------------

## Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		78.500	-59.21	-18.07	-77.28	-13.00	-64.28	peak	
2		244.370	-63.08	-13.28	-76.36	-13.00	-63.36	peak	
3		417.030	-64.44	-8.49	-72.93	-13.00	-59.93	peak	
4		594.540	-62.55	-4.99	-67.54	-13.00	-54.54	peak	
5		770.110	-62.67	-1.61	-64.28	-13.00	-51.28	peak	
6	*	975.750	-64.43	1.73	-62.70	-13.00	-49.70	peak	

Test Mode	LTE Band 26_TX CH26740_10M
-----------	----------------------------




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1		62.980	-62.47	-14.92	-77.39	-13.00	-64.39	peak	
2		157.070	-63.34	-12.51	-75.85	-13.00	-62.85	peak	
3		322.940	-63.67	-10.59	-74.26	-13.00	-61.26	peak	
4		452.920	-62.90	-7.57	-70.47	-13.00	-57.47	peak	
5		684.750	-63.25	-3.51	-66.76	-13.00	-53.76	peak	
6	*	776.900	-63.18	-1.43	-64.61	-13.00	-51.61	peak	



## **APPENDIX F - RADIATED SPURIOUS EMISSIONS (ABOVE 1000MHZ)**


Test Mode	LTE Band 26_TX CH26740_1.4M
-----------	-----------------------------



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	7018.000	-62.16	10.31	-51.85	-13.00	-38.85	peak	

Test Mode	LTE Band 26_TX CH26740_1.4M
-----------	-----------------------------


## Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	4893.000	-59.90	5.58	-54.32	-13.00	-41.32	peak	


Test Mode	LTE Band 26_TX CH26740_5M
-----------	---------------------------

## Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	7222.000	-61.48	10.57	-50.91	-13.00	-37.91	peak	


Test Mode	LTE Band 26_TX CH26740_5M
-----------	---------------------------



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	5947.000	-60.34	6.93	-53.41	-13.00	-40.41	peak	


Test Mode	LTE Band 26_TX CH26740_10M
-----------	----------------------------

## Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	3805.000	-58.87	2.43	-56.44	-13.00	-43.44	peak	

Test Mode	LTE Band 26_TX CH26740_10M
-----------	----------------------------



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	4315.000	-58.69	3.37	-55.32	-13.00	-42.32	peak	

## **APPENDIX G - MASK**



## LTE Band 26\_1.4M

1RB#0



1RB#5

Channel

26697

Channel

26783





## 6RB#0

Channel


26697


Channel

26783











## APPENDIX H - PEAK TO AVERAGE RATIO

## LTE Band 26\_1.4M Spectrum Plot


## QPSK-26697




## QPSK-26740




## QPSK-26783




## 16QAM-26697



## 16QAM-26740




## 16QAM-26783




## LTE Band 26\_3M Spectrum Plot


### QPSK-26705




### QPSK-26740




### QPSK-26775




### 16QAM-26705



### 16QAM-26740



### 16QAM-26775




## LTE Band 26\_5M Spectrum Plot


### QPSK-26715




### QPSK-26740




### QPSK-26765




### 16QAM-26715



### 16QAM-26740



### 16QAM-26765






# LTE Band 26\_10M Spectrum Plot

## QPSK-26740

## 16QAM-26740



## **APPENDIX I - FREQUENCY STABILITY**

Test Mode	LTE Band 26_CH26740_1.4M
-----------	--------------------------

#### Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-30	9.78	0.011941392	±2.5
-20	-0.46	-0.000561661	
-10	9.50	0.011599512	
0	-3.96	-0.004835165	
10	1.25	0.001526252	
20	3.88	0.004737485	
30	-9.29	-0.011343101	
40	8.15	0.00995116	
50	7.50	0.009157509	
Max. Deviation (ppm)	9.5	0.011599512	

#### Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
3.8	2.70	0.003296703	±2.5
3.6	-1.71	-0.002087912	
2.0	4.82	0.005885226	
Max. Deviation (ppm)	4.82	0.005885226	

Test Mode	LTE Band 26_CH26740_3M
-----------	------------------------

#### Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-30	4.31	0.005262515	±2.5
-20	-1.32	-0.001611722	
-10	1.69	0.002063492	
0	6.71	0.008192918	
10	1.45	0.001770452	
20	-3.81	-0.004652015	
30	6.13	0.007484737	
40	7.59	0.009267399	
50	1.35	0.001648352	
Max. Deviation (ppm)	7.59	0.009267399	

#### Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
3.8	4.98	0.006080586	±2.5
3.6	7.02	0.008571429	
2.0	-6.79	-0.008290598	
Max. Deviation (ppm)	7.02	0.008571429	

Test Mode	LTE Band 26_CH26740_5M
-----------	------------------------

#### Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-30	8.78	0.010720391	±2.5
-20	-9.14	-0.011159951	
-10	8.59	0.0104884	
0	6.73	0.008217338	
10	2.84	0.003467643	
20	-5.59	-0.006825397	
30	0.95	0.001159951	
40	-6.02	-0.007350427	
50	-9.24	-0.011282051	
Max. Deviation (ppm)	-9.24	-0.011282051	

#### Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
3.8	7.62	0.009304029	±2.5
3.6	-4.22	-0.005152625	
2.0	-1.31	-0.001599512	
Max. Deviation (ppm)	7.62	0.009304029	

Test Mode	LTE Band 26_CH26740_10M
-----------	-------------------------

#### Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-30	9.39	0.011465201	±2.5
-20	9.91	0.012100122	
-10	-1.75	-0.002136752	
0	-4.24	-0.005177045	
10	-0.89	-0.001086691	
20	-1.49	-0.001819292	
30	0.96	0.001172161	
40	8.55	0.01043956	
50	0.11	0.00013431	
Max. Deviation (ppm)	9.91	0.012100122	

#### Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
3.8	8.62	0.010525031	±2.5
3.6	-5.23	-0.006385836	
2.0	3.88	0.004737485	
Max. Deviation (ppm)	8.62	0.010525031	

End of Test Report