

FCC TEST REPORT (15.247)

REPORT NO.: RF130802E06A R1

MODEL NO.: RE4000W

FCC ID: Q87-RE4000W

RECEIVED: Aug. 02, 2013

TESTED: Aug. 07 to 14, 2013

ISSUED: Mar. 11, 2014

APPLICANT: Linksys LLC

ADDRESS: 131 Theory Drive, Irvine, CA 92617, USA

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by TAF
or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



A D T

Table of Contents

RELEASE CONTROL RECORD.....	6
1. CERTIFICATION.....	7
2. SUMMARY OF TEST RESULTS.....	8
2.1 MEASUREMENT UNCERTAINTY	9
3. GENERAL INFORMATION	10
3.1 GENERAL DESCRIPTION OF EUT.....	10
3.2 DESCRIPTION OF TEST MODES.....	12
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	13
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	17
3.4 DESCRIPTION OF SUPPORT UNITS.....	18
3.5 CONFIGURATION OF SYSTEM UNDER TEST	19
4. TEST TYPES AND RESULTS (For 2.4GHz, 2412 ~ 2462MHz Band)	20
4.1 CONDUCTED EMISSION MEASUREMENT	20
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	20
4.1.2 TEST INSTRUMENTS	20
4.1.3 TEST PROCEDURES.....	21
4.1.4 DEVIATION FROM TEST STANDARD	21
4.1.5 TEST SETUP	22
4.1.6 EUT OPERATING CONDITIONS.....	22
4.1.7 TEST RESULTS (MODE 1).....	23
4.1.8 TEST RESULTS (MODE 2).....	25
4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT	27
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT ...	27
4.2.2 TEST INSTRUMENTS	28
4.2.3 TEST PROCEDURES.....	30
4.2.4 DEVIATION FROM TEST STANDARD	30
4.2.5 TEST SETUP	31
4.2.6 EUT OPERATING CONDITIONS.....	31
4.2.7 TEST RESULTS.....	32
4.3 6dB BANDWIDTH MEASUREMENT	45
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	45
4.3.2 TEST INSTRUMENTS	45
4.3.3 TEST PROCEDURE	45
4.3.4 DEVIATION FROM TEST STANDARD	45
4.3.5 TEST SETUP	45
4.3.6 EUT OPERATING CONDITIONS.....	45
4.3.7 TEST RESULTS.....	46



A D T

4.4	CONDUCTED OUTPUT POWER MEASUREMENT	47
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	47
4.4.2	INSTRUMENTS	47
4.4.3	TEST PROCEDURES	47
4.4.4	DEVIATION FROM TEST STANDARD	48
4.4.5	TEST SETUP	48
4.4.6	EUT OPERATING CONDITIONS	48
4.4.7	TEST RESULTS	49
4.5	AVERAGE OUTPUT POWER	50
4.5.1	FOR REFERENCE	50
4.5.2	TEST INSTRUMENTS	50
4.5.3	TEST PROCEDURES	50
4.5.4	TEST SETUP	50
4.5.5	EUT OPERATING CONDITIONS	50
4.5.6	TEST RESULTS	51
4.6	POWER SPECTRAL DENSITY MEASUREMENT	52
4.6.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	52
4.6.2	TEST INSTRUMENTS	52
4.6.3	TEST PROCEDURE	52
4.6.4	DEVIATION FROM TEST STANDARD	52
4.6.5	TEST SETUP	52
4.6.6	EUT OPERATING CONDITION	52
4.6.7	TEST RESULTS	53
4.7	CONDUCTED OUT-BAND EMISSION MEASUREMENT	54
4.7.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT	54
4.7.2	TEST INSTRUMENTS	54
4.7.3	TEST PROCEDURE	54
4.7.4	DEVIATION FROM TEST STANDARD	55
4.7.5	TEST SETUP	55
4.7.6	EUT OPERATING CONDITION	55
4.7.7	TEST RESULTS	55
5.	TEST TYPES AND RESULTS (For 5GHz, 5725~5850MHz Band)	62
5.1	CONDUCTED EMISSION MEASUREMENT	62
5.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	62
5.1.2	TEST INSTRUMENTS	62
5.1.3	TEST PROCEDURES	63
5.1.4	DEVIATION FROM TEST STANDARD	63
5.1.5	TEST SETUP	63
5.1.6	EUT OPERATING CONDITIONS	64



A D T

5.1.7	TEST RESULTS (MODE 1).....	65
5.1.8	TEST RESULTS (MODE 2).....	67
5.2	RADIATED AND BANDEDGE EMISSION MEASUREMENT	69
5.2.1	LIMITS OF RADIATED AND BANDEDGE EMISSION MEASUREMENT ...	69
5.2.2	TEST INSTRUMENTS	70
5.2.3	TEST PROCEDURES.....	72
5.2.4	DEVIATION FROM TEST STANDARD	72
5.2.5	TEST SETUP	73
5.2.6	EUT OPERATING CONDITIONS.....	73
5.2.7	TEST RESULTS	74
5.3	6dB BANDWIDTH MEASUREMENT	83
5.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	83
5.3.2	TEST INSTRUMENTS	83
5.3.3	TEST PROCEDURE	83
5.3.4	DEVIATION FROM TEST STANDARD	83
5.3.5	TEST SETUP	83
5.3.6	EUT OPERATING CONDITIONS.....	83
5.3.7	TEST RESULTS.....	84
5.4	CONDUCTED OUTPUT POWER MEASUREMENT	85
5.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	85
5.4.2	INSTRUMENTS	85
5.4.3	TEST PROCEDURES.....	85
5.4.4	DEVIATION FROM TEST STANDARD	85
5.4.5	TEST SETUP	86
5.4.6	EUT OPERATING CONDITIONS.....	86
5.4.7	TEST RESULTS.....	87
5.5	AVERAGE OUTPUT POWER.....	88
5.5.1	FOR REFERENCE.....	88
5.5.2	TEST INSTRUMENTS	88
5.5.3	TEST PROCEDURES.....	88
5.5.4	TEST SETUP	88
5.5.5	EUT OPERATING CONDITIONS.....	88
5.5.6	TEST RESULTS.....	89
5.6	POWER SPECTRAL DENSITY MEASUREMENT	90
5.6.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	90
5.6.2	TEST INSTRUMENTS	90
5.6.3	TEST PROCEDURE	90
5.6.4	DEVIATION FROM TEST STANDARD	90
5.6.5	TEST SETUP	90



A D T

5.6.6	EUT OPERATING CONDITION	90
5.6.7	TEST RESULTS.....	91
5.7	CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	92
5.7.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT	92
5.7.2	TEST INSTRUMENTS	92
5.7.3	TEST PROCEDURE	92
5.7.4	DEVIATION FROM TEST STANDARD	93
5.7.5	TEST SETUP	93
5.7.6	EUT OPERATING CONDITION	93
5.7.7	TEST RESULTS.....	93
6.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	99
7.	INFORMATION ON THE TESTING LABORATORIES	100
8.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	101



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130802E06A	Original release	Feb. 12, 2014
RF 130802E06A R1	Cancel Model No.: RE2000 V2	Mar. 11, 2014



A D T

1. CERTIFICATION

PRODUCT: Dual-band Wireless-N Range Extender
BRAND NAME: Linksys
MODEL NO.: RE4000W
TEST SAMPLE: ENGINEERING SAMPLE
APPLICANT: Linksys LLC
TESTED: Aug. 07 to 14, 2013
STANDARDS: FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10-2009

The above equipment (Model: RE4000W) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Midoli Peng , **DATE:** Mar. 11, 2014
(Midoli Peng, Specialist)

APPROVED BY : May Chen , **DATE:** Mar. 11, 2014
(May Chen, Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

For 2.4GHz, 2412~2462MHz Band

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -3.18dB at 0.45859MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -0.2dB at 2483.5.00MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

For 5GHz, 5745~5825MHz Band

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -3.46dB at 0.45469MHz.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.6dB at 38.92MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE: The EUT was operating in 2.400 ~ 2.4835GHz, 5.15~5.25GHz and 5.725~5.850GHz frequencies band. This report was recorded the RF parameters including 2.400 ~ 2.4835GHz and 5.725~5.850GHz. For the 5.15~5.25GHz RF parameters was recorded in another test report.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.98 dB
Radiated emissions (30MHz-1GHz)	5.46 dB
Radiated emissions (1GHz -6GHz)	3.73 dB
Radiated emissions (6GHz -18GHz)	3.90 dB
Radiated emissions (18GHz -40GHz)	4.11 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Dual-band Wireless-N Range Extender
MODEL NO.	RE4000W
POWER SUPPLY	DC 12V from internal power supply
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: up to 11Mbps 802.11g/a: up to 54Mbps 802.11n: up to 300Mbps
OPERATING FREQUENCY	For 15.407 5.18 ~ 5.24GHz
	For 15.247 2.4GHz: 2.412 ~ 2.462GHz 5GHz: 5.745 ~ 5.825GHz
NUMBER OF CHANNEL	For 15.407 4 for 802.11a, 802.11n (HT20) 2 for 802.11n (HT40)
	For 15.247 (2.4GHz) 11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
	For 15.247 (5GHz) 5 for 802.11a, 802.11n (HT20) 2 for 802.11n (HT40)
MAXIMUM OUTPUT POWER	For 15.407 802.11a: 38.282mW 802.11n (HT20): 43.205mW 802.11n (HT40): 45.073mW For 15.247 (2.4GHz) 802.11b: 110.662mW 802.11g: 247.172mW 802.11n (HT20): 407.900mW 802.11n (HT40): 284.887mW For 15.247 (5GHz) 802.11a: 242.661mW 802.11n (HT20): 272.227mW 802.11n (HT40): 294.594mW

ANTENNA TYPE	Please see NOTE
DATA CABLE	RJ-45 cable (unshielded, 1.5m)
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	NA

NOTE:

- There are 2.4GHz and 5GHz WLAN technology used for the EUT.
- The EUT must be supplied with an internal power supply as following table:

No	Brand	Model No.	Spec.
1	HON-KWANG ELECTRIC CO., LTD	HK-XX06-A12	Input: 100-240V, 300-200mA Output: 12V, 500 mA Power cord: 1.6m, unshielded
2	KUANTECH INCORPORATED COMPANY	KSP20A1200050	Input: 100-240V, 100mA Output: 12V, 500 mA Power cord: 1.6m, unshielded

For radiated emissions test, the EUT was pre-tested with above internal power supplies 1~2, the worst case was found in internal power supply 2. Therefore only the test data of the internal power supply was recorded in this report.

- The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Antenna Type	Antenna Gain (dBi)	Connector	Frequency range (MHz to MHz)
Chain (0) < Side antenna >	Dipole	2.88	NA	2400~2500
	Dipole	2.93	NA	5150~5825
Chain (1) < BOT antenna >	Dipole	1.22	NA	2400~2500
	Dipole	4.58	NA	5150~5825

Note: For 802.11abg mode will fix transmission on Chain (0).

- The EUT incorporates a MIMO function without beam forming.

MODULATION MODE	TX/RX FUNCTION
802.11a	1TX/2RX
802.11b	1TX/2RX
802.11g	1TX/2RX
802.11n (HT20)	2TX/2RX
802.11n (HT40)	2TX/2RX

- When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 15.
- The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

Operated in 5725 ~ 5850MHz band:

5 channels are provided for 802.11a, 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz		

2 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY
151	5755 MHz
159	5795 MHz

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ³ 1G	APCM	OB	
1	√	-	-	-	-	Adapter 1
2	√	√	√	√	√	Adapter 2

Where **PLC**: Power Line Conducted Emission

RE < 1G: Radiated Emission below 1GHz

RE ³ 1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

OB: Conducted Out-Band Emission Measurement

NOTE: 1. "-" means no effect.

2. For 2.4GHz : The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane(below 1GHz) & X-plane(above 1GHz)**

3. For 5GHz : The EUT had been pre-tested on the positioned of each 2 axis. The radiated emission worst case was found when positioned on **Y-plane**

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
For 2.4 GHz 802.11n (HT20)	1 to 11	6	OFDM	BPSK	6.5
For 5 GHz 802.11n (HT20)	149 to 165	165	OFDM	BPSK	6.5

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
For 2.4 GHz 802.11n (HT20)	1 to 11	6	OFDM	BPSK	6.5
For 5 GHz 802.11n (HT20)	149 to 165	165	OFDM	BPSK	6.5

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
For 2.4 GHz 802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
For 2.4 GHz 802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5
802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6
For 5 GHz 802.11n (HT20)	149 to 165	149, 157, 165	OFDM	BPSK	6.5
For 5 GHz 802.11n (HT40)	151 to 159	151, 159	OFDM	BPSK	13.5

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
For 2.4 GHz 802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
For 2.4 GHz 802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5
802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6
For 5 GHz 802.11n (HT20)	149 to 165	149, 157, 165	OFDM	BPSK	6.5
For 5 GHz 802.11n (HT40)	151 to 159	151, 159	OFDM	BPSK	13.5

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
For 2.4 GHz 802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
For 2.4 GHz 802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5
802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6
For 5 GHz 802.11n (HT20)	149 to 165	149, 157, 165	OFDM	BPSK	6.5
For 5 GHz 802.11n (HT40)	151 to 159	151, 159	OFDM	BPSK	13.5



A D T

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
PLC	26deg. C, 60%RH	120Vac, 60Hz	Scott Chen
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Tim Ho
RE ³ 1G	25deg. C, 66%RH	120Vac, 60Hz	Tim Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Robert Cheng
OB	25deg. C, 60%RH	120Vac, 60Hz	Robert Cheng

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

558074 D01 DTS Meas Guidance v03r01

662911 D01 Multiple Transmitter Output v01 r02

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

Note: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	FSLB32S	FCC DoC
2	NOTEBOOK COMPUTER	DELL	PP32LA	GSLB32S	FCC DoC

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	UTP cable, 10m
2	UTP cable, 10m

NOTE: All power cords of the above support units are non shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST



4. TEST TYPES AND RESULTS (FOR 2.4GHz, 2412 ~ 2462MHz Band)

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS 30	100375	Mar. 08, 2013	Mar. 07, 2014
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK8127	8127-522	Sep. 06, 2012	Sep. 05, 2013
Line-Impedance Stabilization Network (for Peripheral)	ENV216	100072	June 07, 2013	June 06, 2014
RF Cable (JYEBAO)	5DFB	COCCAB-001	Mar. 11, 2013	Mar. 10, 2014
50 ohms Terminator	50	EMC-3	Sep. 25, 2012	Sep. 24, 2013
Software ADT	BV ADT_Cond_V7.3.7. 3	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.
4. Tested Date: Aug. 07, 2013

4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN.
- b. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- c. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- d. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit – 20dB) were not recorded.


NOTE:

1. The resolution bandwidth of test receiver is 9kHz for Quasi-peak detection (QP) & Average detection (AV).

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

1. Turn on the power of EUT.
2. The communication partner run test program “MT7620 V1.0.6.0 & RT5x9xQA.exe V1.0.9.0” to enable EUT under transmission/receiving condition continuously at specific channel frequency.


4.1.7 TEST RESULTS (MODE 1)

PHASE	Line (L)	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak (QP) / Average (AV), 9kHz
-------	----------	-------------------------------------	--

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.38828	0.20	43.04	38.90	43.24	39.10	58.10	48.10	-14.86	-9.00
2	0.45469	0.20	45.43	41.56	45.63	41.76	56.79	46.79	-11.15	-5.02
3	2.17700	0.35	39.93	30.52	40.28	30.87	56.00	46.00	-15.72	-15.13
4	2.95703	0.40	43.34	35.07	43.74	35.47	56.00	46.00	-12.26	-10.53
5	4.02734	0.47	45.88	37.87	46.35	38.34	56.00	46.00	-9.65	-7.66
6	6.10844	0.62	42.85	32.40	43.47	33.02	60.00	50.00	-16.53	-16.98

REMARKS:

- Q.P. and AV. are abbreviations of quasi-peak and average individually.
- The emission levels of other frequencies were very low against the limit.
- Margin value = Emission level - Limit value
- Correction factor = Insertion loss + Cable loss
- Emission Level = Correction Factor + Reading Value




PHASE	Neutral (N)	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak (QP) / Average (AV), 9kHz
-------	-------------	-------------------------------------	--

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.39609	0.19	44.15	40.15	44.34	40.34	57.93	47.93	-13.60	-7.60
2	0.45859	0.19	46.02	43.35	46.21	43.54	56.72	46.72	-10.51	-3.18
3	1.21875	0.24	37.31	30.45	37.55	30.69	56.00	46.00	-18.45	-15.31
4	3.94172	0.43	42.74	35.56	43.17	35.99	56.00	46.00	-12.83	-10.01
5	5.38494	0.50	40.89	32.13	41.39	32.63	60.00	50.00	-18.61	-17.37
6	21.66406	1.17	35.20	33.21	36.37	34.38	60.00	50.00	-23.63	-15.62

REMARKS:

- Q.P. and AV. are abbreviations of quasi-peak and average individually.
- The emission levels of other frequencies were very low against the limit.
- Margin value = Emission level - Limit value
- Correction factor = Insertion loss + Cable loss
- Emission Level = Correction Factor + Reading Value




4.1.8 TEST RESULTS (MODE 2)

PHASE	Line (L)	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak (QP) / Average (AV), 9kHz
-------	----------	-------------------------------------	--

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.42734	0.20	46.12	34.84	46.32	35.04	57.30	47.30	-10.98	-12.26
2	0.56016	0.21	39.60	29.53	39.81	29.74	56.00	46.00	-16.19	-16.26
3	0.78672	0.23	38.05	27.86	38.28	28.09	56.00	46.00	-17.72	-17.91
4	2.73047	0.39	33.91	24.79	34.30	25.18	56.00	46.00	-21.70	-20.82
5	5.90625	0.61	33.89	26.10	34.50	26.71	60.00	50.00	-25.50	-23.29
6	11.89063	1.02	33.49	30.03	34.51	31.05	60.00	50.00	-25.49	-18.95

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Neutral (N)	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak (QP) / Average (AV), 9kHz
-------	-------------	-------------------------------------	--

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.45469	0.19	36.41	27.28	36.60	27.47	56.79	46.79	-20.19	-19.32
2	0.86094	0.21	29.01	20.58	29.22	20.79	56.00	46.00	-26.78	-25.21
3	1.26953	0.24	24.41	17.18	24.65	17.42	56.00	46.00	-31.35	-28.58
4	2.87891	0.36	27.11	20.84	27.47	21.20	56.00	46.00	-28.53	-24.80
5	9.94141	0.74	25.34	19.53	26.08	20.27	60.00	50.00	-33.92	-29.73
6	21.90625	1.18	28.87	26.22	30.05	27.40	60.00	50.00	-29.95	-22.60

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB.

4.2.2 TEST INSTRUMENTS

For below 1GHz test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250253	Sep. 03, 2012	Sep. 02, 2013
MXE EMI Receiver Agilent	N9038A	MY50010156	Jan. 16, 2013	Jan. 15, 2014
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-04	Nov. 14, 2012	Nov. 13, 2013
Pre-Amplifier Agilent	8449B	3008A01923	Oct. 30, 2012	Oct. 29, 2013
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Mar. 25, 2013	Mar. 24, 2014
Horn_Antenna AISI	AIH.8018	0000220091110	Nov. 27, 2012	Nov. 26, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 12, 2012	Oct. 11, 2013
Loop Antenna ^(*) R&S	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
RF Cable	NA	RF104-205 RF104-207 RF104-202	Dec. 26, 2012	Dec. 25, 2013
RF Cable	NA	CHHCAB_001	Oct. 07, 2012	Oct. 06, 2013
Software	ADT_Radiated _V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3 The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
- 5 The CANADA Site Registration No. is IC 7450H-3.
- 6 Tested Date: Aug. 10, 2013

**A D T****For above 1GHz test:**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250253	Sep. 03, 2012	Sep. 02, 2013
MXE EMI Receiver Agilent	N9038A	MY51210105	Jan. 29, 2013	Jan. 28, 2014
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-03	Nov. 14, 2012	Nov. 13, 2013
Pre-Amplifier Agilent	8449B	3008A02578	June 25, 2013	June 24, 2014
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-360	Mar. 19, 2013	Mar. 18, 2014
Horn_Antenna AISI	AIH.8018	0000320091110	Nov. 19, 2012	Nov. 18, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 12, 2012	Oct. 11, 2013
RF Cable	NA	RF104-201 RF104-203 RF104-204	Dec. 25, 2012	Dec. 24, 2013
RF Cable	NA	CHGCAB_001	Oct. 06, 2012	Oct. 05, 2013
Software	ADT_Radiated V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3 The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
- 5 The VCCI Site Registration No. is G-137.
- 6 The CANADA Site Registration No. is IC 7450H-2.
- 7 Tested Date: Aug. 14, 2013

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

802.11n (HT20)

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	74.57	28.2 QP	40.0	-11.8	2.00 H	67	44.97	-16.81
2	151.54	30.3 QP	43.5	-13.2	2.00 H	70	43.30	-12.96
3	226.91	30.4 QP	46.0	-15.6	1.00 H	85	46.16	-15.80
4	250.00	36.7 QP	46.0	-9.3	1.00 H	69	50.88	-14.18
5	297.82	30.3 QP	46.0	-15.7	1.00 H	316	42.57	-12.28
6	500.01	36.9 QP	46.0	-9.1	2.00 H	241	44.39	-7.53
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	38.92	38.5 QP	40.0	-1.5	1.00 V	333	52.36	-13.87
2	47.80	37.6 QP	40.0	-2.4	1.50 V	100	51.11	-13.48
3	74.57	37.3 QP	40.0	-2.7	1.00 V	360	54.09	-16.81
4	125.01	34.4 QP	43.5	-9.1	1.00 V	355	49.22	-14.79
5	250.00	33.3 QP	46.0	-12.7	1.00 V	295	47.46	-14.18
6	500.01	39.1 QP	46.0	-6.9	1.00 V	183	46.59	-7.53

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

ABOVE 1GHz DATA

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.1 PK	74.0	-9.9	1.31 H	123	65.29	-1.19
2	2390.00	52.3 AV	54.0	-1.7	1.31 H	123	53.49	-1.19
3	*2412.00	107.5 PK			1.31 H	123	108.59	-1.09
4	*2412.00	106.4 AV			1.31 H	123	107.49	-1.09
5	4824.00	55.3 PK	74.0	-18.7	1.04 H	191	47.71	7.59
6	4824.00	49.3 AV	54.0	-4.7	1.04 H	191	41.71	7.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.1 PK	74.0	-18.9	1.34 V	202	56.29	-1.19
2	2390.00	41.2 AV	54.0	-12.8	1.34 V	202	42.39	-1.19
3	*2412.00	98.9 PK			1.34 V	202	99.99	-1.09
4	*2412.00	97.5 AV			1.34 V	202	98.59	-1.09
5	4824.00	57.2 PK	74.0	-16.8	1.00 V	329	49.61	7.59
6	4824.00	53.2 AV	54.0	-0.8	1.00 V	329	45.61	7.59

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.9 PK	74.0	-17.1	1.32 H	120	58.09	-1.19
2	2390.00	43.3 AV	54.0	-10.7	1.32 H	120	44.49	-1.19
3	*2437.00	108.0 PK			1.32 H	120	108.99	-0.99
4	*2437.00	107.0 AV			1.32 H	120	107.99	-0.99
5	2483.50	56.5 PK	74.0	-17.5	1.32 H	120	57.30	-0.80
6	2483.50	45.0 AV	54.0	-9.0	1.32 H	120	45.80	-0.80
7	4874.00	55.3 PK	74.0	-18.7	1.10 H	188	47.53	7.77
8	4874.00	49.5 AV	54.0	-4.5	1.10 H	188	41.73	7.77
9	7311.00	55.1 PK	74.0	-18.9	1.87 H	277	39.61	15.49
10	7311.00	44.3 AV	54.0	-9.7	1.87 H	277	28.81	15.49
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.1 PK	74.0	-19.9	1.30 V	129	55.29	-1.19
2	2390.00	40.2 AV	54.0	-13.8	1.30 V	129	41.39	-1.19
3	*2437.00	100.3 PK			1.30 V	107	101.29	-0.99
4	*2437.00	98.4 AV			1.30 V	107	99.39	-0.99
5	2483.50	54.7 PK	74.0	-19.3	1.30 V	107	55.50	-0.80
6	2483.50	41.2 AV	54.0	-12.8	1.30 V	107	42.00	-0.80
7	4874.00	57.6 PK	74.0	-16.4	1.00 V	337	49.83	7.77
8	4874.00	53.4 AV	54.0	-0.6	1.00 V	337	45.63	7.77
9	7311.00	57.1 PK	74.0	-16.9	1.00 V	9	41.61	15.49
10	7311.00	46.6 AV	54.0	-7.4	1.00 V	9	31.11	15.49

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.7 PK			1.30 H	117	107.59	-0.89
2	*2462.00	105.6 AV			1.30 H	117	106.49	-0.89
3	2483.50	59.8 PK	74.0	-14.2	1.30 H	117	60.60	-0.80
4	2483.50	46.5 AV	54.0	-7.5	1.30 H	117	47.30	-0.80
5	4924.00	55.3 PK	74.0	-18.7	1.16 H	189	47.36	7.94
6	4924.00	49.2 AV	54.0	-4.8	1.16 H	189	41.26	7.94
7	7386.00	54.9 PK	74.0	-19.1	1.87 H	283	39.39	15.51
8	7386.00	44.1 AV	54.0	-9.9	1.87 H	283	28.59	15.51
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.2 PK			1.30 V	276	99.09	-0.89
2	*2462.00	96.6 AV			1.30 V	276	97.49	-0.89
3	2483.50	55.7 PK	74.0	-18.3	1.30 V	276	56.50	-0.80
4	2483.50	42.4 AV	54.0	-11.6	1.30 V	276	43.20	-0.80
5	4924.00	57.8 PK	74.0	-16.2	1.00 V	340	49.86	7.94
6	4924.00	53.7 AV	54.0	-0.3	1.00 V	340	45.76	7.94
7	7386.00	57.4 PK	74.0	-16.6	1.06 V	7	41.89	15.51
8	7386.00	46.7 AV	54.0	-7.3	1.06 V	7	31.19	15.51

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.4 PK	74.0	-2.6	1.33 H	121	72.59	-1.19
2	2390.00	53.4 AV	54.0	-0.6	1.33 H	121	54.59	-1.19
3	*2412.00	110.1 PK			1.33 H	121	111.19	-1.09
4	*2412.00	101.4 AV			1.33 H	121	102.49	-1.09
5	4824.00	51.5 PK	74.0	-22.5	1.04 H	168	43.91	7.59
6	4824.00	39.5 AV	54.0	-14.5	1.04 H	168	31.91	7.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.1 PK	74.0	-7.9	1.35 V	45	67.29	-1.19
2	2390.00	47.8 AV	54.0	-6.2	1.35 V	45	48.99	-1.19
3	*2412.00	106.4 PK			1.35 V	45	107.49	-1.09
4	*2412.00	94.5 AV			1.35 V	45	95.59	-1.09
5	4824.00	57.0 PK	74.0	-17.0	1.04 V	349	49.41	7.59
6	4824.00	43.8 AV	54.0	-10.2	1.04 V	349	36.21	7.59

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.2 PK	74.0	-11.8	1.31 H	120	63.39	-1.19
2	2390.00	46.8 AV	54.0	-7.2	1.31 H	120	47.99	-1.19
3	*2437.00	114.1 PK			1.31 H	120	115.09	-0.99
4	*2437.00	105.7 AV			1.31 H	120	106.69	-0.99
5	2483.50	61.2 PK	74.0	-12.8	1.31 H	120	62.00	-0.80
6	2483.50	48.2 AV	54.0	-5.8	1.31 H	120	49.00	-0.80
7	4874.00	51.3 PK	74.0	-22.7	1.03 H	196	43.53	7.77
8	4874.00	39.6 AV	54.0	-14.4	1.03 H	196	31.83	7.77
9	7311.00	56.4 PK	74.0	-17.6	1.01 H	197	40.91	15.49
10	7311.00	42.5 AV	54.0	-11.5	1.01 H	197	27.01	15.49
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.8 PK	74.0	-14.2	1.40 V	48	60.99	-1.19
2	2390.00	41.5 AV	54.0	-12.5	1.40 V	48	42.69	-1.19
3	*2437.00	108.2 PK			1.40 V	48	109.19	-0.99
4	*2437.00	96.5 AV			1.40 V	48	97.49	-0.99
5	2483.50	58.6 PK	74.0	-15.4	1.40 V	48	59.40	-0.80
6	2483.50	40.8 AV	54.0	-13.2	1.40 V	48	41.60	-0.80
7	4874.00	57.2 PK	74.0	-16.8	1.06 V	347	49.43	7.77
8	4874.00	43.9 AV	54.0	-10.1	1.06 V	347	36.13	7.77
9	7311.00	55.9 PK	74.0	-18.1	1.01 V	18	40.41	15.49
10	7311.00	42.7 AV	54.0	-11.3	1.01 V	18	27.21	15.49

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.8 PK			1.31 H	120	109.69	-0.89
2	*2462.00	100.0 AV			1.31 H	120	100.89	-0.89
3	2483.50	73.8 PK	74.0	-0.2	1.31 H	120	74.60	-0.80
4	2483.50	50.7 AV	54.0	-3.3	1.31 H	120	51.50	-0.80
5	4924.00	50.8 PK	74.0	-23.2	1.00 H	196	42.86	7.94
6	4924.00	39.3 AV	54.0	-14.7	1.00 H	196	31.36	7.94
7	7386.00	56.2 PK	74.0	-17.8	1.00 H	197	40.69	15.51
8	7386.00	42.7 AV	54.0	-11.3	1.00 H	197	27.19	15.51
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	105.8 PK			1.42 V	37	106.69	-0.89
2	*2462.00	94.1 AV			1.42 V	37	94.99	-0.89
3	2483.50	66.0 PK	74.0	-8.0	1.42 V	37	66.80	-0.80
4	2483.50	47.8 AV	54.0	-6.2	1.42 V	37	48.60	-0.80
5	4924.00	56.8 PK	74.0	-17.2	1.05 V	359	48.86	7.94
6	4924.00	43.8 AV	54.0	-10.2	1.05 V	359	35.86	7.94
7	7386.00	56.1 PK	74.0	-17.9	1.05 V	8	40.59	15.51
8	7386.00	42.8 AV	54.0	-11.2	1.05 V	8	27.29	15.51

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.5 PK	74.0	-2.5	1.04 H	346	72.69	-1.19
2	2390.00	52.5 AV	54.0	-1.5	1.04 H	346	53.69	-1.19
3	*2412.00	108.9 PK			1.04 H	346	109.99	-1.09
4	*2412.00	97.2 AV			1.04 H	346	98.29	-1.09
5	4824.00	51.3 PK	74.0	-22.7	1.00 H	194	43.71	7.59
6	4824.00	39.3 AV	54.0	-14.7	1.00 H	194	31.71	7.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	63.3 PK	74.0	-10.7	1.00 V	240	64.49	-1.19
2	2390.00	45.3 AV	54.0	-8.7	1.00 V	240	46.49	-1.19
3	*2412.00	105.3 PK			1.00 V	240	106.39	-1.09
4	*2412.00	93.6 AV			1.00 V	240	94.69	-1.09
5	4824.00	57.4 PK	74.0	-16.6	1.28 V	315	49.81	7.59
6	4824.00	44.4 AV	54.0	-9.6	1.28 V	315	36.81	7.59

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.0 PK	74.0	-14.0	1.08 H	348	61.19	-1.19
2	2390.00	44.6 AV	54.0	-9.4	1.08 H	348	45.79	-1.19
3	*2437.00	111.5 PK			1.08 H	348	112.49	-0.99
4	*2437.00	99.4 AV			1.08 H	348	100.39	-0.99
5	2483.50	58.5 PK	74.0	-15.5	1.08 H	348	59.30	-0.80
6	2483.50	43.8 AV	54.0	-10.2	1.08 H	348	44.60	-0.80
7	4874.00	51.3 PK	74.0	-22.7	1.02 H	182	43.53	7.77
8	4874.00	39.6 AV	54.0	-14.4	1.02 H	182	31.83	7.77
9	7311.00	56.1 PK	74.0	-17.9	1.00 H	195	40.61	15.49
10	7311.00	42.3 AV	54.0	-11.7	1.00 H	195	26.81	15.49
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.8 PK	74.0	-14.2	1.01 V	242	60.99	-1.19
2	2390.00	41.3 AV	54.0	-12.7	1.01 V	242	42.49	-1.19
3	*2437.00	105.5 PK			1.01 V	242	106.49	-0.99
4	*2437.00	93.4 AV			1.01 V	242	94.39	-0.99
5	2483.50	58.5 PK	74.0	-15.5	1.01 V	242	59.30	-0.80
6	2483.50	40.6 AV	54.0	-13.4	1.01 V	242	41.40	-0.80
7	4874.00	57.4 PK	74.0	-16.6	1.23 V	316	49.63	7.77
8	4874.00	44.2 AV	54.0	-9.8	1.23 V	316	36.43	7.77
9	7311.00	56.1 PK	74.0	-17.9	1.58 V	7	40.61	15.49
10	7311.00	42.6 AV	54.0	-11.4	1.58 V	7	27.11	15.49

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.3 PK			1.05 H	358	111.19	-0.89
2	*2462.00	97.7 AV			1.05 H	358	98.59	-0.89
3	2483.50	71.3 PK	74.0	-2.7	1.05 H	358	72.10	-0.80
4	2483.50	53.4 AV	54.0	-0.6	1.05 H	358	54.20	-0.80
5	4924.00	51.2 PK	74.0	-22.8	1.07 H	198	43.26	7.94
6	4924.00	39.7 AV	54.0	-14.3	1.07 H	198	31.76	7.94
7	7386.00	56.3 PK	74.0	-17.7	1.00 H	203	40.79	15.51
8	7386.00	42.7 AV	54.0	-11.3	1.00 H	203	27.19	15.51
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.1 PK			1.01 V	51	106.99	-0.89
2	*2462.00	93.8 AV			1.01 V	51	94.69	-0.89
3	2483.50	68.1 PK	74.0	-5.9	1.01 V	51	68.90	-0.80
4	2483.50	50.0 AV	54.0	-4.0	1.01 V	51	50.80	-0.80
5	4924.00	57.2 PK	74.0	-16.8	1.23 V	316	49.26	7.94
6	4924.00	43.9 AV	54.0	-10.1	1.23 V	316	35.96	7.94
7	7386.00	56.0 PK	74.0	-18.0	1.56 V	20	40.49	15.51
8	7386.00	42.7 AV	54.0	-11.3	1.56 V	20	27.19	15.51

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.4 PK	74.0	-2.6	1.09 H	357	72.59	-1.19
2	2390.00	53.7 AV	54.0	-0.3	1.09 H	357	54.89	-1.19
3	*2422.00	105.1 PK			1.09 H	357	106.15	-1.05
4	*2422.00	93.4 AV			1.09 H	357	94.45	-1.05
5	4844.00	50.7 PK	74.0	-23.3	1.01 H	188	43.04	7.66
6	4844.00	39.1 AV	54.0	-14.9	1.01 H	188	31.44	7.66
7	7266.00	56.1 PK	74.0	-17.9	1.02 H	204	40.59	15.51
8	7266.00	42.6 AV	54.0	-11.4	1.02 H	204	27.09	15.51
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.3 PK	74.0	-7.7	1.00 V	52	67.49	-1.19
2	2390.00	49.8 AV	54.0	-4.2	1.00 V	52	50.99	-1.19
3	*2422.00	101.5 PK			1.00 V	52	102.55	-1.05
4	*2422.00	89.0 AV			1.00 V	52	90.05	-1.05
5	4844.00	57.4 PK	74.0	-16.6	1.19 V	330	49.74	7.66
6	4844.00	44.3 AV	54.0	-9.7	1.19 V	330	36.64	7.66
7	7266.00	56.0 PK	74.0	-18.0	1.56 V	11	40.49	15.51
8	7266.00	42.6 AV	54.0	-11.4	1.56 V	11	27.09	15.51

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.



A D T

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.2 PK	74.0	-0.8	1.07 H	360	74.39	-1.19
2	2390.00	53.7 AV	54.0	-0.3	1.07 H	360	54.89	-1.19
3	*2437.00	108.5 PK			1.07 H	360	109.49	-0.99
4	*2437.00	96.6 AV			1.07 H	360	97.59	-0.99
5	2483.50	73.4 PK	74.0	-0.6	1.07 H	360	74.20	-0.80
6	2483.50	52.6 AV	54.0	-1.4	1.07 H	360	53.40	-0.80
7	4874.00	51.5 PK	74.0	-22.5	1.06 H	173	43.73	7.77
8	4874.00	40.0 AV	54.0	-14.0	1.06 H	173	32.23	7.77
9	7311.00	56.5 PK	74.0	-17.5	1.00 H	186	41.01	15.49
10	7311.00	42.7 AV	54.0	-11.3	1.00 H	186	27.21	15.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.7 PK	74.0	-6.3	1.01 V	52	68.89	-1.19
2	2390.00	49.2 AV	54.0	-4.8	1.01 V	52	50.39	-1.19
3	*2437.00	104.6 PK			1.01 V	52	105.59	-0.99
4	*2437.00	92.8 AV			1.01 V	52	93.79	-0.99
5	2483.50	68.8 PK	74.0	-5.2	1.01 V	52	69.60	-0.80
6	2483.50	49.6 AV	54.0	-4.4	1.01 V	52	50.40	-0.80
7	4874.00	56.9 PK	74.0	-17.1	1.22 V	329	49.13	7.77
8	4874.00	43.8 AV	54.0	-10.2	1.22 V	329	36.03	7.77
9	7311.00	55.9 PK	74.0	-18.1	1.55 V	20	40.41	15.49
10	7311.00	42.6 AV	54.0	-11.4	1.55 V	20	27.11	15.49

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	104.2 PK			1.09 H	360	105.12	-0.92
2	*2452.00	93.7 AV			1.09 H	360	94.62	-0.92
3	2483.50	70.7 PK	74.0	-3.3	1.09 H	360	71.50	-0.80
4	2483.50	53.6 AV	54.0	-0.4	1.09 H	360	54.40	-0.80
5	4904.00	51.4 PK	74.0	-22.6	1.01 H	188	43.52	7.88
6	4904.00	39.7 AV	54.0	-14.3	1.01 H	188	31.82	7.88
7	7356.00	56.1 PK	74.0	-17.9	1.00 H	187	40.61	15.49
8	7356.00	42.2 AV	54.0	-11.8	1.00 H	187	26.71	15.49
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	102.6 PK			1.01 V	52	103.52	-0.92
2	*2452.00	89.7 AV			1.01 V	52	90.62	-0.92
3	2483.50	68.0 PK	74.0	-6.0	1.01 V	52	68.80	-0.80
4	2483.50	49.9 AV	54.0	-4.1	1.01 V	52	50.70	-0.80
5	4904.00	57.3 PK	74.0	-16.7	1.25 V	324	49.42	7.88
6	4904.00	44.1 AV	54.0	-9.9	1.25 V	324	36.22	7.88
7	7356.00	56.1 PK	74.0	-17.9	1.52 V	7	40.61	15.49
8	7356.00	42.4 AV	54.0	-11.6	1.52 V	7	26.91	15.49

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100036	Jan. 21, 2013	Jan. 20, 2014

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 12, 2013


4.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100kHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.42	0.5	PASS
6	2437	8.64	0.5	PASS
11	2462	8.41	0.5	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.41	0.5	PASS
6	2437	16.42	0.5	PASS
11	2462	16.46	0.5	PASS

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	17.12	17.62	0.5	PASS
6	2437	17.34	17.61	0.5	PASS
11	2462	17.38	17.57	0.5	PASS

802.11n (HT40)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
3	2422	36.35	36.46	0.5	PASS
6	2437	36.11	36.42	0.5	PASS
9	2452	36.43	36.45	0.5	PASS

4.4 CONDUCTED OUTPUT POWER MEASUREMENT

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output v01r02 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $NANT \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;

Array Gain = $5 \log(NANT/NSS)$ dB or 3 dB, whichever is less for 20-MHz channel widths with $NANT \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(NANT/NSS)$ dB.

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter Anritsu	ML2495A	0824006	May 20, 2013	May 19, 2014
Power Sensor Anritsu	MA2411B	0738172	May 20, 2013	May 19, 2014

- Note:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. Tested date : Aug. 12, 2013


4.4.3 TEST PROCEDURES

The peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	99.770	19.99	30	PASS
6	2437	110.662	20.44	30	PASS
11	2462	57.943	17.63	30	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	169.434	22.29	30	PASS
6	2437	247.172	23.93	30	PASS
11	2462	127.644	21.06	30	PASS

802.11n (HT20)

CHAN.	FREQUENCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
1	2412	20.68	21.40	254.988	24.07	30	PASS
6	2437	23.05	23.14	407.900	26.11	30	PASS
11	2462	21.22	21.10	261.259	24.17	30	PASS

802.11n (HT40)

CHAN.	FREQUENCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
3	2422	19.58	19.88	188.057	22.74	30	PASS
6	2437	21.84	21.21	284.887	24.55	30	PASS
9	2452	19.70	20.01	193.556	22.87	30	PASS

4.5 AVERAGE OUTPUT POWER

4.5.1 FOR REFERENCE.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter	ML2495A	0824006	May 20, 2013	May 19, 2014
Power Sensor	MA2411B	0738172	May 20, 2013	May 19, 2014


Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 12, 2013

4.5.3 TEST PROCEDURES

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

4.5.4 TEST SETUP



4.5.5 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.5.6 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (mW)	AVERAGE POWER (dBm)
1	2412	48.641	16.87
6	2437	52.845	17.23
11	2462	43.652	16.40

802.11g

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (mW)	AVERAGE POWER (dBm)
1	2412	49.091	16.91
6	2437	110.408	20.43
11	2462	34.594	15.39

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
1	2412	14.73	14.11	55.480	17.44
6	2437	18.72	18.84	151.033	21.79
11	2462	14.48	14.34	55.218	17.42

802.11n (HT40)

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
3	2422	13.06	13.13	40.789	16.11
6	2437	16.47	16.02	84.355	19.26
9	2452	12.47	12.74	36.453	15.62

4.6 POWER SPECTRAL DENSITY MEASUREMENT

4.6.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100036	Jan. 21, 2013	Jan. 20, 2014

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 12, 2013


4.6.3 TEST PROCEDURE

1. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
2. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
3. Use the peak marker function to determine the maximum amplitude level.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS /FAIL
1	2412	-6.93	8	PASS
6	2437	-6.56	8	PASS
11	2462	-5.79	8	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS /FAIL
1	2412	-10.40	8	PASS
6	2437	-7.28	8	PASS
11	2462	-12.52	8	PASS

802.11n (HT20)

TX chain	Channel	FREQ. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	1	2412	-12.07	3.01	-9.06	8	PASS
	6	2437	-7.88	3.01	-4.87	8	PASS
	11	2462	-13.07	3.01	-10.06	8	PASS
1	1	2412	-14.35	3.01	-11.34	8	PASS
	6	2437	-9.49	3.01	-6.48	8	PASS
	11	2462	-14.43	3.01	-11.42	8	PASS

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 5.10\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.

802.11n (HT40)

TX chain	Channel	FREQ. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	3	2422	-17.20	3.01	-14.19	8	PASS
	6	2437	-14.33	3.01	-11.32	8	PASS
	9	2452	-17.65	3.01	-14.64	8	PASS
1	3	2422	-17.58	3.01	-14.57	8	PASS
	6	2437	-14.54	3.01	-11.53	8	PASS
	9	2452	-17.65	3.01	-14.64	8	PASS

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 5.10\text{dBi} < 6\text{dBi}$, so the power density limit shall not be reduced.



A D T

4.7 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.7.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100036	Jan. 21, 2013	Jan. 20, 2014

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 12, 2013

4.7.3 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.


Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP



4.7.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.7.7 TEST RESULTS


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement




A D T

802.11b:


CH 1



CH 6



CH 11







A D T

802.11g:


CH 1



CH 6



CH 11







A D T



802.11n (HT20):

CHAIN (0)



CH 1



CH 6



CH 11







A D T

CHAIN (1)


CH 1



CH 6



CH 11






A D T


802.11n (HT40):

CHAIN (0)


CH 3



CH 6



CH 9







A D T

CHAIN (1)


CH 3



CH 6



CH 9



5. TEST TYPES AND RESULTS (FOR 5GHz, 5725~5850MHz Band)

5.1 CONDUCTED EMISSION MEASUREMENT

5.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS 30	100375	Mar. 08, 2013	Mar. 07, 2014
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK8127	8127-522	Sep. 06, 2012	Sep. 05, 2013
Line-Impedance Stabilization Network (for Peripheral)	ENV216	100072	June 07, 2013	June 06, 2014
RF Cable (JYEBAO)	5DFB	COCCAB-001	Mar. 11, 2013	Mar. 10, 2014
50 ohms Terminator	50	EMC-3	Sep. 25, 2012	Sep. 24, 2013
Software ADT	BV ADT_Cond_V7.3.7. 3	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.
4. Tested Date: Aug. 07, 2013

5.1.3 TEST PROCEDURES

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN.
- The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit – 20dB) were not recorded.


NOTE:

- The resolution bandwidth of test receiver is 9kHz for Quasi-peak detection (QP) & Average detection (AV).

5.1.4 DEVIATION FROM TEST STANDARD

No deviation

5.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.1.6 EUT OPERATING CONDITIONS

Same as the 4.1.6


5.1.7 TEST RESULTS (MODE 1)

PHASE	Line (L)	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak (QP) / Average (AV), 9kHz
-------	----------	-------------------------------------	--

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.38828	0.20	42.36	38.40	42.56	38.60	58.10	48.10	-15.54	-9.50
2	0.45469	0.20	45.45	41.51	45.65	41.71	56.79	46.79	-11.13	-5.07
3	1.91406	0.33	40.76	31.57	41.09	31.90	56.00	46.00	-14.91	-14.10
4	3.33984	0.43	45.88	37.67	46.31	38.10	56.00	46.00	-9.69	-7.90
5	6.06250	0.62	44.35	36.45	44.97	37.07	60.00	50.00	-15.03	-12.93
6	6.84375	0.67	42.83	33.10	43.50	33.77	60.00	50.00	-16.50	-16.23

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




PHASE	Neutral (N)	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak (QP) / Average (AV), 9kHz
-------	-------------	-------------------------------------	--

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.38828	0.19	41.16	38.80	41.35	38.99	58.10	48.10	-16.75	-9.11
2	0.45469	0.19	44.22	43.14	44.41	43.33	56.79	46.79	-12.38	-3.46
3	0.94297	0.22	32.47	27.35	32.69	27.57	56.00	46.00	-23.31	-18.43
4	2.04297	0.30	37.09	31.79	37.39	32.09	56.00	46.00	-18.61	-13.91
5	3.14453	0.37	41.64	35.48	42.01	35.85	56.00	46.00	-13.99	-10.15
6	5.60938	0.51	38.84	30.88	39.35	31.39	60.00	50.00	-20.65	-18.61

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




5.1.8 TEST RESULTS (MODE 2)

PHASE	Line (L)	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak (QP) / Average (AV), 9kHz
-------	----------	-------------------------------------	--

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.41953	0.20	47.00	36.29	47.20	36.49	57.46	47.46	-10.26	-10.97
2	0.52109	0.21	37.07	24.89	37.28	25.10	56.00	46.00	-18.72	-20.90
3	0.77891	0.23	37.88	28.08	38.11	28.31	56.00	46.00	-17.89	-17.69
4	5.07031	0.55	34.10	25.58	34.65	26.13	60.00	50.00	-25.35	-23.87
5	10.06250	0.90	33.37	28.10	34.27	29.00	60.00	50.00	-25.73	-21.00
6	21.66406	1.51	34.98	33.17	36.49	34.68	60.00	50.00	-23.51	-15.32

REMARKS:

- Q.P. and AV. are abbreviations of quasi-peak and average individually.
- The emission levels of other frequencies were very low against the limit.
- Margin value = Emission level - Limit value
- Correction factor = Insertion loss + Cable loss
- Emission Level = Correction Factor + Reading Value




PHASE	Neutral (N)	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak (QP) / Average (AV), 9kHz
-------	-------------	-------------------------------------	--

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.41172	0.19	36.22	28.10	36.41	28.29	57.61	47.61	-21.20	-19.32
2	1.57422	0.27	24.38	16.78	24.65	17.05	56.00	46.00	-31.35	-28.95
3	2.71875	0.35	28.57	22.08	28.92	22.43	56.00	46.00	-27.08	-23.57
4	6.85938	0.58	23.16	17.09	23.74	17.67	60.00	50.00	-36.26	-32.33
5	6.85938	0.58	23.12	17.11	23.70	17.69	60.00	50.00	-36.30	-32.31
6	21.90716	1.18	29.05	26.26	30.23	27.44	60.00	50.00	-29.77	-22.56

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



5.2 RADIATED AND BANDEDGE EMISSION MEASUREMENT

5.2.1 LIMITS OF RADIATED AND BANDEDGE EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB.

5.2.2 TEST INSTRUMENTS

For below 1GHz test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250253	Sep. 03, 2012	Sep. 02, 2013
MXE EMI Receiver Agilent	N9038A	MY50010156	Jan. 16, 2013	Jan. 15, 2014
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-04	Nov. 14, 2012	Nov. 13, 2013
Pre-Amplifier Agilent	8449B	3008A01923	Oct. 30, 2012	Oct. 29, 2013
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Mar. 25, 2013	Mar. 24, 2014
Horn_Antenna AISI	AIH.8018	0000220091110	Nov. 27, 2012	Nov. 26, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 12, 2012	Oct. 11, 2013
Loop Antenna ^(*) R&S	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
RF Cable	NA	RF104-205 RF104-207 RF104-202	Dec. 26, 2012	Dec. 25, 2013
RF Cable	NA	CHHCAB_001	Oct. 07, 2012	Oct. 06, 2013
Software	ADT_Radiated _V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
5. The CANADA Site Registration No. is IC 7450H-3.
6. Tested Date: Aug. 10, 2013

**A D T****For above 1GHz test:**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250253	Sep. 03, 2012	Sep. 02, 2013
MXE EMI Receiver Agilent	N9038A	MY51210105	Jan. 29, 2013	Jan. 28, 2014
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-03	Nov. 14, 2012	Nov. 13, 2013
Pre-Amplifier Agilent	8449B	3008A02578	June 25, 2013	June 24, 2014
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Nov. 14, 2012	Nov. 13, 2013
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-360	Mar. 19, 2013	Mar. 18, 2014
Horn_Antenna AISI	AIH.8018	0000320091110	Nov. 19, 2012	Nov. 18, 2013
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 12, 2012	Oct. 11, 2013
RF Cable	NA	RF104-201 RF104-203 RF104-204	Dec. 25, 2012	Dec. 24, 2013
RF Cable	NA	CHGCAB_001	Oct. 06, 2012	Oct. 05, 2013
Software	ADT_Radiated V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
5. The VCCI Site Registration No. is G-137.
6. The CANADA Site Registration No. is IC 7450H-2.
7. Tested Date: Aug. 14, 2013

5.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

5.2.4 DEVIATION FROM TEST STANDARD

No deviation

5.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.2.6 EUT OPERATING CONDITIONS

Same as the 4.1.6

5.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

802.11n (HT20)

CHANNEL	TX Channel 165	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	74.57	28.0 QP	40.0	-12.0	1.00 H	167	44.83	-16.81
2	151.54	30.1 QP	43.5	-13.4	1.50 H	170	43.03	-12.96
3	226.91	30.2 QP	46.0	-15.8	1.00 H	85	46.01	-15.80
4	250.00	36.6 QP	46.0	-9.4	1.00 H	169	50.75	-14.18
5	297.82	30.1 QP	46.0	-15.9	1.00 H	216	42.40	-12.28
6	500.01	36.7 QP	46.0	-9.3	1.00 H	141	44.21	-7.53
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	38.92	38.4 QP	40.0	-1.6	2.00 V	133	52.24	-13.87
2	47.80	37.5 QP	40.0	-2.6	1.00 V	200	50.93	-13.48
3	74.57	37.2 QP	40.0	-2.8	1.50 V	350	53.98	-16.81
4	125.01	34.3 QP	43.5	-9.2	2.00 V	345	49.08	-14.79
5	250.00	33.1 QP	46.0	-12.9	1.50 V	195	47.30	-14.18
6	500.01	38.9 QP	46.0	-7.1	2.00 V	283	46.40	-7.53

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

ABOVE 1GHz DATA

802.11a

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	57.9 PK	74.0	-16.1	1.18 H	299	48.25	9.65
2	5460.00	46.9 AV	54.0	-7.1	1.18 H	299	37.25	9.65
3	*5745.00	111.1 PK			1.18 H	299	100.68	10.42
4	*5745.00	101.3 AV			1.18 H	299	90.88	10.42
5	11490.00	55.7 PK	74.0	-18.3	1.02 H	133	38.44	17.26
6	11490.00	42.6 AV	54.0	-11.4	1.02 H	133	25.34	17.26

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	56.3 PK	74.0	-17.7	1.22 V	79	46.65	9.65
2	5460.00	45.3 AV	54.0	-8.7	1.22 V	79	35.65	9.65
3	*5745.00	110.4 PK			1.22 V	79	99.98	10.42
4	*5745.00	100.6 AV			1.22 V	79	90.18	10.42
5	11490.00	55.0 PK	74.0	-19.0	1.01 V	208	37.74	17.26
6	11490.00	41.9 AV	54.0	-12.1	1.01 V	208	24.64	17.26

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.

CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	58.2 PK	74.0	-15.8	1.18 H	287	48.55	9.65
2	5460.00	47.4 AV	54.0	-6.6	1.18 H	287	37.75	9.65
3	*5785.00	111.3 PK			1.18 H	287	100.81	10.49
4	*5785.00	101.6 AV			1.18 H	287	91.11	10.49
5	11570.00	55.3 PK	74.0	-18.7	1.00 H	136	38.01	17.29
6	11570.00	42.3 AV	54.0	-11.7	1.00 H	136	25.01	17.29
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	56.9 PK	74.0	-17.1	1.25 V	82	47.25	9.65
2	5460.00	46.3 AV	54.0	-7.7	1.25 V	82	36.65	9.65
3	*5785.00	109.9 PK			1.25 V	82	99.41	10.49
4	*5785.00	100.3 AV			1.25 V	82	89.81	10.49
5	11570.00	55.7 PK	74.0	-18.3	1.02 V	202	38.41	17.29
6	11570.00	42.1 AV	54.0	-11.9	1.02 V	202	24.81	17.29

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.

CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	58.2 PK	74.0	-15.8	1.16 H	289	48.55	9.65
2	5460.00	47.0 AV	54.0	-7.0	1.16 H	289	37.35	9.65
3	*5825.00	111.2 PK			1.16 H	289	100.55	10.65
4	*5825.00	101.3 AV			1.16 H	289	90.65	10.65
5	11650.00	55.6 PK	74.0	-18.4	1.00 H	147	37.94	17.66
6	11650.00	42.2 AV	54.0	-11.8	1.00 H	147	24.54	17.66
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	57.1 PK	74.0	-16.9	1.22 V	77	47.45	9.65
2	5460.00	45.8 AV	54.0	-8.2	1.22 V	77	36.15	9.65
3	*5825.00	110.1 PK			1.22 V	77	99.45	10.65
4	*5825.00	100.1 AV			1.22 V	77	89.45	10.65
5	11650.00	54.9 PK	74.0	-19.1	1.02 V	218	37.24	17.66
6	11650.00	41.8 AV	54.0	-12.2	1.02 V	218	24.14	17.66

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.

802.11n (HT20)

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	62.9 PK	74.0	-11.1	1.05 H	356	53.25	9.65
2	5460.00	49.5 AV	54.0	-4.5	1.05 H	356	39.85	9.65
3	*5745.00	108.7 PK			1.05 H	356	98.28	10.42
4	*5745.00	99.0 AV			1.05 H	356	88.58	10.42
5	11490.00	55.4 PK	74.0	-18.6	1.00 H	142	38.14	17.26
6	11490.00	42.0 AV	54.0	-12.0	1.00 H	142	24.74	17.26
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	62.5 PK	74.0	-11.5	1.00 V	12	52.85	9.65
2	5460.00	49.3 AV	54.0	-4.7	1.00 V	12	39.65	9.65
3	*5745.00	107.4 PK			1.00 V	12	96.98	10.42
4	*5745.00	97.8 AV			1.00 V	12	87.38	10.42
5	11490.00	55.3 PK	74.0	-18.7	1.01 V	223	38.04	17.26
6	11490.00	42.4 AV	54.0	-11.6	1.01 V	223	25.14	17.26

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.

CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	63.3 PK	74.0	-10.7	1.08 H	360	53.65	9.65
2	5460.00	49.8 AV	54.0	-4.2	1.08 H	360	40.15	9.65
3	*5785.00	108.8 PK			1.08 H	360	98.31	10.49
4	*5785.00	99.3 AV			1.08 H	360	88.81	10.49
5	11570.00	55.5 PK	74.0	-18.5	1.07 H	122	38.21	17.29
6	11570.00	42.6 AV	54.0	-11.4	1.07 H	122	25.31	17.29
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	61.6 PK	74.0	-12.4	1.02 V	50	51.95	9.65
2	5460.00	47.9 AV	54.0	-6.1	1.02 V	50	38.25	9.65
3	*5785.00	106.9 PK			1.02 V	50	96.41	10.49
4	*5785.00	97.7 AV			1.02 V	50	87.21	10.49
5	11570.00	56.0 PK	74.0	-18.0	1.00 V	209	38.71	17.29
6	11570.00	42.3 AV	54.0	-11.7	1.00 V	209	25.01	17.29

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.

CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	63.4 PK	74.0	-10.6	1.08 H	359	53.75	9.65
2	5460.00	49.9 AV	54.0	-4.1	1.08 H	359	40.25	9.65
3	*5825.00	108.6 PK			1.08 H	359	97.95	10.65
4	*5825.00	98.8 AV			1.08 H	359	88.15	10.65
5	11650.00	56.1 PK	74.0	-17.9	1.02 H	123	38.44	17.66
6	11650.00	42.9 AV	54.0	-11.1	1.02 H	123	25.24	17.66
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	62.3 PK	74.0	-11.7	1.07 V	63	52.65	9.65
2	5460.00	48.6 AV	54.0	-5.4	1.07 V	63	38.95	9.65
3	*5825.00	106.6 PK			1.07 V	63	95.95	10.65
4	*5825.00	96.9 AV			1.07 V	63	86.25	10.65
5	11650.00	55.7 PK	74.0	-18.3	1.00 V	207	38.04	17.66
6	11650.00	42.2 AV	54.0	-11.8	1.00 V	207	24.54	17.66

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.



A D T

802.11n (HT40)

CHANNEL	TX Channel 151	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	60.8 PK	74.0	-13.2	1.09 H	0	51.15	9.65
2	5460.00	46.9 AV	54.0	-7.1	1.09 H	0	37.25	9.65
3	*5755.00	104.8 PK			1.09 H	0	94.37	10.43
4	*5755.00	96.3 AV			1.09 H	0	85.87	10.43
5	11510.00	55.3 PK	74.0	-18.7	1.07 H	140	38.07	17.23
6	11510.00	42.2 AV	54.0	-11.8	1.07 H	140	24.97	17.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	59.7 PK	74.0	-14.3	1.01 V	49	50.05	9.65
2	5460.00	45.6 AV	54.0	-8.4	1.01 V	49	35.95	9.65
3	*5755.00	102.8 PK			1.01 V	49	92.37	10.43
4	*5755.00	94.4 AV			1.01 V	49	83.97	10.43
5	11510.00	55.5 PK	74.0	-18.5	1.06 V	215	38.27	17.23
6	11510.00	42.7 AV	54.0	-11.3	1.06 V	215	25.47	17.23

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.

CHANNEL	TX Channel 159	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	60.7 PK	74.0	-13.3	1.15 H	3	51.05	9.65
2	5460.00	47.0 AV	54.0	-7.0	1.15 H	3	37.35	9.65
3	*5795.00	104.7 PK			1.15 H	3	94.20	10.50
4	*5795.00	96.0 AV			1.15 H	3	85.50	10.50
5	11590.00	55.9 PK	74.0	-18.1	1.02 H	125	38.59	17.31
6	11590.00	42.6 AV	54.0	-11.4	1.02 H	125	25.29	17.31
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	59.2 PK	74.0	-14.8	1.03 V	59	49.55	9.65
2	5460.00	45.2 AV	54.0	-8.8	1.03 V	59	35.55	9.65
3	*5795.00	103.2 PK			1.03 V	59	92.70	10.50
4	*5795.00	94.7 AV			1.03 V	59	84.20	10.50
5	11590.00	55.5 PK	74.0	-18.5	1.00 V	214	38.19	17.31
6	11590.00	42.8 AV	54.0	-11.2	1.00 V	214	25.49	17.31

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The limit value is defined as per 15.247.

5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

5.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100036	Jan. 21, 2013	Jan. 20, 2014

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 12, 2013


5.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100kHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

5.3.4 DEVIATION FROM TEST STANDARD

No deviation

5.3.5 TEST SETUP



5.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

5.3.7 TEST RESULTS

802.11a

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
149	5745	15.88	0.5	PASS
157	5785	16.12	0.5	PASS
165	5825	15.86	0.5	PASS

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
149	5745	15.88	16.33	0.5	PASS
157	5785	15.83	15.40	0.5	PASS
165	5825	15.84	16.09	0.5	PASS

802.11n (HT40)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
151	5755	35.26	35.32	0.5	PASS
159	5795	35.27	35.20	0.5	PASS

5.4 CONDUCTED OUTPUT POWER MEASUREMENT

5.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 5725 –5850 MHz band: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output v01r02 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $NANT \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;

Array Gain = $5 \log(NANT/NSS)$ dB or 3 dB, whichever is less for 20-MHz channel widths with $NANT \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(NANT/NSS)$ dB.

5.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter Anritsu	ML2495A	0824006	May 20, 2013	May 19, 2014
Power Sensor Anritsu	MA2411B	0738172	May 20, 2013	May 19, 2014

Note: 3. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4. Tested date : Aug. 12, 2013


5.4.3 TEST PROCEDURES

The peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

5.4.4 DEVIATION FROM TEST STANDARD

No deviation

5.4.5 TEST SETUP



5.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

5.4.7 TEST RESULTS

802.11a

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
149	5745	221.309	23.45	30	PASS
157	5785	242.661	23.85	30	PASS
165	5825	211.836	23.26	30	PASS

802.11n (HT20)

CHAN.	FREQUENCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
149	5745	21.51	20.97	266.605	24.26	30	PASS
157	5785	21.49	21.00	266.822	24.26	30	PASS
165	5825	21.61	21.05	272.227	24.35	30	PASS

802.11n (HT40)

CHAN.	FREQUENCY (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
151	5755	21.12	21.15	259.737	24.15	30	PASS
159	5795	21.55	21.81	294.594	24.69	30	PASS

5.5 AVERAGE OUTPUT POWER

5.5.1 FOR REFERENCE.

5.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter	ML2495A	0824006	May 20, 2013	May 19, 2014
Power Sensor	MA2411B	0738172	May 20, 2013	May 19, 2014


Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 12, 2013

5.5.3 TEST PROCEDURES

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

5.5.4 TEST SETUP



5.5.5 EUT OPERATING CONDITIONS

Same as Item 4.3.6

5.5.6 TEST RESULTS

802.11a

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (mW)	AVERAGE POWER (dBm)
149	5745	96.161	19.83
157	5785	101.859	20.08
165	5825	79.433	19.00

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
149	5745	16.55	16.12	86.112	19.35
157	5785	16.53	16.23	86.954	19.39
165	5825	16.56	16.25	87.460	19.42

802.11n (HT40)

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
151	5755	16.22	16.23	83.855	19.24
159	5795	16.31	16.56	88.046	19.45

5.6 POWER SPECTRAL DENSITY MEASUREMENT

5.6.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100036	Jan. 21, 2013	Jan. 20, 2014

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 12, 2013


5.6.3 TEST PROCEDURE

1. Set the RBW = 3 kHz, VBW = 10 kHz, Detector = peak.
2. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
3. Use the peak marker function to determine the maximum amplitude level.

5.6.4 DEVIATION FROM TEST STANDARD

No deviation

5.6.5 TEST SETUP



5.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

5.6.7 TEST RESULTS

802.11a

CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS /FAIL
149	5745	-4.75	8	PASS
157	5785	-4.47	8	PASS
165	5825	-5.30	8	PASS

802.11n (HT20)

TX chain	Channel	FREQ. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	149	5745	-5.35	3.01	-2.34	7.2	PASS
	157	5785	-6.58	3.01	-3.57	7.2	PASS
	165	5825	-7.36	3.01	-4.35	7.2	PASS
1	149	5745	-8.59	3.01	-5.58	7.2	PASS
	157	5785	-8.39	3.01	-5.38	7.2	PASS
	165	5825	-10.43	3.01	-7.42	7.2	PASS

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 6.80\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(6.80-6) = 7.2\text{dBm}$.

802.11n (HT40)

TX chain	Channel	FREQ. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	151	5755	-6.02	3.01	-3.01	7.2	PASS
	159	5795	-6.60	3.01	-3.59	7.2	PASS
1	151	5755	-8.22	3.01	-5.21	7.2	PASS
	159	5795	-8.71	3.01	-5.70	7.2	PASS

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 6.80\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(6.80-6) = 7.2\text{dBm}$.



A D T

5.7 CONDUCTED OUT-BAND EMISSION MEASUREMENT

5.7.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100036	Jan. 21, 2013	Jan. 20, 2014

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 12, 2013

5.7.3 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.


Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

5.7.4 DEVIATION FROM TEST STANDARD

No deviation

5.7.5 TEST SETUP



5.7.6 EUT OPERATING CONDITION

Same as Item 4.3.6

5.7.7 TEST RESULTS



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.





A D T

802.11a



CH 149



CH 157



CH 165






A D T


802.11n (HT20)

CHAIN (0)


CH 149



CH 157



CH 165







A D T

CHAIN (1)


CH 149



CH 157



CH 165






A D T


802.11n (HT40)

CHAIN (0)

CH 151



CH 159









A D T

CHAIN (1)

CH 151



CH 159



6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

8. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---