

WCDMA

Data List								
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.	Det
WCDMA_Band II_5M_CH9538	35.8229	-55.97	-59.45	-3.48	-13.00	46.45	V	PK
	62.5113	-55.16	-65.26	-10.10	-13.00	52.26	V	PK
	86.2881	-52.87	-58.03	-5.16	-13.00	45.03	V	PK
	119.7699	-57.54	-60.03	-2.49	-13.00	47.03	V	PK
	245.933	-57.20	-57.25	-0.05	-13.00	44.25	H	PK
	875.7779	-69.64	-61.36	8.28	-13.00	48.36	H	PK
	3814.0000	-60.94	-46.09	14.85	-13.00	33.09	V	PK
	5721.0000	-60.13	-41.67	18.46	-13.00	28.67	V	PK
	7628.0000	-62.16	-38.46	23.70	-13.00	25.46	V	PK
	9535.0000	-68.19	-44.92	23.27	-13.00	31.92	H	PK
	11442.0000	-68.34	-42.87	25.47	-13.00	29.87	V	PK
	13349.0000	-69.14	-42.88	26.26	-13.00	29.88	V	PK
	15256.0000	-70.26	-41.30	28.96	-13.00	28.30	V	PK
	17163.0000	-69.86	-36.75	33.11	-13.00	23.75	H	PK
WCDMA_Band IV_5M_CH1312	35.8229	-54.80	-58.28	-3.48	-13.00	45.28	V	PK
	62.5113	-56.16	-66.26	-10.10	-13.00	53.26	V	PK
	119.7699	-57.58	-60.07	-2.49	-13.00	47.07	V	PK
	235.7429	-52.30	-56.58	-4.28	-13.00	43.58	H	PK
	470.1151	-62.57	-62.57	0.00	-13.00	49.57	H	PK
	882.5713	-70.29	-61.61	8.68	-13.00	48.61	H	PK
	3424.0000	-58.89	-46.13	12.76	-13.00	33.13	V	PK
	5136.0000	-60.97	-42.94	18.03	-13.00	29.94	V	PK
	6848.0000	-62.30	-40.33	21.97	-13.00	27.33	H	PK
	8560.0000	-67.25	-45.09	22.16	-13.00	32.09	H	PK
	10272.0000	-68.74	-43.91	24.83	-13.00	30.91	V	PK
	11984.0000	-69.89	-44.30	25.59	-13.00	31.30	V	PK
	13696.0000	-69.62	-43.38	26.24	-13.00	30.38	V	PK
	15480.0000	-69.27	-39.99	29.28	-13.00	26.99	V	PK

	17120.0000	-70.30	-37.03	33.27	-13.00	24.03	H	PK
WCDMA_Band V_5M_CH4233	35.8229	-57.68	-61.16	-3.48	-13.00	48.16	V	PK
	61.0555	-54.19	-65.08	-10.89	-13.00	52.08	V	PK
	81.921	-52.60	-59.77	-7.17	-13.00	46.77	V	PK
	119.7699	-56.88	-59.37	-2.49	-13.00	46.37	V	PK
	239.1396	-53.59	-56.75	-3.16	-13.00	43.75	H	PK
	469.6298	-63.84	-63.86	-0.02	-13.00	50.86	H	PK
	1694.0000	-59.60	-43.86	15.74	-13.00	30.86	V	PK
	2541.0000	-60.03	-38.73	21.30	-13.00	25.73	V	PK
	3388.0000	-61.18	-48.20	12.98	-13.00	35.20	V	PK
	4235.0000	-60.92	-45.28	15.64	-13.00	32.28	V	PK
	5082.0000	-60.84	-42.74	18.10	-13.00	29.74	H	PK
	5929.0000	-61.38	-41.78	19.60	-13.00	28.78	V	PK
	6776.0000	-62.14	-40.63	21.51	-13.00	27.63	H	PK
	7623.0000	-63.19	-39.66	23.53	-13.00	26.66	V	PK
	8470.0000	-67.02	-44.81	22.21	-13.00	31.81	H	PK

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal

LTE

Data List								
Test Mode	Frequency [MHz]	Reading [dBm]	Level [dBm]	Factor [dB]	Limit [dBm]	Margin [dB]	Pol.	Det
LTE_B2_20M_CH18900	41.6458	-52.71	-54.72	-2.01	-13.00	41.72	H	PK
	59.5998	-53.09	-58.48	-5.39	-13.00	45.48	H	PK
	112.006	-51.77	-48.96	2.81	-13.00	35.96	V	PK
	251.7559	-52.36	-50.18	2.18	-13.00	37.18	H	PK
	442.4562	-51.17	-52.50	-1.33	-13.00	39.50	H	PK
	879.6598	-50.45	-41.63	8.82	-13.00	28.63	H	PK
	3742.0000	-60.57	-46.11	14.46	-13.00	33.11	V	PK
	5613.0000	-57.69	-38.68	19.01	-13.00	25.68	V	PK
	7848.0000	-63.15	-39.42	23.73	-13.00	26.42	H	PK
	9355.0000	-67.85	-45.28	22.57	-13.00	32.28	H	PK
	11226.0000	-68.64	-44.08	24.56	-13.00	31.08	V	PK
	13097.0000	-69.51	-43.30	26.21	-13.00	30.30	V	PK
	14968.0000	-67.56	-39.31	28.25	-13.00	26.31	V	PK
	16839.0000	-68.44	-35.74	32.70	-13.00	22.74	V	PK
LTE_B4_20M_CH20300	35.8229	-56.56	-60.04	-3.48	-13.00	47.04	V	PK
	90.1701	-58.03	-61.66	-3.63	-13.00	48.66	V	PK
	119.7699	-58.92	-61.41	-2.49	-13.00	48.41	V	PK
	236.7134	-57.20	-61.37	-4.17	-13.00	48.37	H	PK
	468.1741	-60.54	-60.64	-0.10	-13.00	47.64	H	PK
	884.9975	-76.40	-67.83	8.57	-13.00	54.83	H	PK
	3472.0000	-59.06	-45.95	13.11	-13.00	32.95	V	PK
	5208.0000	-60.50	-42.28	18.22	-13.00	29.28	V	PK
	6944.0000	-61.50	-39.45	22.05	-13.00	26.45	H	PK
	8680.0000	-66.39	-44.42	21.97	-13.00	31.42	V	PK
	10416.0000	-68.31	-43.29	25.02	-13.00	30.29	V	PK
	12152.0000	-67.70	-43.12	24.58	-13.00	30.12	H	PK
	13888.0000	-69.09	-42.61	26.48	-13.00	29.61	V	PK
	15624.0000	-69.09	-39.44	29.65	-13.00	26.44	V	PK

	17360.0000	-68.54	-34.16	34.38	-13.00	21.16	H	PK
LTE_B12_10M_CH23130	33.3967	-52.61	-54.34	-1.73	-13.00	41.34	H	PK
	53.7769	-52.84	-57.76	-4.92	-13.00	44.76	H	PK
	107.6388	-51.85	-49.90	1.95	-13.00	36.90	V	PK
	252.7264	-52.39	-50.52	1.87	-13.00	37.52	H	PK
	631.7008	-50.52	-48.10	2.42	-13.00	35.10	H	PK
	888.8794	-50.94	-42.70	8.24	-13.00	29.70	H	PK
	1412.0000	-58.96	-43.74	15.22	-13.00	30.74	V	PK
	2118.0000	-60.05	-39.78	20.27	-13.00	26.78	H	PK
	2824.0000	-58.67	-35.88	22.79	-13.00	22.88	H	PK
	3530.0000	-60.86	-47.71	13.15	-13.00	34.71	V	PK
	4236.0000	-60.90	-45.34	15.56	-13.00	32.34	H	PK
	4942.0000	-61.57	-44.87	16.70	-13.00	31.87	H	PK
	5648.0000	-61.38	-42.46	18.92	-13.00	29.46	V	PK
	6354.0000	-60.98	-41.22	19.76	-13.00	28.22	V	PK
	7060.0000	-62.97	-40.85	22.12	-13.00	27.85	H	PK

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

(3)V=Vertical,H= Horizontal