

## RF Exposure evaluation

Product Description: Bluetooth speaker

Model Number: BT-068

FCC ID: 2AHLIBT-068

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

According to the follow transmitter output power (  $P_t$  ) formula :

$$P_t = (E \times d)^2 / (30 \times g_t)$$

$P_t$ =transmitter output power in watts

$g_t$ =numeric gain of the transmitting antenna (unitless)

$E$ =electric field strength in V/m

$d$ =measurement distance in meters (m)

According to the above test data,

$E_{\text{max}}=95.31 \text{ dBuV/m}=0.058 \text{ V/m}$ ,  $d=3 \text{ m}$ ,  $g_t=1.7$

$$P_t = (E \times d)^2 / (30 \times g_t) = (0.058 \times 3)^2 / (30 \times 1.7) = 0.000594 \text{ W} = 0.6 \text{ mW}$$

The result is rounded to one decimal place for comparison

Worse case is as below: [2480MHz -0.6mW output power]

$(0.6 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 0.189 < 3.0$  for 1-g SAR

Then SAR evaluation is not required

NOTE: For the maximum power, you can refer FCC test report.