

Report No.: SEWM2309000384RG02

Rev.: 01 Page: 1 of 8

TEST REPORT

Application No.: SEWM2309000384RG

Applicant: Quectel Wireless Solutions Co., Ltd.

Address of Applicant: Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin

Road, Minhang District, Shanghai 200233, China

Manufacturer: Quectel Wireless Solutions Co., Ltd.

Address of Manufacturer: Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin

Road, Minhang District, Shanghai 200233, China

EUT Description: LTE-A Module

Model No.: EM061K-GL

Trade Mark: QUECTEL

FCC ID: XMR2023EM061KGL Standards: 47 CFR Part 2.1091


FCC KDB 447498 D01 v06

Date of Receipt: 2023/09/26 (for new report SEWM2309000384RG02)

Date of Issue: 2023/10/10

Test Result: PASS*

Authorized Signature:



Well Wei Wireless Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://mww.sgs.com/en/Erms-and-Conditions/Erms-e-Documents, subject to Terms and Conditions for Electronic Documents at https://mww.sgs.com/en/Terms-and-Conditions/Ferms-e-Document.aspx.Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein, any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000

中国 - 苏州 - 中国 (江苏) 自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980 t (86-512) 62992980

www.sgsgroup.com.cn sgs.china@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SEWM2309000384RG02

Rev.: 01 Page: 2 of 8

Version

Revision Record							
Version Chapter Date Modifier Remark							
01		2023/10/10		Original			

Prepared By	Nick VIII		
	(Nick Hu) / Test Engineer		
Checked By	Stone Ju		
	(Stone Gu) / Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sps.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Felectronic Documents at http://www.sps.com/en/Terms-and-Conditions.frems-b-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document sadvised that information contained hereon reflects the Company's findings at the time of its intermiton only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. For one of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the Attention. To check the authenticity of testing /inspection report & certificate, please contact us at telephone; (86-755) 8307 1443, or email: CND Doccheck@sas.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国・苏州・中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980 www.sgsgroup.com.cn t (86-512) 62992980



Report No.: SEWM2309000384RG02

Rev.: 01 3 of 8 Page:

Contents

1	Ver	rsion	2
		neral Information	
		Client Information Test Facility	
	2.3	General Description of EUT	5
3	RF	Exposure Evaluation	6
	3.1	RF Exposure Compliance Requirement	6
		.1 Limits	
		.2 Test Procedure	
	3.1	.3 EUT RF Exposure Evaluation	7
	3.1	.4 Exposure calculations for multiple sources	8



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Fleetornic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervition only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. Government of the company, any unauthorized alteration, forgery or fatsification of the content or results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CMD.Doccheck@sas.com



Report No.: SEWM2309000384RG02

Rev.: 01 Page: 4 of 8

2 **General Information**

2.1 Client Information

Applicant:	Quectel Wireless Solutions Co., Ltd.
Address of Applicant:	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China
Manufacturer:	Quectel Wireless Solutions Co., Ltd.
Address of Manufacturer:	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

A2LA (Certificate No. 6336.01)

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

Innovation, Science and Economic Development Canada

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

FCC –Designation Number: CN1312

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an

accredited testing laboratory. Designation Number: CN1312.

Test Firm Registration Number: 717327





Report No.: SEWM2309000384RG02

Rev.: 01 Page: 5 of 8

2.3 General Description of EUT

EUT Description:	LTE-A Module							
Model No.:	EM061K-GL	EM061K-GL						
Trade Mark:	QUECTEL							
Hardware Version:	R1.0							
Software Version:	EM061KGLAAR01	A02M2G						
Power Supply:	DC 3.7V							
Antenna Type:	External Antenna PIFA Antenna							
	WCDMA Band II:	0.25dBi	WCDMA Band IV:	1.47dBi				
	WCDMA Band V:	2.68dBi						
	LTE Band 2:	0.25dBi	LTE Band 4:	1.47dBi				
	LTE Band 5:	2.68dBi	LTE Band 7:	2.4dBi				
	LTE Band 12:	1.3dBi	LTE Band 13:	1.3dBi				
	LTE Band 14:	2.42dBi	LTE Band 17:	-0.2dBi				
Antenna Gain:	LTE Band 25:	0.25dBi	LTE Band 26:	2.87dBi				
	LTE Band 30:	-3dBi	LTE Band 38:	2.4dBi				
	LTE Band 41:	2.4dBi	LTE Band 66:	1.47dBi				
	LTE Band 71:	1.22dBi						
	Note:	Note:						
	The antenna gain a manufacturer.	re derived from the	gain information report	provided by the				

As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditio



Report No.: SEWM2309000384RG02

Rev.: 01 Page: 6 of 8

3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm2)	Averaging time (minutes)						
(A) Limits for Occupational/Controlled Exposures										
0.3-3.0	614	1.63	*(100)	6						
3.0-30	1842/f	4.89/f	*(900/f2)	6						
30-300	61.4	0.163	1.0	6						
300-1500	1	1	f/300	6						
1500-100,000	/	1	5	6						
(B) Limits for General P	opulation/Uncontrolled	Exposure							
0.3-1.34	614	1.63	*(100)	30						
1.34-30	824/f	2.19/f	*(180/f2)	30						
30-300	27.5	0.073	0.2	30						
300-1500		1	f/1500	30						
1500-100,000	/	1	1.0	30						

F=frequency in MHz

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4* Pi * R²)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Decument.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgor falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained of 3 days only.

South of No. 6 Pfart, No. 1, Runsteing Read, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000 t (86-512) 62992980 t (86-512) 62992980 www.sgsgroup.com.cn sgs.china@sgs.com

^{*=}Plane-wave equivalent power density



Report No.: SEWM2309000384RG02

Rev.: 01 Page: 7 of 8

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

3.1.3 EUT RF Exposure Evaluation

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	Max Conducted Power (dBm)	EIRP(ERP) (dBm)	EIRP(ERP) Limit (dBm)	Power Density at R = 20 cm (mW/cm2)	Limit (mW/cm2)	Gain according to EIRP(ERP) (dBi)	Gain according to Pd (dBi)	Max Gain Allowed (dBi)	conclusion
WCDMA Band II	1852.4	0.25	25.00	25.25	33.00	0.0666	1.0000	8.00	12.01	8.00	Pass
WCDMA Band VI	1712.4	1.47	25.00	26.47	30.00	0.0883	1.0000	5.00	12.01	5.00	Pass
WCDMA Band V	828.4	2.68	25.00	25.53	38.50	0.1166	0.5523	15.65	9.43	9.43	Pass
LTE Band 2	1850.7	0.25	24.50	24.75	33.00	0.0594	1.0000	8.50	12.51	8.50	Pass
LTE Band 4	1710.7	1.47	24.50	25.97	30.00	0.0787	1.0000	5.50	12.51	5.50	Pass
LTE Band 5	824.7	2.68	24.50	25.03	38.45	0.1039	0.5498	16.10	9.91	9.91	Pass
LTE Band 7	2502.5	2.40	24.00	26.40	33.00	0.0868	1.0000	9.00	13.01	9.00	Pass
LTE Band 12	699.7	1.30	24.50	23.65	34.77	0.0756	0.4665	12.42	9.20	9.20	Pass
LTE Band 13	779.5	1.30	24.50	23.65	34.77	0.0756	0.5197	12.42	9.66	9.66	Pass
LTE Band 14	790.5	2.42	24.50	24.77	34.77	0.0979	0.5270	12.42	9.73	9.73	Pass
LTE Band 17	706.5	-0.20	24.50	22.15	34.77	0.0535	0.4710	12.42	9.24	9.24	Pass
LTE Band 25	1850.7	0.25	24.50	24.75	33.00	0.0594	1.0000	8.50	12.51	8.50	Pass
LTE Band 26 (814-824)	814.7	2.87	24.50	25.22	NA	0.1086	0.5431	NA	9.86	9.86	Pass
LTE Band 26 (824-849)	824.7	2.87	24.50	25.22	38.45	0.1086	0.5498	16.10	9.91	9.91	Pass
LTE Band 30	2307.5	-3.00	23.00	20.00	23.98	0.0199	1.0000	0.98	14.01	0.98	Pass
LTE Band 38	2572.5	2.40	24.00	26.40	33.00	0.0868	1.0000	9.00	13.01	9.00	Pass
LTE Band 41	2498.5	2.40	24.00	26.40	33.00	0.0868	1.0000	9.00	13.01	9.00	Pass
LTE Band 66	1710.7	1.47	24.50	25.97	30.00	0.0787	1.0000	5.50	12.51	5.50	Pass
LTE Band 71	665.5	1.22	24.50	23.57	34.77	0.0743	0.4437	12.42	8.98	8.98	Pass
Bluetooth	2402.0	5.00	23.00	28.00	NA	0.1255	1.0000	NA	NA	NA	NA
WLAN2.4GHz	2412.0	5.00	23.00	28.00	NA	0.1255	1.0000	NA	NA	NA	NA
WLAN5GHz	5180.0	5.00	23.00	28.00	NA	0.1255	1.0000	NA	NA	NA	NA

Note:

- 1. This MPE analysis is applicable to any collocated transmitters with transmit power for WLAN is less than or equal to 28dBm and for Bluetooth is less than or equal to 28dBm.
- 2. A maximum antenna gain of 5dBi for WLAN/BT has been assumed for all collocated antennas.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://mww.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents subject to Terms and Conditions for Electronic Documents at https://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits to client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forey or falsification of the content on appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained of 3d days only.



Report No.: SEWM2309000384RG02

Rev.: 01 Page: 8 of 8

3.1.4 Exposure calculations for multiple sources

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE in accordance with the provisions of Table(A) and Table(B). To comply with the MPE, the fraction of the MPE in terms of E2, H2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity.

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^{n} \frac{S_i}{MPE_i} \le 1$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration
1	WWAN + WiFi 2.4G + WiFi 5G + Bluetooth

No.	Mode	Power Density (mW/cm²)	MPE Limit (mW/cm²)	Result Ratio	Total Ratio	Limit	Result
	WCDMA Band V	0.1166	0.5523	0.2111		1.0000	Pass
1	Bluetooth	0.1255	1.0000	0.1255	0.5876		
	WiFi 2.4G	0.1255	1.0000	0.1255	0.5676		
	WiFi 5G	0.1255	1.0000	0.1255			

Note: Considering the WWAN module collocation with the WLAN and Bluetooth transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 3 collocated transmitters is compliant.

---End of Report---



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its Intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exencise to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained of days only.