



Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : Ningbo Litesun Electronics Co., Ltd.

Simen Town, Yuyao City, Zhejiang, 315472, China

Manufacturer : Ningbo Litesun Electronics Co., Ltd.

Simen Town, Yuyao City, Zhejiang, 315472, China

Product Name : Relocatable Power Taps with Surge Protector

Type/Model: LTS-4G-W

TEST RESULT : PASS

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The S = PG / $(4\pi R^2)$

Where $S = power density in mW/cm^2$

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

For WIFI, as we can see from the test report 171201127SHA-001

Frequency band (MHz)	Max power		Antenna Gain		R	S
2400-2483.5MHz	15.94dBm	39.26mW	3.0dBi	1.995	20cm	0.01558

The sum of the MPE ratios = 0.01558mW/cm²

This level is below the simultaneous transmission MPE test exclusion requirements (≤ 1.0).

Date of issue: Jan 23, 2018

Prepared by:

Teddy Yin (*Project Engineer*)

Teddy yin

Reviewed by:

Daniel Zhao (Reviewer)



Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.