

VARIANT FCC TEST REPORT

(Part 15, Subpart C)



| | |
|------------|---|
| Applicant: | Gosuncn Technology Group Co., Ltd. |
| Address: | 6F, 2819 KaiChuang Blvd., Science Town, Huangpu District, Guangzhou City, Guangdong, China. |

| | |
|--------------------------|---|
| Manufacturer or Supplier | Gosuncn Technology Group Co., Ltd. |
| Address | 6F, 2819 KaiChuang Blvd., Science Town, Huangpu District, Guangzhou City, Guangdong, China. |
| Product | Automatic Database Diagnostic Monitor (LTE OBD II Dongle) |
| Brand Name | GOSUNCN |
| Model Name | GD500A |
| FCC ID | 2APNR-GD500 |
| Date of tests | Aug. 01, 2018 ~ Sep. 21, 2021 |

The tests have been carried out according to the requirements of the following standard:

- ☒ **FCC Part 15, Subpart C, Section 15.247**
- ☒ **ANSI C63.10-2013**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

| | |
|--|--|
| Prepared by Roger Li Engineer / Mobile Department | Approved by Sam Tung Manager / Mobile Department |
|  Date: Sep. 22, 2021 |  Date: Sep. 22, 2021 |

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

| | |
|--|-----------|
| RELEASE CONTROL RECORD | 4 |
| 1 SUMMARY OF TEST RESULTS..... | 5 |
| 1.1 MEASUREMENT UNCERTAINTY | 5 |
| 2 GENERAL INFORMATION | 6 |
| 2.1 GENERAL DESCRIPTION OF EUT | 6 |
| 2.2 DESCRIPTION OF TEST MODES | 8 |
| 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST | 9 |
| 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... | 9 |
| 2.3 DUTY CYCLE OF TEST SIGNAL | 11 |
| 2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS | 11 |
| 2.5 DESCRIPTION OF SUPPORT UNITS | 11 |
| 3 TEST TYPES AND RESULTS..... | 12 |
| 3.1 CONDUCTED EMISSION MEASUREMENT | 12 |
| 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT | 12 |
| 3.1.2 TEST INSTRUMENTS..... | 12 |
| 3.1.3 TEST PROCEDURES | 13 |
| 3.1.4 DEVIATION FROM TEST STANDARD | 13 |
| 3.1.5 TEST SETUP | 14 |
| 3.1.6 EUT OPERATING CONDITIONS | 14 |
| 3.1.7 TEST RESULTS | 15 |
| 3.2 RADIATED EMISSION MEASUREMENT | 16 |
| 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT | 16 |
| 3.2.2 TEST INSTRUMENTS..... | 17 |
| 3.2.3 TEST PROCEDURES | 18 |
| 3.2.4 DEVIATION FROM TEST STANDARD | 18 |
| 3.2.5 TEST SETUP | 19 |
| 3.2.6 EUT OPERATING CONDITIONS | 20 |
| 3.2.7 TEST RESULTS | 21 |
| 3.3 6 DB BANDWIDTH MEASUREMENT | 24 |
| 3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT | 24 |
| 3.3.2 TEST INSTRUMENTS..... | 24 |
| 3.3.3 TEST PROCEDURE..... | 24 |
| 3.3.4 DEVIATION FROM TEST STANDARD | 25 |



| | | |
|---------|---|-----------|
| 3.3.5 | TEST SETUP | 25 |
| 3.3.6 | EUT OPERATING CONDITIONS | 25 |
| 3.3.7 | TEST RESULTS | 26 |
| 3.4 | CONDUCTED OUTPUT POWER..... | 27 |
| 3.4.1 | LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT | 27 |
| 3.4.2 | TEST SETUP | 27 |
| 3.4.3 | TEST INSTRUMENTS..... | 27 |
| 3.4.4 | TEST PROCEDURES | 27 |
| 3.4.5 | DEVIATION FROM TEST STANDARD | 27 |
| 3.4.6 | EUT OPERATING CONDITIONS | 27 |
| 3.4.7 | TEST RESULTS | 28 |
| 3.4.7.1 | MAXIMUM PEAK OUTPUT POWER | 28 |
| 3.4.7.2 | AVERAGE OUTPUT POWER (FOR REFERENCE)..... | 29 |
| 3.5 | POWER SPECTRAL DENSITY MEASUREMENT | 30 |
| 3.5.1 | LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT | 30 |
| 3.5.2 | TEST SETUP | 30 |
| 3.5.3 | TEST INSTRUMENTS..... | 30 |
| 3.5.4 | TEST PROCEDURE..... | 30 |
| 3.5.5 | DEVIATION FROM TEST STANDARD | 30 |
| 3.5.6 | EUT OPERATING CONDITION | 30 |
| 3.5.7 | TEST RESULTS | 31 |
| 3.6 | OUT OF BAND EMISSION MEASUREMENT | 32 |
| 3.6.1 | LIMITS OF OUT OF BAND EMISSION MEASUREMENT | 32 |
| 3.6.2 | TEST SETUP | 32 |
| 3.6.3 | TEST INSTRUMENTS..... | 32 |
| 3.6.4 | TEST PROCEDURE..... | 32 |
| 3.6.5 | DEVIATION FROM TEST STANDARD | 33 |
| 3.6.6 | EUT OPERATING CONDITION | 33 |
| 3.6.7 | TEST RESULTS | 33 |
| 4 | PHOTOGRAPHS OF THE TEST CONFIGURATION | 34 |
| 5 | APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB | 35 |



**BUREAU
VERITAS**

Test Report No.: RF210816W001-1

RELEASE CONTROL RECORD

| ISSUE NO. | REASON FOR CHANGE | DATE ISSUED |
|----------------|--|---------------|
| RF180205W003-1 | Original release | Aug. 23, 2018 |
| RF210816W001-1 | Based on the original RF180205W003-1 added VOLTE functionality and two DC Power Cables. Verify the RSE replace worse data for 802.11g Channel 6, Other reference original report | Sep. 22, 2021 |



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) | | | |
|---|----------------------------------|--------|--|
| STANDARD SECTION | TEST TYPE AND LIMIT | RESULT | REMARK |
| 15.207 | AC Power Conducted Emission | PASS | N/A |
| 15.205 15.209 | Radiated Emissions | PASS | Meet the requirement of limit. Minimum passing margin is -9.34dB at 2483.5MHz. |
| 15.247(d) | Out of band Emission Measurement | PASS | N/A |
| 15.247(a)(2) | 6dB bandwidth | PASS | N/A |
| 15.247(b) | Conducted Output power | PASS | N/A |
| 15.247(e) | Power Spectral Density | PASS | N/A |
| 15.203 | Antenna Requirement | PASS | N/A |

Note: N/A refer to original report RF180205W003-1

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in ETSI TR 100 028-2001:

| MEASUREMENT | FREQUENCY | UNCERTAINTY |
|---------------------|---------------|-------------|
| Conducted emissions | 9kHz~30MHz | 2.66dB |
| Radiated emissions | 9KHz ~ 30MHz | 2.68dB |
| | 30MHz ~ 1GMHz | 3.26dB |
| | 1GHz ~ 18GHz | 4.48dB |
| | 18GHz ~ 40GHz | 4.12dB |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | |
|------------------------------|--|
| PRODUCT | Automatic Database Diagnostic Monitor (LTE OBD II Dongle) |
| BRAND NAME | GOSUNCN |
| MODEL NAME | GD500A |
| NOMINAL VOLTAGE | 12/24Vdc (adapter or host equipment) 3.7Vdc (Li-ion, battery) |
| MODULATION TECHNOLOGY | DSSS, OFDM, DTS |
| MODULATION TYPE | CCK, DQPSK, DBPSK for DSSS BT-LE(GFSK) for DTS |
| TRANSMISSION RATE | 802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n: up to 65 Mbps BT_LE: 1 Mbps |
| OPERATING FREQUENCY | 2412-2462MHz for 11b/g/n(HT20) 2402-2480MHz for BT-LE(GFSK) |
| MAX. OUTPUT POWER | WLAN: 163.682mW (Maximum) BT-LE: 1.250mW (Maximum) |
| ANTENNA TYPE | PIFA Antenna with 2.8dBi gain |
| HW VERSION | SD6500.H03 |
| SW VERSION | EN_SD6500V1.0.0B01 |
| I/O PORTS | Refer to user's manual |
| CABLE SUPPLIED | N/A |

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

| MODULATION MODE | TX/RX FUNCTION |
|-----------------|----------------|
| 802.11b | 1TX /1RX |
| 802.11g | 1TX /1RX |
| 802.11n (20MHz) | 1TX /1RX |
| BT_LE | 1TX /1RX |



**BUREAU
VERITAS**

Test Report No.: RF210816W001-1

3. There two configurations for this project:

| EUT | Configurations |
|-------|-----------------|
| EUT 1 | SIM |
| EUT 2 | E-SIM + Battery |

4. Add two OBD extension cords, and select one of them to ship
5. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

| CHANNEL | FREQUENCY | CHANNEL | FREQUENCY |
|---------|-----------|---------|-----------|
| 1 | 2412 MHz | 7 | 2442 MHz |
| 2 | 2417 MHz | 8 | 2447 MHz |
| 3 | 2422 MHz | 9 | 2452 MHz |
| 4 | 2427 MHz | 10 | 2457 MHz |
| 5 | 2432 MHz | 11 | 2462 MHz |
| 6 | 2437 MHz | | |

40 channels are provided for BT-LE (GFSK):

| CHANNEL | FREQ. (MHZ) | CHANNEL | FREQ. (MHZ) | CHANNEL | FREQ. (MHZ) | CHANNEL | FREQ. (MHZ) |
|---------|----------------|---------|----------------|---------|----------------|---------|----------------|
| 0 | 2402 | 10 | 2422 | 20 | 2442 | 30 | 2462 |
| 1 | 2404 | 11 | 2424 | 21 | 2444 | 31 | 2464 |
| 2 | 2406 | 12 | 2426 | 22 | 2446 | 32 | 2466 |
| 3 | 2408 | 13 | 2428 | 23 | 2448 | 33 | 2468 |
| 4 | 2410 | 14 | 2430 | 24 | 2450 | 34 | 2470 |
| 5 | 2412 | 15 | 2432 | 25 | 2452 | 35 | 2472 |
| 6 | 2414 | 16 | 2434 | 26 | 2454 | 36 | 2474 |
| 7 | 2416 | 17 | 2436 | 27 | 2456 | 37 | 2476 |
| 8 | 2418 | 18 | 2438 | 28 | 2458 | 38 | 2478 |
| 9 | 2420 | 19 | 2440 | 29 | 2460 | 39 | 2480 |



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

| EUT CONFIGURE MODE | APPLICABLE TO | | | | MODE |
|--------------------------|---------------|-------|-----|------|------|
| | RE<1G | RE≥1G | PLC | APCM | |
| - | √ | √ | N/A | N/A | - |

Where

RE<1G: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|---------|----------------------|-------------------|--------------------------|--------------------|------------------------|
| 802.11g | 1 to 11 | 6 | OFDM | BPSK | 6.0 |

**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

| MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|---------|-------------------|----------------|-----------------------|-----------------|------------------|
| 802.11g | 1 to 11 | 6 | OFDM | BPSK | 6.0 |

TEST CONDITION:

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | TEST VOLTAGE | TESTED BY |
|---------------|--------------------------|---------------------|--------------|
| RE<1G | 22deg. C, 54%RH | DC 12V from adaptor | Vincent Chen |
| RE≥1G | 22deg. C, 54%RH | DC 12V from adaptor | Vincent Chen |



2.3 Duty Cycle of Test Signal

Reference original report RF180205W003-1

2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v04

ANSI C63.10-2013

Note:

1. All test items have been performed and recorded as per the above standards.

2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND | MODEL NO. | SERIAL NO. | FCC ID |
|-----|---------|-------|-----------|------------|--------|
| 1 | PC | HP | A6608CN | 3CR83825X3 | N/A |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|---|
| 1 | AC Line: Unshielded, Detachable 1.5m |



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

| FREQUENCY OF EMISSION (MHz) | CONDUCTED LIMIT (dB μ V) | |
|-----------------------------|------------------------------|----------|
| | Quasi-peak | Average |
| 0.15 ~ 0.5 | 66 to 56 | 56 to 46 |
| 0.5 ~ 5 | 56 | 46 |
| 5 ~ 30 | 60 | 50 |

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
|---------------------|---------------|-----------|------------|------------|------------|
| EMI Test Receiver | Rohde&Schwarz | ESR3 | 101900 | Mar. 15,18 | Mar. 14,19 |
| EMC32 test software | Rohde&Schwarz | EMC32 | NA | NA | NA |
| LISN network | Rohde&Schwarz | ENV216 | 101922 | Sep. 18,17 | Sep. 17,18 |
| EMI Test Receiver | Rohde&Schwarz | ESR3 | 101900 | Mar. 03,21 | Mar. 02,22 |
| EMC32 test software | Rohde&Schwarz | EMC32 | NA | NA | NA |
| LISN network | Rohde&Schwarz | ENV216 | 101922 | Feb. 22,21 | Feb. 21,22 |

NOTE:

1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



Test Report No.: RF210816W001-1

3.1.7 TEST RESULTS

Reference original report RF180205W003-1



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

| FREQUENCIES (MHz) | FIELD STRENGTH (microvolts/meter) | MEASUREMENT DISTANCE (meters) |
|------------------------------|--|--|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.2.2 TEST INSTRUMENTS

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
|----------------------------|--------------|------------------------------|-----------------------------|-------------|-------------|
| 3m Semi-anechoic Chamber | ETS-LINDGREN | 9m*6m*6m | Euroshieldpn-CT0001143-1216 | Apr. 21,18 | Apr. 20,19 |
| Bilog Antenna | ETS-LINDGREN | 3143B | 00161965 | Nov. 26,16 | Nov. 25,18 |
| Horn Antenna | ETS-LINDGREN | 3117 | 00168728 | Nov. 26,16 | Nov. 25,18 |
| Loop antenna | Daze | ZN30900A | 0708 | Nov. 20,17 | Nov. 19,18 |
| Horn Antenna (18GHz-40GHz) | N/A | QWH-SL-18-40-K-SG/QMS-003 61 | 15433 | Dec. 16,16 | Dec. 15,18 |
| Test Software | E3 | V 9.160323 | N/A | N/A | N/A |
| Test Software | ADT | ADT_Radiated_V7.6.15.9.2 | N/A | N/A | N/A |
| 10dB Attenuator | JFW/USA | 50HF-010-SMA | 1505 | Jul. 09,18 | Jul. 08,19 |
| MXE EMI Receiver | KEYSIGHT | N9038A-544 | MY54450026 | Mar. 16,18 | Mar. 15,19 |
| Signal Pre-Amplifier | EMSI | EMC 9135 | 980249 | Jul. 09,18 | Jul. 08,19 |
| Signal Pre-Amplifier | EMSI | EMC 012645B | 980257 | Jul. 09,18 | Jul. 08,19 |
| Signal Pre-Amplifier | EMSI | EMC 184045B | 980259 | Jul. 09,18 | Jul. 08,19 |
| 3m Semi-anechoic Chamber | ETS-LINDGREN | 9m*6m*6m | Euroshieldpn-CT0001143-1216 | May. 19,20 | May. 18,23 |
| Bilog Antenna | ETS-LINDGREN | 3143B | 00161965 | Mar. 05,21 | Mar. 04,22 |
| Horn Antenna | ETS-LINDGREN | 3117 | 00168728 | Aug. 21,21 | Aug. 20,22 |
| Horn Antenna (18GHz-40GHz) | N/A | QWH-SL-18-40-K-SG/QMS-003 61 | 15433 | Aug. 26, 20 | Aug. 25, 21 |
| Horn Antenna (18GHz-40GHz) | N/A | QWH-SL-18-40-K-SG/QMS-003 61 | 15433 | Aug. 26, 21 | Aug. 25, 22 |
| Test Software | E3 | V 9.160323 | N/A | N/A | N/A |
| Test Software | ADT | ADT_Radiated_V7.6.15.9.2 | N/A | N/A | N/A |
| 10dB Attenuator | JFW/USA | 50HF-010-SMA | 1505 | Jun. 03,21 | Jun. 02,22 |
| MXE EMI Receiver | KEYSIGHT | N9038A-544 | MY54450026 | Apr. 22,21 | Apr. 21,22 |
| Signal Pre-Amplifier | EMSI | EMC 9135 | 980249 | Jun. 02,21 | Jun. 01,22 |
| Signal Pre-Amplifier | EMSI | EMC 012645B | 980257 | Jun. 03,21 | Jun. 02,22 |
| Signal Pre-Amplifier | EMSI | EMC 184045B | 980259 | Apr. 22,21 | Apr. 21,22 |

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.
 3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


3.2.4 DEVIATION FROM TEST STANDARD

No deviation




3.2.5 TEST SETUP

< Frequency Range below 30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



3.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

9 KHz – 30 MHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:


802.11g

| | | | |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL | TX Channel 6 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz | | |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | | | |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|--------|
| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK |
| 31.94 | 30.95 | 51.91 | 40 | -9.05 | 15.76 | 0.82 | 37.54 | 200 | 269 | QP |
| 121.06 | 21.95 | 49.86 | 43.5 | -21.55 | 7.33 | 1.69 | 36.93 | 200 | 334 | QP |
| 154.37 | 24.12 | 49.35 | 43.5 | -19.38 | 9.64 | 1.9 | 36.77 | 200 | 155 | QP |
| 185.36 | 31.82 | 56.43 | 43.5 | -11.68 | 9.95 | 2.09 | 36.65 | 200 | 89 | QP |
| 250.68 | 28.39 | 50.05 | 46 | -17.61 | 12.41 | 2.45 | 36.52 | 200 | 134 | QP |
| 345.69 | 27.72 | 46.48 | 46 | -18.28 | 14.92 | 2.92 | 36.6 | 200 | 48 | QP |

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.





**BUREAU
VERITAS**


Test Report No.: RF210816W001-1

| | | | |
|------------------------|--------------|--------------------------|-----------------|
| CHANNEL | TX Channel 6 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz | | |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | | | |
|---|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|--------|
| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK |
| 55.22 | 25.78 | 55.55 | 40 | -14.22 | 6.45 | 1.13 | 37.35 | 100 | 95 | QP |
| 85.37 | 23.92 | 52.83 | 40 | -16.08 | 6.76 | 1.42 | 37.09 | 100 | 30 | QP |
| 156.34 | 27.25 | 52.27 | 43.5 | -16.25 | 9.83 | 1.91 | 36.76 | 100 | 116 | QP |
| 210.94 | 33.35 | 57.06 | 43.5 | -10.15 | 10.6 | 2.23 | 36.54 | 100 | 342 | QP |
| 270.65 | 24.75 | 46.05 | 46 | -21.25 | 12.65 | 2.56 | 36.51 | 100 | 268 | QP |
| 425.26 | 34.46 | 50.51 | 46 | -11.54 | 17.5 | 3.23 | 36.78 | 100 | 196 | QP |

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.





**BUREAU
VERITAS**

Test Report No.: RF210816W001-1

ABOVE 1GHz WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

802.11g

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 6 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M | | | | | | | | | | |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK |
| 2390 | 58.03 | 63.51 | 74 | -15.97 | 32.29 | 8.15 | 45.92 | 252 | 320 | Peak |
| 2390 | 42.93 | 48.41 | 54 | -11.07 | 32.29 | 8.15 | 45.92 | 252 | 320 | Average |
| 2437 | 106.18 | 111.51 | | | 32.34 | 8.24 | 45.91 | 252 | 320 | Peak |
| 2437 | 100.6 | 105.93 | | | 32.34 | 8.24 | 45.91 | 252 | 320 | Average |
| 2483.5 | 59.79 | 64.98 | 74 | -14.21 | 32.38 | 8.32 | 45.89 | 252 | 320 | Peak |
| 2483.5 | 44.66 | 49.85 | 54 | -9.34 | 32.38 | 8.32 | 45.89 | 252 | 320 | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M | | | | | | | | | | |
| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK |
| 2390 | 56.33 | 61.81 | 74 | -17.67 | 32.29 | 8.15 | 45.92 | 100 | 282 | Peak |
| 2390 | 42.39 | 47.87 | 54 | -11.61 | 32.29 | 8.15 | 45.92 | 100 | 282 | Average |
| 2437 | 105.51 | 110.84 | | | 32.34 | 8.24 | 45.91 | 100 | 282 | Peak |
| 2437 | 95.19 | 100.52 | | | 32.34 | 8.24 | 45.91 | 100 | 282 | Average |
| 2483.5 | 56.22 | 61.41 | 74 | -17.78 | 32.38 | 8.32 | 45.89 | 100 | 282 | Peak |
| 2483.5 | 43.52 | 48.71 | 54 | -10.48 | 32.38 | 8.32 | 45.89 | 100 | 282 | Average |

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



3.3 6 dB BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

3.3.2 TEST INSTRUMENTS

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
|---------------------|--------------|------------|------------|------------|------------|
| Power Meter | ANRITSU | ML2495A | 1506002 | Mar. 02,18 | Mar. 01,19 |
| Power Meter | ANRITSU | ML2495A | 1506002 | Apr. 07,21 | Apr. 06,22 |
| EXA Signal Analyzer | KEYSIGHT | N9010A-526 | MY54510322 | Mar. 16,18 | Mar. 15,19 |
| EXA Signal Analyzer | KEYSIGHT | N9010A-526 | MY54510322 | Feb. 25,21 | Feb. 24,22 |
| EXA Signal Analyzer | KEYSIGHT | N9010A-544 | MY54510355 | Mar. 16,18 | Mar. 15,19 |
| EXA Signal Analyzer | KEYSIGHT | N9010A-544 | MY54510355 | Jun. 03,21 | Jun. 02,22 |
| Power Sensor | ANRITSU | MA2411B | 1339352 | Mar. 16,18 | Mar. 15,19 |
| Power Sensor | ANRITSU | MA2411B | 1339352 | Feb. 25,21 | Feb. 24,22 |

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

3.3.3 TEST PROCEDURE


1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



3.3.4 DEVIATION FROM TEST STANDARD

No deviation.

3.3.5 TEST SETUP



3.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: RF210816W001-1

3.3.7 TEST RESULTS

Reference original report RF180205W003-1




3.4 CONDUCTED OUTPUT POWER

3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: RF210816W001-1

3.4.7 TEST RESULTS

3.4.7.1 MAXIMUM PEAK OUTPUT POWER

Reference original report RF180205W003-1



Test Report No.: RF210816W001-1

3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

Reference original report RF180205W003-1




3.5 POWER SPECTRAL DENSITY MEASUREMENT

3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW $\geq 3 \times$ RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



Test Report No.: RF210816W001-1

3.5.7 TEST RESULTS

Reference original report RF180205W003-1




3.6 OUT OF BAND EMISSION MEASUREMENT

3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

3.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

Reference original report RF180205W003-1



Test Report No.: RF210816W001-1

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF210816W001-1

5 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---