

FCC RF Exposure

EUT Description: **PORTABLE BLUETOOTH CD PLAYER**

Model No.: **PCDBT01**

FCC ID: **2AJMW-PCDBT01**

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max power of channel, including tune - up tolerance, mW)/(min. test separation distance, mm)] • [$\sqrt{f(\text{GHz})}$] ≤ 3.0 for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

Result = $P/D^2 \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn - up power in mW

D = Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

2.4G

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm ²)	SAR Test Exclusion
BT (GFSK)	3.21	3 ± 1	4/2.51	5	0.791	3.0	Pass
BT (π/4DQPSK)	3.00	3 ± 1	4/2.51	5	0.791	3.0	Pass
Note: PK Output power = conducted power. Conducted power see the test report HK1812061887-2E, antenna gain = 0dBi							

Note: Exclusion Thresholds Results = [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [$\sqrt{f(\text{GHz})}$]

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance = 5mm