

FCC PART 15.407 TEST REPORT

For

TECNO MOBILE LIMITED

FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET
FOTAN NT Hong Kong

FCC ID: 2ADYY-KF6

Report Type: Original Report	Product Type: Mobile phone
Report Number: SZ1210205-04282E-00D	
Report Date: 2021-04-07	
Reviewed By: RF Engineer	Jacob Kong
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	7
EQUIPMENT MODIFICATIONS	8
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS.....	9
TEST EQUIPMENT LIST	10
FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION	12
APPLICABLE STANDARD	12
FCC §15.203 – ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
TEST DATA	15
§15.205 & §15.209 & §15.407(B) (1), (4), (6), (7) – UNDESIRABLE EMISSION	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST DATA	20
FCC §15.407(a) (1) – 26 dB & 6dB EMISSION BANDWIDTH.....	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST DATA	32
FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	33

FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	35
APPENDIX	36
APPENDIXA1: EMISSION BANDWIDTH	36
APPENDIXA2: OCCUPIED CHANNEL BANDWIDTH	44
APPENDIXA3: MIN EMISSION BANDWIDTH.....	59
APPENDIXB: MAXIMUM CONDUCTED OUTPUT POWER	67
APPENDIXC: MAXIMUM POWER SPECTRAL DENSITY	68
APPENDIXH: DUTYCYCLE	83

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Mobile phone
Model	KF6
Frequency Range	5G Wi-Fi: 5150-5250 MHz; 5725-5850 MHz
Maximum conducted output power	5150-5250 MHz: 6.69dBm 5725-5850 MHz: 4.78dBm
Modulation Technique	OFDM
Antenna Specification*	1.2 dBi (It is provided by the applicant)
Voltage Range	DC 3.87V from battery or DC 5.0V from adapter
Date of Test	2021-03-09 to 2021-04-04
Sample serial number	SZ1210205-04282E-RF-S1(RSE&CE Test), SZ1210205-04282E-RF-S2(RF Conducted Test) (Assigned by BACL, Shenzhen)
Received date	2021-02-05
Sample/EUT Status	Good condition
Adapter information	Model: U100TSA Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 2.0A

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB789033D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

The EUT can operate in 802.11a/n20/n40/ac20/ac40/ac80 modes.

For 5150-5250MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 802.11a, 802.11n20/ac20 mode: channel 36, 40, 48 were tested; For 802.11n40/ac40 mode: channel 38, 46 were tested. For 802.11ac80 mode, channel 42 was tested.

For 5725-5850MHz Band, 8 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785
151	5755	159	5795
153	5765	161	5805
155	5775	165	5825

For 802.11a, 802.11n20/ac20 mode: channel 149, 157, 165 were tested; For 802.11n40/ac40 mode: channel 151, 159 were tested. For 802.11ac80 mode, channel 155 was tested.

EUT Exercise Software

Test in the engineer mode.

Test frequencies and power level were configured as below:

U-NII	Mode	Frequency (MHz)	Rate (Mbps)	Power Level*
5150 – 5250MHz	802.11 a	5180	6	11
		5200	6	11
		5240	6	11
	802.11 n20	5180	MCS0	11
		5200	MCS0	11
		5240	MCS0	11
	802.11 n40	5190	MCS0	11
		5230	MCS0	11
	802.11 ac20	5180	MCS0	11
		5200	MCS0	11
		5240	MCS0	11
	802.11 ac40	5190	MCS0	11
		5230	MCS0	11
	802.11 ac80	5210	MCS0	11
5725 – 5850MHz	802.11 a	5745	6	11
		5785	6	11
		5825	6	11
	802.11 n20	5745	MCS0	11
		5785	MCS0	11
		5825	MCS0	11
	802.11 n40	5755	MCS0	11
		5795	MCS0	11
	802.11 ac20	5745	MCS0	11
		5785	MCS0	11
		5825	MCS0	11
	802.11 ac40	5755	MCS0	11
		5795	MCS0	11
	802.11 ac80	5775	MCS0	11

Note 1: The worse-case data rates are determined to be as follows for each mode based upon investigations by measuring the output power and PSD across all data rated bandwidths, and modulations.

Note 2: The power level was provided by the applicant.

Duty cycle

Test Result: Pass. Please refer to the Appendix.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Detachable Earphone Cable	1.2	EUT	Earphone
Shielded Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) (1) & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.407(b)(6)& §15.207(a)	Conducted Emissions	Compliance
§15.205& §15.209 &§15.407(b) (1), (4),(7)	Undesirable Emission& Restricted Bands	Compliance
§15.407(a) (1), (5),(e)	26 dB Emission Bandwidth & 6dB Bandwidth	Compliance
§15.407(a)(1),(3)	Conducted Transmitter Output Power	Compliance
§15.407 (a)(1),(3)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2020/08/04	2021/08/03
Rohde & Schwarz	LISN	ENV216	101613	2020/08/04	2021/08/03
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2020/11/29	2021/11/28
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2020/11/29	2021/11/28
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Radiated Emission Test (Below 1G)					
R&S	EMI Test Receiver	ESR3	102455	2020/08/04	2021/08/03
Sonoma instrument	Pre-amplifier	310 N	186238	2020/08/04	2021/08/03
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2020/12/22	2023/12/21
Unknown	Cable 2	RF Cable 2	F-03-EM197	2020/11/29	2021/11/28
Unknown	Cable	Chamber Cable 1	F-03-EM236	2020/11/29	2021/11/28
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR
Radiated Emission Test (Above 1G)					
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2020/08/04	2021/08/03
COM-POWER	Pre-amplifier	PA-122	181919	2020/11/29	2021/11/28
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2020/11/29	2021/11/28
Sunol Sciences	Horn Antenna	3115	9107-3694	2021/01/15	2024/01/14
Insulted Wire Inc.	RF Cable	SPS-2503-3150	02222010	2020/11/29	2021/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2020/11/29	2021/11/28
Ducommun technologies	RF Cable	RG-214	1	2020/11/12	2021/11/12
Ducommun technologies	RF Cable	RG-214	2	2020/11/12	2021/11/12
SNSD	Band Reject filter	BSF5150-5850MN-0899-004	5G filter	2020/04/20	2021/04/20
Ducommun Technologies	Horn antenna	ARH-4223-02	1007726-02 1304	2020/12/06	2023/12/05
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-03	2020/12/06	2023/12/05

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Tonscend Corporation	RF control Unit	JS0806-2	19D8060154	2020/08/04	2021/08/03
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2020/08/04	2021/08/03
Unknown	RF Cable	Unknown	2301 276	2020/11/29	2021/11/28

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

Frequency (MHz)	Maximum Tune-up power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
	(dBm)	(mW)				
5180-5240	6.8	4.79	5	2.2	3.0	Yes
5745-5825	5.0	3.16	5	1.5	3.0	Yes

Result: No Standalone SAR test is required

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement for 5G Wi-Fi, which was permanently attached and the antenna gain is 1.2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Pass

FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (6)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.


All data was recorded in the Quasi-peak and average detection mode.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2021-03-09.


EUT operation mode: Transmitting & Charging

AC 120V/60 Hz, Line:**Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.593210	46.9	9.000	L1	19.8	9.1	56.0
2.918530	44.2	9.000	L1	19.9	11.8	56.0
3.265610	45.5	9.000	L1	19.9	10.5	56.0
3.308770	45.5	9.000	L1	19.9	10.5	56.0
3.734170	47.8	9.000	L1	19.9	8.2	56.0
4.029070	46.8	9.000	L1	19.9	9.2	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.593210	38.5	9.000	L1	19.8	7.5	46.0
2.918530	36.4	9.000	L1	19.9	9.6	46.0
3.265610	38.6	9.000	L1	19.9	7.4	46.0
3.308770	38.8	9.000	L1	19.9	7.2	46.0
3.734170	41.1	9.000	L1	19.9	4.9	46.0
4.029070	39.5	9.000	L1	19.9	6.5	46.0

AC120V, 60 Hz, Neutral:**Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.581390	44.2	9.000	N	19.8	11.8	56.0
2.906350	44.0	9.000	N	19.9	12.0	56.0
3.213790	46.0	9.000	N	19.9	10.0	56.0
3.572990	48.1	9.000	N	19.9	7.9	56.0
3.638770	48.2	9.000	N	19.9	7.8	56.0
4.001610	47.2	9.000	N	19.9	8.8	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.574000	33.8	9.000	N	19.8	12.2	46.0
2.914000	31.6	9.000	N	19.9	14.4	46.0
3.218000	33.9	9.000	N	19.9	12.1	46.0
3.562000	36.0	9.000	N	19.9	10.0	46.0
3.694000	36.4	9.000	N	19.9	9.6	46.0
4.038000	34.8	9.000	N	19.9	11.2	46.0

§15.205 & §15.209 & §15.407(B) (1), (4), (6), (7) – UNDESIRABLE EMISSION**Applicable Standard**

FCC §15.407 (b) (1), (4), (6), (7); §15.209; §15.205;

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.


(4) For transmitters operating in the 5.725-5.85 GHz band:


(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

EUT Setup

Below 1 GHz:



Above 1 GHz:

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure**Radiated Spurious Emission**

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to ANSI C63.10-2013,9.4: For field strength measurements made at other than the distance at which the applicable limit is specified, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance). In some cases, a different distance correction factor may be required;

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left(\frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dBμV/m
E_{Meas}	is the field strength of the emission at the measurement distance, in dBμV/m
d_{Meas}	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1/3) = -9.5$ dB

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data


Environmental Conditions

Temperature:	24~26.1 °C
Relative Humidity:	52~54%
ATM Pressure:	101.0~101.1 kPa

The testing was performed by Kilroy Deng on 2021-03-18 for below 1GHz and by Troy Wang on 2021-03-21 for above 1GHz.

EUT operation mode: Transmitting

30 MHz~1 GHz: (the worst case is 802.11a Mode, 5180MHz)



Critical_Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
59.342500	23.38	40.00	16.62	100.0	V	345.0	-16.5
64.920000	23.86	40.00	16.14	100.0	V	0.0	-16.3
97.900000	26.98	43.50	16.52	200.0	H	277.0	-14.3
575.988750	35.63	46.00	10.37	100.0	V	214.0	-3.8
834.857500	29.43	46.00	16.57	300.0	H	241.0	0.0
947.741250	32.40	46.00	13.60	200.0	H	0.0	1.6

1 ~ 40 GHz:

Note: The test distance is 1m, so the correct factor from 3m to 1m is $20\log(3/1)=9.5\text{dB}$ which was added into the final limit.

5150-5250 MHz:

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11a									
5180 MHz									
5146.82	30.93	PK	245	2.0	H	38.36	69.29	83.5	14.21
5146.82	17.07	Ave.	245	2.0	H	38.36	55.43	63.5	8.07
5357.26	30.89	PK	28	1.1	H	39.09	69.98	83.5	13.52
5357.26	16.91	Ave.	28	1.1	H	39.09	56.00	63.5	7.50
10360.00	44.38	PK	101	1.3	H	17.42	61.80	77.7	15.90
5200 MHz									
10400.00	42.83	PK	85	1.7	H	17.52	60.35	77.7	17.35
5240 MHz									
5148.14	30.45	PK	314	2.4	H	38.36	68.81	83.5	14.69
5148.14	17.05	Ave.	314	2.4	H	38.36	55.41	63.5	8.09
5354.47	30.92	PK	240	1.6	H	39.09	70.01	83.5	13.49
5354.47	16.93	Ave.	240	1.6	H	39.09	56.02	63.5	7.48
10480.00	43.15	PK	315	2.1	H	17.25	60.40	77.7	17.30
802.11n20									
5180 MHz									
5149.50	30.56	PK	307	1.9	H	38.36	68.92	83.5	14.58
5149.50	17.16	Ave.	307	1.9	H	38.36	55.52	63.5	7.98
5352.34	30.65	PK	130	2.2	H	39.09	69.74	83.5	13.76
5352.34	17.34	Ave.	130	2.2	H	39.09	56.43	63.5	7.07
10360.00	43.02	PK	165	1.6	H	17.42	60.44	77.7	17.26
5200 MHz									
10400.00	42.81	PK	353	2.0	H	17.52	60.33	77.7	17.37
5240 MHz									
5147.38	31.82	PK	184	1.0	H	38.36	70.18	83.5	13.32
5147.38	17.22	Ave.	184	1.0	H	38.36	55.58	63.5	7.92
5350.65	32.29	PK	350	1.1	H	39.09	71.38	83.5	12.12
5350.65	17.38	Ave.	350	1.1	H	39.09	56.47	63.5	7.03
10480.00	42.33	PK	178	2.3	H	17.25	59.58	77.7	18.12

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11n40									
5190 MHz									
5147.65	30.41	PK	124	1.6	H	38.36	68.77	83.5	14.73
5147.65	17.71	Ave.	124	1.6	H	38.36	56.07	63.5	7.43
5353.43	31.06	PK	277	1.8	H	39.09	70.15	83.5	13.35
5353.43	17.81	Ave.	277	1.8	H	39.09	56.90	63.5	6.60
10380.00	42.67	PK	91	1.1	H	17.42	60.09	77.7	17.61
5230 MHz									
5146.32	30.24	PK	111	2.4	H	38.36	68.60	83.5	14.90
5146.32	17.70	Ave.	111	2.4	H	38.36	56.06	63.5	7.44
5354.18	31.31	PK	344	1.9	H	39.09	70.40	83.5	13.10
5354.18	17.85	Ave.	344	1.9	H	39.09	56.94	63.5	6.56
10460.00	42.51	PK	309	1.3	H	17.15	59.66	77.7	18.04
802.11ac20									
5180 MHz									
5147.51	30.44	PK	358	1.7	H	38.36	68.80	83.5	14.70
5147.51	17.15	Ave.	358	1.7	H	38.36	55.51	63.5	7.99
5352.37	31.22	PK	33	2.2	H	39.09	70.31	83.5	13.19
5352.37	17.24	Ave.	33	2.2	H	39.09	56.33	63.5	7.17
10360.00	42.62	PK	106	1.7	H	17.42	60.04	77.7	17.66
5200 MHz									
10400.00	42.47	PK	197	2.0	H	17.52	59.99	77.7	17.71
5240 MHz									
5146.14	29.93	PK	135	2.1	H	38.36	68.29	83.5	15.21
5146.14	17.27	Ave.	135	2.1	H	38.36	55.63	63.5	7.87
5352.25	30.78	PK	324	2.1	H	39.09	69.87	83.5	13.63
5352.25	17.28	Ave.	324	2.1	H	39.09	56.37	63.5	7.13
10480.00	42.41	PK	111	1.7	H	17.25	59.66	77.7	18.04
802.11ac40									
5190 MHz									
5148.31	31.27	PK	210	1.4	H	38.36	69.63	83.5	13.87
5148.31	17.54	Ave.	210	1.4	H	38.36	55.90	63.5	7.60
5353.19	30.46	PK	242	2.3	H	39.09	69.55	83.5	13.95
5353.19	17.82	Ave.	242	2.3	H	39.09	56.91	63.5	6.59
10380.00	42.48	PK	180	2.2	H	17.42	59.90	77.7	17.80
5230 MHz									
5147.35	30.61	PK	111	1.5	H	38.36	68.97	83.5	14.53
5147.35	17.51	Ave.	111	1.5	H	38.36	55.87	63.5	7.63
5352.57	31.05	PK	5	1.2	H	39.09	70.14	83.5	13.36
5352.57	17.89	Ave.	5	1.2	H	39.09	56.98	63.5	6.52
10460.00	42.21	PK	267	2.4	H	17.15	59.36	77.7	18.34

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11ac80									
5210MHz									
5148.37	30.20	PK	144	1.4	H	38.36	68.56	83.5	14.94
5148.37	17.81	Ave.	144	1.4	H	38.36	56.17	63.5	7.33
5352.26	31.34	PK	159	1.3	H	39.09	70.43	83.5	13.07
5352.26	17.06	Ave.	159	1.3	H	39.09	56.15	63.5	7.35
10420.00	42.57	PK	305	2.3	H	17.52	60.09	77.7	17.61

5725-5850 MHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBµV/m)	FCC Part 15.407/205/209	
	Reading (dBµV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
802.11a									
5745 MHz									
5649.21	30.67	PK	271	1.5	H	39.46	70.13	77.7	7.57
5698.47	31.48	PK	26	2.5	H	39.49	70.97	113.57	42.60
5718.61	32.69	PK	162	1.8	H	39.49	72.18	119.91	47.73
5724.82	32.77	PK	191	1.6	H	39.49	72.26	131.29	59.03
11590.00	42.75	PK	267	1.8	H	17.51	60.26	83.5	23.24
11590.00	29.42	Ave.	267	1.8	H	17.51	46.93	63.5	16.57
5785 MHz									
11570.00	42.68	PK	218	2.0	H	17.51	60.19	83.5	23.31
11570.00	29.35	Ave.	218	2.0	H	17.51	46.86	63.5	16.64
5825 MHz									
5851.14	36.72	PK	356	1.1	H	39.87	76.59	129.1	52.51
5855.61	33.58	PK	112	2.2	H	39.87	73.45	120.13	46.68
5876.72	32.74	PK	263	2.3	H	39.87	72.61	113.43	40.82
5925.71	33.10	PK	105	1.2	H	39.97	73.07	77.7	4.63
11650.00	42.47	PK	328	1.8	H	16.18	58.65	83.5	24.85
11650.00	29.12	Ave.	328	1.8	H	16.18	45.30	63.5	18.20
802.11n20									
5745 MHz									
5648.64	30.81	PK	87	2.4	H	39.46	70.27	77.7	7.43
5698.53	31.72	PK	228	2.0	H	39.49	71.21	113.61	42.40
5719.42	32.82	PK	203	2.2	H	39.49	72.31	120.14	47.83
5723.79	33.05	PK	100	2.2	H	39.49	72.54	128.94	56.40
11490.00	42.67	PK	57	1.1	H	17.47	60.14	83.5	23.36
11490.00	29.52	Ave.	57	1.1	H	17.47	46.99	63.5	16.51
5785 MHz									
11570.00	42.32	PK	199	2.4	H	17.51	59.83	83.5	23.67
11570.00	29.15	Ave.	199	2.4	H	17.51	46.66	63.5	16.84
5825 MHz									
5851.34	33.81	PK	150	1.1	H	39.87	73.68	128.64	54.96
5856.57	33.24	PK	265	1.2	H	39.87	73.11	119.86	46.75
5875.64	32.91	PK	12	2.0	H	39.87	72.78	114.23	41.45
5926.29	32.60	PK	52	1.7	H	39.97	72.57	77.7	5.13
11650.00	42.53	PK	227	2.5	H	16.18	58.71	83.5	24.79
11650.00	29.02	Ave.	227	2.5	H	16.18	45.20	63.5	18.30

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
802.11n40									
5755 MHz									
5648.67	30.51	PK	208	1.1	H	39.46	69.97	77.7	7.73
5698.32	31.88	PK	353	2.2	H	39.49	71.37	113.46	42.09
5719.16	33.02	PK	303	2.2	H	39.49	72.51	120.06	47.55
5724.82	33.94	PK	287	1.9	H	39.49	73.43	131.29	57.86
11510.00	42.63	PK	265	1.2	H	17.47	60.10	83.5	23.40
11510.00	28.96	Ave.	265	1.2	H	17.47	46.43	63.5	17.07
5795 MHz									
5852.14	33.87	PK	162	1.4	H	39.87	73.74	126.82	53.08
5856.37	33.45	PK	150	1.5	H	39.87	73.32	119.92	46.60
5875.42	32.82	PK	50	1.5	H	39.87	72.69	114.39	41.70
5926.63	32.67	PK	235	2.0	H	39.97	72.64	77.7	5.06
11590.00	42.57	PK	224	2.0	H	17.51	60.08	83.5	23.42
11590.00	28.84	Ave.	224	2.0	H	17.51	46.35	63.5	17.15
802.11ac20									
5745 MHz									
5649.30	30.94	PK	240	1.1	H	39.46	70.40	77.7	7.30
5697.27	31.21	PK	229	2.3	H	39.49	70.70	112.68	41.98
5719.16	31.96	PK	57	1.2	H	39.49	71.45	120.06	48.61
5724.58	32.55	PK	5	2.2	H	39.49	72.04	130.74	58.70
11490.00	42.56	PK	42	2.3	H	17.47	60.03	83.5	23.47
11490.00	29.12	Ave.	42	2.3	H	17.47	46.59	63.5	16.91
5785 MHz									
11570.00	42.37	PK	318	2.1	H	17.51	59.88	83.5	23.62
11570.00	29.04	Ave.	318	2.1	H	17.51	46.55	63.5	16.95
5825 MHz									
5851.24	33.45	PK	285	1.8	H	39.87	73.32	128.87	55.55
5856.15	33.01	PK	77	1.8	H	39.87	72.88	119.98	47.10
5875.40	32.87	PK	323	1.2	H	39.87	72.74	114.4	41.66
5926.36	32.52	PK	306	1.9	H	39.97	72.49	77.7	5.21
11650.00	42.24	PK	106	2.1	H	16.18	58.42	83.5	25.08
11650.00	28.87	Ave.	106	2.1	H	16.18	45.05	63.5	18.45

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
802.11ac40									
5755 MHz									
5648.51	30.82	PK	22	1.3	H	39.46	70.28	77.7	7.42
5697.27	31.05	PK	234	2.2	H	39.49	70.54	112.68	42.14
5718.21	31.96	PK	13	1.7	H	39.49	71.45	119.80	48.35
5724.42	32.68	PK	283	1.5	H	39.49	72.17	130.38	58.21
11510.00	42.73	PK	334	1.7	H	17.47	60.20	83.5	23.30
11510.00	29.02	Ave.	334	1.7	H	17.47	46.49	63.5	17.01
5795 MHz									
5851.16	33.33	PK	174	1.6	H	39.87	73.20	129.06	55.86
5858.38	33.05	PK	194	1.3	H	39.87	72.92	119.35	46.43
5875.92	32.61	PK	298	1.2	H	39.87	72.48	114.02	41.54
5926.43	32.12	PK	266	1.6	H	39.97	72.09	77.7	5.61
11590.00	42.74	PK	198	1.3	H	17.51	60.25	83.5	23.25
11590.00	29.46	Ave.	198	1.3	H	17.51	46.97	63.5	16.53
802.11ac80									
5775 MHz									
5648.37	30.73	PK	235	1.8	H	39.46	70.19	77.7	7.51
5697.28	31.82	PK	327	1.3	H	39.49	71.31	112.69	41.38
5719.65	32.05	PK	61	2.2	H	39.49	71.54	120.20	48.66
5724.38	32.30	PK	6	1.1	H	39.49	71.79	130.29	58.50
5851.65	33.23	PK	16	1.9	H	39.87	73.10	123.38	50.28
5858.53	33.10	PK	272	1.6	H	39.87	72.97	119.31	46.34
5876.42	32.85	PK	32	2.4	H	39.87	72.72	113.6	40.88
5925.49	32.93	PK	192	1.1	H	39.97	72.90	77.7	4.80
11550.00	42.62	PK	170	1.5	H	17.51	60.13	83.5	23.37
11550.00	29.37	Ave.	170	1.5	H	17.51	46.88	63.5	16.62

Note:

Corrected Amplitude = Corrected Factor + Reading


Corrected Factor=Antenna factor (RX) + Cable Loss – Amplifier Factor

Margin = Limit- Corr. Amplitude


All other spurious emissions are 20 dB below the limit or are on the system noise floor level.

Peak


Pre-scan with 802.11a 5180MHz
Horizontal



Date: 21.MAR.2021 14:02:48




Date: 21.MAR.2021 14:40:35




Date: 21.MAR.2021 14:50:23


Vertical



Date: 21.MAR.2021 14:07:47



Date: 21.MAR.2021 14:45:09



Date: 21.MAR.2021 14:55:48

FCC §15.407(a) (1) – 26 dB & 6dB EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure


1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Coco Liu from 2021-03-11 to 2021-04-04.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix


FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER**Applicable Standard**

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

**Test Data****Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Coco Liu from 2021-03-11 to 2021-04-04.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix

FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY

Applicable Standard

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.1.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log(500 \text{ kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Coco Liu on 2021-03-19.

EUT operation mode: Transmitting

Test Result: Pass


Please refer to the Appendix


APPENDIX

AppendixA1: Emission Bandwidth Test Result


TestMode	Antenna	Channel	26db EBW [MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	19.800	---	PASS
		5200	20.000	---	PASS
		5240	19.640	---	PASS
11N20SISO	Ant1	5180	20.120	---	PASS
		5200	20.240	---	PASS
		5240	20.160	---	PASS
11N40SISO	Ant1	5190	42.160	---	PASS
		5230	45.440	---	PASS
11AC20SISO	Ant1	5180	20.160	---	PASS
		5200	20.240	---	PASS
		5240	20.360	---	PASS
11AC40SISO	Ant1	5190	41.200	---	PASS
		5230	40.960	---	PASS
11AC80SISO	Ant1	5210	81.760	---	PASS

Test Graphs






11N20SISO_Ant1_5200




Date: 11.MAR.2021 14:34:44

11N20SISO_Ant1_5240




Date: 11.MAR.2021 14:35:02

11N40SISO_Ant1_5190




Date: 11.MAR.2021 14:36:13

11N40SISO_Ant1_5230




Date: 11.MAR.2021 14:36:31

11AC20SISO_Ant1_5180




Date: 11.MAR.2021 14:13:08

11AC20SISO_Ant1_5200




Date: 11.MAR.2021 14:14:34

11AC20SISO_Ant1_5240




Date: 11.MAR.2021 14:15:35

11AC40SISO_Ant1_5190




Date: 11.MAR.2021 14:22:01

11AC40SISO_Ant1_5230



Date: 11.MAR.2021 14:23:06

11AC80SISO_Ant1_5210




Date: 11.MAR.2021 14:26:58

AppendixA2: Occupied channel bandwidth Test Result


TestMode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	17.383	---	PASS
		5200	17.383	---	PASS
		5240	17.463	---	PASS
		5745	17.582	---	PASS
		5785	18.142	---	PASS
		5825	18.102	---	PASS
11N20	Ant1	5180	18.382	---	PASS
		5200	18.382	---	PASS
		5240	18.382	---	PASS
		5745	18.941	---	PASS
		5785	18.981	---	PASS
		5825	18.861	---	PASS
11N40	Ant1	5190	37.083	---	PASS
		5230	36.923	---	PASS
		5755	38.202	---	PASS
		5795	37.962	---	PASS
11AC20	Ant1	5180	18.102	---	PASS
		5200	18.102	---	PASS
		5240	18.142	---	PASS
		5745	18.581	---	PASS
		5785	18.861	---	PASS
		5825	18.781	---	PASS
11AC40	Ant1	5190	36.603	---	PASS
		5230	36.523	---	PASS
		5755	37.962	---	PASS
		5795	37.722	---	PASS
11AC80	Ant1	5210	75.445	---	PASS
		5775	77.522	---	PASS

Note: No transmitted signal in the 99% bandwidth extends into the U-NII-2A and U-NII-2C band.

Test Graphs




11A_Ant1_5240



Date: 11.MAR.2021 13:49:37

11A_Ant1_5745



Date: 11.MAR.2021 13:52:06

11A_Ant1_5785





Date: 11.MAR.2021 13:56:44


11A_Ant1_5825





Date: 11.MAR.2021 13:58:11
































**AppendixA3: Min emission bandwidth
Test Result**


TestMode	Antenna	Channel	6db EBW [MHz]	Limit[MHz]	Verdict
11A	Ant1	5745	15.200	0.5	PASS
		5785	15.200	0.5	PASS
		5825	15.560	0.5	PASS
11N20	Ant1	5745	15.240	0.5	PASS
		5785	15.200	0.5	PASS
		5825	15.240	0.5	PASS
11N40	Ant1	5755	35.280	0.5	PASS
		5795	35.280	0.5	PASS
11AC20	Ant1	5745	15.200	0.5	PASS
		5785	15.200	0.5	PASS
		5825	15.200	0.5	PASS
11AC40	Ant1	5755	35.280	0.5	PASS
		5795	35.280	0.5	PASS
11AC80	Ant1	5775	75.520	0.5	PASS


Test Graphs

















AppendixB: Maximum conducted output power Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11A	Ant1	5180	6.69	<=23.98	PASS
		5200	6.64	<=23.98	PASS
		5240	6.51	<=23.98	PASS
		5745	4.78	<=30	PASS
		5785	4.31	<=30	PASS
		5825	4.14	<=30	PASS
11N20	Ant1	5180	6.51	<=23.98	PASS
		5200	6.42	<=23.98	PASS
		5240	6.44	<=23.98	PASS
		5745	4.62	<=30	PASS
		5785	4.18	<=30	PASS
		5825	3.50	<=30	PASS
11N40	Ant1	5190	6.32	<=23.98	PASS
		5230	6.16	<=23.98	PASS
		5755	4.14	<=30	PASS
		5795	3.91	<=30	PASS
11AC20	Ant1	5180	6.00	<=23.98	PASS
		5200	6.01	<=23.98	PASS
		5240	6.11	<=23.98	PASS
		5745	4.16	<=30	PASS
		5785	3.76	<=30	PASS
		5825	3.57	<=30	PASS
11AC40	Ant1	5190	6.31	<=23.98	PASS
		5230	6.19	<=23.98	PASS
		5755	4.20	<=30	PASS
		5795	3.93	<=30	PASS
11AC80	Ant1	5210	6.58	<=23.98	PASS
		5775	4.26	<=30	PASS


AppendixC: Maximum power spectral density Test Result

TestMode	Antenna	Channel	Result [dBm/MHz]	Limit[dBm/MHz]	Verdict
11A	Ant1	5180	1.27	<=11	PASS
		5200	0.56	<=11	PASS
		5240	0.89	<=11	PASS
		5745	-2.74	<=30	PASS
		5785	-2.99	<=30	PASS
		5825	-2.83	<=30	PASS
11N20	Ant1	5180	0.5	<=11	PASS
		5200	-0.07	<=11	PASS
		5240	0.49	<=11	PASS
		5745	-2.65	<=30	PASS
		5785	-3.54	<=30	PASS
		5825	-3.65	<=30	PASS
11N40	Ant1	5190	-2.7	<=11	PASS
		5230	-2.78	<=11	PASS
		5755	-6.41	<=30	PASS
		5795	-6.54	<=30	PASS
11AC20	Ant1	5180	0.73	<=11	PASS
		5200	-0.15	<=11	PASS
		5240	0.03	<=11	PASS
		5745	-3.44	<=30	PASS
		5785	-3.85	<=30	PASS
		5825	-3.28	<=30	PASS
11AC40	Ant1	5190	-2.89	<=11	PASS
		5230	-2.84	<=11	PASS
		5755	-6.18	<=30	PASS
		5795	-6.22	<=30	PASS
11AC80	Ant1	5210	-5.53	<=11	PASS
		5775	-9.52	<=30	PASS

Note: 1.TheResult and LimitUnit is dBm/500 kHz in the band 5.725–5.85 GHz.

2. The Duty Cycle Factorand RBW Factoriscompensatedinthegraph.

Test Graphs




11A_Ant1_5240




Date: 19.MAR.2021 21:15:03

11A_Ant1_5745




Date: 19.MAR.2021 21:16:21

11A_Ant1_5785





Date: 19.MAR.2021 21:18:04


11A_Ant1_5825





Date: 19.MAR.2021 21:19:10





























**AppendixH: DutyCycle
Test Result**

TestMode	Antenna	Channel	TransmissionDuration [ms]	Transmission Period [ms]	Duty Cycle [%]
11A	Ant1	5180	1.37	1.44	95.14
		5745	1.37	1.44	95.14
11N20	Ant1	5180	1.28	1.35	94.81
		5745	1.28	1.34	95.52
11N40	Ant1	5190	0.62	0.69	89.86
		5755	0.63	0.69	91.30
11AC20	Ant1	5180	1.29	1.36	94.85
		5745	1.30	1.36	95.59
11AC40	Ant1	5190	0.63	0.69	91.30
		5755	0.64	0.70	91.43
11AC80	Ant1	5210	0.30	0.37	81.08
		5775	0.30	0.36	83.33

Test Graphs














***** END OF REPORT *****