



**Spectrum Research & Testing Lab., Inc.**

No.167, Ln. 780, Shan-Tong Rd., Ling 8, Shan-Tong Li, Chung-Li Dist., Taoyuan City 320, Taiwan (R.O.C.)

# TEST REPORT

Reference No.: A23080102  
Report No.: FCCA23080102-M0  
FCC ID : 2AZ3ICC180W  
Page: 1 of 7  
Date: Aug. 21, 2023

Product Name: Projector  
Brand Name: HP  
Model No.: CC180W  
Series Model: ---  
Applicant: GT Technology Chongqing Limited  
3-1, No, 20 Qixin Road Yanjia Street Changshou District  
Chongqing  
Date of Receipt: Aug. 01, 2023  
Finished date of Test: Aug. 01, 2023 ~ Aug. 18, 2023  
Applicable Standards: 47 CFR Part 15, Subpart C, 15.247  
ANSI C63.10: 2013  
FCC publication KDB 558074 D01 15.247 Meas Guidance  
v05r02 Apr 02, 2019

We, **Spectrum Research & Testing Laboratory Inc.**, hereby certify that one sample of the above was tested in our laboratory with positive results according to the above-mentioned standards. The records in the report are an accurate account of the results. Details of the results are given in the subsequent pages of this report.

Tested By : Anny Ho (Auth) , Date: 8/21/2023  
(Jimmy Tseng)

Approved By : J Johnson , Date: 8/21/2023  
( Johnson Ho, Director )



|  |                      |  |
|--|----------------------|--|
|  <b>Spectrum Research &amp; Testing Lab., Inc.</b><br>No.167,Ln. 780, Shan-Tong Rd.,Ling 8, Shan-Tong Li, Chung-Li Dist., Taoyuan City 320, Taiwan (R.O.C.) | <h1>TEST REPORT</h1> | Reference No.: A23080102<br>Report No.: FCCA23080102-M0<br>FCC ID : 2AZ3ICC180W<br>Page: 2 of 7<br>Date: Aug. 21, 2023 |
|--|----------------------|--|

## Revisions History

| Report No.      | Issue Date    | Revisions      |
|-----------------|---------------|----------------|
| FCCA23080102-M0 | Aug. 21, 2023 | Initial issue. |

|  |                      |  |
|--|----------------------|--|
|  <b>Spectrum Research &amp; Testing Lab., Inc.</b><br>No.167,Ln. 780, Shan-Tong Rd.,Ling 8, Shan-Tong Li, Chung-Li Dist., Taoyuan City 320, Taiwan (R.O.C.) | <h1>TEST REPORT</h1> | Reference No.: A23080102<br>Report No.: FCCA23080102-M0<br>FCC ID : 2AZ3ICC180W<br>Page: 3 of 7<br>Date: Aug. 21, 2023 |
|--|----------------------|--|

## 1. DOCUMENT POLICY AND TEST STATEMENT

### 1.1 DOCUMENT POLICY

- The report shall not be reproduced except in full, without the written approval of SRT Lab, Inc.
- FCC Registered Test Site Number : TW1016

### 1.2 TEST STATEMENT

- This random test report is for FCC's market spot check action by FCC ID: **2AZ3ICC180W** project, applied only to the specific samples tested under conditions.
- The test results in the report apply only to the unit tested by SRT Lab.
- There was no deviation from the requirements of test standards during the test.
- DC power source from DC adapter: 15V = 3A



## 2. GENERAL CONCLUSION

According to FCC §1.1307 and KDB 447498 D04, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW).

### 1) Option A. 1-mW Test Exemption

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

### 2) Option B. SAR-Based Exemption

A more comprehensive exemption, considering a variable power threshold that depends on both the separation distance and power, is provided in §

1.1307(b)(3)(i)(B). This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions.

Accordingly, a RF source is considered an RF exempt device if its available maximum time-averaged (matched conducted) power or its effective radiated power (ERP), whichever is greater, are below a specified threshold.

This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

|  |                      |   |
|--|----------------------|---|
|  <b>Spectrum Research &amp; Testing Lab., Inc.</b><br>No.167,Ln. 780, Shan-Tong Rd.,Ling 8, Shan-Tong Li, Chung-Li Dist., Taoyuan City 320, Taiwan (R.O.C.) | <h1>TEST REPORT</h1> | Reference No.: A23080102<br>Report No.: FCCA23080102-M0<br>FCC ID : 2AZ3IC180W<br>Page: 5 of 7<br>Date: Aug. 21, 2023 |
|--|----------------------|---|

**Table B2-Example Power Thresholds (mW)**

| Frequency<br>(MHz) | Distance(mm) |    |    |    |     |     |     |     |     |     |     |
|--------------------|--------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|
|                    | mW           | 5  | 10 | 15 | 20  | 25  | 30  | 35  | 40  | 45  | 50  |
|                    | 300          | 39 | 65 | 88 | 110 | 129 | 148 | 166 | 184 | 201 | 217 |
|                    | 450          | 22 | 44 | 67 | 89  | 112 | 135 | 158 | 180 | 203 | 226 |
|                    | 835          | 9  | 25 | 44 | 66  | 90  | 116 | 145 | 175 | 207 | 240 |
|                    | 1900         | 3  | 12 | 26 | 44  | 66  | 92  | 122 | 157 | 195 | 236 |
|                    | 2450         | 3  | 10 | 22 | 38  | 59  | 83  | 111 | 143 | 179 | 219 |
|                    | 3600         | 2  | 8  | 18 | 32  | 49  | 71  | 96  | 125 | 158 | 195 |
|                    | 5800         | 1  | 6  | 14 | 25  | 40  | 58  | 80  | 106 | 136 | 169 |

### 3) Option C MPE-Based Exemption

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

**Table B.1 - Thresholds for Single RF Sources  
Subject to Routine Environmental Evaluation**

| RF Source Frequency  |   |           | Minimum Distance   |   |                    | Threshold ERP    |
|--|---|-----------|--------------------|---|--------------------|------------------|
| $f_L$ MHz  |   | $f_H$ MHz | $\lambda_L / 2\pi$ |   | $\lambda_H / 2\pi$ | W                |
| 0.3  | - | 1.34      | 159 m              | - | 35.6 m             | $1920 R^2$       |
| 1.34   | - | 30        | 35.6 m             | - | 1.6 m              | $3450 R^2 / f^2$ |
| 30   | - | 300       | 1.6 m              | - | 159 mm             | $3.83 R^2$       |
| 300  | - | 1,500     | 159 mm             | - | 31.8 mm            | $0.0128 R^2 f$   |
| 1,500  | - | 100,000   | 31.8 mm            | - | 0.5 mm             | $1932 R^2$       |
| Subscripts L and H are low and high; $\lambda$ is wavelength.<br>From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns. |   |           |                    |   |                    |                  |

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.



$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P<sub>th</sub>, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P<sub>i</sub> = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

P<sub>th,i</sub> = the exemption threshold power (P<sub>th</sub>) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERP<sub>j</sub> = the ERP of fixed, mobile, or portable RF source j.

ERP<sub>th,j</sub> = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated<sub>k</sub> = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit<sub>k</sub> = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

|  |                      |  |
|--|----------------------|--|
|  <b>Spectrum Research &amp; Testing Lab., Inc.</b><br>No.167,Ln. 780, Shan-Tong Rd.,Ling 8, Shan-Tong Li, Chung-Li Dist., Taoyuan City 320, Taiwan (R.O.C.) | <h1>TEST REPORT</h1> | Reference No.: A23080102<br>Report No.: FCCA23080102-M0<br>FCC ID : 2AZ3ICC180W<br>Page: 7 of 7<br>Date: Aug. 21, 2023 |
|--|----------------------|--|

### 3. PRDUCT INFO

| Band     | Freq. (MHz) | AVGP (dBm) | Ant. Gain (dBi) | ERP (dBm) | Distances (mm) | AVGP (mW) | ERP (mW) |
|----------|-------------|------------|-----------------|-----------|----------------|-----------|----------|
| BT       | 2402        | 5.37       | 1.87            | 5.09      | 200            | 3.44      | 3.23     |
| LE       | 2402        | 4.97       | 1.87            | 4.69      | 200            | 3.14      | 2.94     |
| 2.4G     | 2437        | 21.61      | 4.25            | 23.71     | 200            | 144.88    | 234.96   |
| 5G Band4 | 5825        | 19.47      | 2.99            | 20.31     | 200            | 88.51     | 107.40   |

### 4. TEST RESULTS

| Band     | Freq (MHz) | $\lambda/2\pi$ (mm) | Distances applies | ERP Limit (mW) | Ratio  | Result Option C |
|----------|------------|---------------------|-------------------|----------------|--------|-----------------|
| BT       | 2402       | 19.88               | apply             | 768.00         | 0.0045 | exempt          |
| LE       | 2402       | 19.88               | apply             | 768.00         | 0.0041 | exempt          |
| 2.4G     | 2437       | 19.59               | apply             | 768.00         | 0.3059 | exempt          |
| 5G Band4 | 5825       | 8.2                 | apply             | 768.00         | 0.1398 | exempt          |

For the max simultaneous transmission MPE:

| Ratio  |        | Total  | Limit of Ratio | Test Result |
|--------|--------|--------|----------------|-------------|
| BT     | 2.4GHz |        |                |             |
| 0.0045 | 0.3059 | 0.3104 | 1              | Complies    |

**Note:**

- (1)Output power including tune up tolerance.
- (2)MPE evaluation is not required.