



WHA YU INDUSTRIAL CO., LTD.(HEAD OFFICE)

DONGGUAN AEON TECH CO.,LTD.(CHINA)

SPECIFICATION FOR APPROVAL

CUSTOMER: 優必閣



PART NAME: RF Antenna Assembly

PART NO.:

REVISION:

W. Y. P/NO.: C1991-510073-A(SRF2020776)

REV.: XI

	MANUFACTURER SIGNATURE	CUSTOMER SIGNATURE
APPROVED BY :		
DATE :	6/23	

WHA YU GROUP

WHA YU INDUSTRIAL CO., LTD.(HEAD OFFICE)

譚裕實業股份有限公司

Address: No. 326, Sec. 2, Kung Tao 5 Road, Hsin Chu City, Taiwan, R.O.C.

Tel:+886-3-5714225(REP.)

Fax:+ 886-3-5713853 • + 886-3-5723600

DONGGUAN AEON TECH CO.,LTD.(CHINA)

東莞台霖電子通訊有限公司

Address:Hupan Industrial District,Tai Ling Shan Town,Dong Guan City,Guangdong,China

Tel:+86-769-85655858

Fax:+86-769-85655258

Contents

<i>Item</i>	<i>Description</i>	<i>Page</i>
1.	規格表	 1
2.	成品圖	 2
3.	測試報告	 3~12

RF Antenna Assembly

Specification

1. Electrical Properties WITH HOUSING


- 1.1 Frequency Range.....698~960;1710~2690 MHz
- 1.2 Impedance50Ω Nominal
- 1.3 VSWR<2.6
- 1.4 Return Loss.....>7 dB
- 1.5 RadiationOmni-directional
- 1.6 Gain.....< 2 dBi
- 1.7 Cable Loss..... 0.2dB Max.
- 1.8 Polarization.....Linear
- 1.9 Admitted Power..... 1W
- 1.10 Cable..... 1.37 Coaxial Cable

2. Physical Properties :


- 3.1 Operating Temp. -10°C ~ +60°C
- 3.2 Storage Temp. -10°C ~ +70°C

CG-

REV	DATE	DESCRIPTION
X1	06/22-2020	New Issue



熱封留氣孔



Packing : 10 pcs/bag

6	Connector	SMA Straight Plug Standard	1	
5	Cable	1.37 Coaxial Cable	1	
4	Rivet	POM,Color: Black[黑色]	2	
3	Antenna Base	(CD-13)PC+PBT Color : Black[黑色]	1	
2	Antenna Base	(CD-761)PC ; Color : Black[黑色]	1	
1	Antenna Cap	(CD-702)ABS ; Color : Black[黑色]	1	
NO	DESCRIPTION		Q'TY	REMARK

CUSTOMER'S SINGATURE

XX.	±5.0	APPROVED
X.	±3.0	
.X	±1.0	
.XX	±0.5	CHECKED
.XXX	±0.1	
⊕	⊖	
		DRAWING

CUSTOMER: 優必閣		
PART NO :		
PART NAME: RF Antenna Assembly		
W.Y P/NO : C1991-510073-A		
REV	UNIT	FILE : SRF2020776
X1	mm	SHEET : 1/1

M.gear Wha Yu Group

THIS DRAWING, AND IT'S INHERANT DESIGN CONCEPTS, ARE THE PROPERTY OF WHA YU AND AS SUCH MAY NOT BE COPIED, REPRODUCED, OR GIVEN TO THIRD PARTIES WITHOUT THE WRITTEN CONSENT OF WHA YU.

LTE All Band Antenna Datasheet

*Document Number: **NE3-20xxx***

*Version: **V 1.1***

*Released Date: **2024/03/28***

*Prepared By: **Sky Lo***

*Reviewed By: **Sky Lo***



WHA YU INDUSTRIAL CO., LTD.
TEL : 886-3-5714225 FAX : 886-3-5713853 / 5723600
Website : www.whayu.com
E-mail : market@whayu.com

Contents

- Reversion History
- Antenna Performance Summary
- Specification
- Antenna Placement & Solution
- Test Setup for S-parameter Measurement
- Return Loss Results
- Test Setup for Radiation Pattern Measurement
- 2D Radiation Pattern Results
- Results Summary (return loss)

Revision History

Released Date	Version	Record
2020/06/23	1.00	Antenna Testing Report

Antenna Performance Summary

Antenna Only Gain & Efficiency – (Req. : Efficiency 30%)

Frequency	Peak Gain (dBi)	Efficiency	Frequency	Peak Gain (dBi)	Efficiency	Frequency	Peak Gain (dBi)	Efficiency
698MHz	-1.2	40%	875MHz	-1.0	32%	1980MHz	-0.4	41%
703MHz	-1.3	40%	880MHz	-1.3	30%	1990MHz	-0.5	41%
716MHz	-1.0	44%	890MHz	-0.6	32%	1995MHz	-0.9	38%
728MHz	-1.3	40%	915MHz	-0.6	34%	2010MHz	-0.7	39%
738MHz	-1.1	39%	925MHz	0.2	35%	2020MHz	-0.5	38%
746MHz	-0.8	41%	960MHz	-0.3	37%	2110MHz	-0.1	34%
758MHz	-1.1	39%	1710MHz	-0.5	43%	2170MHz	1.0	40%
768MHz	-1.3	35%	1750MHz	-0.7	47%	2180MHz	1.0	39%
777MHz	-0.9	38%	1770MHz	-0.8	46%	2200MHz	1.1	42%
798MHz	-1.1	38%	1780MHz	-0.6	45%	2300MHz	1.0	48%
803MHz	-1.2	37%	1785MHz	-1.2	43%	2350MHz	1.0	50%
814MHz	-0.8	37%	1805MHz	-0.8	47%	2400MHz	1.9	60%
824MHz	-0.2	33%	1850MHz	-0.4	43%	2450MHz	0.8	57%
830MHz	0.1	32%	1880MHz	-0.4	40%	2500MHz	1.3	57%
849MHz	-0.1	34%	1900MHz	-0.2	42%	2570MHz	-0.4	58%
859MHz	-0.7	34%	1910MHz	-0.1	39%	2620MHz	-0.8	53%
862MHz	-0.9	33%	1920MHz	0.2	42%	2690MHz	0.1	52%
869MHz	-0.5	35%	1930MHz	0.6	39%			

Specification

RF Function	Number of ANT	Frequency Band	Remark
LTE Ant.		698~960,1710~2690MHz	
Test Item	Specification		
Return Loss	> 7dB (Antenna only)		
Peak gain	< 2 dBi (Antenna only)		
Efficiency	>30~55% (Antenna only)		
Radiation pattern	Scale: +10 ~ -40dBi, Angle step size: 5 degree		


Antenna Placement & Solution



Antenna only


Antenna	ANT Type	Size (L * W * H)	Cable Length (mm)	Cable Type
LTE ANT	Dipole	176x18x6.1mm		

Return Loss Results




Antenna only

2D Radiation Pattern Results



2D Radiation Pattern Results



Conclusion

Antenna Performance Summary