

October 20, 2006

Timco Engineering, Inc.
Telecommunication Certification Body
849 NW State Road 45
Newberry, FL 32669

**SUBJECT: ITRONIX CORPORATION
FCC ID: KBCIX325-AC860BT
Part 24(E) - Certification
Composite Application (PCB)**

On behalf of Itronix Corporation is a composite application for Part 24(E) Certification of Model: IX325-AC860BT Rugged Tablet PC with internal Dual-Band GSM/GPRS/EDGE/UMTS PCMCIA Modem (Model: AirCard 860 manufactured by Sierra Wireless Inc.) utilizing the AirCard 860 hinged monopole antenna installed on the PCMCIA modem. The antenna is located externally to the tablet PC and housed within the low-profile hatch attached to the IX325. The DUT also incorporates a co-located MSI MS-6837 Bluetooth Transmitter with internal PIFA antenna installed in the left edge section of the DUT. The Part 15(C) composite certification application for the MSI MS-6837 Bluetooth portion of the DUT under the same FCC ID: KBCIX325-AC860BT is submitted simultaneously with this application. The AirCard 860 PCMCIA Modem can transmit simultaneously with the MSI MS-6837 Bluetooth. Co-transmit EMC evaluations (radiated spurious emissions) were performed and the DUT was found to be in compliance. Co-transmit SAR evaluation data is submitted within this filing.

Model:	IX325-AC860BT
Device Classification:	PCS Licensed Transmitter (PCB)
RF Exposure Category:	Portable
Device Description:	Rugged Tablet PC
LCD Display User Orientation(s):	0 Degrees Landscape, -90 Degrees Portrait
Internal Transmitter Tested:	GSM/GPRS/EDGE/UMTS PCMCIA Modem (Sierra Wireless AirCard 860)
Antenna Type(s) Tested:	External Hinged Monopole (Sierra Wireless AirCard 860 Antenna)
Transmit Frequency Range(s):	1850.2 - 1909.8 MHz (PCS GSM/GPRS/EDGE) 1852.4 - 1907.5 MHz (PCS UMTS) 824.2 - 848.8 MHz (Cellular GSM/GPRS/EDGE) 826.4 - 846.6 MHz (Cellular UMTS)
Max. SAR Level(s) Measured (Body):	PCS GPRS: 0.628 W/kg; Cellular GPRS: 0.334 W/kg (1g average) PCS EDGE: 0.306 W/kg; Cellular EDGE: 0.0919 W/kg (1g average) PCS UMTS: 0.252 W/kg; Cellular UMTS: 0.251 W/kg (1g average)

Submitted with this application is the TCB Form 731, applicant's authorization letter, applicant's long-term confidentiality request, applicant's device orientation attestation, Parts 24(E) and 22(H) EMC conducted measurement report (Sierra Wireless Inc.), Parts 24(E) and 22(H) EMC radiated measurement report and test setup photographs (Celltech Labs Inc.), SAR RF exposure measurement report data and test setup photographs (Celltech Labs Inc.), FCC ID label and location, internal and external device photographs, block diagram(s) (confidential), schematic diagram(s) (confidential), operational description (confidential), parts list (confidential), tune-up procedure (confidential), user manual (provided to the user with the built-in software on the IX325 Tablet PC), and the Radio-Specific Safety Information (provided to the user in hard copy format).

If you have any questions or comments concerning the above, please contact the undersigned.

Sincerely,



Jonathan Hughes
General Manager
Celltech Labs Inc.

cc: Itronix Corporation