

Certification Radio test report

According to the standard:
CFR 47 FCC PART 15

Equipment under test:
Parrot BLUEGRASS

FCC ID: 2AG6ICHIMERA

Company:
PARROT DRONES

Distribution: Mr EL HANBALI

(Company: PARROT DRONES)

Number of pages: 7

Ed.	Date	Modified Page(s)	Technical Verification and Quality Approval	
			Name and Function	Visa
0	18-Dec-17	Creation	M. DUMESNIL, Radio Technical Manager	

Duplication of this document is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above.

This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole manufactured products of the tested sample.



Siège Social : Emitech - 3, rue des Coudriers - Z.A. de l'Observatoire - 78180 MONTIGNY LE BX - France

Siret : 344 545 645 00022 - Tél. : 33 (0)1 30 57 55 55 - Fax : 33 (0)1 30 43 74 48 - E-mail : contact@emitech.fr - URL : www.emitech.fr

S.A. au capital de 1 560 000 € - R.C.S. VERSAILLES 344 545 645 - APE 7112B

DESIGNATION OF PRODUCT: Parrot BLUEGRASS

Serial number (S/N): DV04

Reference / model (P/N): CHIMERA

Software version: RF software

MANUFACTURER: PARROT DRONES

COMPANY SUBMITTING THE PRODUCT:

Company: PARROT DRONES

Address: 174 QUA DE JEMMAPES
7501 PARIS
FRANCE

Responsible: Mr EL HANBALI

TESTING LOCATION: EMITECH ANGERS laboratory at JUIGNE SUR LOIRE (49) FRANCE
FCC Accredited under US-EU MRA Designation Number: FR0009
Test Firm Registration Number: 873677

TESTED BY: T. LEDRESSEUR

VISA:



WRITTEN BY: T. LEDRESSEUR

CONTENTS

	<i>TITLE</i>	<i>PAGE</i>
1.	INTRODUCTION.....	4
2.	PRODUCT DESCRIPTION	4
3.	NORMATIVE REFERENCE.....	6
4.	RF EXPOSURE.....	7

1. INTRODUCTION

This report presents the results of radio test carried out on the following radio equipment: **Parrot BLUEGRASS**, in accordance with normative reference.

The product integrates a WLAN radio part, 2.4GHz and 5 GHz .
The report concern only the calcul of MPE

2. PRODUCT DESCRIPTION

UNII band

Class:	B
Utilization:	Residential
Antenna type and gain:	2 integral identical antennas 2.8 dBi for U-NII-1 band and 4.2 dBi for U-NII-3 band
Operating frequency range:	From 5150 MHz to 5250 MHz band U-NII-1 From 5725 MHz to 5850 MHz band U-NII-3
Number of channels:	4 for band 5150MHz to 5250 MHz 5 for band 5725MHz to 5850 MHz
Channel spacing:	20 MHz
Modulation:	OFDM: BPSK OFDM: 64-QAM
Power source:	14.8Vdc by internal battery The battery is rechargeable outside the product.
Mode tested:	802.11 a 802.11 n
Data rate:	For 802.11a: 6Mbit/s For 802.11n: MCS0
Channel tested:	
Band U-NII-1:	Chanel 36, 5180 MHz Chanel 40, 5200 MHz Chanel 48, 5240 MHz
Band U-NII-3:	Chanel 149, 5745 MHz Chanel 157, 5785 MHz Chanel 165, 5825 MHz

Power level, frequency range and channels characteristics are not user adjustable.
The details pictures of the product and the circuit boards are joined with this file.

Band 2.4 GHz

Class:	B
Utilization:	Residential
Antenna type and gain:	(3.8 dBi) 2 integral identical antennas
Operating frequency range:	From 2400 MHz to 2483.5MHz
Number of channels:	11
Channel spacing:	5 MHz
Modulation:	DBPSK OFDM: BPSK OFDM: 64-QAM
Power source:	14.8Vdc by internal battery The battery is rechargeable outside the product.
Mode tested:	802.11 b 802.11 g 802.11 n
Data rate:	For 802.11b: 1Mbit/s For 802.11g: 6Mbit/s For 802.11n: MCS0
Channel tested:	Channel 1: 2412 MHz Channel 6: 2437 MHz Channel 11: 2462 MHz

3. ***NORMATIVE REFERENCE***

The standards and testing methods related throughout this report are those listed below.

They are applied on the whole test report even though the extensions (version, date and amendment) are not repeated.

CFR 47 FCC Part 15 (2017) Radio Frequency Devices

ANSI C63.10 2013
Procedures for Compliance Testing of Unlicensed Wireless Devices.

789033 D02 General UNII
Test Procedures New
Rules v01r04 Guidelines for compliances testing of unlicensed national information
infrastructure (U-NII) devices pat 15, subpart E

662911 D01 Multiple
Transmitter Output V02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band

447498 D01 General RF
Exposure Guidance v06 RF Exposure procedures and equipment authorization policies for mobile and
portable equipment

4. RF EXPOSURE

For 5 GHz

Maximum conducted measured power = 18.24 dBm at 5825 MHz

With *Gain* = 4.2dBi

EIRP = 22.44 dBm

In accordance with KDB 447498 D01 General RF Exposure Guidance v06:

$$PSD = EIRP / (4 * \pi * R^2)$$

$$\Rightarrow 175.39 / (4 * \pi * (20 \text{ cm})^2) = 0.0349 \text{ mW/cm}^2 \text{ (limit = 1 mW/cm}^2 \text{ above 1500 MHz)}$$

The equipment fulfils the requirements on power density for general population/uncontrolled exposure and therefore fulfils the requirements of 47 CFR §1.1310.

For 2.4 GHz

Maximum conducted measured power = 25.57dBm at 2462 MHz

With *Gain* = 3.8dBi

EIRP = 29.37dBm

In accordance with KDB 447498 D01 General RF Exposure Guidance v06:

$$PSD = EIRP / (4 * \pi * R^2)$$

$$\Rightarrow 864.97 / (4 * \pi * (20 \text{ cm})^2) = 0.172 \text{ mW/cm}^2 \text{ (limit = 1 mW/cm}^2 \text{ above 1500 MHz)}$$

The equipment fulfils the requirements on power density for general population/uncontrolled exposure and therefore fulfils the requirements of 47 CFR §1.1310.