

FCC ID:2BNT0-S6S-PRO

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

Left ear:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	6.051	4.03	6±1	7.00	5.01	<5	1.55352	3.00	YES
	2.441	5.945	3.93	5±1	6.00	3.98	<5	1.24398	3.00	YES
	2.480	4.67	2.93	4±1	5.00	3.16	<5	0.99599	3.00	YES
π /4DQPSK	2.402	6.762	4.74	6±1	7.00	5.01	<5	1.55352	3.00	YES
	2.441	6.62	4.59	6±1	7.00	5.01	<5	1.56608	3.00	YES
	2.480	5.354	3.43	5±1	6.00	3.98	<5	1.25388	3.00	YES
8DQPSK	2.402	6.976	4.98	6±1	7.00	5.01	<5	1.55352	3.00	YES
	2.441	6.69	4.67	6±1	7.00	5.01	<5	1.56608	3.00	YES
	2.480	5.648	3.67	5±1	6.00	3.98	<5	1.25388	3.00	YES

Right ear:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	6.01	3.99	6±1	7.00	5.01	<5	1.55352	3.00	YES
	2.441	5.865	3.86	5±1	6.00	3.98	<5	1.24398	3.00	YES
	2.480	4.641	2.91	4±1	5.00	3.16	<5	0.99599	3.00	YES
π /4DQPSK	2.402	6.738	4.72	6±1	7.00	5.01	<5	1.55352	3.00	YES
	2.441	6.434	4.40	6±1	7.00	5.01	<5	1.56608	3.00	YES
	2.480	5.271	3.37	5±1	6.00	3.98	<5	1.25388	3.00	YES
8DQPSK	2.402	6.927	4.93	6±1	7.00	5.01	<5	1.55352	3.00	YES
	2.441	6.604	4.58	6±1	7.00	5.01	<5	1.56608	3.00	YES
	2.480	5.58	3.61	5±1	6.00	3.98	<5	1.25388	3.00	YES

Conclusion:

For the max result : $1.56608 \leq \text{FCC Limit } 3.0$ for 1g SAR.