

**FCC - TEST REPORT**

Report Number : **68.950.22.0502.01** Date of Issue: **2022-06-23**

Model : **MW-02**

Product Type : **TURBOPOWER 50W WIRELESS CHARGING STAND**

Brand name : **MOTO**

Applicant : **Motorola Mobility LLC**

Address : **222 W. Merchandise Mart Plaza, Chicago Illinois 60654 USA**

Manufacturer : **Motorola Mobility LLC**

Address : **222 W. Merchandise Mart Plaza, Chicago Illinois 60654 USA**

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including Appendices : **26**

TÜV SÜD Certification and Testing (China) Co., Ltd. – Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. – Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. – Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. – Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval

## 1 Table of Contents

|     |                                              |    |
|-----|----------------------------------------------|----|
| 1   | Table of Contents.....                       | 2  |
| 2   | Details about the Test Laboratory.....       | 3  |
| 3   | Description of the Equipment Under Test..... | 4  |
| 4   | Summary of Test Standards .....              | 5  |
| 5   | Summary of Test Results.....                 | 6  |
| 6   | General Remarks .....                        | 7  |
| 7   | Test Setups .....                            | 8  |
| 8   | Systems test configuration.....              | 9  |
| 9   | Technical Requirement .....                  | 10 |
| 9.1 | Conducted Emission Test .....                | 10 |
| 9.2 | 20 dB Bandwidth .....                        | 15 |
| 9.3 | Radiated Emission Test .....                 | 16 |
| 10  | Test Equipment List.....                     | 25 |
| 11  | System Measurement Uncertainty .....         | 26 |

## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch  
Building 12 & 13, Zhiheng Wisdomland Business Park, Nantou Checkpoint  
Road 2, Nanshan District  
Shenzhen 518052  
P.R. China

Telephone: 86 755 8828 6998

Fax: 86 755 828 5299

FCC Registration No.: 514049

### 3 Description of the Equipment Under Test

|                            |                                                                                    |
|----------------------------|------------------------------------------------------------------------------------|
| Product:                   | TURBOPOWER 50W WIRELESS CHARGING STAND                                             |
| Model no.:                 | MW-02                                                                              |
| FCC ID:                    | IHDT6AA2                                                                           |
| Rating:                    | Input: 5-20VDC 3.5A Max<br>Output: 50W Max                                         |
| RF Transmission Frequency: | 111-145KHz                                                                         |
| Antenna Type:              | Integrated coil antenna                                                            |
| Description of the EUT:    | The Equipment Under Test (EUT) is a Wireless Charger which operated at 111-145kHz. |

## 4 Summary of Test Standards

| Test Standards                             |                                                                        |
|--------------------------------------------|------------------------------------------------------------------------|
| FCC Part 15 Subpart C<br>10-1-2020 Edition | PART 15 - RADIO FREQUENCY DEVICES<br>Subpart C - Intentional Radiators |

All the test methods were according to ANSI C63.10 (2013).

## 5 Summary of Test Results

| Technical Requirements |                                  |            |                                     |                          |                          |
|------------------------|----------------------------------|------------|-------------------------------------|--------------------------|--------------------------|
| FCC Part 15 Subpart C  |                                  |            |                                     |                          |                          |
| Test Condition         |                                  | Test Site  | Test Result                         |                          |                          |
|                        |                                  |            | Pass                                | Fail                     | N/A                      |
| §15.207                | Conducted emission AC power port | Site 1     | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| --                     | 20dB bandwidth                   | Site 1     | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| §15.205                | Restricted bands of operation    | Site 1     | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| §15.209                | Radiated emission                | Site 1     | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| §15.203                | Antenna requirement              | See note 1 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

Note 1: The EUT uses an integrated coil antenna, which gain is 0dBi. In accordance to §15.203, it is considered sufficiently to comply with the provisions of this section.

## 6 General Remarks

### Remarks

This submittal(s) (test report) complies with Section 15.207, 15.209, 15.205 of the FCC Part 15, Subpart C rules.

### SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.


Sample Received Date: 2022-05-06

Testing Start Date: 2022-05-06

Testing End Date: 2022-06-16

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:


  
John Zhi  
Project Manager

Prepared by:

  
Warlen Song  
Project Engineer

Tested by:




  
Carry Cai  
Test Engineer


## 7 Test Setups

### 7.1 Radiated test setups


Below 30MHz




30MHz-1GHz



### 7.2 AC Power Conducted test setups



### 7.3 Conducted RF test setups



## 8 Systems test configuration

Auxiliary Equipment Used during Test:

| Description               | Manufacturer | Model NO. | S/N |
|---------------------------|--------------|-----------|-----|
| Adapter                   | Moto         | MC688     | --- |
| Communicated<br>Auxiliary | ---          | ---       | --- |

## 9 Technical Requirement

### 9.1 Conducted Emission Test

#### Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

#### Limit


According to §15.207, conducted emissions limit as below:

| Frequency   | QP Limit   | AV Limit   |
|-------------|------------|------------|
| MHz         | dB $\mu$ V | dB $\mu$ V |
| 0.150-0.500 | 66-56*     | 56-46*     |
| 0.500-5     | 56         | 46         |
| 5-30        | 60         | 50         |

\*Decreasing linearly with logarithm of the frequency

## Conducted Emission

Model: MW-02  
 Test mode: Top coil+Charging  
 Test Voltage: AC 120V/60Hz  
 Remark:



## Critical\_Freqs

| Frequency (MHz) | MaxPeak (dBμV) | Average (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|----------------|----------------|--------------|-------------|------|------------|
| 0.502500        | 46.47          | ---            | 56.03        | 9.56        | L1   | 9.65       |
| 0.661500        | 46.53          | ---            | 56.00        | 9.47        | L1   | 9.65       |
| 1.118000        | 43.93          | ---            | 56.00        | 12.07       | L1   | 9.66       |
| 3.105500        | 47.29          | ---            | 56.00        | 8.71        | L1   | 9.74       |
| 7.394000        | 47.03          | ---            | 60.00        | 12.97       | L1   | 9.96       |
| 16.546000       | 47.53          | ---            | 60.00        | 12.47       | L1   | 10.27      |

## Final Result

| Frequency (MHz) | QuasiPeak (dBμV) | Average (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|------------------|----------------|--------------|-------------|------|------------|
| 0.502500        | ---              | 35.73          | 46.00        | 10.27       | L1   | 9.65       |
| 0.502500        | 42.96            | ---            | 56.00        | 13.04       | L1   | 9.65       |
| 0.661500        | ---              | 30.10          | 46.00        | 15.90       | L1   | 9.65       |
| 0.661500        | 41.80            | ---            | 56.00        | 14.20       | L1   | 9.65       |
| 3.105500        | ---              | 37.43          | 46.00        | 8.57        | L1   | 9.74       |
| 3.105500        | 42.54            | ---            | 56.00        | 13.46       | L1   | 9.74       |

Remark:


Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

## Conducted Emission

Model: MW-02  
 Test mode: Top coil+Charging  
 Test Voltage: AC 120V/60Hz  
 Remark:



## Critical Freqs

| Frequency (MHz) | MaxPeak (dBμV) | Average (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|----------------|----------------|--------------|-------------|------|------------|
| 0.278000        | 44.73          | ---            | 60.88        | 16.14       | L1   | 9.22       |
| 0.374000        | 39.76          | ---            | 58.41        | 18.65       | L1   | 9.21       |
| 0.546000        | 45.20          | ---            | 56.00        | 10.80       | L1   | 9.20       |
| 0.690000        | 43.30          | ---            | 56.00        | 12.70       | L1   | 9.20       |
| 1.382000        | 37.64          | ---            | 56.00        | 18.36       | L1   | 9.21       |
| 2.650000        | 36.95          | ---            | 56.00        | 19.05       | L1   | 9.25       |

| Frequency (MHz) | QuasiPeak (dBμV) | Average (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|------------------|----------------|--------------|-------------|------|------------|
| ---             | ---              | ---            | ---          | ---         | ---  | ---        |

Remark:


Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

## Conducted Emission

Model: MW-02  
 Test mode: Down coil+Charging  
 Test Voltage: AC 120V/60Hz  
 Remark:



## Critical Freqs

| Frequency (MHz) | MaxPeak (dBμV) | Average (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|----------------|----------------|--------------|-------------|------|------------|
| 0.274000        | 44.32          | ---            | 61.00        | 16.68       | N    | 9.39       |
| 0.530000        | 44.52          | ---            | 56.00        | 11.48       | N    | 9.40       |
| 0.694000        | 43.12          | ---            | 56.00        | 12.88       | N    | 9.39       |
| 0.946000        | 38.89          | ---            | 56.00        | 17.11       | N    | 9.39       |
| 1.638000        | 39.33          | ---            | 56.00        | 16.67       | N    | 9.41       |
| 6.638000        | 43.19          | ---            | 60.00        | 16.81       | N    | 9.55       |

## Final Result

| Frequency (MHz) | QuasiPeak (dBμV) | Average (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|------------------|----------------|--------------|-------------|------|------------|
| ---             | ---              | ---            | ---          | ---         |      | ---        |

Remark:


Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

## Conducted Emission

Model: MW-02  
 Test mode: Down coil+Charging  
 Test Voltage: AC 120V/60Hz  
 Remark:



## Critical\_Freqs

| Frequency (MHz) | MaxPeak (dBμV) | Average (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|----------------|----------------|--------------|-------------|------|------------|
| 0.238000        | 48.56          | ---            | 62.17        | 13.61       | L1   | 9.23       |
| 0.438000        | 40.97          | ---            | 57.10        | 16.13       | L1   | 9.20       |
| 0.574000        | 44.01          | ---            | 56.00        | 11.99       | L1   | 9.20       |
| 0.734000        | 44.74          | ---            | 56.00        | 11.26       | L1   | 9.20       |
| 12.118000       | 39.10          | ---            | 60.00        | 20.90       | L1   | 9.39       |
| 18.574000       | 41.49          | ---            | 60.00        | 18.51       | L1   | 9.44       |

## Final\_Result

| Frequency (MHz) | QuasiPeak (dBμV) | Average (dBμV) | Limit (dBμV) | Margin (dB) | Line | Corr. (dB) |
|-----------------|------------------|----------------|--------------|-------------|------|------------|
| ---             | ---              | ---            | ---          | ---         |      | ---        |

Remark:

Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

## 9.2 20 dB Bandwidth

### Test Method

1. Use the following spectrum analyzer settings:  
RBW=200Hz, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 20 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq$  20 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

### Limit

#### Limit [kHz]

No Limit

### The Top coil Test result

| Frequency<br>KHz | 20dB<br>bandwidth<br>KHz | Result<br>F <sub>L</sub> (KHz)    F <sub>H</sub> (KHz) |        | Result |
|------------------|--------------------------|--------------------------------------------------------|--------|--------|
| 111KHz           | 0.87                     | 110.64                                                 | --     | Pass   |
| 145KHz           | 0.87                     | --                                                     | 145.75 | Pass   |

### The Down coil Test result

| Frequency<br>KHz | 20dB<br>bandwidth<br>KHz | Result<br>F <sub>L</sub> (KHz)    F <sub>H</sub> (KHz) |        | Result |
|------------------|--------------------------|--------------------------------------------------------|--------|--------|
| 111KHz           | 0.87                     | 110.69                                                 | --     | Pass   |
| 145KHz           | 0.87                     | --                                                     | 145.94 | Pass   |

The fundamental frequency is outside the restricted bands of 15.205 section.

## 9.3 Radiated Emission Test

### Test Method

- 1: The EUT was placed on a turn table which is 0.8m above ground for below 1GHz at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:

### Limit

the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:


| Frequency<br>MHz | Field Strength<br>$\mu\text{V/m}$ | Field Strength<br>$\text{dB}\mu\text{V/m}$ | Detector | Measurement distance<br>meters |
|------------------|-----------------------------------|--------------------------------------------|----------|--------------------------------|
| 0.009-0.490      | 2400/F(kHz)                       | 48.5-13.8                                  | AV       | 300                            |
| 0.490-1.705      | 24000/F(kHz)                      | 33.8-23.0                                  | QP       | 30                             |
| 1.705-30         | 30                                | 29.5                                       | QP       | 30                             |
| 30-88            | 100                               | 40                                         | QP       | 3                              |
| 88-216           | 150                               | 43.5                                       | QP       | 3                              |
| 216-960          | 200                               | 46                                         | QP       | 3                              |
| 960-1000         | 500                               | 54                                         | QP       | 3                              |
| Above 1000       | 500                               | 54                                         | AV       | 3                              |
| Above 1000       | 5000                              | 74                                         | PK       | 3                              |

Note 1: Limit  $3\text{m}(\text{dB}\mu\text{V/m}) = \text{Limit } 300\text{m}(\text{dB}\mu\text{V/m}) + 40\text{Log}(300\text{m}/3\text{m})$  (Below 30MHz)

Note 2: Limit  $3\text{m}(\text{dB}\mu\text{V/m}) = \text{Limit } 30\text{m}(\text{dB}\mu\text{V/m}) + 40\text{Log}(30\text{m}/3\text{m})$  (Below 30MHz)

## Radiated emissions test (9KHz-30MHz)

Model: MW-02  
 Test mode: Top coil+Charging  
 Test Voltage: AC 120V/60Hz  
 Remark:



### Critical Freqs


| Frequency (MHz) | MaxPeak (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|------------------------|----------------------|-------------|-----|---------------|--------------|
| 0.023946        | 61.07                  | 120.02               | 58.95       | H   | 0.0           | 20.11        |
| 0.039973        | 57.60                  | 115.57               | 57.97       | H   | 0.0           | 20.13        |
| 0.056000        | 54.86                  | 112.64               | 57.78       | H   | 0.0           | 20.17        |
| 0.108123*       | 62.50                  | 106.92               | 44.42       | H   | 258.0         | 20.14        |
| 0.128233        | 91.12                  | 105.44               | 14.32       | H   | 183.0         | 20.13        |
| 0.219650        | 60.01                  | 100.77               | 40.76       | H   | 254.0         | 20.08        |
| 0.383825        | 68.67                  | 95.92                | 27.25       | H   | 188.0         | 20.05        |
| 0.637550        | 68.43                  | 71.51                | 3.08        | H   | 188.0         | 19.96        |
| 0.896250        | 60.99                  | 68.55                | 7.561       | H   | 354.0         | 20.08        |
| 1.413650        | 49.43                  | 64.60                | 15.17       | H   | 359.0         | 20.05        |

### Final Result

| Frequency (MHz) | QuasiPeak (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|--------------------------|----------------------|-------------|-----|---------------|--------------|
| 0.637550        | 65.48                    | 71.51                | 6.03        | H   | 201.0         | 20.13        |

Model: MW-02  
 Test mode: Top coil+Charging  
 Test Voltage: AC 120V/60Hz  
 Remark:


Level in dB $\mu$ V/m



### Critical\_Freqs

| Frequency (MHz) | MaxPeak (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|------------------------|----------------------|-------------|-----|---------------|--------------|
| 0.009000        | 59.17                  | 128.52               | 69.35       | V   | 355.0         | 20.60        |
| 0.027565        | 60.03                  | 118.80               | 58.76       | V   | 279.0         | 20.12        |
| 0.104128        | 55.27                  | 107.25               | 51.98       | V   | 333.0         | 20.14        |
| 0.108029*       | 59.26                  | 106.93               | 47.67       | V   | 333.0         | 20.14        |
| 0.128380        | 78.47                  | 105.43               | 26.96       | V   | 272.0         | 20.13        |
| 0.129884        | 77.57                  | 105.33               | 27.76       | V   | 292.0         | 20.12        |
| 0.209700        | 56.26                  | 101.17               | 44.91       | V   | 324.0         | 20.08        |
| 0.383825        | 56.16                  | 95.92                | 39.76       | V   | 280.0         | 20.05        |
| 0.642525        | 64.24                  | 71.44                | 7.20        | V   | 280.0         | 19.96        |
| 0.896250        | 55.05                  | 68.55                | 13.50       | V   | 103.0         | 20.08        |

Model: MW-02  
 Test mode: Down coil+Charging  
 Test Voltage: AC 120V/60Hz  
 Remark:

Level in dB $\mu$ V/m

### Critical\_Freqs


| Frequency (MHz) | MaxPeak (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|------------------------|----------------------|-------------|-----|---------------|--------------|
| 0.009000        | 57.14                  | 128.52               | 71.38       | H   | 6.0           | 20.60        |
| 0.023946        | 61.54                  | 120.02               | 58.48       | H   | 0.0           | 20.11        |
| 0.039973        | 57.92                  | 115.57               | 57.65       | H   | 0.0           | 20.13        |
| 0.055953        | 55.41                  | 112.64               | 57.24       | H   | 0.0           | 20.17        |
| 0.126653        | 102.06                 | 105.55               | 3.49        | H   | 201.0         | 20.13        |
| 0.254475        | 58.67                  | 99.49                | 40.82       | H   | 243.0         | 20.08        |
| 0.378850        | 78.61                  | 96.03                | 17.42       | H   | 184.0         | 20.05        |
| 0.632575        | 68.57                  | 71.58                | 3.01        | H   | 184.0         | 19.96        |
| 0.881325        | 64.08                  | 68.70                | 4.62        | H   | 184.0         | 20.08        |
| 1.135050        | 58.83                  | 66.50                | 7.67        | H   | 184.0         | 20.05        |

### Final\_Result

| Frequency (MHz) | Average (dB $\mu$ V/m)   | Limit (dB $\mu$ V/m) | Margin (dB) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|--------------------------|----------------------|-------------|-----|---------------|--------------|
| 0.126653        | 99.37                    | 105.55               | 6.18        | H   | 201.0         | 20.13        |
| Frequency (MHz) | QuasiPeak (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) | Pol | Azimuth (deg) | Corr. (dB/m) |
| 0.632575        | 65.66                    | 71.58                | 5.92        | H   | 184.0         | 19.96        |
| 0.881325        | 62.84                    | 68.70                | 5.86        | H   | 184.0         | 20.08        |

Model: MW-02  
 Test mode: Down coil+Charging  
 Test Voltage: AC 120V/60Hz  
 Remark:

Level in dB $\mu$ V/m



### Critical Freqs


| Frequency (MHz) | MaxPeak (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|------------------------|----------------------|-------------|-----|---------------|--------------|
| 0.009000        | 59.25                  | 128.52               | 69.27       | V   | 6.0           | 20.60        |
| 0.023946        | 53.53                  | 120.02               | 66.49       | V   | 0.0           | 20.11        |
| 0.027565        | 60.05                  | 118.79               | 58.74       | V   | 283.0         | 20.12        |
| 0.039973        | 50.24                  | 115.57               | 65.33       | V   | 0.0           | 20.13        |
| 0.055154        | 53.75                  | 112.77               | 59.02       | V   | 324.0         | 20.17        |
| 0.126747        | 96.69                  | 105.54               | 8.85        | V   | 283.0         | 20.13        |
| 0.378850        | 73.06                  | 96.03                | 22.97       | V   | 280.0         | 20.05        |
| 0.632575        | 61.96                  | 71.58                | 9.62        | V   | 280.0         | 19.96        |
| 0.881325        | 60.15                  | 68.70                | 8.55        | V   | 280.0         | 20.08        |
| 7.025450        | 39.14                  | 50.67                | 11.53       | V   | 309.0         | 20.15        |

Remark:

- (1) "\*" means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.
- (2) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) Below 1GHz: Corrector factor = Antenna Factor + Cable Loss.

## Radiated emissions test (30MHz-1000MHz)

Model: MW-02  
 Test Mode: Top coil+Charging  
 Test Voltage: AC 120V/50Hz  
 Remark:



### Critical\_Freqs

| Frequency (MHz) | MaxPeak (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|------------------|----------------|-------------|-------------|-----|---------------|--------------|
| 48.915000       | 20.93            | 40.00          | 19.07       | 100.0       | H   | 0.0           | 21.20        |
| 106.751250      | 19.35            | 43.50          | 24.15       | 100.0       | H   | 359.0         | 18.80        |
| 178.895000      | 22.93            | 43.50          | 20.57       | 200.0       | H   | 15.0          | 16.94        |
| 199.992500      | 30.76            | 43.50          | 12.74       | 100.0       | H   | 121.0         | 18.84        |
| 406.238750      | 25.19            | 46.00          | 20.81       | 200.0       | H   | 355.0         | 24.29        |
| 927.674375      | 34.25            | 46.00          | 11.75       | 200.0       | H   | 184.0         | 32.90        |


Remark:

Level=Reading Level + Correction Factor

Correction Factor=Antenna Factor + Cable Loss

(The Reading Level is recorded by software which is not shown in the sheet)

Model: MW-02  
 Test Mode: Top coil+Charging  
 Test Voltage: AC 120V/50Hz  
 Remark:



### Critical Freqs

| Frequency (MHz) | MaxPeak (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|------------------|----------------|-------------|-------------|-----|---------------|--------------|
| 38.124063       | 35.20            | 40.00          | 4.80        | 100.0       | V   | 230.0         | 19.31        |
| 56.068750       | 24.43            | 40.00          | 15.57       | 100.0       | V   | 0.0           | 20.58        |
| 84.501875       | 19.88            | 40.00          | 20.12       | 200.0       | V   | 0.0           | 15.05        |
| 126.636250      | 16.89            | 43.50          | 26.61       | 100.0       | V   | 240.0         | 16.38        |
| 199.992500      | 32.24            | 43.50          | 11.26       | 100.0       | V   | 0.0           | 18.84        |
| 533.430000      | 27.86            | 46.00          | 18.14       | 200.0       | V   | 0.0           | 26.62        |


Remark:

Level=Reading Level + Correction Factor

Correction Factor=Antenna Factor + Cable Loss

(The Reading Level is recorded by software which is not shown in the sheet)

Model: MW-02  
 Test Mode: Down coil+Charging  
 Test Voltage: AC 120V/50Hz  
 Remark:



### Critical\_Freqs

| Frequency (MHz) | MaxPeak (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|------------------|----------------|-------------|-------------|-----|---------------|--------------|
| 47.641875       | 20.53            | 40.00          | 19.47       | 100.0       | H   | 239.0         | 21.21        |
| 105.356875      | 18.86            | 43.50          | 24.64       | 200.0       | H   | 0.0           | 18.86        |
| 199.992500      | 29.48            | 43.50          | 14.02       | 100.0       | H   | 110.0         | 18.84        |
| 251.220625      | 24.40            | 46.00          | 21.60       | 100.0       | H   | 0.0           | 20.61        |
| 520.274375      | 28.28            | 46.00          | 17.72       | 200.0       | H   | 0.0           | 26.46        |
| 919.186875      | 34.47            | 46.00          | 11.53       | 200.0       | H   | 0.0           | 32.96        |


Remark:

Level=Reading Level + Correction Factor

Correction Factor=Antenna Factor + Cable Loss

(The Reading Level is recorded by software which is not shown in the sheet)

Model: MW-02  
 Test Mode: Down coil+Charging  
 Test Voltage: AC 120V/50Hz  
 Remark:



### Critical Freqs

| Frequency (MHz) | MaxPeak (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|------------------|----------------|-------------|-------------|-----|---------------|--------------|
| 37.881250       | 32.69            | 40.00          | 7.31        | 100.0       | V   | 0.0           | 19.20        |
| 56.190000       | 24.76            | 40.00          | 15.24       | 100.0       | V   | 98.0          | 20.55        |
| 72.013125       | 19.33            | 40.00          | 20.67       | 200.0       | V   | 0.0           | 15.84        |
| 199.992500      | 32.92            | 43.50          | 10.58       | 100.0       | V   | 44.0          | 18.84        |
| 448.797500      | 26.70            | 46.00          | 19.30       | 100.0       | V   | 0.0           | 25.11        |
| 712.091875      | 31.12            | 46.00          | 14.88       | 100.0       | V   | 0.0           | 29.89        |

Remark:

Level=Reading Level + Correction Factor

Correction Factor=Antenna Factor + Cable Loss

(The Reading Level is recorded by software which is not shown in the sheet)

## 10 Test Equipment List

### List of Test Instruments

#### Radiated Spurious Emission Test

| DESCRIPTION                         | MANUFACTURER    | MODEL NO. | EQUIPMENT ID       | SERIAL NO.      | CAL INTERVAL (YEAR) | CAL. DUE DATE |
|-------------------------------------|-----------------|-----------|--------------------|-----------------|---------------------|---------------|
| EMI Test Receiver                   | Rohde & Schwarz | ESR 7     | 68-4-74-19-001     | 102176          | 1                   | 2023-5-27     |
| Trilog Super Broadband Test Antenna | Schwarzbeck     | VULB 9163 | 68-4-80-14-002     | 707             | 1                   | 2022-7-23     |
| Loop Antenna                        | Rohde & Schwarz | HFH2-Z2   | 68-4-80-14-006     | 100398          | 1                   | 2022-8-25     |
| Pre-amplifier                       | Rohde & Schwarz | SCU 18    | 68-4-29-14-001     | 102230          | 1                   | 2023-5-28     |
| Attenuator                          | Agilent         | 8491A     | 68-4-81-16-001     | MY39264334      | 1                   | 2023-5-27     |
| 3m Semi-anechoic chamber            | TDK             | 9X6X6     | 68-4-90-14-001     | ----            | 3                   | 2023-5-28     |
| Test software                       | Rohde & Schwarz | EMC32     | 68-4-90-14-001-A10 | Version10.35.02 | N/A                 | N/A           |

#### Conducted Emission Test

| DESCRIPTION       | MANUFACTURER      | MODEL NO. | EQUIPMENT ID       | SERIAL NO.     | CAL INTERVAL (YEAR) | CAL. DUE DATE |
|-------------------|-------------------|-----------|--------------------|----------------|---------------------|---------------|
| EMI Test Receiver | Rohde & Schwarz   | ESR 3     | 68-4-74-14-001     | 101782         | 1                   | 2023-5-27     |
| LISN              | Rohde & Schwarz   | ENV4200   | 68-4-87-14-001     | 100249         | 1                   | 2023-5-27     |
| LISN              | Rohde & Schwarz   | ENV432    | 68-4-87-16-001     | 101318         | 1                   | 2023-5-27     |
| LISN              | Rohde & Schwarz   | ENV216    | 68-4-87-14-002     | 100326         | 1                   | 2023-5-27     |
| Attenuator        | Shanghai Huaxiang | TS2-26-3  | 68-4-81-16-003     | 080928189      | 1                   | 2023-5-27     |
| Test software     | Rohde & Schwarz   | EMC32     | 68-4-90-14-003-A10 | Version9.15.00 | N/A                 | N/A           |

#### RF Test

| DESCRIPTION     | MANUFACTURER    | MODEL NO. | EQUIPMENT ID   | SERIAL NO. | CAL INTERVAL (YEAR) | CAL. DUE DATE |
|-----------------|-----------------|-----------|----------------|------------|---------------------|---------------|
| Signal Analyzer | Rohde & Schwarz | FSV40     | 68-4-74-14-004 | 101030     | 1                   | 2023-5-27     |

## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

| System Measurement Uncertainty                                                            |                                          |
|-------------------------------------------------------------------------------------------|------------------------------------------|
| Test Items                                                                                | Extended Uncertainty                     |
| Uncertainty for Conducted Emission 150kHz-30MHz<br>(for test using AMN ENV432 or ENV4200) | 3.62dB                                   |
| Uncertainty for Radiated Emission in 3m chamber<br>9KHz-30MHz                             | 4.60 dB                                  |
| Uncertainty for Radiated Emission in 3m chamber<br>30MHz-1000MHz                          | Horizontal: 4.63dB;<br>Vertical: 4.61dB; |

Remark:

Measurement Uncertainty Decision Rule

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2007, clause 4.4.3 and 4.5.1.