

TEST REPORT

Report No.	CISRR24092927801
Project No.	CISR240929278
FCC ID	2BLGM-A29
Applicant	Shenzhen Weisitai Technology Co., Ltd
Address	2, Yilai Industrial Park, No. 18 Shuitian Road, Shiyan Street, Baoan District, Shenzhen City, Guangdong Province, China
Manufacturer	Shenzhen Weisitai Technology Co., Ltd
Address	2, Yilai Industrial Park, No. 18 Shuitian Road, Shiyan Street, Baoan District, Shenzhen City, Guangdong Province, China
Product Name	Surveillance camera
Trade Mark	
Model/Type reference	A29
Listed Model(s)	Q6, Q7, Q8, V52, A1, A8B, A18, A21, A8S, A22S, A28B, A32, A33, A33-3, R10-30X, R7-30R, R11-30E, V1-30, D6-20, E27C, D8-20, CB54, CB880, CB850, B430, B70, R5, CV331S, CS621SR, CB880, CB870, CB850, CB830
Standard	47 CFR Part 15.247
Test date	September 29, 2024 to October 29, 2024
Issue date	November 2, 2024
Test result	Complied

Rory Huang

Prepared by: Rory Huang

Genry Long

Approved by: Genry Long

The test results relate only to the tested samples.

The test report should not be reproduced except in full without the written approval of Shenzhen Bangce Testing Technology Co., Ltd.

Contents

1. REPORT VERSION	3
2. TEST DESCRIPTION	4
3. SUMMARY	5
3.1. Product Description *	5
3.2. Radio Specification Description *	5
3.3. Modification of EUT	5
3.4. Deviation from standards	6
3.5. Testing Site	6
4. TEST CONFIGURATION	7
4.1. Test frequency list	7
4.2. Descriptions of test mode	7
4.3. Support unit used in test configuration	7
4.4. Test sample information	7
4.5. Environmental conditions	7
4.6. Equipment Used during the Test	8
5. TEST RESULTS	10
5.1. Evaluation Results (Evaluation)	10
5.1.1. Antenna Requirement	10
5.2. Radio Spectrum Matter Test Results (RF)	11
5.2.1. Conducted Emission at AC power line	11
5.2.2. 6dB Bandwidth	15
5.2.3. Maximum Conducted Output Power	16
5.2.4. Power Spectral Density	17
5.2.5. Conducted band edge and spurious emission	18
5.2.6. Radiated band edge emission	19
5.2.7. Radiated Spurious Emission	22
5.2.8. Duty Cycle	27
6. TEST SETUP PHOTOS	28
7. EXTERNAL AND INTERNAL PHOTOS	30
7.1. External Photos	30
7.2. Internal Photos	34

1. REPORT VERSION

Version No.	Issue date	Description
00	November 2, 2024	Original

2. TEST DESCRIPTION

No.	Test Item	Standard Requirement	Result
1	Antenna Requirement	47 CFR 15.203	Pass
2	Conducted Emission at AC power line	47 CFR 15.207(a)	Pass
3	6dB Bandwidth	47 CFR 15.247(a)(2)	Pass
4	Maximum Conducted Output Power	47 CFR 15.247(b)(3)	Pass
5	Power Spectral Density	47 CFR 15.247(e)	Pass
6	Conducted band edge and spurious emission	47 CFR 15.247(d), 15.209, 15.205	Pass
7	Radiated band edge emission	47 CFR 15.247(d), 15.209, 15.205	Pass
8	Radiated Spurious Emission	47 CFR 15.247(d), 15.209, 15.205	Pass
9	Duty Cycle Correction Factor	-	Pass

Note:

- The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Product Description *

Main unit information:	
Product Name:	Surveillance camera
Trade Mark:	
Model No.:	A29
Listed Model(s):	Q6, Q7, Q8, V52, A1, A8B, A18, A21, A8S, A22S, A28B, A32, A33, A33-3, R10-30X, R7-30R, R11-30E, V1-30, D6-20, E27C, D8-20, CB54, CB880, CB850, B430, B70, R5, CV331S, CS621SR, CB880, CB870, CB850, CB830
Power supply:	DC 5V
Hardware version:	IPC-RM1-BLK535-2M6P V1.03
Software version:	F1168011M00001-8MB_General_IPC_XM535D1_X6E-WEQ_WIFIATBM6012BX_TB.at6012bx.Nat.ds

3.2. Radio Specification Description *

Modulation type:	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g/n(HT20): OFDM(BPSK, QPSK, 16QAM, 64QAM)
Operation frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel number:	802.11b/g/n(HT20): 11 Channels
Channel separation:	5MHz
Antenna type:	IPEX
Antenna gain:	3dBi

Note:

- 1) *: Since the above information is provided by the applicant relevant results or conclusions of this report are only made for these information, Bangce is not responsible for the authenticity, integrity and results of the information and/or the validity of the conclusion.
- 2) Operation frequency list as follow:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

3.3. Modification of EUT

No modifications are made to the EUT during all test items.

3.4. Deviation from standards

None

3.5. Testing Site

Laboratory Name	Shenzhen Bangce Testing Technology Co., Ltd.
Laboratory Location	101, building 10, Yunli Intelligent Park, Shutianpu community, Matian Street, Guangming District, Shenzhen, Guangdong, China
Contact information	Tel: 86-755-2319 6848, email: service@cis-cn.net Website: http://www.cis-cn.net/
FCC registration number	736346
FCC designation number	CN1372

4. TEST CONFIGURATION

4.1. Test frequency list

Lowest Channel (LCH) (MHz)	Middle Channel (MCH) (MHz)	Highest Channel (HCH) (MHz)
2412	2437	2462

4.2. Descriptions of test mode

No	Test mode	Description
TM1	802.11b mode	Keep the EUT in 802.11b transmitting mode at lowest, middle and highest channel.
TM2	802.11g mode	Keep the EUT in 802.11g transmitting mode at lowest, middle and highest channel.
TM3	802.11n(HT20) mode	Keep the EUT in 802.11n(HT20) transmitting mode at lowest, middle and highest channel.
TM4	Link mode	Keep the EUT in WiFi linking mode with AE.

4.3. Support unit used in test configuration

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Item	Equipment name	Trade Name	Model No.
1	Adapter	Guangdong Sangu Technology Co. Ltd	SG-0501000AU
2	Phone	Huawei	MLD-AL00

4.4. Test sample information

Type	Sample No.
Engineer sample	CISR240929278-S01
Normal sample	CISR240929278-S02

4.5. Environmental conditions

Type	Requirement
Temperature:	15~35°C
Relative Humidity:	25~75%
Air Pressure:	860~1060mbar

4.6. Equipment Used during the Test

Conducted Emission at AC power line						
Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCi7	100853	2024-01-08	2025-01-07
2	Artificial power network	Schwarzbeck	NSLK8127	8127-01096	2024-01-08	2025-01-07
3	8-wire Impedance Stabilization Network	Schwarzbeck	NTFM 8158	8158-00337	2024-01-08	2025-01-07
4	Artificial power network	Schwarzbeck	ENV216	/	2024-01-08	2025-01-07

Occupied Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in non-restricted frequency bands						
Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	MXG RF Signal Generator	Agilent	N5181A	MY50145362	2024-01-08	2025-01-07
2	Spectrum analyzer	R&S	FSV-40N	102130	2024-01-08	2025-01-07
3	Vector Signal Generator	Agilent	N5182A	MY50142364	2024-06-14	2025-06-13
4	Power Meter	WCS	WCS-PM	WCSPM230405A	2024-01-08	2025-01-07

Emissions in frequency bands (above 1GHz) Band edge emissions (Radiated) Emissions in frequency bands (below 1GHz)						
Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCi7	100853	2024-01-08	2025-01-07
2	Amplifier	Tonscend	TAP9K3G40	AP23A8060270	2024-01-08	2025-01-07
3	Prime amplifier	Tonscend	TAP01018050	AP23A8060280	2024-01-08	2025-01-07
4	9*6*6 anechoic chamber	SKET	9.3*6.3*6	N/A	2024-09-02	2027-09-01
5	Spectrum analyzer	Agilent	N9020A	MY50530263	2024-01-08	2025-01-07
6	Spectrum analyzer	R&S	FSV-40N	102130	2024-01-08	2025-01-07
7	Bilog Antenna	Schwarzbeck	VULB 9163	1463	2023-01-09	2025-01-08
8	Horn Antenna	SCHWARZBECK	BBHA 9120 D	2487	2023-01-09	2025-01-08
9	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	/	2023-01-09	2025-01-08

10	RF Cable	Tonscend	Cable 1	/	2024-01-08	2025-01-07
11	RF Cable	Tonscend	Cable 2	/	2024-01-08	2025-01-07
12	RF Cable	SKET	Cable 3	/	2024-01-08	2025-01-07
13	L.I.S.N.#1	Schwarzbeck	NSLK812 7	/	2024-01-08	2025-01-07
14	L.I.S.N.#2	ROHDE&SCHWA RZ	ENV216	/	2024-01-08	2025-01-07
15	Horn Antenna	SCHWARZBECK	BBHA917 0	1130	2023-01-09	2025-01-08
16	Preamplifier	Tonscend	TAP1804 0048	AP21C806126	2024-01-08	2025-01-07
17	Variable-frequency power source	Pinhong	PH1110	/	2024-01-08	2025-01-07
18	6dB Attenuator	SKET	DC-6G	/	/	/
19	Antenna tower	SKT	Bk-4AT- BS	AT202104010 1-V1	2024-06-14	2025-06-13

5. TEST RESULTS

5.1. Evaluation Results (Evaluation)

5.1.1. Antenna Requirement

Test Requirement:

Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

5.1.1.1. Test Result

Pass

5.1.1.2. Conclusion:

The EUT antenna is IPEX(3dBi), the directional gain of the antenna less than 6dBi. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used. Antenna structure please refer to the EUT internal photographs antenna photo.

5.2. Radio Spectrum Matter Test Results (RF)


5.2.1. Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
*Decreases with the logarithm of the frequency.			
Test Method:	ANSI C63.10-2020 section 6.2		
Procedure:	1. The EUT was setup according to ANSI C63.10 requirements. 2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. 3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. 4. The peripheral devices are also connected to the main power through a LISN. (Refer to the block diagram of the test setup and photographs) 5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source. 6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length. 7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz. 8. During the above scans, the emissions were maximized by cable manipulation.		

5.2.1.1. E.U.T. Operation

Operating Environment:					
Temperature:	22.9 °C	Humidity:	56.3 %	Atmospheric Pressure:	103 kPa
Pre test mode:	TM1, TM2, TM3, TM4				
Final test mode:	TM1, TM2, TM3, TM4				

5.2.1.2. Test Setup Diagram




5.2.1.3. Test Result

Pass

5.2.1.4. Test Data


Have pre-scan all test mode, found TM4 mode which it was worst case, so only show the worst case's data on this report.

Mode4 / Line: Line



No.	Frequency	Limit dBuV	Level dBuV	Margin dB	Reading dBuV	Factor dB	Detector	Polar
1	150.000kHz	66.0	50.3	-15.7	50.3	0.0	QP	L1
2	470.000kHz	56.5	42.6	-13.9	42.5	0.1	QP	L1
3	906.000kHz	56.0	34.0	-22.0	33.9	0.1	QP	L1
4	4.914MHz	56.0	38.6	-17.4	38.4	0.2	QP	L1
5	9.406MHz	60.0	32.0	-28.0	31.7	0.3	QP	L1
6	19.550MHz	60.0	27.9	-32.1	27.4	0.5	QP	L1
7	150.000kHz	56.0	28.3	-27.7	28.3	0.0	CAV	L1
8	470.000kHz	46.5	27.2	-19.3	27.1	0.1	CAV	L1
9	898.000kHz	46.0	24.0	-22.0	23.9	0.1	CAV	L1
10	1.886MHz	46.0	19.2	-26.8	19.1	0.1	CAV	L1
11	4.854MHz	46.0	29.2	-16.8	29.0	0.2	CAV	L1
12	19.294MHz	50.0	17.7	-32.3	17.2	0.5	CAV	L1

Mode4 / Line: Neutral



No.	Frequency	Limit dBuV	Level dBuV	Margin dB	Reading dBuV	Factor dB	Detector	Polar
1	234.000kHz	62.3	37.6	-24.7	37.6	0.0	QP	N
2	466.000kHz	56.6	40.2	-16.4	40.1	0.1	QP	N
3	934.000kHz	56.0	35.7	-20.3	35.6	0.1	QP	N
4	1.866MHz	56.0	28.8	-27.2	28.7	0.1	QP	N
5	4.958MHz	56.0	41.2	-14.8	41.0	0.2	QP	N
6	20.578MHz	60.0	30.8	-29.2	30.3	0.5	QP	N
7	226.000kHz	52.6	26.7	-25.9	26.6	0.1	CAV	N
8	470.000kHz	46.5	34.1	-12.4	34.0	0.1	CAV	N
9	938.000kHz	46.0	23.9	-22.1	23.8	0.1	CAV	N
10	4.926MHz	46.0	31.6	-14.4	31.4	0.2	CAV	N
11	8.830MHz	50.0	24.7	-25.3	24.4	0.3	CAV	N
12	19.954MHz	50.0	19.6	-30.4	19.1	0.5	CAV	N

Note:

- 1). Result = Reading +Correct (Insertion Loss + Cable Loss + Attenuator Factor)
- 2). Margin = Result - Limit

5.2.2. 6dB Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020, section 11.8
Procedure:	11.8.1 Option 1 The steps for the first option are as follows: a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max-hold. e) Sweep = No faster than coupled (auto) time. f) Allow the trace to stabilize. g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value. 11.8.2 Option 2 The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

5.2.2.1. E.U.T. Operation

Operating Environment:					
Temperature:	22.9 °C	Humidity:	56.3 %	Atmospheric Pressure:	103 kPa
Pre test mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

5.2.2.2. Test Setup Diagram



5.2.2.3. Test Result

Pass

5.2.2.4. Test Data

Please Refer to Appendix for Details.

5.2.3. Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2020 section 11.9.1
Procedure:	ANSI C63.10-2020, section 11.9.1 Maximum peak conducted output power

5.2.3.1. E.U.T. Operation

Operating Environment:					
Temperature:	22.9 °C	Humidity:	56.3 %	Atmospheric Pressure:	103 kPa
Pre test mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

5.2.3.2. Test Setup Diagram



5.2.3.3. Test Result

Pass

5.2.3.4. Test Data

Please Refer to Appendix for Details.

5.2.4. Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2020, section 11.10
Procedure:	ANSI C63.10-2020, section 11.10, Maximum power spectral density level in the fundamental emission

5.2.4.1. E.U.T. Operation

Operating Environment:					
Temperature:	22.9 °C	Humidity:	56.3 %	Atmospheric Pressure:	103 kPa
Pre test mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

5.2.4.2. Test Setup Diagram



5.2.4.3. Test Result

Pass

5.2.4.4. Test Data

Please Refer to Appendix for Details.

5.2.5. Conducted band edge and spurious emission

Test Requirement:	47 CFR 15.247(d), 15.209, 15.205
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020 section 11.11
Procedure:	ANSI C63.10-2020 Section 11.11.1, Section 11.11.2, Section 11.11.3

5.2.5.1. E.U.T. Operation

Operating Environment:					
Temperature:	22.9 °C	Humidity:	56.3 %	Atmospheric Pressure:	103 kPa
Pre test mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

5.2.5.2. Test Setup Diagram



5.2.5.3. Test Result

Pass

5.2.5.4. Test Data

Please Refer to Appendix for Details.


5.2.6. Radiated band edge emission

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.10		
Procedure:	1. EUT was setup and tested according to ANSI C63.10 . 2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. 3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. 4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement. 5. Use the following spectrum analyzer settings: a) Span shall wide enough to fully capture the emission being measured b) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement For average measurement: use duty cycle correction factor method (DCCF), Averager level = Peak level + DCCF		

5.2.6.1. E.U.T. Operation

Operating Environment:					
Temperature:	22.9 °C	Humidity:	56.3 %	Atmospheric Pressure:	103 kPa
Pre test mode:	TM1, TM2, TM3, TM4				
Final test mode:	TM1, TM2, TM3, TM4				

5.2.6.2. Test Setup Diagram



5.2.6.3. Test Result

Pass

5.2.6.4. Test Data

Have pre-scan all test mode, found TM1 mode which it was worst case, so only show the worst case's data on this report.

Test channel:CH1										
Freq. (MHz)	Reading (dBuv)	Ant. Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correc tion Factor (dB/m)	Level (dBuv)	Limit (dBu V/m)	Margin (dB)	Remark	Polarity
2390.00	70.21	28.62	4.08	38.62	-5.92	64.29	74	9.71	Peak	Horizontal
2390.00	51.40	28.62	4.08	38.62	-5.92	45.48	54	8.52	Average	Horizontal
2390.00	69.33	28.62	4.08	38.62	-5.92	63.41	74	10.59	Peak	Vertical
2390.00	50.11	28.62	4.08	38.62	-5.92	44.19	54	9.81	Average	Vertical

Test channel:CH11										
Freq. (MHz)	Reading (dBuv)	Ant. Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correc tion Factor (dB/m)	Level (dBuv)	Limit (dBu V/m)	Margin (dB)	Remark	Polarity
2483.50	69.89	29.45	3.91	40.17	-6.81	63.08	74	10.92	Peak	Horizontal
2483.50	49.67	29.45	3.91	40.17	-6.81	42.86	54	11.14	Average	Horizontal
2483.50	68.37	29.45	3.91	40.17	-6.81	61.56	74	12.44	Peak	Vertical
2483.50	50.70	29.45	3.91	40.17	-6.81	43.89	54	10.11	Average	Vertical

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Margin = Limit - Level
- 3) Average measurement was not performed if peak level is lower than average limit
- 4) The other emission levels were very low against the limit.

5.2.7. Radiated Spurious Emission

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`																																
Test Limit:	FCC CFR Title 47 Part 15 Subpart C Section 15.209 <table><tr><th>Frequency</th><th>Limit (dBuV/m)</th><th>Value</th></tr><tr><td>0.009 MHz ~0.49 MHz</td><td>2400/F(kHz) @300m</td><td>Quasi-peak</td></tr><tr><td>0.49 MHz ~ 1.705 MHz</td><td>24000/F(kHz) @30m</td><td>Quasi-peak</td></tr><tr><td>1.705 MHz ~30 MHz</td><td>30 @30m</td><td>Quasi-peak</td></tr></table> Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3) Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3) <table><tr><th>Frequency</th><th>Limit (dBuV/m @3m)</th><th>Value</th></tr><tr><td>30MHz~88MHz</td><td>40.00</td><td>Quasi-peak</td></tr><tr><td>88MHz~216MHz</td><td>43.50</td><td>Quasi-peak</td></tr><tr><td>216MHz~960MHz</td><td>46.00</td><td>Quasi-peak</td></tr><tr><td>960MHz~1GHz</td><td>54.00</td><td>Quasi-peak</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.00</td><td>Average</td></tr><tr><td>74.00</td><td>Peak</td></tr></table>	Frequency	Limit (dBuV/m)	Value	0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak	0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak	1.705 MHz ~30 MHz	30 @30m	Quasi-peak	Frequency	Limit (dBuV/m @3m)	Value	30MHz~88MHz	40.00	Quasi-peak	88MHz~216MHz	43.50	Quasi-peak	216MHz~960MHz	46.00	Quasi-peak	960MHz~1GHz	54.00	Quasi-peak	Above 1GHz	54.00	Average	74.00	Peak
Frequency	Limit (dBuV/m)	Value																															
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak																															
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak																															
1.705 MHz ~30 MHz	30 @30m	Quasi-peak																															
Frequency	Limit (dBuV/m @3m)	Value																															
30MHz~88MHz	40.00	Quasi-peak																															
88MHz~216MHz	43.50	Quasi-peak																															
216MHz~960MHz	46.00	Quasi-peak																															
960MHz~1GHz	54.00	Quasi-peak																															
Above 1GHz	54.00	Average																															
	74.00	Peak																															
Test Method:	ANSI C63.10-2020 section 6.6.4																																
Procedure:	below 1GHz: 1. The EUT was setup and tested according to ANSI C63.10. 2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level. 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower. 4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines. 5. Set to the maximum power setting and enable the EUT transmit continuously. 6. Use the following spectrum analyzer settings a) Span shall wide enough to fully capture the emission being measured; b) RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold; If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. Above 1GHz: 1. The EUT was setup and tested according to ANSI C63.10. 2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level. 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower. 4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines. 5. Set to the maximum power setting and enable the EUT transmit continuously.																																

6. Use the following spectrum analyzer settings
a) Span shall wide enough to fully capture the emission being measured;
b) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement
For average measurement: use duty cycle correction factor method (DCCF) Averager level = Peak level + DCCF

5.2.7.1. E.U.T. Operation



Operating Environment:

Temperature:	22.9 °C	Humidity:	56.3 %	Atmospheric Pressure:	103 kPa
--------------	---------	-----------	--------	-----------------------	---------

Pre test mode:	TM1, TM2, TM3, TM4
----------------	--------------------

Final test mode:	TM1, TM2, TM3, TM4
------------------	--------------------

5.2.7.2. Test Setup Diagram



5.2.7.3. Test Result

Pass

5.2.7.4. Test Data

For 9 kHz ~ 30 MHz


The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

For 30 MHz ~ 1000 MHz

Have pre-scan all test mode, found TM1 mode CH01 which it was worst case, so only show the worst case's data on this report.

Polarization: Horizontal / CH: L

Test Graph




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	49.4	3.50	19.01	15.51	40.00	20.99	Horizontal	PASS
2	57.16	3.10	17.56	14.46	40.00	22.44	Horizontal	PASS
3	105.66	3.46	17.10	13.64	43.50	26.40	Horizontal	PASS
4	289.96	4.88	20.29	15.41	46.00	25.71	Horizontal	PASS
5	546.04	4.78	25.35	20.57	46.00	20.65	Horizontal	PASS
6	986.42	4.82	31.11	26.29	54.00	22.89	Horizontal	PASS

Polarization: Vertical / CH: L

Test Graph



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	49.4	3.72	19.23	15.51	40.00	20.77	Vertical	PASS
2	59.1	3.80	17.97	14.17	40.00	22.03	Vertical	PASS
3	99.84	3.49	17.15	13.66	43.50	26.35	Vertical	PASS
4	289.96	5.65	21.06	15.41	46.00	24.94	Vertical	PASS
5	551.86	6.15	26.84	20.69	46.00	19.16	Vertical	PASS
6	968.96	6.44	32.48	26.04	54.00	21.52	Vertical	PASS

Note:

- 1) $\text{Level} = \text{Reading} + \text{Factor/Transd}$; $\text{Factor/Transd} = \text{Antenna Factor} + \text{Cable Loss} - \text{Preamp Factor}$
- 2) $\text{Margin} = \text{Limit} - \text{Level}$
- 3) Average measurement was not performed if peak level is lower than average limit (54 dBμV/m) for above 1GHz.
- 4) The other emission levels were very low against the limit.
- 5) This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.

For 1 GHz ~ 25 GHz

Have pre-scan all test mode, found TM1 mode which it was worst case, so only show the worst case's data on this report.

Test channel:CH01										
Freq. (MHz)	Reading (dBuv)	Ant. Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)	Level (dBuv)	Limit (dBu V/m)	Margin (dB)	Remark	Polarity
4824.00	69.46	31.33	4.23	38.62	-3.06	66.40	74	7.60	Peak	Horizontal
4824.00	49.44	31.33	4.23	38.62	-3.06	46.38	54	7.62	Average	Horizontal
4824.00	65.51	31.33	4.23	38.62	-3.06	62.45	74	11.55	Peak	Vertical
4824.00	50.81	31.33	4.23	38.62	-3.06	47.75	54	6.25	Average	Vertical

Test channel:CH06										
Freq. (MHz)	Reading (dBuv)	Ant. Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)	Level (dBuv)	Limit (dBu V/m)	Margin (dB)	Remark	Polarity
4874.00	70.83	30.26	4.09	38.29	-3.94	66.89	74	7.11	Peak	Horizontal
4874.00	50.42	30.26	4.09	38.29	-3.94	46.48	54	7.52	Average	Horizontal
4874.00	67.04	30.26	4.09	38.29	-3.94	63.10	74	10.90	Peak	Vertical
4874.00	50.82	30.26	4.09	38.29	-3.94	46.88	54	7.12	Average	Vertical

Test channel:CH11										
Freq. (MHz)	Reading (dBuv)	Ant. Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)	Level (dBuv)	Limit (dBu V/m)	Margin (dB)	Remark	Polarity
4924.00	64.19	31.97	4.11	38.47	-2.39	61.80	74	12.20	Peak	Horizontal
4924.00	49.74	31.97	4.11	38.47	-2.39	47.35	54	6.65	Average	Horizontal
4924.00	67.31	31.97	4.11	38.47	-2.39	64.92	74	9.08	Peak	Vertical
4924.00	51.19	31.97	4.11	38.47	-2.39	48.80	54	5.20	Average	Vertical

5.2.8. Duty Cycle

Test Limit:	1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously 3. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel, RBW= 10 MHz, VBW $\geq$ RBW, Sweep = as necessary to capture the entire dwell time channel Detector function = RMS, Trigger mode Measure and record the duty cycle data
Limit:	--

5.2.8.1. E.U.T. Operation

Operating Environment:					
Temperature:	22.9 °C	Humidity:	56.3 %	Atmospheric Pressure:	103 kPa
Pre test mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

5.2.8.2. Test Setup Diagram



5.2.8.3. Test Result


Pass

5.2.8.4. Test Data


Please Refer to Appendix for Details.

6. TEST SETUP PHOTOS


Conducted Emission at AC power line



Radiated Spurious Emission (Above 1GHz)



Radiated Spurious Emission (below 1GHz)





7. EXTERNAL AND INTERNAL PHOTOS

7.1. External Photos



















7.2. Internal Photos






















-----End of the report-----