


REV	DESCRIPTION OF REVISION	ENG APPD	DATE
01	INITIAL RELEASE	AHAN	12OCT21
-	-	-	-





- NOTE:
1. REFER TO NETGEAR SPEC. DOC-00093 FOR COLOR TOLERANCES.
 2. INK COLOR IS SHOWN TO THE RIGHT.
 3. DIE LINES ARE MAGENTA COLOR AND DO NOT PRINT.
 4. MAC & SERIAL NUMBERS TO BE PRINTED BY THE ODM.
 5. See NTGR DOC-00112 for SN standard.

6. SN, MAC address,
to be encoded QR (2D) barcode.
A. EACH DATA ELEMENT IS TO BE SEPARATED BY A
SEMICOLON WITH NO SPACE, AND TO BE PRINTED IN
THIS EXACT ORDER.

ELEMENT: SN:SERIAL NUMBER;SK:NETGEAR SKU NAME;MAC:MAC ADDRESS;
EXAMPLE: 510789235724097;ORBI BASE STATION;8A:00:27:C5:84:B3

The definition and sequence of QR code
WIFI:S:SSID;T:WPA2;P:PASSWORD;SN:SERIAL NUMBER;SK:NETGEAR SKU NAME;MAC:MAC ADDRESS;
The information of string
[WIFI:S:SSID]->(WIFI:S:ORBIXX) -> Preset SSID, Example - ORBI75
[T:WPA2;P:PASSWORD]-> (T:WPA2;P:PASSWORD) -> Random Network Key, Example - blackrabbit386
[SN:SERIAL NUMBER] ->(SN:)->固定字元/ (SERIAL NUMBER)->依照產品輸入訊息(EX:@62NDYMSC00001@)
[SK:NETGEAR SKU NAME] -> (SK:)->固定字元/ NETGEAR SKU NAME->依照工單&生產品名By work order and

7. INSURE COUNTRY OF ORIGIN IS CORRECT.
- A. IF COUNTRY OF ORIGIN IS PRE-PRINTED, UNHIDE THE APPROPRIATE COUNTRY OF ORIGIN LAYER
AND INCLUDE COUNTRY OF ORIGIN ON LABEL.
 - B. IF COUNTRY OF ORIGIN IS POST-PRINTED USING A THERMAL PRINTER (OR EQUIVALENT), OMIT TEXT
FROM ARTWORK (USE LAYERS).



AUTHOR: AHAN	TITLE: AW,PLBL,RBR760NA,V1	NETGEAR	
SHEET: 1 of 1	THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WHEREWITH IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF NETGEAR, INC.	P/N: AW-14920-03	REV: 01