



FCC Test Report

Report No.: ARFR-19AU0427VTSHPB-2

FCC ID: 2ANDLTYGWBS-01

Product: BLEMESH(SIG) Gateway

Model: TYGWBS-01;TYGWBS-01N

Received Date: Aug.06, 2019

Test Date: Aug.06 to Aug.15, 2019

Issued Date: Aug.20, 2019

Applicant: Hangzhou Tuya Information Technology Co., Ltd

Address: Room701, Building3, More Center,No.87 GuDun Road, Hangzhou, Zhejiang, China

Manufacturer: Hangzhou Tuya Information Technology Co., Ltd

Address: Room701, Building3, More Center,No.87 GuDun Road, Hangzhou, Zhejiang, China

Issued By: BUREAU VERITAS ADT (Shanghai) Corporation

Lab Address: No. 829, Xinzhuan Road, Shanghai, P.R.China (201612)

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record.....	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Test Instruments.....	7
2.2 Measurement Uncertainty	8
2.3 Modification Record	8
3 General Information.....	9
3.1 General Description of EUT.....	9
3.2 Description of Test Modes	10
3.2.1 Test Mode Applicability:	10
3.2.2 Test Condition:	12
3.3 Duty Cycle of Test Signal	13
3.4 Description of Support Units.....	14
3.5 General Description of Applied Standards	14
4 Test Procedure and Results	15
4.1 6dB Bandwidth Measurement	15
4.1.1 Limit.....	15
4.1.2 Test Setup.....	15
4.1.3 Test Procedures	15
4.1.4 Deviation of Test Standard.....	15
4.1.5 Test Results	16
4.2 Conducted Output Power Measurement.....	20
4.2.1 Limit.....	20
4.2.2 Test Setup.....	20
4.2.3 Test Procedures	20
4.2.4 Deviation of Test Standard.....	20
4.2.5 Test Results	21
4.3 Power Spectral Density Measurement.....	25
4.3.1 Limit.....	25
4.3.2 Test Setup.....	25
4.3.3 Test Procedures	25
4.3.4 Deviation of Test Standard.....	25

4.3.5	Test Results	26
4.4	Emissions in non-restricted frequency bands.....	31
4.4.1	Limit.....	31
4.4.2	Test Setup.....	31
4.4.3	Test Procedures	31
4.4.4	Deviation of Test Standard.....	32
4.4.5	Test Results	33
4.5	Radiated Emission Measurement.....	46
4.5.1	Limits	46
4.5.2	Test Procedures	46
4.5.3	Deviation from Test Standard.....	48
4.5.4	Test Setup.....	49
4.5.5	EUT Operating Conditions.....	50
4.5.6	Test Results	50
4.6	Conducted Emission Measurement.....	57
4.6.1	Limits	57
4.6.2	Test Procedures	57
4.6.3	Deviation from Test Standard.....	57
4.6.4	Test Setup.....	58
4.6.5	EUT Operating Conditions.....	58
4.6.6	Test Results	59
5	Pictures of Test Arrangements	61



Release Control Record

Issue No.	Description	Date Issued
ARFR-19AU0427VTSHPB-2	Original release	Aug.20, 2019

1 Certificate of Conformity

Product: BLEMESH(SIG) Gateway

Brand: --

Model: TYGWBS-01; TYGWBS-01N

Applicant: Hangzhou Tuya Information Technology Co., Ltd

Test Date: Aug.06 to Aug.15, 2019

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2013

The above equipment has been tested by **BUREAU VERITAS ADT (Shanghai) Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :




, Date:

Aug.20, 2019

Will YAN

Project Engineer

Approved by :


Daniel SUN
RF Supervisor

, Date:

Aug.20, 2019

2 Summary of Test Results

The EUT has been tested according to the following specifications:

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.205 / 15.209 / 15.247(d)	Radiated Emissions Measurement	PASS	Meet the requirement of limit.
15.247(d)	Emissions in non-restricted frequency bands	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 Test Instruments

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Hybrid antenna(25MHz-1.5GHz)	Schwarzbeck	VULB9168	E1A1012	Feb.09,18	Feb.08,20
Horn Antenna(1GHz -18GHz)	Schwarzbeck	BBHA9120D	E1A1017	Aug.26,19	Aug.25,20
Pre-Amplifier(100kHz-1.3GHz)	Agilent	8447D	E1A2001	Oct.19, 18	Oct.18, 19
Pre-Amplifier(1GHz-26.5GHz)	Agilent	8449B	E1A2002	Mar. 26, 18	Mar. 25, 20
EMI test receiver	R&S	ESR7	E1R1005	Dec.05, 18	Dec.04, 19
Spectrum Analyzer	Keysight	N9030B	E1S1003	Jul.23,19	Jul.22, 20
EMI test receiver	R&S	ESCS30	E1R1001	Mar.26, 19	Mar.25, 20
LISN	R&S	ENV216	E1L1011	Jul.18, 19	Jul.17, 20
Humidity&Temp Tester	Baolima	WS508	E1H1011	Apr. 04, 19	Apr. 03, 20
Test Software	ADT	ADT_COND_V 7.3.1	N/A	N/A	N/A
Test Software	Toscend	JS32-RE	N/A	N/A	N/A
Test Software	Toscend	JS1120	N/A	N/A	N/A

2.2 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Frequency	Expanded Uncertainty ($k=2$) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.83 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.36 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	3.47 dB
	6GHz ~ 18GHz	3.75 dB
	18GHz ~ 40GHz	3.30 dB

2.3 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	BLEMESH(SIG) Gateway
Brand	--
Test Model	TYGWBS-01; TYGWBS-01N
Model Difference	The two models exactly are the same except the model name and the package.
Power Rating	5VDC/1A with adaptor 100-240V~,50/60Hz
Modulation Type	GFSK
Modulation Technology	Bluetooth Low Energy 4.2&5.0
Operating Frequency	2402 ~ 2480MHz
Number of Channel	40
Antenna Type	PCB Antenna
Antenna Connector	--
Antenna Gain	2.5dBi

Note: For more details, please refer to the User's manual of the EUT.

Modulation Mode	TX /RX Function
BLE	1TX / 1RX

3.2 Description of Test Modes

40 channels are provided for Bluetooth LE.

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
0	2402 MHz	20	2442 MHz
1	2404 MHz	21	2444 MHz
2	2406 MHz	22	2446 MHz
3	2408 MHz	23	2448 MHz
4	2410 MHz	24	2450 MHz
5	2412 MHz	25	2452 MHz
6	2414 MHz	26	2454 MHz
7	2416 MHz	27	2456 MHz
8	2418 MHz	28	2458 MHz
9	2420 MHz	29	2460 MHz
10	2422 MHz	30	2462 MHz
11	2424 MHz	31	2464 MHz
12	2426 MHz	32	2466 MHz
13	2428 MHz	33	2468 MHz
14	2430 MHz	34	2470 MHz
15	2432 MHz	35	2472 MHz
16	2434 MHz	36	2474 MHz
17	2436 MHz	37	2476 MHz
18	2438 MHz	38	2478 MHz
19	2440 MHz	39	2480 MHz

3.2.1 Test Mode Applicability:

EUT Configure Mode	Applicable to				Description
	RE ≥ 1G	RE < 1G	PLC	APCM	
-	√	√	-	√	-

Where **RE≥1G**: Radiated Emission above 1GHz

RE≤1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1 GHz):

- ☒ ☐ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0, 19, 39	GFSK

Radiated Emission Test (Below 1 GHz):

- ☒ ☐ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0	GFSK

Power Line Conducted Emission Test:

- ☐ ☐ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☐ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0	GFSK

Antenna Port Conducted Measurement

- ☒ ☐ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0, 19, 39	GFSK

3.2.2 Test Condition:

Applicable to	Normal Environmental Conditions	Normal Input Power
RE $\geq$ 1G	23deg. C, 58%RH	120Vac, 60Hz
RE < 1G	23deg. C, 58%RH	120Vac, 60Hz
PLC	--	--
APCM	25deg. C, 60%RH	120Vac, 60Hz

3.3 Duty Cycle of Test Signal

Modulation	Test Freq (MHz)	Duty Cycle (%)
BLE	2402	100

3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standard:

FCC Part 15, Subpart C (15.247)

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10:2013

All relaxed test items have been performed and recorded as per the above standard.


4 Test Procedure and Results

4.1 6dB Bandwidth Measurement

4.1.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz

4.1.2 Test Setup



4.1.3 Test Procedures

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” for compliance to FCC 47CFR 15.247 requirements (clause 8.2).

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., $RBW = 100 \text{ kHz}$, $VBW \geq 3 \cdot RBW$, peak detector with maximum hold) is implemented by the instrumentation function.

4.1.4 Deviation of Test Standard

No deviation.


4.1.5 Test Results

BLE 4.2

Channel	Frequency (MHz)	Occpuied Bandwidth (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	1.0620	0.6692	0.5	Pass
19	2440	1.0596	0.6742	0.5	Pass
39	2480	1.0536	0.6721	0.5	Pass



BLE (2440MHz)



BLE (2480MHz)




BLE 5.0

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	2.0933	1.3920	0.5	Pass
19	2440	2.0828	1.3940	0.5	Pass
39	2480	2.0754	1.3530	0.5	Pass

Spectrum Plot

BLE (2402MHz)



BLE (2440MHz)



BLE (2480MHz)




4.2 Conducted Output Power Measurement

4.2.1 Limit

For systems using digital modulation in the 2400 – 2483.5 MHz bands: 1 Watt (30 dBm)

4.2.2 Test Setup



4.2.3 Test Procedures

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” for compliance to FCC 47CFR 15.247 requirements (clause 9.2.2.4).

- a) Set RBW $\geq$ DTS bandwidth
- b) Set VBW $\geq$ 3 RBW.
- c) Set Span $\geq$ 3 RBW.
- d) Sweep time = auto couple.
- e) Detector = peak
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize
- h) Use peak marker function to determine the peak amplitude level.

4.2.4 Deviation of Test Standard

No deviation.


4.2.5 Test Results

BLE 4.2


Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
0	2402	7.98	30	Pass
19	2440	8.11	30	Pass
39	2480	8.41	30	Pass

Spectrum Plot


BLE (2402MHz)



BLE (2440MHz)



BLE (2480MHz)




BLE 5.0


Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
0	2402	8.13	30	Pass
19	2440	8.23	30	Pass
39	2480	8.49	30	Pass

Spectrum Plot


BLE (2402MHz)



BLE (2440MHz)



BLE (2480MHz)




4.3 Power Spectral Density Measurement

4.3.1 Limit

The Maximum of Power Spectral Density Measurement is 8 dBm.

4.3.2 Test Setup



4.3.3 Test Procedures

The power output per FCC § 15.247(e) was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” (clause 10.5) for compliance to FCC 47CFR 15.247 requirements.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.3.4 Deviation of Test Standard


No deviation.

4.3.5 Test Results


BLE 4.2

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
0	2402	-3.54	8	Pass
19	2440	-3.27	8	Pass
39	2480	-4.02	8	Pass


Spectrum Plot
BLE (2402MHz)



BLE (2440MHz)



BLE (2480MHz)




BLE 5.0


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
0	2402	-6.80	8	Pass
19	2440	-6.46	8	Pass
39	2480	-7.34	8	Pass

Spectrum Plot


BLE (2402MHz)



BLE (2440MHz)



BLE (2480MHz)




4.4 Emissions in non-restricted frequency bands

4.4.1 Limit

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

4.4.2 Test Setup



4.4.3 Test Procedures

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” (clause 11.0) for compliance to FCC 47CFR 15.247 requirements.

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.4.4 Deviation of Test Standard

No deviation.


4.4.5 Test Results

BLE 4.2

Channel	Frequency (MHz)	Pass / Fail
0	2402	Pass
19	2440	Pass
39	2480	Pass

Spectrum Plot


BLE (2402MHz)



BLE (2440MHz)




BLE (2480MHz)




Spectrum Plot

BLE (2402MHz) Band Edge




BLE (2480MHz) Band Edge





TestMode	Channel	FreqRange	RefLevel	Result	Limit	Verdict
BLE	2402	30~1000	0.0	-53.80	-12.26	PASS
BLE	2402	1000~26500	0.0	-35.49	-12.26	PASS
BLE	2440	30~1000	0.0	-54.36	-12.00	PASS
BLE	2440	1000~26500	0.0	-35.88	-12.00	PASS
BLE	2480	30~1000	0.0	-53.72	-11.92	PASS
BLE	2480	1000~26500	0.0	-37.29	-11.92	PASS

Spectrum Plot



BLE (2402MHz) Out-of-Band Emissions



BLE (2440MHz) Out-of-Band Emissions



BLE (2480MHz) Out-of-Band Emissions




BLE 5.0


Channel	Frequency (MHz)	Pass / Fail
0	2402	Pass
19	2440	Pass
39	2480	Pass

Spectrum Plot


BLE (2402MHz)



BLE (2440MHz)




BLE (2480MHz)




Spectrum Plot

BLE (2402MHz) Band Edge




BLE (2480MHz) Band Edge





TestMode	Channel	FreqRange	RefLevel	Result	Limit	Verdict
BLE	2402	30~1000	0.0	-53.89	-13.47	PASS
BLE	2402	1000~26500	0.0	-36.42	-13.47	PASS
BLE	2440	30~1000	0.0	-53.42	-13.22	PASS
BLE	2440	1000~26500	0.0	-36.62	-13.22	PASS
BLE	2480	30~1000	0.0	-52.74	-13.12	PASS
BLE	2480	1000~26500	0.0	-37.94	-13.12	PASS

Spectrum Plot

BLE (2402MHz) Out-of-Band Emissions



BLE (2440MHz) Out-of-Band Emissions



BLE (2480MHz) Out-of-Band Emissions



4.5 Radiated Emission Measurement

4.5.1 Limits

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

4.5.2 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degree to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotate table was turned from

0 degree to 360 degree to find the maximum reading.

- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz & 360 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1/T for

RMS Average (Duty cycle < 98 %) for Peak detection at frequency above 1 GHz.


4. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz
(Duty cycle $\geq$ 98 %) for Average detection (AV) at frequency above 1 GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

4.5.3 Deviation from Test Standard


No deviation.

4.5.4 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.5.5 EUT Operating Conditions

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.

4.5.6 Test Results

Radiated Emissions Range 9kHz~30MHz

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Radiated Emissions Range 30MHz~1GHz

Below is the worst test data


Channel	TX Channel 0	Detector Function	Quasi-Peak (QP)
Frequency Range	30MHz ~ 1GHz	Antenna Polarity	Horizontal

Spurious Emission Level					
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Correction Factor (dB/m)
1	30.97	19.68	40.00	-20.32	-12.01
2	56.57	18.22	40.00	-21.78	-10.40
3	120.40	16.84	43.50	-26.66	-13.17
4	191.21	18.16	43.50	-25.34	-12.63
5	254.26	20.51	46.50	-25.99	-10.91
6	624.99	24.12	46.50	-22.38	-2.70

REMARKS:

1. Emission Level(dBuV/m) = Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Test Plot:




Channel	TX Channel 0	Detector Function	Quasi-Peak (QP)
Frequency Range	30MHz ~ 1GHz	Antenna Polarity	Vertical

Spurious Emission Level					
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Correction Factor (dB/m)
1	32.52	20.99	40.00	-19.01	-11.85
2	51.53	25.61	40.00	-14.39	-10.33
3	55.80	24.96	40.00	-15.04	-10.39
4	120.98	24.71	43.50	-18.79	-13.10
5	178.6	23.79	43.50	-19.71	-11.60
6	482.60	27.18	46.50	-19.32	-5.36

REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Test Plot:



Radiated Emission Range 1GHz~10th Harmonic

BLE 4.1

Below is the worst test data

Channel	TX Channel 0	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Spurious Emission Level							
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Correction Factor (dB/m)	Antenna Polarity	Detector
1	4803.75	52.49	74.00	-21.51	-6.24	H	PK
2	4804.60	49.30	54.00	-4.70	-6.24	H	AV
3	4803.75	53.76	74.00	-20.24	-6.24	V	PK
4	4804.60	50.95	54.00	-3.05	-6.24	V	AV

REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Channel	TX Channel 19	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Spurious Emission Level							
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Correction Factor (dB/m)	Antenna Polarity	Detector
1	4879.40	51.45	74.00	-22.55	-6.38	H	PK
2	4880.25	48.23	54.00	-5.77	-6.38	H	AV
3	4880.25	54.33	74.00	-19.67	-6.38	V	PK
4	4881.10	52.25	54.00	-1.75	-6.39	V	AV

REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Channel	TX Channel 39	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Spurious Emission Level							
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Correction Factor (dB/m)	Antenna Polarity	Detector
1	4959.30	50.30	74.00	-23.70	-6.53	H	PK
2	4960.15	46.58	54.00	-7.42	-6.53	H	AV
3	4959.30	51.26	74.00	-22.74	-6.53	V	PK
4	4961.00	47.88	54.00	-6.12	-6.54	V	AV

REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

BLE 5.0

Below is the worst test data

Channel	TX Channel 0	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Spurious Emission Level							
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Correction Factor (dB/m)	Antenna Polarity	Detector
1	4804.60	52.20	74.00	-21.80	-6.24	H	PK
2	4805.45	48.33	54.00	-5.67	-6.24	H	AV
3	4802.90	53.72	74.00	-20.28	-6.24	V	PK
4	4803.75	49.31	54.00	-4.69	-6.24	V	AV

REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Channel	TX Channel 19	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Spurious Emission Level							
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Correction Factor (dB/m)	Antenna Polarity	Detector
1	4881.10	51.56	74.00	-22.44	-6.39	H	PK
2	4881.95	46.49	54.00	-7.51	-6.39	H	AV
3	4881.10	53.09	74.00	-20.91	-6.39	V	PK
4	4881.10	49.33	54.00	-4.67	-6.39	V	AV

REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Channel	TX Channel 39	Detector Function	Peak (PK)
Frequency Range	1GHz ~ 25GHz		Average (AV)

Spurious Emission Level							
No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Correction Factor (dB/m)	Antenna Polarity	Detector
1	4961.00	49.89	74.00	-24.11	-6.54	H	PK
2	4961.00	45.25	54.00	-8.75	-6.54	H	AV
3	4959.30	50.30	74.00	-23.70	-6.53	V	PK
4	4960.15	45.67	54.00	-8.33	-6.53	V	AV

REMARKS:

1. Emission Level(dBuV/m) = Original Spectrum reading (dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.6 Conducted Emission Measurement

4.6.1 Limits

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.6.2 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.6.3 Deviation from Test Standard

No deviation.

4.6.4 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.6.5 EUT Operating Conditions

Same as 4.1.6.

4.6.6 Test Results

Working While Charging


Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	-----------------------------------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.54882	9.68	29.60	25.49	39.28	35.17	56.00	46.00	-16.72	-10.83
2	0.84598	9.58	21.93	17.86	31.51	27.44	56.00	46.00	-24.49	-18.56
3	0.98283	9.59	20.91	16.62	30.50	26.21	56.00	46.00	-25.50	-19.79
4	1.19159	9.62	21.55	17.32	31.17	26.94	56.00	46.00	-24.83	-19.06
5	1.59823	9.69	29.81	23.17	39.50	32.86	56.00	46.00	-16.50	-13.14
6	3.07621	9.78	13.20	10.12	22.98	19.90	56.00	46.00	-33.02	-26.10

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.

Test Plot:




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	-----------------------------------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.36505	9.85	20.12	12.79	29.97	22.64	58.61	48.61	-28.64	-25.97
2	0.56055	9.82	29.98	22.74	39.80	32.56	56.00	46.00	-16.20	-13.44
3	0.71695	9.81	21.85	15.07	31.66	24.88	56.00	46.00	-24.34	-21.12
4	0.932	9.89	21.64	11.93	31.53	21.82	56.00	46.00	-24.47	-24.18
5	1.5474	9.90	23.92	19.55	33.82	29.45	56.00	46.00	-22.18	-16.55
6	20.22074	10.19	14.94	4.82	25.13	15.01	60.00	50.00	-34.87	-34.99

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.

Test Plot:



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

--- END ---