

FCC ID: 2ALYR-RIDBC001

RF Exposure Evaluation

Limits

KDB447498 D01 General RF Exposure Guidance v06

FCC Part 2.1091

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)				
(A) Limits for Occupational/Controlled Exposures								
0.3–3.0	614	1.63	*(100)	6				
3.0–30	1842/f	4.89/f	*(900/f ²)	6				
30–300	61.4	0.163	1.0	6				
300–1500			f/300	6				
1500–100,000			5	6				
(B) Limits for General Population/Uncontrolled Exposure								
0.3–1.34	614	1.63	*(100)	30				
1.34–30	824/f	2.19/f	*(180/f ²)	30				
30–300	27.5	0.073	0.2	30				
300–1500			f/1500	30				
1500–100,000			1.0	30				

f = frequency in MHz

Friis transmission formula: $Pd = (Pout*G)/(4*pi*r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Test Result of RF Exposure Evaluation

ANT 1 gain: 3.97

Band	Frequency	Max output power (dBm)	Output power (mW)	Antenna gain (dBi)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm²)	Verdict
BLE	2402MHz	7.75	5.96	3.97	0.0030	1.0	PASS
WIFI 2.4G	2462MHz	20.27	106.41	3.97	0.0528	1.0	FASS

ANT 2 gain: 4.01

Band	Frequency	Max output power (dBm)	Output power (mW)	Antenna gain (dBi)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm²)	Verdict
BLE	2402MHz	7.75	5.96	4.01	0.0030	1.0	PASS
WIFI 2.4G	2462MHz	20.27	106.41	4.01	0.0533	1.0	FASS

The max power density is less than MPE exempt limit, so it is compliance.