

FCC RF EXPOSURE REPORT

FCC ID: TE7EAP245V3

Project No. : 1806C097
Equipment : AC1750 Wireless MU-MIMO Gigabit Ceiling Mount Access Point
Test Model : EAP245
Series Model : N/A
Applicant : TP-Link Technologies Co., Ltd.
**Address : Building 24(floors1,3,4,5) and 28(floors1-4)
Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China**

According: : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

1. CERTIFICATION

Equipment : AC1750 Wireless MU-MIMO Gigabit Ceiling Mount Access Point
Brand Name : tp-link
Test Model : EAP245
Series Model : N/A
Applicant : TP-Link Technologies Co., Ltd.
Manufacturer : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Factory : TP-Link Technologies Co., Ltd.
Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China
Date of Test : Jun. 21, 2018 ~ Sep. 29, 2018
Test Sample : Engineering Sample No.: D180605110
Standards : FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-3-1806C097) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of A2LA according to the ISO-17025 quality assessment standard and technical standard(s).

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density




P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:




For 2.4G

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		N/A	PIFA	N/A	3.48
2		N/A	PIFA	N/A	3.49
3		N/A	PIFA	N/A	2.45

Note:

This EUT supports MIMO 3X3, any transmit signals are correlated with each other, so Directional gain = $10\log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N]$ dBi, that is Directional gain = $10\log[(10^{3.48/20} + 10^{3.49/20} + 10^{2.45/20})^2 / 3]$ dBi = 7.92. So, the average out power limit is 30-7.92+6=28.08, the power density limit is 8-7.92+6=6.08.

For 5G

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1		N/A	PIFA	N/A	3.97
2		N/A	PIFA	N/A	3.89
3		N/A	PIFA	N/A	3.92

Note:

(1) This EUT supports MIMO 3X3, any transmit signals are correlated with each other,

so Directional gain = $10\log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N]$ dBi, that is Directional gain

= $10\log[(10^{3.97/20} + 10^{3.89/20} + 10^{3.92/20})^2 / 3]$ dBi = 8.70; So, the UNII-1, UNII-3 output power limit is 30-8.70+6=27.30. The UNII-1 power density limit is 17-8.70+6=14.30, the UNII-3 power density limit is 30-8.70+6=27.30.

(2) Beamforming gain: 4.77dBi, so Directional gain = 4.77+3.97=8.74dBi. Then, the UNII-1, UNII-3 output power limit is 30-8.74+6=27.26. The UNII-1 power density limit is 17-8.74+6=14.26, the UNII-3 power density limit is 30-8.74+6=27.26.

3. TEST RESULTS

2.4G WIFI

Directional Gain (dBi)	Directional Gain (numeric)	AVG Output Power (dBm)	AVG Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
7.92	6.1944	26.18	414.9540	0.51162	1	Complies

5G Band UNII-1

Directional Gain (dBi)	Directional Gain (numeric)	Max Output Power (dBm)	Max Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
8.70	7.4131	25.18	329.6097	0.48635	1	Complies

5G Band UNII-1 with Beamforming

Directional Gain (dBi)	Directional Gain (numeric)	Max Output Power (dBm)	Max Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
8.74	7.4817	25.09	322.8494	0.48078	1	Complies

5G Band UNII-3

Directional Gain (dBi)	Directional Gain (numeric)	Max Output Power (dBm)	Max Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
8.70	7.4131	25.01	316.9567	0.46768	1	Complies

5G Band UNII-3 with Beamforming

Directional Gain (dBi)	Directional Gain (numeric)	Max Output Power (dBm)	Max Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
8.74	7.4817	24.72	296.4831	0.44152	1	Complies

For the max simultaneous transmission MPE:

Power Density (S) (mW/cm ²)	Power Density (S) (mW/cm ²)	Total (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.4G	5G			
0.51162	0.48635	0.99797	1	Complies

Note: the calculated distance is 20 cm.

End of Test Report