



# Maximum Permissible Exposure Evaluation

**FCC ID: 2AF2R-81TX**

## 1. Client Information

<b>Applicant</b>	:	Shenzhen Videotimes Technology Co.,Ltd
<b>Address</b>	:	Room 2106, Building 11, Tianan Yungu Phase II(Plot of Land 02-08) , Gangtou Community, Bantian Street, Longgang District, Shenzhen, Guangdong.China
<b>Manufacturer</b>	:	Shenzhen Videotimes Technology Co.,Ltd
<b>Address</b>	:	Room 2106, Building 11, Tianan Yungu Phase II(Plot of Land 02-08) , Gangtou Community, Bantian Street, Longgang District, Shenzhen, Guangdong.China

## 2. General Description of EUT

<b>EUT Name</b>	:	2.4GHz Digital Wireless Video Baby Camera
<b>Models No.</b>	:	HB6081, BBM818, BBM818-2, BBM818TX, HB6081-2, HB6081TX, VT510, VT510-2, VT510TX, FK8160, FK8160-2, FK8160TX, JA2302, JA2302-2, JA2302TX, BG1055, BG1055-2, BG1055TX, VV6010, VV6010-2, VV6010TX, BL9055, BL9055-2, BL9055TX
<b>Model Different</b>	:	All these models are identical in the same PCB, layout and circuitry, the only difference is the different sales designation
<b>Product Description</b>	Operation Frequency:	802.11b/g: 2412MHz~2462MHz
	Number of Channel:	802.11b/g:11 channels
	Antenna Gain:	3.05dBi Monopole antenna
<b>Power Rating</b>	:	Adapter: K05V050120U Input: 100-240V~50/60Hz, 0.2A Output:5.0V1.2A
<b>Software Version</b>	:	1.0
<b>Hardware Version</b>	:	1.0
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual
<b>Remark</b>	:	the evaluation report used the EUT(202303-0036-11-2#).

## MPE Calculations for WIFI

### 1. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 2. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

**S:** power density

**P:** power input to the antenna

**G:** power gain of the antenna in the direction of interest relative to an isotropic radiator.

**R:** distance to the center of radiation of the antenna

### 3. Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is  $\leq 1.0$ .

This means that:

$\sum$  of MPE ratios  $\leq 1.0$

### 4. Test Result:

Mode	Frequency (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]	Limit of Power Density (mW/ cm <sup>2</sup> ) (S)
802.11b	2412	12.372	12±1	13	3.05	20	0.00801	1
	2437	18.331	18±1	19	3.05	20	0.03190	1
	2462	13.261	13±1	14	3.05	20	0.01009	1
802.11g	2412	13.647	13±1	14	3.05	20	0.01009	1
	2437	15.166	15±1	16	3.05	20	0.01599	1
	2462	13.174	13±1	14	3.05	20	0.01009	1



## 5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

### Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm <sup>2</sup> )
300-1,500	F/1500
1,500-100,000	1.0

For 2.4WIFI:2412~2462

MPE limit S: 1mW/ cm<sup>2</sup>

The MPE is calculated as **0.03190** < **limit 1mW / cm<sup>2</sup>**. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

## Note

For a more detailed features description, please refer to the RF Test Report.

## 6. Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF REPORT-----

