

Report on the FCC and IC Testing of the SEW-EURODRIVE GmbH & Co KG

Model: CAB11A


In accordance with FCC 47 CFR Part 15 C and ISED RSS-210 and ISED RSS-Gen

Prepared for: SEW-EURODRIVE GmbH & Co KG GmbH
Ernst-Blickle-Straße 42
D-76646 Bruchsal
GERMANY

FCC ID: VEB-CAB11A
IC: 7177A-CAB11A

COMMERCIAL-IN-CONFIDENCE

Date: 2024-02-21
Document Number: TR-713308150-05 | Revision 0



RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Project Management	Michael Ingerl	2024-02-21	 SIGN-ID 898092
Authorised Signatory	Matthias Stumpe	2024-02-22	 SIGN-ID 898874

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Product Service document control rules.

Engineering Statement:

This measurement shown in this report were made in accordance with the procedures described on test pages.
All reported testing was carried out on a sample equipment to demonstrate limited compliance with with FCC 47 CFR Part 15 C and ISED RSS-210 and RSS-GEN.
The sample tested was found to comply with the requirements defined in the applied rules.

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Testing	Michael Ingerl	2024-02-21	 SIGN-ID 898092

Laboratory Accreditation DAkKS Reg. No. D-PL-11321-11-02 DAkKS Reg. No. D-PL-11321-11-03	Laboratory recognition Registration No. BNetzA-CAB-16/21-15	Industry Canada test site registration 3050A-2
--	--	---

Executive Statement:

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 15 C:2021 and ISED RSS210:2019 and ISED RSSGen:2019

DISCLAIMER AND COPYRIGHT This non-binding report has been prepared by TÜV SÜD Product Service with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD Product Service. No part of this document may be reproduced without the prior written approval of TÜV SÜD Product Service. © 2024 TÜV SÜD Product Service.

TÜV SÜD Product Service



Trade Register Munich HRB 85742 VAT ID No. DE129484267 Information pursuant to Section 2(1) DL-InfoV (Germany) at www.tuvsud.com/imprint	Managing Directors: Walter Reithmaier (Sprecher / CEO) Patrick van Welij	Phone: +49 (0) 9421 56 82-0 Fax: +49 (0) 9421 56 82-199 www.tuvsud.com	TÜV SÜD Product Service GmbH Äußere Frühlingsstraße 45 94315 Straubing Germany
---	--	--	---



Content

1	Report Summary.....	2
1.1	Modification Report.....	2
1.2	Introduction	2
1.3	Brief Summary of Results.....	3
1.4	Product Information	4
1.5	Test Configuration	4
1.6	Modes of Operation	4
1.7	EUT Modifications Record	4
1.8	Test Location	4
2	Test Details.....	6
2.1	Antenna requirement	6
2.2	Bandwidth of Signal	7
2.3	Radiated Emissions	10
2.4	Conducted Emissions on Mains Terminals	18
2.5	Temperature Stability	22
3	Measurement Uncertainty	25
Annex A: Photographs of Test Setup		
Annex B: Photos of EUT		
Annex C: Internal Photos		



1 Report Summary

1.1 Modification Report

Alternations and additions of this report will be issued to the holders of each copy in the form of a complete document.

Revision	Description of changes	Date of Issue
0	First Issue	2024-02-21

Table 1: Report of Modifications

1.2 Introduction

Applicant	SEW-EURODRIVE GmbH & Co KG GmbH
Model Number(s)	CAB11A
Serial Number(s)	#5
Hardware Version(s)	A-Sample
Software Version(s)	18299652v0030r2023103101_CAB11A.hex
Number of Samples Tested	1
Test Specification(s) / Issue / Date	FCC 47 CFR Part 15 C : 2019 and ISED RSS-210, Issue 10, Amd. 1 : 2019 ISED RSS-Gen, Issue 5, Amd. 1 : 2019
Test Plan/Issue/Date	N/A
Order Number	713308150
Date	
Date of Receipt of EUT	2023-11-13
Start of Test	2023-11-13
Finish of Test	2023-11-23
Name of Engineer(s)	Michael Ingerl
Related Document(s)	ANSI C63.10:2013



1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 15 C and ISED RSS-210 and RSS-Gen is shown below.

<i>Section</i>	<i>Specification Clause</i>	<i>Test Description</i>	<i>Result</i>
2.1	15.203	Antenna requirement	Pass
2.2	15.215(c)	Bandwidth of Signal	Pass
2.3	15.207	Conducted Disturbance at Mains Terminal	Pass
2.4	15.209, 15.225	Radiated Disturbance	Pass
2.5	15.225(e)	Frequency Tolerance	Pass

Table 2: Results according to FCC 47 CFR Part 15 C

<i>Section</i>	<i>Specification Clause</i>	<i>Test Description</i>	<i>Result</i>
2.3	7.3	Radiated Emissions	Pass
2.4	7.3	AC Power Line Conducted Emissions	Pass
2.5	B.6 b.	Frequency Tolerance	Pass

Table 3: Results according to ISED RSS-210

<i>Section</i>	<i>Specification Clause</i>	<i>Test Description</i>	<i>Result</i>
2.2	6.7	Bandwidth of Signal	Pass
2.4	8.8	AC Power Line Conducted Emissions	Pass
2.3	8.9, 8.10	Radiated Emissions	Pass
2.5	6.11	Frequency Tolerance	Pass

Table 4: Results according to ISED RSS-Gen



1.4 Product Information

1.4.1 Technical Description

Equipment characteristics	
Type designation:	CAB11A
Type of equipment:	Bluetooth Low Energy to CAN gateway with NFC tag
Manufacturer:	SEW-EURODRIVE GmbH & Co KG
Frequency Band:	2400 – 2483.5 MHz (Bluetooth Low Energy) and 13.56 MHz (NFC)
Kind of equipment:	Transceiver
Power supply:	DC Nominal: 24 V Minimum: 18 V Maximum: 30 V Nominal frequency: DC

1.5 Test Configuration

The EUT was 24V DC power supplied

1.6 Modes of Operation

Transmitting continuously (NFC)

1.7 EUT Modifications Record

The table below details modifications made to the EUT during the test programme.
The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
0	As supplied by the customer	Not Applicable	Not Applicable

Table 5

1.8 Test Location

TÜV SÜD Product Service conducted the following tests at our Straubing test laboratory:



Product Service

Test Name	Name of Engineer(s)
Antenna requirement	Michael Ingerl
Bandwidth of Signal	Michael Ingerl
Radiated Emission	Michael Ingerl
Conducted Emission at Mains Terminal	Michael Ingerl
Frequency Tolerance	Michael Ingerl

Office Address:

Äußere Frühlingstraße 45
94315 Straubing
Germany



2 Test Details

2.1 Antenna requirement

2.1.1 Specification Reference

FCC 47 CFR Part 15 C, Clauses 15.203

2.1.2 Equipment under Test and Modification State

CAB11A; S/N #5; Modification State 0

2.1.3 Date of Test

2023-11-23

2.1.4 Specification Limits

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some fields disturbance sensors, or to other intentional radiators which must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits are not exceeded.

2.1.5 Test Results

<i>Antenna connector type:</i>	Integrated antenna
<i>Antenna connector impedance:</i>	N/A



2.2 Bandwidth of Signal

2.2.1 Specification Reference

FCC 47 CFR Part 15 C, Clause 15.215(c)
ISED RSS-Gen, Clause 6.7

2.2.2 Equipment under Test and Modification State

CAB11A; S/N #5; Modification State 0

2.2.3 Date of Test

2023-11-23

2.2.4 Environmental Conditions

Ambient Temperature	24 °C
Relative Humidity	34 %


2.2.5 Specification Limits

No limitation – Bandwidth noted

2.2.6 Test Method

The test was performed according to ANSI C63.10, clauses 6.9
See section 2.3 of this test report for details.


2.2.7 Test Results



Date: 23.NOV.2023 10:31:11

Center frequency	20 dB Bandwidth
13.56 MHz	26.124 kHz

Table 6: 20 dB bandwidth



Date: 23.NOV.2023 10:33:52

Centre Frequency	99% Bandwidth
13.56 MHz	30.499 kHz

Table 7: 99% bandwidth

2.2.8 Test Location and Test Equipment

The test was carried out in radio test laboratory.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
Radio and Spectrum Analysator	Rohde & Schwarz	FSV40	20219	24	2024-02-29
Temperature test chamber	Feutron	KPK200-2	19868	36	2024-08-31

Table 8



Product Service

2.3 Radiated Emissions

2.3.1 Specification Reference

FCC 47 CFR Part 15 C, Clauses 15.205, 15.209 and 15.225
ISED RSS-210, Clause 7.7 and B.6
ISED RSS-Gen, Clauses 8.9 and 8.10

2.3.2 Equipment under Test and Modification State

CAB11A; S/N #5; Modification State 0

2.3.3 Date of Test

2023-11-13

2.3.4 Environmental Conditions

Ambient Temperature	21 °C
Relative Humidity	35 %



2.3.5 Specification Limits

Radiated emission limits:					
Frequency Range (MHz)	Test distance (m)	Field strength		Field strength	
		($\mu\text{A/m}$)	($\text{dB}\mu\text{A/m}$)	($\mu\text{V/m}$)	($\text{dB}\mu\text{V/m}$)
0.009 – 0.49	300	$6.37 / f$	$20*\lg(6.37 / f)$	$2400 / f$	$20*\lg(2400 / f)$
0.49 – 1.705	30	$63.7 / f$	$20*\lg(63.7 / f)$	$24000 / f$	$20*\lg(24000 / f)$
1.705 – 13.110	30	0.08	-21.94	30	29.54
13.110 – 13.410	30	0.283	-11.0	106	40.5
13.410 – 13.553	30	0.891	-1.0	334	50.5
13.553 – 13.567	30	42.26	32.5	15848	84
13.567 – 13.710	30	0.891	-1.0	334	50.5
13.710 – 14.010	30	0.283	-11.0	106	40.5
14.010 - 30	30	0.08	-21.94	30	29.54
30 – 88	3	---	---	100	40
88 – 216	3	--	---	150	43.5
126 – 960	3	--	---	200	46
above 960	3	--	---	500	54

Note 1: f in kHz

Table 9 Radiated emission limits

At frequencies at or above 30 MHz, measurements may be performed at distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 m, unless it can be further demonstrated that measurements at a distance of 30 m or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempts should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

2.3.6 Test Method

The test was performed according to ANSI C63.10, sections 11.11 and 11.12


Prescans are performed in six positions of the EUT to get the full spectrum of emission caused by the EUT with the measuring antenna raised and lowered from 1 m to 4 m with vertical and horizontal polarisation to find the combination of table position, antenna height and antenna polarisation for the maximum emission levels.

Data reduction is applied to these results to select those levels having less margin than 10 dB or exceeding the limit using subranges and limited number of maximums.

Further maximisation for adjusting the maximum position is following.

Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

2.3.6.1 Frequency range 9 kHz – 30 MHz




The EUT was placed on a non-conductive table, 0.8 m above the ground.

Radiated emissions in the frequency 9 kHz – 30 MHz is measured within a semi-anechoic room with an active loop antenna with the measurement detector set to peak. In addition in the frequency range 9 kHz to 490 kHz also an average detector was used. The measurement bandwidth of the receiver was set to 300 Hz in the frequency range 9 kHz to 150 kHz and 10 kHz in the frequency range 150 kHz to 30 MHz. Prescans were performed in six positions of the EUT.

For final measurements the detector was set to CISPR quasi-peak and in addition to CISPR average in the frequency range 9 kHz to 490 kHz with a resolution bandwidth 200 Hz in the frequency range 9 kHz to 150 kHz and 9 kHz in the frequency range 150 kHz to 30 MHz. Final tests were performed immediately after a final frequency and zoom (for drifting disturbances) and maximum adjustment.

2.3.6.2 Frequency range 30 MHz – 1 GHz



Alternate test site (semi anechoic room)

The EUT was placed on a non-conductive table, 0.8 m above the ground plane. Radiated emissions in the frequency range 30 MHz – 1 GHz is measured within a semi-anechoic room with groundplane complying with the NSA requirements of ANSI C63.4. for alternative test sites. A linear polarised logarithmic periodic antenna combined with a 4:1 broadband dipole (“Trilog broadband antenna”) is used.

For prescan tests the test receiver is set to peak-detector with a bandwidth of 120 kHz.

With the measurement bandwidth of the test receiver set to 120 kHz CISPR quasi-peak detector is selected for final measurements following immediately after a final frequency zoom (for drifting disturbances) and maximum adjustment.

2.3.7 Test Results

Frequency range	Limit applied	Test distance
9 kHz – 1 GHz	§ 15.209, § 15.225	3 m

Table 10

Sample calculation:

Final Value (dB μ V/m) = Reading Value (dB μ V) + (Cable attenuation (dB) + Antenna Transducer (dB(1/m)))


Additional correction of limit in the frequency range 9 – 490 kHz (300 m to 3 m): +80.0 dB

Additional correction of limit in the frequency range 490 kHz – 30 MHz (30 m to 3 m): +40.0 dB

Additional correction of limit in the frequency ranges above 1 GHz (3 m to 1 m): +9.54 dB



Frequency range 9 kHz – 30 MHz:




Final Results 1:

Frequency	QuasiPeak	Limit	Margin	Meas. Time	Bandwidth	Height	Pol	Azimuth	Corr.
MHz	dBµV/m	dBµV/m	dB	ms	kHz	cm		deg	dB
13.560375	78.33	124.00	45.67	1000.0	9.000	100.0	H	-115.0	19.2




Frequency range 13.01 MHz – 14.11 MHz (Spectrum Mask acc. 15.225(a)-(c)):





Frequency range 30 MHz – 1 GHz:



Final Results 1:

Frequency MHz	QuasiPeak dBµV/m	Limit dBµV/m	Margin dB	Meas. Time ms	Bandwidth kHz	Height cm	Pol	Azimuth deg	Corr. dB
50.010000	36.59	40.00	3.41	1000.0	120.000	100.0	V	47.0	12.9
279.990000	45.40	46.02	0.62	1000.0	120.000	115.0	H	-86.0	18.5
560.010000	42.44	46.02	3.58	1000.0	120.000	185.0	H	88.0	25.6
600.000000	43.44	46.02	2.58	1000.0	120.000	100.0	V	124.0	26.3
639.990000	45.44	46.02	0.58	1000.0	120.000	100.0	V	29.0	26.9
720.000000	42.15	46.02	3.87	1000.0	120.000	105.0	H	98.0	28.1
859.980000	37.88	46.02	8.14	1000.0	120.000	100.0	H	-72.0	29.8
900.000000	36.81	46.02	9.21	1000.0	120.000	100.0	H	94.0	30.4
926.940000	34.53	46.02	11.49	1000.0	120.000	115.0	V	72.0	30.5



2.3.8 Test Location and Test Equipment

The test was carried out in semi anechoic room, cabin No. 11

Instrument	Manufacturer	Type No	TE No	Calibra- tion Peri- od (months)	Calibration Due
EMI test receiver	Rohde & Schwarz	ESW44	39897	12	2024-04-30
Loop antenna	Schwarzbeck	FMZB 1519B	44334	36	2026-06-30
ULTRALOG antenna	Rohde & Schwarz	HL562E	39969	36	2025-03-31
Fixed attenuator	Aeroflex	Model 6 dB	39632	36	2026-01-31
Semi anechoic room	Frankonia	Cabin No. 11	42961	36	2024-09-30
EMC measurement software	Rohde & Schwarz	EMC32 Emission - V10.60.20	42986	---	---

Table 11



2.4 Conducted Emissions on Mains Terminals

2.4.1 Specification Reference

FCC 47 CFR Part 15 C, Clause 15.207
ISED RSS-Gen, Clause 8.8

2.4.2 Equipment under Test and Modification State

CAB11A; S/N #5; Modification State 0

2.4.3 Date of Test

2023-11-21

2.4.4 Environmental Conditions

Ambient Temperature 22 °C
Relative Humidity 38 %


2.4.5 Specification Limits

Required Specification Limits			
Line Under Test	Frequency Range (MHz)	Quasi-peak (dBμV)	Average (dBμV)
AC Power Port	0.15 to 0.5	66 to 56*	56 to 46*
	0.5 to 5	56	46
	5 to 30	60	50
Supplementary information: *Decreases with the logarithm of the frequency.			

Table 12 Emission limits

2.4.6 Test Method

The test was performed according to ANSI C63.10, section 6.2.



The EUT was placed on a non-conductive table 0.8 m above a reference ground plane and 0.4 m away from a vertical coupling plane

All power was connected to the EUT through an Line Impedance Stabilization Network (LISN). Conducted disturbance voltage measurements on mains lines were made at the output of the LISN. The LISN was placed 0.8 m from the boundary of the EUT and bounded to the reference ground plane. To simplify testing with quasi-peak and linear average (cisp-r-average) detector the following procedure is used:

First the whole spectrum of emission caused by the equipment under test (EUT) is recorded with the detectors set to peak and average using CISPR bandwidth of 10 kHz. After that all emission levels having less margin than 10 dB to or exceeding the average limit are retested with the detectors set to quasi-peak and average. If the average limit is kept with quasi-peak levels measurement with average detector is optional. In cases of emission levels between quasi-peak and average limit an additional measurement with average detector has to be performed.

The test was performed with the internal antenna attached and disconnected.




2.4.7 Test Results

Sample calculation:

Final Value (dBμV) = Reading Value (dBμV) + (Cable attenuation (dB) + LISN Transducer (dB))

Plus and Minus



Final Results 1:

Frequency MHz	QuasiPeak dBμV	CAverage dBμV	Limit dBμV	Margin dB	Meas. Time ms	Bandwidth kHz	Line	Filter	Corr. dB
0.996000	---	37.83	46.00	8.17	1000.0	9.000	Plus	ON	10.1
1.493250	---	35.89	46.00	10.11	1000.0	9.000	Plus	ON	10.1
2.987250	---	37.86	46.00	8.14	1000.0	9.000	Plus	ON	10.1
3.484500	---	37.10	46.00	8.90	1000.0	9.000	Plus	ON	10.1
13.940250	---	43.37	50.00	6.63	1000.0	9.000	Minus	ON	10.3
15.931500	---	43.84	50.00	6.16	1000.0	9.000	Plus	ON	10.3
18.420000	---	44.34	50.00	5.66	1000.0	9.000	Plus	ON	10.3
22.400250	40.08	---	60.00	19.92	1000.0	9.000	Minus	ON	10.3
24.085500	---	43.26	50.00	6.74	1000.0	9.000	Plus	ON	10.3
24.396000	---	42.44	50.00	7.56	1000.0	9.000	Minus	ON	10.3
24.893250	---	45.64	50.00	4.36	1000.0	9.000	Plus	ON	10.3
25.388250	40.24	---	60.00	19.76	1000.0	9.000	Plus	ON	10.3



2.4.8 Test Location and Test Equipment

The test was carried out in shielded room, cabin No. 9

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
EMI test receiver	Rohde & Schwarz	ESU8	19904	12	2024-02-29
V-Network	Rohde & Schwarz	ENV216	39908	12	2024-05-31
EMC measurement software	Rohde & Schwarz	EMC32 V10.60.20	20090	---	---
Shielded room	Albatross Projects	Cabin No. 9	21083	---	---

Table 13



2.5 Temperature Stability

2.5.1 Specification Reference

FCC 47 CFR Part 15 E, Clause 15.225(e)
ISSED RSS-210, Clause B.6 b.
ISED RSS-Gen, Clause 6.11

2.5.2 Equipment under Test and Modification State

CAB11A; S/N #5; Modification State 0

2.5.3 Date of Test

2023-11-23

2.5.4 Environmental Conditions

Ambient Temperature	24 °C
Relative Humidity	34 %


2.5.5 Specification Limits

The frequency tolerance of the carrier signal shall be maintained within ± 0.01 % of the operating frequency over a temperature variation of -20 °C to +50 °C at normal supply voltage, and for a variation in the primary supply voltage from 85 % to 115 % of the rated supply voltage at a temperature of 20 °C. For battery operated equipment, the equipment tests shall be performed using a new battery.



2.5.6 Test Method

The test was performed according to ANSI C63.10, section 6.8.



The frequency tolerance of the carrier signal is measured over a temperature variation of -20°C to $+50^{\circ}\text{C}$ at normal supply voltage, and for a variation in the primary supply voltage from 85 % to 115 % of the rated supply voltage at a temperature of 20°C . Temperature and voltage range may vary if the manufacturer states another temperature or voltage range.

If the EUT provides an antenna connector the spectrum analyzer is connected to this port. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as a DC block and appropriate (50 Ω) attenuators. In case where the EUT does not provide an antenna connector or a test fixture is used.

For battery operated equipment, the test is performed using a new battery. Alternatively, an external supply voltage can be used and is at least set to:

- The maximum battery voltage as delivered by a new battery or 115 % of the battery nominal voltage;
- The battery nominal voltage
- 85 % of the battery nominal voltage
- The battery operating end point voltage which shall be specified by the equipment manufacturer.

The EUT is operating providing an unmodulated carrier for frequency error tests. The peak detector of the spectrum analyzer is selected and resolution as well as video bandwidth are set to values appropriate to shape of the spectrum of the EUT. The frequency counter mode of the spectrum analyzer is used to maximize the accuracy of the measured frequency tolerance.

If an unmodulated carrier is not available a significant and stable point of the spectrum is selected and the span is reduced to a value that delivers an accuracy which shall be better than 1 % of the maximum frequency tolerance allowed for the carrier signal. This method may be performed as long as the margin to the frequency tolerance is larger than the uncertainty of the measured frequency tolerance.



2.5.7 Test Results

<i>Temperature (°C)</i>	<i>Supply Voltage (V)</i>	<i>Frequency (MHz)</i>	<i>Frequency drift (ppm)</i>	<i>Frequency drift (%)</i>
-20	24.0	13.5600910	-0.221	-0.000022
-10	24.0	13.5600920	-0.147	-0.000015
0	24.0	13.5600920	-0.147	-0.000015
10	24.0	13.5600930	-0.074	-0.000007
20	18.0	13.5600930	-0.074	-0.000007
20	24.0	13.5600940	0.000	0.000000
20	30.0	13.5600970	0.221	0.000022
30	24.0	13.5600970	0.221	0.000022
40	24.0	13.5600980	0.295	0.000029
50	24.0	13.5600980	0.295	0.000029

Table 14

2.5.8 Test Location and Test Equipment

The test was carried out in radio test laboratory.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
Radio and Spectrum Analysator	Rohde & Schwarz	FSV40	20219	24	2024-02-29
Temperature test chamber	Feutron	KPK200-2	19868	36	2024-08-31

Table 15



3 Measurement Uncertainty

For a 95% confidence level, the measurement uncertainties for defined systems are:

<i>Radio Interference Emission Testing</i>		
<i>Test Name</i>	<i>kp</i>	<i>Expanded Uncertainty</i>
Conducted Voltage Emission		
9 kHz to 150 kHz (50Ω/50μH AMN)	2	± 3.8 dB
150 kHz to 30 MHz (50Ω/50μH AMN)	2	± 3.4 dB
100 kHz to 200 MHz (50Ω/5μH AMN)	2	± 3.6 dB
Discontinuous Conducted Emission		
9 kHz to 150 kHz (50Ω/50μH AMN)	2	± 3.8 dB
150 kHz to 30 MHz (50Ω/50μH AMN)	2	± 3.4 dB
Conducted Current Emission		
9 kHz to 200 MHz	2	± 3.5 dB
Magnetic Fieldstrength		
9 kHz to 30 MHz (with loop antenna)	2	± 3.9 dB
9 kHz to 30 MHz (large-loop antenna 2 m)	2	± 3.5 dB
Radiated Emission		
30 MHz to 300 MHz	2	± 4.9 dB
300 MHz to 1 GHz	2	± 5.0 dB
1 GHz to 6 GHz	2	± 4.6 dB
Test distance 10 m		
30 MHz to 300 MHz	2	± 4.9 dB
300 MHz to 1 GHz	2	± 4.9 dB
The expanded uncertainty reported according to CISPR16-4-2: 2011 + A1 + A2 + Cor1 is based on a standard uncertainty multiplied by a coverage factor of $k_p = 2$, providing a level of confidence of $p = 95.45\%$		

Table 16 Measurement uncertainty based on CISPR 16-4-2



<i>Radio Interference Emission Testing</i>		
<i>Test Name</i>	<i>kp</i>	<i>Expanded Uncertainty</i>
Occupied Bandwidth	2	± 5 %
Conducted Power		
9 kHz ≤ f < 30 MHz	2	± 1.0 dB
30 MHz ≤ f < 1 GHz	2	± 1.5 dB
1 GHz ≤ f ≤ 40 GHz	2	± 2.5 dB
1 MS/s power sensor (TS8997)	2	± 1.5 dB
Occupied Bandwidth	2	± 5 %
Power Spectral Density	2	± 3.0 dB
Radiated Power		
25 MHz – 6 GHz	1.96	±4.4 dB
1 GHz – 18 GHz	1.96	±4.7 dB
18 GHz – 40 GHz	1.96	±4.9 dB
40 GHz – 325 GHz	1.96	±6.1 dB
Conducted Spurious Emissions	2	± 3.0 dB
Radiated Spurious Emissions	2	± 6.0 dB
Voltage		
DC	2	± 1.0 %
AC	2	± 2.0 %
Time (automatic)	2	± 5 %
Frequency	2	± 10 ⁻⁷
The expanded uncertainty reported according to to ETSI TR 100 028:2001 is based on a standard uncertainty multiplied by a coverage factor of kp = 2, providing a level of confidence of p = 95.45%		

Table 17 Measurement uncertainty based on ETSI TR 100 028

The measurement uncertainty in the laboratory is less than or equal to the maximum measurement uncertainty according to CISPR16-4-2: 2011 + A1 + A2 + Cor1 (U_{CISPR}) and as specified in the test report below. This normative regulation means that the measured value is also the value to be assessed in relation to the limit value.



Test Name	Expanded Uncertainty
Occupied Bandwidth	±5 %
Conducted Power	
9 kHz ≤ f < 30 MHz	±1.0 dB
30 MHz ≤ f < 1 GHz	±1.5 dB
1 GHz ≤ f ≤ 40 GHz	±2.5 dB
1 MS/s power sensor (2.4 / 5 GHz band)	±1.5 dB
Power Spectral Density	±3.0 dB
Radiated Power	
25 MHz – 26.5 GHz	±6.0 dB
26.5 GHz – 66 GHz	±8.0 dB
40 GHz – 325 GHz	±10.0 dB
Conducted Spurious Emissions	±3.0 dB
Radiated Field Strength 9 kHz – 40 GHz	±6.0 dB
Voltage	
DC	± 1.0 %
AC	± 2.0 %
Time (automatic)	± 5 %
Frequency	± 10 ⁻⁷

Table 18 Decision Rule: Maximum allowed measurement uncertainty