

8.3 MAXIMUM POWER SPECTRAL DENSITY

8.3.1 Applicable Standard

According to FCC Part15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02

8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to:10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

Note: If antenna Gain exceeds 6 dBi, then PSD Limit=8-(Gain- 6)

8.3.5 Test Results

Temperature:	24 °C
Relative Humidity:	70 %
ATM Pressure:	1011 mbar

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11b	1	2412	-8.01	8	PASS
	6	2437	-8.30	8	PASS
	11	2462	-7.45	8	PASS
802.11g	1	2412	-11.55	8	PASS
	6	2437	-11.72	8	PASS
	11	2462	-11.50	8	PASS
802.11n (HT20)	1	2412	-12.24	8	PASS
	6	2437	-12.30	8	PASS
	11	2462	-12.19	8	PASS
802.11n (HT40)	3	2422	-15.95	8	PASS
	6	2437	-16.46	8	PASS
	9	2452	-16.44	8	PASS

Test Model	Power Spectral Density
	802.11b
	Channel 1: 2412MHz




Test Model	Power Spectral Density
	802.11b
	Channel 6: 2437MHz



Test Model	Power Spectral Density 802.11b Channel 11: 2462MHz
------------	--




Test Model	Power Spectral Density 802.11g Channel 1: 2412MHz
------------	---




Test Model

Power Spectral Density
802.11g
Channel 6: 2437MHz



Test Model


Power Spectral Density
802.11g
Channel 11: 2462MHz




Test Model	Power Spectral Density 802.11n (HT20) Channel 1: 2412MHz
------------	--




Test Model	Power Spectral Density 802.11n (HT20) Channel 6: 2437MHz
------------	--





Test Model	Power Spectral Density 802.11n (HT20) Channel 11: 2462MHz
------------	---



Test Model	Power Spectral Density 802.11n (HT40) Channel 3: 2422MHz
------------	--





8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02

8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.



Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.


8.4.5 Test Results

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:



Test Model

Band edge
802.11b
Channel 1: 2412MH




Test Model

PSD(Power Spectral Density)
802.11b
Channel 6: 2437MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands
802.11b
Channel 6: 2437MH




Test Model

PSD(Power Spectral Density)
802.11b
Channel 11: 2462MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands
802.11b
Channel 1: 2462MH



Test Model

Band edge
802.11b
Channel 1: 2462MH



8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz (1GHz to 25GHz), 100 kHz for $f < 1$ GHz (30MHz to 1GHz), 200Hz for $f < 150$ KHz (9KHz to 150KHz), 9KHz for $f < 30$ MHz (150KHz to 30KHz)

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results

Temperature:	25 °C
Relative Humidity:	70 %
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

- Spurious Emission Above 1GHz(1GHz to 25GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:

Test mode: 802.11 b

Frequency:

Channel 1: 2412 MHz

Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
4824.000	60.42	-8.65	51.77	74.00	22.23	PK+	V	PASS
4824.000	45.10	-8.65	36.45	54.00	17.55	AVG	V	PASS
14217.000	43.11	9.05	52.16	74.00	21.84	PK+	V	PASS
14217.000	28.54	9.05	37.59	54.00	16.41	AVG	V	PASS
17944.500	41.66	12.99	54.65	74.00	19.35	PK+	V	PASS
17944.500	26.39	12.99	39.38	54.00	14.62	AVG	V	PASS
Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
4824.000	61.50	-8.65	52.85	74.00	21.15	PK+	H	PASS
4824.000	46.61	-8.65	37.96	54.00	16.04	AVG	H	PASS
14149.500	43.29	9.08	52.37	74.00	21.63	PK+	H	PASS
14149.500	27.20	9.08	36.28	54.00	17.72	AVG	H	PASS
17905.000	41.18	12.5	53.68	74.00	20.32	PK+	H	PASS
17905.000	25.91	12.5	38.41	54.00	15.59	AVG	H	PASS

Test mode: 802.11 b

Frequency:

Channel 6:2437 MHz

Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
4874.000	64.04	-8.27	55.77	74.00	18.23	PK+	V	PASS
4874.000	46.46	-8.27	38.19	54.00	15.81	AVG	V	PASS
14260.500	43.94	8.96	52.90	74.00	21.10	PK+	V	PASS
14260.500	29.50	8.96	38.46	54.00	15.54	AVG	V	PASS
17986.500	40.72	13.5	54.22	74.00	19.78	PK+	V	PASS
17986.500	25.72	13.5	39.22	54.00	14.78	AVG	V	PASS
Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
4874.500	61.82	-8.26	53.56	74.00	20.44	PK+	H	PASS
4874.500	45.62	-8.26	37.36	54.00	16.64	AVG	H	PASS
14252.000	43.76	8.98	52.74	74.00	21.26	PK+	H	PASS
14252.000	29.44	8.98	38.42	54.00	15.58	AVG	H	PASS
17783.000	41.17	11.64	52.81	74.00	21.19	PK+	H	PASS
17783.000	25.93	11.64	37.57	54.00	16.43	AVG	H	PASS

Test mode: 802.11 b

Frequency:

Channel 11:2462 MHz

Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
4924.000	65.31	-7.81	57.50	74.00	16.50	PK+	V	PASS
4924.000	46.07	-7.81	38.26	54.00	15.74	AVG	V	PASS
14251.000	43.11	8.98	52.09	74.00	21.91	PK+	V	PASS
14251.000	28.65	8.98	37.63	54.00	16.37	AVG	V	PASS
17929.000	40.88	12.8	53.68	74.00	20.32	PK+	V	PASS
17929.000	25.47	12.8	38.27	54.00	15.73	AVG	V	PASS
Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
4924.000	62.53	-7.81	54.72	74.00	19.28	PK+	H	PASS
4924.000	46.46	-7.81	38.65	54.00	15.35	AVG	H	PASS
13950.500	42.56	9.24	51.80	74.00	22.20	PK+	H	PASS
13950.500	25.02	9.24	34.26	54.00	19.74	AVG	H	PASS
17968.500	40.31	13.28	53.59	74.00	20.41	PK+	H	PASS
17968.500	24.26	13.28	37.54	54.00	16.46	AVG	H	PASS

- Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Correct Factor.
 (3) Correct Factor= Ant_F + Cab_L - Preamp
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11g recorded was report as below:

Test mode: 802.11 b Frequency: Channel 1: 2412MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2361.280	H	58.81	74.00	44.78	54.00
2329.000	V	57.94	74.00	45.79	54.00

Test mode: 802.11 b Frequency: Channel 11: 2462MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2493.705	H	59.67	74.00	44.12	54.00
2499.126	V	57.91	74.00	45.23	54.00

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Test Model	Spurious Emission in Restricted Band 2310-2390MHz	
	802.11b	
	Channel 1: 2412MHz	Polarity: H




Test Model	Spurious Emission in Restricted Band 2310-2390MHz	
	802.11b	
	Channel 1: 2412MHz	Polarity: V



Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	802.11b		
	Channel 11: 2462MHz	Polarity: H	




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	802.11b		
	Channel 11: 2462MHz	Polarity: V	




- Spurious Emission below 1GHz (30MHz to 1GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11g recorded was report as below:

Project Information			
Mode:	TX2412 MHz	Voltage:	DC 5V for USB
Environment:	Temp: 22 °C; Humi:65 %	Engineer:	matteus zhang




Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
31.649	48.53	-25.16	23.37	40.00	16.63	QPK	100	V	279.0	PASS
77.045	47.63	-26.56	21.07	40.00	18.93	QPK	100	V	296.9	PASS
117.591	53.29	-26.36	26.93	43.50	16.57	QPK	200	V	178.4	PASS
124.672	52.23	-26.97	25.26	43.50	18.24	QPK	100	V	4.6	PASS
133.693	55.58	-27.34	28.24	43.50	15.26	QPK	100	V	46.9	PASS
139.998	52.28	-27.44	24.84	43.50	18.66	QPK	100	V	17.1	PASS

Project Information			
Mode:	TX2412 MHz	Voltage:	DC 5V for USB
Environment:	Temp: 22 °C; Humi:65 %	Engineer:	matteus zhang




Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
133.596	54.39	-27.34	27.05	43.50	16.45	QPK	200	H	113.5	PASS
200.041	50.35	-24.19	26.16	43.50	17.34	QPK	100	H	276.9	PASS
249.996	53.21	-22.29	30.92	46.00	15.08	QPK	100	H	31.7	PASS
375.029	54.61	-20.07	34.54	46.00	11.46	QPK	100	H	262.0	PASS
625.095	53.50	-14.52	38.98	46.00	7.02	QPK	100	H	219.2	PASS
750.128	53.79	-13.68	40.11	46.00	5.89	QPK	100	H	274.5	PASS

Project Information			
Mode:	TX2437 MHz	Voltage:	DC 5V for USB
Environment:	Temp: 22 °C; Humi:65 %	Engineer:	matteus zhang




Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
31.843	49.03	-25.11	23.92	40.00	16.08	QPK	100	V	153.2	PASS
77.918	47.20	-26.59	20.61	40.00	19.39	QPK	100	V	290.1	PASS
118.561	51.98	-26.49	25.49	43.50	18.01	QPK	200	V	205.0	PASS
134.566	54.07	-27.36	26.71	43.50	16.79	QPK	100	V	85.9	PASS
425.081	50.04	-18.45	31.59	46.00	14.41	QPK	100	V	168.0	PASS
625.095	53.43	-14.52	38.91	46.00	7.09	QPK	100	V	294.8	PASS

Project Information			
Mode:	TX2437 MHz	Voltage:	DC 5V for USB
Environment:	Temp: 22 °C; Humi:65 %	Engineer:	matteus zhang




Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
132.723	53.38	-27.33	26.05	43.50	17.45	QPK	200	H	109.8	PASS
175.015	49.40	-26.05	23.35	43.50	20.15	QPK	200	H	290.8	PASS
200.041	49.83	-24.19	25.64	43.50	17.86	QPK	100	H	256.8	PASS
250.093	51.83	-22.29	29.54	46.00	16.46	QPK	100	H	69.9	PASS
375.029	54.58	-20.07	34.51	46.00	11.49	QPK	100	H	266.3	PASS
750.128	53.73	-13.68	40.05	46.00	5.95	QPK	100	H	271.1	PASS

Project Information			
Mode:	TX2462 MHz	Voltage:	DC 5V for USB
Environment:	Temp: 22 °C; Humi:65 %	Engineer:	matteus zhang



Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
30.485	52.45	-25.46	26.99	40.00	13.01	QPK	100	V	162.0	PASS
77.918	48.59	-26.59	22.00	40.00	18.00	QPK	100	V	323.9	PASS
105.272	48.49	-24.82	23.67	43.50	19.83	QPK	100	V	0.0	PASS
118.076	50.74	-26.43	24.31	43.50	19.19	QPK	100	V	220.9	PASS
132.917	52.80	-27.33	25.47	43.50	18.03	QPK	100	V	82.2	PASS
625.095	53.48	-14.52	38.96	46.00	7.04	QPK	200	V	292.9	PASS

Project Information			
Mode:	TX2462 MHz	Voltage:	DC 5V for USB
Environment:	Temp: 22 °C; Humi:65 %	Engineer:	matteus zhang



Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Height (cm)	Pol.	Azimuth (deg)	Verdict
132.723	50.62	-27.33	23.29	43.50	20.21	QPK	200	H	122.6	PASS
249.996	52.90	-22.29	30.61	46.00	15.39	QPK	100	H	31.4	PASS
375.029	54.43	-20.07	34.36	46.00	11.64	QPK	100	H	273.1	PASS
425.081	50.15	-18.45	31.70	46.00	14.30	QPK	200	H	245.9	PASS
625.095	53.14	-14.52	38.62	46.00	7.38	QPK	100	H	221.3	PASS
750.128	53.63	-13.68	39.95	46.00	6.05	QPK	100	H	274.3	PASS

8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration

Test according to clause 7.3conducted emission test setup

8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results

N/A.

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

PASS.

- The EUT has 1 antenna: one an IPEX antenna for WIFI 2.4G, the gain is 0.86 dBi,
Note: ☒ Antenna uses a permanently attached antenna which is not replaceable.
☐ Not using a standard antenna jack or electrical connector for antenna replacement
☐ The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.

*** End of Report ***

声 明 Statement

1. 本报告无授权批准人签字及“检验检测专用章”无效;
This report will be void without authorized signature or special seal for testing report.
2. 未经许可本报告不得部分复制;
This report shall not be copied partly without authorization.
3. 本报告的检测结果仅对送测样品有效, 委托方对样品的代表性和资料的真实性负责;
The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.
4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内, 仅作为客户委托、科研、教学或内部质量控制等目的使用;
The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
5. 本检测报告以实测值进行符合性判定, 未考虑不确定度所带来的风险, 本实验室不承担相关责任, 特别约定、标准或规范中有明确规定的除外;
The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.
6. 对本检测报告若有异议, 请于收到报告之日起 20 日内提出;
Objections shall be raised within 20 days from the date receiving the report.