



## **TEST REPORT**

Report No. : AF002020-001 Date : 2005 January 31

Applicant No. : LF200156(3)

Client : Mattel Asia Pacific Sourcing Limited  
13/F., South Tower, World Finance Centre,  
Harbour City, Tsimshatsui, Kowloon, Hong Kong.

Sample Description : One(1) submitted sample stated to be 1 : 10 Drifting Vehicle Nissan Silvia S15  
of Model No. H3623  
Rating : 7.2V rechargeable battery  
No. of sample(s) : Three (3) piece(s)\*\*\*

Date Received : 2005 January 18

Test Period : 2005 January 18 – 2005 January 28

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – July 2004  
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC  
Part 15 Subpart B.

*For and on behalf of*  
CMA Testing and Certification Laboratories

Authorized Signature : \_\_\_\_\_

Danny Chui  
EMC Engineer - EL. Division

Page 1 of 11

FCC ID : PIYH3623-05A4R

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: [info@cmatcl.com](mailto:info@cmatcl.com) Web Site: <http://www.cmatcl.com>



## **TEST REPORT**

Report No. : AF002020-001

Date : 2005 January 31

### **Table of Contents**

1	General Information .....	3
1.1	General Description .....	3
1.2	Related Submittal Grants .....	3
1.3	Location of the test site .....	4
1.4	List of measuring equipment.....	5
2	Description of the radiated emission test .....	6
2.1	Test Procedure .....	6
2.2	Test Result .....	6
2.3	Radiated Emission Measurement Data .....	7
3	Description of the Line-conducted Test .....	8
3.1	Test Procedure .....	8
3.2	Test Result .....	8
3.3	Graph and Table of Conducted Emission Measurement Data .....	8
4	Photograph .....	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission.....	9
4.2	Photographs of the External and Internal Configurations of the EUT .....	9
5	Supplementary document.....	10
5.1	Bandwidth.....	10
5.2	Duty cycle .....	10
6	Appendices .....	11



## **TEST REPORT**

Report No. : AF002020-001

Date : 2005 January 31

### **1 General Information**

#### **1.1 General Description**

The equipment under test (EUT) is a superregenerative receiver for 1:10 Drifting Vehicle Nissan Silvia S15 operating at 49.860 MHz which is controlled by a LRC circuit. The EUT is powered by 7.2V rechargeable battery. It has a on / off switch and 27cm receiving antenna. When it received a forward or backward signal, it will go forward or backward. When it received a turn left or turn right signal it will go left or right.

The brief circuit description is listed as follows:

- Q1 ~ Q4 , Q8, K1 – K2 and associated circuit act as motor control for M1.
- Q5 ~ Q7, Q25, Q26, Q18 ~ Q21 and associated circuit act as motor control for M2.
- X1 and associated circuit act as oscillator for U1.
- U1 and associated circuit act as decoder.
- Q9, Q27 ~ Q30 and associated circuit act as voltage readjust.

#### **1.2 Related Submittal Grants**

This is a single application for certification of a receiver. The transmitter for this receiver is authorized by Certification procedure.



## **TEST REPORT**

Report No. : AF002020-001

Date : 2005 January 31

### **1.3 Location of the test site**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A double shielded room is located at :

Roof Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.



## **TEST REPORT**

Report No. : AF002020-001

Date : 2005 January 31

### **1.4 List of measuring equipment**

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S43284
Broadband Antenna	Schaffner	CBL6112B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	S43098
LISN	R&S	ESH3-Z5	100038	S43101
Pulse Limiter	R&S	ESH3-Z2	100001	S43325
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02



## **TEST REPORT**

Report No. : AF002020-001

Date : 2005 January 31

### **2 Description of the radiated emission test**

#### **2.1 Test Procedure**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to “cohere” the characteristic broadband emissions from the receiver.

#### **2.2 Test Result**

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasip-peak detector.

It was found that the EUT meet the FCC requirement.



## **TEST REPORT**

Report No. : AF002020-001

Date : 2005 January 31

### **2.3 Radiated Emission Measurement Data**

**Radiated emission  
pursuant to  
the requirement of FCC Part 15 subpart B**

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
49.450	V	17.3	10.8	28.1	40.0	-11.9
50.295	V	22.7	8.8	31.5	40.0	-8.5
50.725	V	22.2	8.8	31.0	40.0	-9.0
51.598	V	18.2	8.8	27.0	40.0	-13.0
100.154	V	9.0	11.9	20.9	43.5	-22.6
100.589	V	7.9	11.9	19.8	43.5	-23.7
148.277	V	9.8	12.5	22.3	43.5	-21.2
198.136	V	12.9	10.1	23.0	43.5	-20.5
203.805	V	10.4	10.8	21.2	43.5	-22.3
244.936	V	10.7	10.8	21.5	46.0	-24.5



## **TEST REPORT**

Report No. : AF002020-001

Date : 2005 January 31

### **3 Description of the Line-conducted Test**

#### **3.1 Test Procedure**

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

#### **3.2 Test Result**

No measurement is required as the EUT is a battery-operated product.

#### **3.3 Graph and Table of Conducted Emission Measurement Data**

Not Applicable





## **TEST REPORT**

Report No. : AF002020-001

Date : 2005 January 31

### **4 Photograph**

#### **4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission**

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

#### **4.2 Photographs of the External and Internal Configurations of the EUT**

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



## **TEST REPORT**

Report No. : AF002020-001

Date : 2005 January 31

### **5 Supplementary document**

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

<b>Document</b>	<b>Filename</b>
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

#### **5.1 Bandwidth**

N/A

#### **5.2 Duty cycle**

N/A



## **TEST REPORT**

Report No. : AF002020-001

Date : 2005 January 31

### **6 Appendices**

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of External Configurations	1 page
A3.	Photos of Internal Configurations	1 page
A4.	ID Label/Location	1 page
A5.	Block Diagram	1 page
A6.	Schematics	1 page
A7.	User Manual	2 pages
A8.	Operation Description	1 page

\*\*\*\*\* End of Report \*\*\*\*\*