

# **FCC Test Report**

Report No.: AGC00408230802FR05

FCC ID : 2A3DR-AGMH6

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: 4G Smart Phone

**BRAND NAME** : AGM

**MODEL NAME** : AGM H6

**APPLICANT**: AGM MOBILE LIMITED

**DATE OF ISSUE** : Aug. 25, 2023

**STANDARD(S)** : FCC Part 15 Subpart C §15.225

**REPORT VERSION**: V 1.0


Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 36

## REPORT REVISE RECORD


Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Aug. 25, 2023	Valid	Initial Release





## **TABLE OF CONTENTS**

1. GENERAL INFORMATION	
2. PRODUCT INFORMATION	6
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 TEST FREQUENCY LIST	6
2.3 RELATED SUBMITTAL(S) / GRANT (S)	
2.4 TEST METHODOLOGY	
2.5 SPECIAL ACCESSORIES	
2.6 EQUIPMENT MODIFICATIONS	7
2.7 ANTENNA REQUIREMENT	
3. TEST ENVIRONMENT	
3.1 ADDRESS OF THE TEST LABORATORY	
3.2 TEST FACILITY	
3.3 ENVIRONMENTAL CONDITIONS	9
3.4 MEASUREMENT UNCERTAINTY	9
3.5 LIST OF EQUIPMENTS USED	10
4.SYSTEM TEST CONFIGURATION	11
4.1 EUT CONFIGURATION	1′
4.2 EUT EXERCISE	1′
4.3 CONFIGURATION OF TESTED SYSTEM	1 <sup>7</sup>
4.4 EQUIPMENT USED IN TESTED SYSTEM	1 <sup>2</sup>
4.5 SUMMARY OF TEST RESULTS	
5. DESCRIPTION OF TEST MODES	13
6. FIELD STRENGTH OF FUNDAMENTAL	14
6.1 PROVISIONS APPLICABLE	14
6.2 MEASUREMENT PROCEDURE	14
6.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATI	ON)16
6.4 MEASUREMENT RESULTS	
7. RADIATED EMISSION	19
7.1 LIMITS OF RADIATED EMISSION TEST	
7.2 MEASUREMENT PROCEDURE	19
7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATI	ON)2 <sup>2</sup>
7.4 MEASUREMENT RESULT	
8. 20 DB BANDWIDTH	28
8.1 PROVISIONS APPLICABLE	28
8.2 MEASUREMENT PROCEDURE	28





8.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	28
8.4 MEASUREMENT RESULTS	29
9. FREQUENCY STABILITY	30
9.1 PROVISIONS APPLICABLE	30
9.2 MEASUREMENT PROCEDURE	30
9.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	30
9.4 MEASUREMENT RESULTS	31
10. AC POWER LINE CONDUCTED EMISSION TEST	32
10.1 LIMITS OF LINE CONDUCTED EMISSION TEST	32
10.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	32
10.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	33
10.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	33
10.5 MEASUREMENT RESULTS	33
APPENDIX I: PHOTOGRAPHS OF TEST SETUP	36
APPENDIX II: PHOTOGRAPHS OF TEST EUT	36



Page 5 of 36

## 1. GENERAL INFORMATION

Applicant	AGM MOBILE LIMITED
Address	FLAT/RM 2253 22/F HOI TAI FACTORY ESTATE TSING YEUNG CIRCUIT TUEN MUN NT HONG KONG,CHINA
Manufacturer	SHENZHEN AIJIEMO SCIENCE AND TECHNOLOGY CO.,LTD
Address	1st Floor 101 and 2nd Floor 201, Building A2, Huafeng Century Technology Park, Nanchang Community, Xixiang, Baoan District, Shenzhen, China
Factory	SHENZHEN AIJIEMO SCIENCE AND TECHNOLOGY CO.,LTD
Address	1st Floor 101 and 2nd Floor 201, Building A2, Huafeng Century Technology Park, Nanchang Community, Xixiang, Baoan District, Shenzhen, China
Product Designation	4G Smart Phone
Brand Name	AGM
Test Model	AGM_H6
Deviation from Standard	No any deviation from the test method
Date of Receipt	Aug. 11, 2023
Date of Test	Aug. 11, 2023~Aug. 25, 2023
Test Result	Pass
Test Report Form No	AGCTR-ER-FCC-NFC V1.0

Prepared By	Bibo Zhang	
	Bibo Zhang (Project Engineer)	Aug. 25, 2023
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Aug. 25, 2023
Approved By	Max Zhang	
•	Max Zhang Authorized Officer	Aug. 25, 2023



Page 6 of 36

## 2. PRODUCT INFORMATION

## 2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	S681_V1
Software Version	Android 13
Operation Frequency	13.56MHz
Modulation Type	ASK
Number of channels	1
Field Strength of Fundamental	61.30dBuV/m
Antenna Designation	PIFA Antenna
Antenna Gain	0dBi
Power Supply	DC 3.85V by battery or DC 5V by adapter

## 2.2 TEST FREQUENCY LIST

Frequency Band Channel Number		Frequency		
13.110~14.010 MHz	01	13.56 MHz		



Page 7 of 36

## 2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: **2A3DR-AGMH6**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

#### 2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

#### 2.5 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

## 2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.7 ANTENNA REQUIREMENT

## **Standard Requirement**

## 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

## **EUT Antenna:**

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 0dBi.



Page 8 of 36

## 3. TEST ENVIRONMENT

#### 3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

#### 3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

## CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

## A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

## FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

#### IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 9 of 36

## 3.3 ENVIRONMENTAL CONDITIONS

	NORMAL CONDITIONS	EXTREME CONDITIONS		
Temperature range (°C)	15 - 35	-30℃~50℃		
Relative humidty range	20 % - 75 %	20 % - 75 %		
Pressure range (kPa)	86 - 106	86 - 106		
Power supply	DC 3.85V DC 3.27V or 4.40			

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

#### 3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$
Uncertainty of Radiated Emission below 150kHz	$U_c = \pm 4.2 \text{ dB}$
Uncertainty of Radiated Emission below 30MHz	$U_c = \pm 3.8 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



Page 10 of 36

## 3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Jun. 03, 2023	Jun. 02, 2024
LISN	R&S	ESH2-Z5	100086	Jun. 03, 2023	Jun. 02, 2024
Test software	R&S	ES-K1(Ver.V1.71)	N/A	N/A	N/A
TEST RECEIVER	R&S	ESCI	10096	Feb. 18, 2023	Feb. 17, 2024
EXA Signal Analyzer	Aglient	N9010A	MY5347050 4	Jun. 01, 2023	May 31, 2024
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 05, 2023	Jan. 04, 2025
Test software	Tonscend	JS32-RE (Ver.2.5)	N/A	N/A	N/A



Page 11 of 36

## **4.SYSTEM TEST CONFIGURATION**

## **4.1 EUT CONFIGURATION**


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

## **4.2 EUT EXERCISE**


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

## **4.3 CONFIGURATION OF TESTED SYSTEM**

Radiated Emission Configure:



Conducted Emission Configure:



## **4.4 EQUIPMENT USED IN TESTED SYSTEM**

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement:

	Test	Accessories	Come	From	The	Labora	tory
--	------	-------------	------	------	-----	--------	------

☐ Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	4G Smart Phone	AGM_H6	FCC ID: 2A3DR-AGMH6	EUT
2	Adapter	U312E0A050200	Input: AC 100-240V 50/60Hz, 0.35A Output: DC 5.0V 2A	AE
3	Battery	AGM_H6	DC 3.85V 4930mAh	AE
4	USB Cable	N/A	N/A	AE



Page 12 of 36

## 4.5 SUMMARY OF TEST RESULTS

Item	FCC Rules	Description Of Test	Result
1	§15.203	Antenna Equipment	Pass
2	15.225(a)(b)(c)	Field Strength of Fundamental	Pass
3	§15.209	Radiated Emission	Pass
4	§15.215(c)	20dB Bandwidth	Pass
5	§15.205(a)	Restricted Bands of Operation	Pass
6	§15.225(e)	Frequency Stability	Pass
7	§15.207	AC Power Line Conducted Emission	Pass



Page 13 of 36

## 5. DESCRIPTION OF TEST MODES

	Summary table of Test Cases
Test Item	Data Rate / Modulation
iest item	NFC/ ASK
Radiated & Conducted Test Cases	Mode 1: Tx _13.56 MHz
AC Conducted Emission	Mode 2: Tx _13.56 MHz

## Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.



Page 14 of 36

## 6. FIELD STRENGTH OF FUNDAMENTAL

## **6.1 PROVISIONS APPLICABLE**

Rules and specifications		FCC CFR 47 Part	15 section 15.225	
Description	Compliance v	vith the spectrum ma	sk is tested with RBV	V set to 9kHz.
Freq. of Emission (MHz)	Field Strength (µV/m) at 30m	Field Strength (dBµV/m) at 30m	Field Strength (dBµV/m) at 10m	Field Strength (dBµV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

#### **6.2 MEASUREMENT PROCEDURE**

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the



Report No.: AGC00408230802FR05 Page 15 of 36


pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
Start ~Stop i requerity	1MHz/3MHz for Peak, 1MHz/3MHz for Average


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP






## 6.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)

## RADIATED EMISSION TEST SETUP 9KHz-30MHz



## RADIATED EMISSION TEST SETUP 30MHz-1000MHz






Page 17 of 36

## **6.4 MEASUREMENT RESULTS**

EUT	4G Smart Phone	Model Name	AGM_H6
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Face
132.0 dBuV/m			Limit: — Margin: —
12.0 12.560 12.76		13.76 13.96 14.16	
12.0	Reading Correct Freq. Level Factor	13.76 13.96 14.16  Measure- ment Limit (	14.56 MHz Over
12.0 12.560 12.76 No. Mk.	Reading Correct Freq. Level Factor MHz dBuV dB	Measure- ment Limit (	14.56 MHz  Dver  dB Detector
12.0 12.560 12.76 No. Mk.	Reading Correct Freq. Level Factor	13.76 13.96 14.16  Measure- ment Limit C  dBuV/m dBuV/m  36.11 69.50 -3	14.56 MHz Over

## **RESULT: PASS**





EUT	4G Smart Phone	Model Name	AGM_H6
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Side
132.0 dBuV/m			
			Limit: — Margin: —
		_	
72			
	Maria de la companya		
ortotoro de solocolo condicacido o	1 Million and a second agree of the second block of which the second block of the seco	Aproportion of the second of t	3 Populari programa pr
ومرافي بالمرابط والمرابط والم والمرابط	When the control of t		And Department and the second
12.0			
	12.96 13.16 13.36 13.56	13.76 13.96 14.16	14.56 MHz
	Reading Correct	Measure-	
No. Mk.	Freq. Level Factor		Over
	MHz dBuV dB	dBuV/m dBuV/m	dB Detector
1 * 12	2.9060 10.31 24.59	34.90 69.50 -	34.60 peak
2 13	3.5600 33.78 24.64	58.42 124.0 -	65.58 peak
2 10			•

## **RESULT: PASS**



Page 19 of 36

## 7. RADIATED EMISSION

## 7.1 LIMITS OF RADIATED EMISSION TEST

According to 15.35, on any frequency or frequencies below or equal to 1000 MHz, the limits Shown are based on measuring equipment employing a CISPR quasi-peak detector function and related measurement bandwidths, unless otherwise specified the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test.

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

15.209 Limit in the below table has to be followed:

Frequency	Distance	Field Streng	gths Limit
(MHz)	Meters	μ <b>V/m</b>	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV) 54.0 dB(μV)/n	, ,

Remark:

- (1) Emission level dB  $\mu$  V = 20 log Emission level  $\mu$  V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

## 7.2 MEASUREMENT PROCEDURE

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was



Report No.: AGC00408230802FR05 Page 20 of 36


5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.

- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
Start ~Stop i requertey	1MHz/3MHz for Peak, 1MHz/3MHz for Average


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP






## 7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)

## RADIATED EMISSION TEST SETUP 9KHz-30MHz



## RADIATED EMISSION TEST SETUP 30MHz-1000MHz





Page 22 of 36

#### 7.4 MEASUREMENT RESULT


## **RADIATED EMISSION BELOW 30MHz**

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

#### THE MAGNETIC FIELD FROM 9KHz-150KHz

			MAGNETIC						
EUT		4G Smart Phone		Model Na	Model Name		AGM_H6		
Temperatu	ıre	25° C	25° C		Relative	Relative Humidity		55.4%	
Pressure		960hPa			Test Volt	Test Voltage		Normal Voltage	
Test Mode		Mode 1		Antenna		Face	Face		
130	.0 dBuV/m								
70	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	- Z		4			Limi		
10.C	0.009		The "	(MHz)		adjunatur mail will y	indian through	0.150	
			D 1"	Corroct	Magazira				
			Reading	Correct	Measure-				
	No. Mk.	Freq.	Reading Level	Correct Factor	ment	Limit	Over		
	No. Mk.	Freq.					Over	Detector	
	No. Mk.		Level	Factor	ment	Limit		Detector peak	
		MHz	Level dBuV	Factor dB	ment dBuV/m	Limit dB/m	dB		
	1	MHz 0.0117	dBuV 6.76	Factor dB 28.21	ment dBuV/m 34.97	dB/m	dB -91.07	peak	
	1 2	MHz 0.0117 0.0160	dBuV 6.76 7.02	Factor dB 28.21 27.89	ment dBuV/m 34.97 34.91	dB/m 126.0 123.3	dB -91.07 -88.43	peak peak	
	1 2 3	MHz 0.0117 0.0160 0.0252	dBuV 6.76 7.02 6.78	Factor dB 28.21 27.89 27.21	ment dBuV/m 34.97 34.91 33.99	126.0 123.3 119.4	dB -91.07 -88.43 -85.43	peak peak peak	

## **RESULT: PASS**





EUT			4G Smart Phone		Model N	ame	AGN	//_H6	
Temperatu	ire		25° C			Relative	Humidity	55.4	.%
Pressure			960hPa			Test Volt	age	Norr	nal Voltage
Test Mode			Mode 1			Antenna		Side	<b>)</b>
130.	0 dBuV	/m							imit: — (argin: —
70				3	4	5			6
10.0 0.	.009	wythra	The Comments	Vargon And	(MHz)	Now of the Manufacture	Mayor	and provide the	0.150
-	No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	4
-			MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
-	1		0.0099	6.19	28.35	34.54	127.4	-92.94	peak
-	2		0.0154	3.26	27.94	31.20	123.6	-92.47	peak
-	3		0.0267	8.10	27.09	35.19	118.9	-83.73	peak
-	4		0.0352	8.26	26.46	34.72	116.5	-81.81	peak
-	5		0.0563	11.84	24.88	36.72	112.4	-75.76	peak

## **RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

21.57

38.32

105.4

-67.11

peak

0.1274


16.75



Page 24 of 36


## THE MAGNETIC FIELD FROM 150KHz-30MHz

EUT	4G Smart Phone	Model Name	AGM_H6
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Face
120 0 dRuV/m			




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		0.4420	1.36	20.99	22.35	94.69	-72.34	peak
2		0.7389	2.19	21.08	23.27	70.23	-46.96	peak
3		1.9173	-1.27	22.04	20.77	69.54	-48.77	peak
4		4.6467	0.01	22.91	22.92	69.54	-46.62	peak
5	*	13.5600	11.24	24.64	35.88	69.54	-33.66	peak
6		20.3773	0.20	25.07	25.27	69.54	-44.27	peak

## **RESULT: PASS**





EUT	4G Smart Phone	Model Name	AGM_H6
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Side



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	0.2391	4.52	21.36	25.88	99.99	-74.11	peak
2	0.5701	4.92	20.94	25.86	72.48	-46.62	peak
3	1.2555	1.49	21.50	22.99	65.63	-42.64	peak
4	4.2240	1.34	22.78	24.12	69.54	-45.42	peak
5 *	13.5600	8.24	24.64	32.88	69.54	-36.66	peak
6	24.2706	-1.82	24.68	22.86	69.54	-46.68	peak


## **RESULT: PASS**



Page 26 of 36


## RADIATED EMISSION FROM 30MHz ~1000MHz

EUT	4G Smart Phone	Model Name	AGM_H6
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal



NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	38.73	29.38	9.69	40.00	10.62	100	160	Horizontal
2	62.01	26.66	12.60	40.00	13.34	100	80	Horizontal
3	101.78	28.89	20.60	43.50	14.61	100	270	Horizontal
4	462.62	31.93	27.40	46.00	14.07	100	340	Horizontal
5	608.12	34.14	28.42	46.00	11.86	100	150	Horizontal
6	872.93	37.40	32.13	46.00	8.60	100	40	Horizontal

**RESULT: PASS** 





EUT		4G Sm	art Phone		Model Na	ame	AGM_F	16
Tempera	ature	25° C			Relative	Humidity	55.4%	
Pressur	е	960hP	а		Test Volta	age	Normal	Voltage
Test Mo	de	Mode	1		Antenna		Vertical	
	130	•		FCC PART	15C		·	
	120							
	110							
	90							
	80							
BµV/m	70 60							
Level[dBµV/m]	50							
_	40							<b>3</b> 5 3 <b>3</b> € 6
	30	*2	~**\	· ····································	M.	Land Land Land Land	بالتهميم ليهدونه والمدين والمراجعة و	
	10			~~~~	and a supplemental of the	Mary Mary Mary		
	0							
	-10 L		100M			<u> </u>		1G
	— QP Limit			Frequency[	Hz]			
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	39.7	31.31	11.67	40.00	8.69	100	100	Vertical
2	61.04	28.60	14.77	40.00	11.40	100	130	Vertical
3	81.41	26.27	12.20	40.00	13.73	100	290	Vertical
4	141.55	26.79	20.04	43.50	16.71	100	350	Vertical
-	782.72	35.86	30.77	46.00	10.14	100	30	Vertical
5		38.32	32.23	46.00	7.68	100	0	Vertical

## **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Margin= Limit-Measurement.

2. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.



Page 28 of 36

## 8. 20 dB BANDWIDTH

## **8.1 PROVISIONS APPLICABLE**


Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.

## **8.2 MEASUREMENT PROCEDURE**

Set the parameters of SPA as below:

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. Centre frequency = Operation Frequency
- 3. The resolution bandwidth of 10 kHz and the video bandwidth of 30 kHz were used.
- 4. Span: 100kHz, Sweep time: Auto
- Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.
- 6. Measured the spectrum width with power higher than 20dB below carrier.
- 7. Measured the 99% OBW.
- 8. Record the plots and Reported.

## 8.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)






Page 29 of 36

#### **8.4 MEASUREMENT RESULTS**

	Test Data of Occupied Bandwidth and -20dB Bandwidth						
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-20dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail		
ASK	13.56	0.025066	0.02757	N/A	Pass		

## Test Graphs of Occupied Bandwidth &-20dB Bandwidth





Page 30 of 36

## 9. FREQUENCY STABILITY


## 9.1 PROVISIONS APPLICABLE

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -30 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

## 9.2 MEASUREMENT PROCEDURE

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT.
- 2. EUT have transmitted signal and fixed channelize.
- 3. Set the spectrum analyzer span to view the entire emissions bandwidth.
- 4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
- 5. The fc is declaring of channel frequency. Then the frequency error formula is (fc-f)/fc × 106 ppm and the limit is less than ±100ppm.
- 6. Extreme temperature rule is -30°C~50°C.

## 9.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)





Page 31 of 36

## 9.4 MEASUREMENT RESULTS

Operating frequency: 13.56MHz

Voltage vs. Frequency Stability (Test Temperature: 20 °C)

Voltage(V)	Measurement Frequency (MHz)	Max. Deviation (ppm)	Limit(ppm)	Conclusion
3.85	13.56082			
3.27	13.56066	+60.74	±100	PASS
4.40	13.56079			

Temperature vs. Frequency Stability (Test Voltage: 3.85V)

Temperature	Measurement Frequency (MHz)	Max. Deviation (ppm)	Limit(ppm)	Conclusion
-30℃	13.56050			
<b>-20</b> ℃	13.56062			
-10℃	13.56069			
0℃	13.56055			
10℃	13.56050	+50.88	$\pm 100$	PASS
20℃	13.56048			
30℃	13.56041			
40℃	13.56053			
50℃	13.56060			



Report No.: AGC00408230802FR05 Page 32 of 36

## 10. AC POWER LINE CONDUCTED EMISSION TEST


## 10.1 LIMITS OF LINE CONDUCTED EMISSION TEST

Francisco	Maximum RF Line Voltage				
Frequency	Q.P. (dBµV)	Average (dBμV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

#### Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

## 10.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)





Page 33 of 36

#### 10.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


#### 10.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

#### **10.5 MEASUREMENT RESULTS**







#### MEASUREMENT RESULT: "agc fin"

	_			
2023	10	100	O -	40
Z11 Z 3	/ H .	1//	- 4 -	42
20201	0,			1 -

Frequency MHz			Limit dBµV	Margin dB	Detector	Line
0.154000	43.90	6.1	66	21.9	QP	L1
0.326000	32.70	6.1	60	26.9	QP	L1
0.506000	39.80	6.2	56	16.2	QP	L1
0.526000	39.50	6.2	56	16.5	QP	L1
0.858000	29.00	6.2	56	27.0	QP	L1
1.034000	29.20	6.2	56	26.8	OP	T.1

## MEASUREMENT RESULT: "agc fin2"


2023/8/22 9:42

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.458000 0.506000 0.530000 0.554000 0.854000 1.134000	27.70 37.40 36.60 27.30 25.50 25.10	6.1 6.2 6.2 6.2 6.2	47 46 46 46 46	19.0 8.6 9.4 18.7 20.5 20.9	AV AV AV	L1 L1 L1 L1 L1

RESULT: PASS
Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection and Testing Inspection of AGC. The test result is not permitted without the written authorization of AGC. The test resulting Inspection of AGC. Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report.  $Further\ enquiry\ of\ validity\ or\ verification\ of\ the\ test\ report\ should\ be\ addressed\ to\ AGC\ by\ agc 01@agccert.com.$ 

Web: http://www.agccert.com/





## MEASUREMENT RESULT: "agc fin2"

40.90

42.00

32.00

30.60

0.502000

0.526000

1.030000

1.054000

2023/8/22 Frequen			Transd dB	Limit dBµV	Margin dB	Detector	Line
0.4580 0.4820		26.60 24.30	6.1 6.1	47 46	20.1	AV AV	N N
0.5060	00	34.80	6.2	46	11.2	AV	N
0.5300 0.5540		35.40 26.80	6.2 6.2	46 46	10.6 19.2	AV AV	N N
1.1340	00	22.20	6.2	46	23.8	AV	N

6.2

6.2

6.2

6.2

56

56

56

56

15.1

14.0

24.0

25.4

QP

QΡ

QΡ

QP

Ν

Ν

Ν

## **RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report.  $Further\ enquiry\ of\ validity\ or\ verification\ of\ the\ test\ report\ should\ be\ addressed\ to\ AGC\ by\ agc 01@agccert.com.$ 

Web: http://www.agccert.com/



Page 36 of 36

## **APPENDIX I: PHOTOGRAPHS OF TEST SETUP**

Refer to the Report No.: AGC00408230802AP01

APPENDIX II: PHOTOGRAPHS OF TEST EUT

Refer to the Report No.: AGC00408230802AP04

----END OF REPORT-----



## Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.