

RF Exposure Report

Report No.: SA200417E02

FCC ID: MAD-G08RRH-46-06B

Test Model: G08RRH-46-06B

Received Date: Apr. 17, 2020

Test Date: May 23, 2020

Issued Date: June 18, 2020

Applicant: Microelectronics Technology Inc.

Address: No. 1, Innovation Road II, Hsinchu Science Park, Hsinchu 300, Taiwan,
R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Antenna Gain	6
4 Calculation Result	7

Release Control Record

Issue No.	Description	Date Issued
SA200417E02	Original release.	June 18, 2020

1 Certificate of Conformity

Product: LionHead 2x40W B5 RRH

Brand: MTI

Test Model: G08RRH-46-06B

Sample Status: ENGINEERING SAMPLE

Applicant: Microelectronics Technology Inc.

Test Date: May 23, 2020

Standards: FCC Part 2 (Section 2.1091)
IEEE C95.3 -2002

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Vivian Huang , **Date:** June 18, 2020
Vivian Huang / Specialist

Approved by : Clark Lin , **Date:** June 18, 2020
Clark Lin / Technical Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	F/300	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 400 cm away from the body of the user. So, this device is classified as fixed station and installations by professional service personnel device.

3 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

Antenna Gain (dBi)	Frequency range(MHz)	Antenna Type	Connector Type
18	806-894	Sector	4×4.3-10 Female

4 Calculation Result

For LTE Band 5

Frequency Band (MHz)	Conducted Average Power - Per Chain (dBm/MHz)		Max Conducted Average Power - Total (dBm/MHz)	Antenna Gain (dBi)	Max EIRP Power (dBm/MHz)	Max EIRP Power (mW/MHz)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
	CHAIN 0	CHAIN 1							
871.5~891.5	39.13	39.11	42.13	18	60.13	1030386.12	400	0.51251	0.581

EIRP Power = Conducted Power+ Antenna gain

--- END ---