

MPE TEST REPORT

Applicant	MeiG Smart Technology Co., Ltd
FCC ID	2APJ4-SLM336-L
Product	LTE Cat1 Module
Brand	MEIGLink
Model	SLM336-L
Report No.	EFTA25010039-IE-06-M1
Issue Date	February 24, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310.** The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Wei Fangying

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd. Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China TEL: +86-021-50791141/2/3 FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Tes	t Laboratory	3
1	.1	Notes of the Test Report	3
1	.2	Test Facility	. 3
1	.3	Testing Location	. 3
1	.4	Laboratory Environment	3
2	Des	scription of Equipment Under Test	4
3	Max	ximum Tune up and Antenna Gain	5
4	MP	E Limit	7
5	RF	Exposure Evaluation Result	9
AN	NEX	A: The EUT Appearance 1	10

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company:	Eurofins TA Technology (Shanghai) Co., Ltd.
Address:	Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Xu Kai
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	https://www.eurofins.com/electrical-and-electronics
E-mail:	Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C			
Relative humidity	Min. = 20%, Max. = 80%			
Ground system resistance	< 0.5 Ω			
Ambient noise is checked and found very low and in compliance with requirement of standards.				
Reflection of surrounding objects is minimized and in compliance with requirement of standards.				

2 Description of Equipment Under Test

Client Information

Applicant	MeiG Smart Technology Co., Ltd	
Applicant address	2nd Floor,Office Building,No.5 Lingxia Road,Fenghuang,Fuyong Street,Bao'an District,Shenzhen, China.	
Manufacturer	MeiG Smart Technology Co., Ltd	
Manufacturer address	2nd Floor,Office Building,No.5 Lingxia Road,Fenghuang,Fuyong Street,Bao'an District,Shenzhen, China.	

General Technologies

EUT Description					
Model	SLM336-L				
IMEI	867442070188525				
Hardware Version	SLM336E_MB_PCB_V1.0	00			
Software Version	V51_U04				
	Band	TX (MHz)	RX (MHz)		
	GSM 850	824 ~ 849	869 ~ 894		
	GSM 1900	1850 ~ 1910	1930 ~ 1990		
Fraguanay	LTE Band 2	1850 ~ 1910	1930 ~ 1990		
Frequency	LTE Band 4	1710 ~ 1755	2110 ~ 2155		
	LTE Band 5	824 ~ 849	869 ~ 894		
	LTE Band 7	2500 ~ 2570	2620 ~ 2690		
	LTE Band 66	1710 ~ 1780	2110 ~ 2180		
Date of Testing	January 2, 2025 ~ January 26, 2025				
Date of Sample Received	December 30, 2024				

Note:

1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.

2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

3 Maximum Tune up and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by Numeric gain (G)=10⁽antenna gain/10)

According to specification 3GPP TS 51.010, the maximum power of the GSM can do the power reduction for the multi-slot. The allowed power reduction in the multi-slot configuration is as following:

Number of timeslots in uplink assignment	Permissible nominal reduction of maximum output power (dB)
1	0
2	0 to 3,0
3	1,8 to 4,8
4	3,0 to 6,0

Each Tx slots maximum tune up use the most strictest factor for evaluation by making calculation.

Band		Burst-Averaged output power (adjusted for tune up) (dBm)		Frame-Averaged output power (adjusted for tune up) (dBm)
	GSM	35.00	-9.03	25.97
	1 Txslot	35.00	-9.03	25.97
GSM850	2 Txslots	35.00	-6.02	28.98
	3 Txslots	33.20	-4.26	28.94
	4 Txslots	32.00	-3.01	28.99
	GSM	32.00	-9.03	22.97
	1 Txslot	32.00	-9.03	22.97
GSM1900	2 Txslots	32.00	-6.02	25.98
	3 Txslots	30.20	-4.26	25.94
	4 Txslots	29.00	-3.01	25.99
Note:				

Division Factors

To average the power, the division factor is as follows:

- 1Txslot = 1 transmit time slot out of 8 time slots
 - = conducted power divided by (8/1) = -9.03 dB
- 2Txslots = 2 transmit time slots out of 8 time slots
 - => conducted power divided by (8/2) => -6.02 dB
- 3Txslots = 3 transmit time slots out of 8 time slots
 - => conducted power divided by (8/3) => -4.26 dB
- 4Txslots = 4 transmit time slots out of 8 time slots
 - \Rightarrow conducted power divided by (8/4) \Rightarrow -3.01 dB



MPE Test Report

Band	Maximum Tune up Power		Antenna Gain	Numeric Gain	
5	(dBm)	(mW)	(dBi)		
GSM 850	28.99	792.50	2.52	1.79	
GSM 1900	25.99	397.19	2.10	1.62	
LTE Band 2	25.70	371.53	2.10	1.62	
LTE Band 4	25.70	371.53	2.40	1.74	
LTE Band 5	25.70	371.53	2.52	1.79	
LTE Band 7	25.70	371.53	3.19	2.08	
LTE Band 66	25.70	371.53	2.40	1.74	

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure

(MPE) are as following.

Frequency range (MHz)	quency ange (V/m) Magnetic field strengt (A/m)		Power density (mW/cm ²)	Averaging time (minutes)			
	(I) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE						
0.3-3.0	614	1.63	*(100)	<u>≤</u> 6			
3.0-30	1842/f	4.89/f	*(900/f ²)	<6			
30-300	-300 61.4 0.163 1.0		1.0	<6			
300-1,500			f/300	<6			
1,500-100,000			5	<6			
	(II) LIMITS FOR GENERA	L POPULATION/UNCONTROLLED	Exposure				
0.3-1.34	614	1.63	*(100)	<30			
1.34-30	824/f	2.19/f	*(180/f ²)	<30			
30-300	27.5	0.073	0.2	<30			
300-1,500			f/1500	<30			
1,500-100,000			1.0	<30			

f = frequency in MHz. * = Plane-wave equivalent power density.

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.



MPE Test Report

The maximum permissible exposure for 300~1500 MHz is f/1500, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
GSM850	0.549
GSM1900	1.000
LTE Band 2	1.000
LTE Band 4	1.000
LTE Band 5	0.549
LTE Band 7	1.000
LTE Band 66	1.000

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$S = PG / 4\pi R^2$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)
GSM 850	28.99	2.52	31.51	1415.79	0.28	0.549
GSM 1900	25.99	2.10	28.09	644.17	0.13	1.000
LTE Band 2	25.70	2.10	27.80	602.56	0.12	1.000
LTE Band 4	25.70	2.40	28.10	645.65	0.13	1.000
LTE Band 5	25.70	2.52	28.22	663.74	0.13	0.549
LTE Band 7	25.70	3.19	28.89	774.46	0.15	1.000
LTE Band 66	25.70	2.40	27.40	645.65	0.13	1.000
Note: R = 20cm						
π = 3.1416						

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

******END OF REPORT ******