



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM161101015501
Page: 1 of 18

TEST REPORT

Application No.: SZEM1611010155CR
Applicant: SZ DJI TECHNOLOGY CO., LTD
Address of Applicant: 14th floor, West Wing, Skyworth Semiconductor Design Building NO. 18 Gaoxin South 4th Ave, Nanshan District, Shenzhen, China
Manufacturer: SZ DJI TECHNOLOGY CO., LTD
Address of Manufacturer: 14th floor, West Wing, Skyworth Semiconductor Design Building NO. 18 Gaoxin South 4th Ave, Nanshan District, Shenzhen, China
Factory: SZ DJI TECHNOLOGY CO., LTD
Address of Factory: 14th floor, West Wing, Skyworth Semiconductor Design Building NO. 18 Gaoxin South 4th Ave, Nanshan District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: DJI CINESSD
Model No.: PS522M2, PS266M2, PS168M2 ♣
♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: DJI
FCC ID : SS3-PS522M21611
Standards: 47 CFR PART 15, Subpart B:2015
Date of Receipt: 2016-11-30
Date of Test: 2016-12-02 to 2016-12-14
Date of Issue: 2016-12-15

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



2 Test Summary

Item	Standard	Method	Class	Result
Conducted Disturbance at Mains Terminals (150kHz-30MHz)	47 CFR PART 15, Subpart B:2015	ANSI C63.4	Class B	Pass
Radiated Disturbance (30MHz-1GHz)	47 CFR PART 15, Subpart B:2015	ANSI C63.4	Class B	Pass
Radiated Disturbance (above 1GHz)	47 CFR PART 15, Subpart B:2015	ANSI C63.4	Class B	Pass

Remark:

Model No.: PS522M2, PS266M2, PS168M2

Only the model PS522M2 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models, only different on flash storage and model No..



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 DETAILS OF E.U.T.	4
4.2 DESCRIPTION OF SUPPORT UNITS	4
4.3 STANDARDS APPLICABLE FOR TESTING	5
4.4 TEST LOCATION	6
4.5 TEST FACILITY	6
4.6 DEVIATION FROM STANDARDS	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
5 EQUIPMENT LIST	7
6 EMISSION TEST RESULTS	9
6.1 CONDUCTED DISTURBANCE AT MAINS TERMINALS(150kHz-30MHz)	9
6.1.1 E.U.T. Operation	9
6.1.2 Test Setup	9
6.1.3 Measurement Data	9
6.2 RADIATED DISTURBANCE(BELOW 1GHz)	12
6.2.1 E.U.T. Operation	12
6.2.2 Measurement Data	12
6.3 RADIATED DISTURBANCE(ABOVE 1GHz)	16
6.3.1 E.U.T. Operation	16
6.3.2 Measurement Data	16



4 General Information

4.1 Details of E.U.T.

Power Supply: Powered by the Drone or the DJI CINESSD STATION

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	Lenovo	T430u	REF. No.SEA1800
DJI CINESSD STATION	DJI	PR05GU3	--
Router	NETGEAR	DGN2200	REF. No.SEA2200
Mouse	Lenovo	M-U0025-O	REF. No.:SEA2400



4.3 Standards Applicable for Testing

Table 1 : Tests Carried Out Under 47 CFR PART 15,Subpart B:2015

Method	Item	Status
ANSI C63.4	Conducted Disturbance at Mains Terminals (150kHz-30MHz)	√
ANSI C63.4	Radiated Disturbance(30MHz-1GHz)	√
ANSI C63.4	Radiated Disturbance(above 1GHz)	√

- × Indicates that the test is not applicable
√ Indicates that the test is applicable



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong,
China 518057

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

•CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

• Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Disturbance at Mains Terminals(150kHz-30MHz)						
Item	Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
1	Shielding Room	ChangZhou ZhongYu	GB-88	SEM001-06	2016-05-13	2017-05-13
2	LISN	Rohde & Schwarz	ENV216	SEM007-01	2016-10-09	2017-10-09
3	LISN	ETS-LINDGREN	3816/2	SEM007-02	2016-04-25	2017-04-25
4	EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2016-04-25	2017-04-25

Radiated Disturbance(below 1GHz)						
Item	Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
1	10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2016-05-13	2017-05-13
2	EMI Test Receiver (9kHz-7GHz)	Rohde & Schwarz	ESR	SEM004-03	2016-04-25	2017-04-25
3	Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-29
4	Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2016-07-06	2017-07-06

Radiated Disturbance(above 1GHz)						
Item	Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
1	3m Full-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
2	EXA Spectrum Analyzer	AgilentTechnologies Inc	N9010A	SEM004-09	2016-07-19	2017-07-19
3	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-06	2015-06-14	2018-06-14
4	Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09



General used equipment						
Item	Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
1	Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
2	Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
3	Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
4	Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2016-05-18	2017-05-18

6 Emission Test Results


6.1 Conducted Disturbance at Mains Terminals(150kHz-30MHz)

Test Requirement:	47 CFR PART 15, Subpart B:2015
Test Method:	ANSI C63.4
Frequency Range:	150kHz to 30MHz
Limit:	
0.15M-0.5MHz	66dB(μV)-56dB(μV) quasi-peak, 56dB(μV)-46dB(μV) average
0.5M-5MHz	56dB(μV) quasi-peak, 46dB(μV) average
5M-30MHz	60dB(μV) quasi-peak, 50dB(μV) average
Detector:	Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

6.1.1 E.U.T. Operation

Operating Environment:					
Temperature:	25	°C	Humidity:	55	% RH
			Atmospheric Pressure:	1015	mbar
Test mode:	a: PC mode: Keep the EUT in data exchanging with PC mode.				
Note:	Three models were tested during the pretest and found the data of model PS522M2 is the worst. Only the data of the worst is recorded in the report.				


6.1.2 Test Setup



6.1.3 Measurement Data

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.


Mode:a;Line:Live Line



Site : Shielding Room
 Condition : CE LINE
 Job No. : 10155IT
 Test Mode : a

	Freq	Cable	LISN	Read	Limit	Over	
	MHz	Loss	Factor	Level	Line	Limit	Remark
		dB		dBuV	dBuV	dB	
1	0.16327	0.02	9.60	40.48	50.10	65.30	-15.20 QP
2	0.16327	0.02	9.60	19.35	28.97	55.30	-26.33 AVERAGE
3	0.17491	0.02	9.60	26.02	35.64	54.72	-19.09 AVERAGE
4 @	0.17491	0.02	9.60	40.78	50.40	64.72	-14.33 QP
5	0.22083	0.02	9.60	32.85	42.47	62.79	-20.32 QP
6	0.22083	0.02	9.60	13.63	23.25	52.79	-29.53 AVERAGE
7	0.61726	0.02	9.61	8.79	18.42	46.00	-27.58 AVERAGE
8	0.61726	0.02	9.61	21.79	31.42	56.00	-24.58 QP
9	1.433	0.03	9.59	20.73	30.35	56.00	-25.65 QP
10	1.433	0.03	9.59	11.39	21.00	46.00	-25.00 AVERAGE
11	13.768	0.15	9.75	11.67	21.57	50.00	-28.43 AVERAGE
12	13.768	0.15	9.75	17.46	27.37	60.00	-32.63 QP

Mode:a;Line:Neutral Line



Site : Shielding Room
Condition : CE NEUTRAL
Job No. : 10155IT
Test Mode : a

	Freq	Cable	LISN	Read	Limit	Over	
	MHz	Loss	Factor	Level	Line	Limit	Remark
		dB		dBuV	dBuV	dBuV	dB
1 @	0.17034	0.02	9.60	41.59	51.21	64.94	-13.73 QP
2	0.17034	0.02	9.60	24.73	34.36	54.94	-20.59 AVERAGE
3	0.18838	0.02	9.61	19.50	29.14	54.11	-24.97 AVERAGE
4	0.18838	0.02	9.61	38.60	48.23	64.11	-15.88 QP
5	0.22083	0.02	9.62	33.15	42.79	62.79	-20.00 QP
6	0.22083	0.02	9.62	14.12	23.75	52.79	-29.03 AVERAGE
7	0.27587	0.02	9.62	5.31	14.95	50.94	-35.99 AVERAGE
8	0.27587	0.02	9.62	25.66	35.30	60.94	-25.64 QP
9	0.55814	0.02	9.63	19.65	29.30	56.00	-26.70 QP
10	0.55814	0.02	9.63	8.58	18.23	46.00	-27.77 AVERAGE
11	11.807	0.15	9.83	9.01	18.99	50.00	-31.01 AVERAGE
12	11.807	0.15	9.83	15.56	25.55	60.00	-34.45 QP

6.2 Radiated Disturbance(below 1GHz)

Test Requirement: 47 CFR PART 15,Subpart B:2015

Test Method: ANSI C63.4

Frequency Range: 25MHz to 1GHz

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3


6.2.1 E.U.T. Operation

Operating Environment:						
Temperature:	24.0 °C	Humidity:	54 % RH	Atmospheric Pressure:	1010	mbar
Test mode:	a: PC mode: Keep the EUT in data exchanging with PC mode.					
Note:	Three models were tested during the pretest and found the data of model PS522M2 is the worst. Only the data of the worst is recorded in the report.					

6.2.2 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.

Mode:a;Polarization:Horizontal



Condition: 10m HORIZONTAL


Job No. : 10155IT

Test Mode: a

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dB
1 pp	75.71	7.02	9.17	32.88	35.18	18.49	29.50	-11.01
2	180.02	7.50	10.92	32.72	31.85	17.55	33.10	-15.55
3	202.10	7.61	9.34	32.70	33.84	18.09	33.10	-15.01
4	259.23	7.90	11.46	32.64	34.10	20.82	35.60	-14.78
5	303.54	8.06	12.76	32.60	32.48	20.70	35.60	-14.90
6	629.48	8.97	19.28	32.60	27.36	23.01	35.60	-12.59



Mode:a;Polarization:Vertical



Condition: 10m VERTICAL

Job No. : 10155IT

Test Mode: a

	Freq	Cable	Ant	Preamp	Read	Limit	Over
	MHz	Loss	Factor	Factor	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	51.12	6.92	12.69	32.99	31.21	17.83	29.50 -11.67
2	75.71	7.02	9.17	32.88	39.03	22.34	29.50 -7.16
3	177.51	7.50	11.29	32.72	32.36	18.43	33.10 -14.67
4 pp	240.00	7.80	11.07	32.66	45.92	32.13	35.60 -3.47
5	257.42	7.89	11.42	32.64	43.91	30.58	35.60 -5.02
6	404.67	8.31	14.99	32.60	28.12	18.82	35.60 -16.78



For frequencies below 1GHz, the test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L_3 : Level @ 3m distance. Unit: $\mu\text{V/m}$;

L_{10} : Level @ 10m distance. Unit: $\mu\text{V/m}$;

D_3 : 3m distance. Unit: m

D_{10} : 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m ($\mu\text{V/m}$)	Level @ 3m ($\mu\text{V/m}$)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
51.12	17.83	7.79	25.96	28.29	40.00	-11.71	V
75.71	22.34	13.09	43.64	32.80	40.00	-7.20	V
177.51	18.43	8.35	27.82	28.89	43.50	-14.61	V
240.00	32.13	40.41	134.70	42.59	46.00	-3.41	V
257.42	30.58	33.81	112.69	41.04	46.00	-4.96	V
404.67	18.82	8.73	29.10	29.28	46.00	-16.72	V
75.71	18.49	8.40	28.01	28.95	40.00	-11.05	H
180.02	17.55	7.54	25.14	28.01	43.50	-15.49	H
202.10	18.09	8.03	26.75	28.55	43.50	-14.95	H
259.23	20.82	10.99	36.63	31.28	46.00	-14.72	H
303.54	20.70	10.84	36.13	31.16	46.00	-14.84	H
629.48	23.01	14.14	47.14	33.47	46.00	-12.53	H

Remark:

Scan from 25MHz to 1GHz, the disturbance below 30MHz was very low, and the above emission was the highest point could be found when testing, so only the above emission has been displayed. The amplitude of emissions which are attenuated more than 20dB below the limit need not be reported.



6.3 Radiated Disturbance(above 1GHz)

Test Requirement: 47 CFR PART 15, Subpart B:2015
Test Method: ANSI C63.4
Frequency Range: Above 1GHz
Limit:
Above 1GHz 74(dB μ V/m) peak, 54(dB μ V/m) average
Detector: Peak for pre-scan (1000kHz resolution bandwidth) 1000M to 18000MHz

6.3.1 E.U.T. Operation


Operating Environment:							
Temperature:	24.0	°C	Humidity:	56	% RH	Atmospheric Pressure:	1015 mbar
Test mode:	a: PC mode: Keep the EUT in data exchanging with PC mode.						
Note:	Three models were tested during the pretest and found the data of model PS522M2 is the worst. Only the data of the worst is recorded in the report.						

6.3.2 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.



Mode:a;Polarization:Horizontal



Condition: 3m Horizontal


Job No. : 10155IT

Test Mode: a

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2000.528	5.01	27.80	38.10	42.33	37.04	54.00	-16.96	Average
2	2000.528	5.01	27.80	38.10	55.82	50.53	74.00	-23.47	Peak
3	2489.310	5.41	29.37	38.15	45.67	42.30	54.00	-11.70	Average
4	2489.310	5.41	29.37	38.15	63.12	59.75	74.00	-14.25	Peak
5 pp	2993.840	5.92	31.28	38.20	45.78	44.78	54.00	-9.22	Average
6 pk	2993.840	5.92	31.28	38.20	60.94	59.94	74.00	-14.06	Peak



Mode:a;Polarization:Vertical



Condition: 3m Vertical

Job No. : 10155IT

Test Mode: a

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2498.247	5.42	29.39	38.15	47.80	44.46	54.00	-9.54	Average
2	2498.247	5.42	29.39	38.15	65.01	61.67	74.00	-12.33	Peak
3 pp	2993.840	5.92	31.28	38.20	46.45	45.45	54.00	-8.55	Average
4 pk	2993.840	5.92	31.28	38.20	64.70	63.70	74.00	-10.30	Peak
5	3233.621	6.11	31.74	38.33	38.79	38.31	54.00	-15.69	Average
6	3233.621	6.11	31.74	38.33	52.88	52.40	74.00	-21.60	Peak