



RF Exposure Evaluation Report

1. Product Information

FCC ID:	2A4OE-B-19
Number of tested samples	2
Sample number	A050423093-1(Engineer sample), A050423093-2(Normal sample)
Product Name	4 in1 Wireless Charger
Model Number	B-19
Power Supply	Input: 9V $\overline{\sim}$ 3A, 12V $\overline{\sim}$ 3A Mobile phone output1: 15W Max Mobile phone output2: 10W Headphone port output: 3W Watch Output: 2W
Modulation Type	Continuous Wave
Frequency Range	110.3~205.0KHz
Antenna Type	Coil Antenna
Hardware version	/
Software version	/
Accessories	/
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device





2. Evaluation Method

Per KDB 680106 D01 Section 3. RF Exposure Requirements;

- 1) Consumer wireless power transfer devices approved under Part 15 in some cases have to demonstrate compliance with RF exposure requirements. The potential for exposure must be assessed according to the operating configurations of the wireless system and the exposure conditions of users and bystanders. RF exposure must be evaluated with the client device(s) being charged by the primary at maximum output power. The RF exposure requirements must be determined in conjunction with the device operating characteristics, according to the mobile and portable exposure requirements in Section 2.1091 and Section 2.1093 of the rules. SAR and MPE limits do not cover the frequency range for wireless power transfer applications which operate below 100 kHz and 300 kHz respectively; therefore, RF exposure compliance needs to be determined with respect to 1.1307 (c) and (d) of the FCC rules.
- 2) Based on the design and implementation of the power transfer application, it must be clearly identified if mobile or portable RF exposure conditions apply. Devices that are installed to provide separation of at least 20 cm from users and bystanders may qualify for mobile exposure conditions. For some conditions where users and bystanders may be exposed at closer than 20 cm, section 2.1091(d) (4) of the rules may apply.
- 3) For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.
- 4) Portable exposure conditions from 100 kHz to 6 GHz are determined with respect to SAR requirements. Existing SAR systems and test procedures are generally intended for measurements above 100 MHz. While numerical modeling can be an alternative, the constraints of substantial computational resources at low frequencies could introduce further limitations. Under these circumstances, including operations below 100 kHz, the Commission may consider a combination of analytical analysis, field strength, radiated and conducted power measurements, in conjunction with some limited numerical modeling to assess compliance.
- 5) Depending on the operating frequency, existing SAR and MPE measurement procedures may be adapted to evaluate wireless power transfer devices for compliance with respect to mobile or portable exposure conditions. If the grantee or its test lab have any questions regarding RF exposure evaluation they should contact the FCC Laboratory with sufficient system operating configuration details to determine if RF exposure evaluation is necessary and, if required, how to apply specific test procedures. Below 100 MHz, when SAR testing is required and the device is operating at close proximity to persons, information on device design, implementation, operating configurations, exposure conditions of users and bystanders are needed to determine the evaluation and testing requirements. In addition, the influence of nearby objects may also need consideration according to the wireless power transfer system implementation; for example, the effects of placing the device, its coils or radiating elements on or near metallic surfaces



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3. Evaluation Limit

3.1 Refer evaluation method

[ANSI C95.1–1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 680106 D01 RF Exposure Wireless Charging Apps v03](#): RF Exposure Considerations for Low Power Consumer Wireless Power Transfer Applications

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500	/	/	f/300	6
1,500-100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500	/	/	f/1500	30
1,500-100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

According to FCC KDB 680106 D01 Section 3. RF Exposure Requirements clause 3 the Emission-Limits in the frequency range from 100 KHz to 300 KHz should be assessed versus the limits at 300 KHz in Table 1 of CFR 47 – Section1.310 as following (measured distance shall be 15cm from the center of the probe to the edge of the device):

	E-Field	*/*	B-Field
Frequency	V/m	A/m	uT
0.3 MHz – 3.0 MHz	614	1.613	2.0
3.0 MHz – 30 MHz	824/f (=27.5 _{30MHz})	2.19/f (=0.073 _{30MHz})	--

A KDB inquire was required to determine/confirm the applicable limits below 100 KHz.




Shenzhen LCS Compliance Testing Laboratory Ltd.


Add:101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



4. Test Setup Diagram



5. Test Equipment

Equipment	Manufacturer	Model	Serial no.	Calibrated date	Calibrated Due
Exposure Level Tester	Narda	ELT-400	N-0713	2022-10-29	2023-10-28
B-Field Probe	Narda	ELT-400	M-1154	2022-10-29	2023-10-28
Electric field probe	Narda	EP601	611WX70332	2023-01-29	2024-01-28

6. Measurement Uncertainty

(95% confidence levels, $k=2$)

Measurement Uncertainty

Magnetic field expanded uncertainty

= 3.65dB, $k=2$

Electric Field expanded uncertainty

= 2.67dB, $k=2$

7. Measurement Procedure

- The RF exposure test was performed on 360 degree turn table in anechoic chamber.
- The measurement probe was placed at test distance (15cm and 20cm) which is between the edges of the charger and the geometric center of probe.
- The turn table was rotated 360 degree to search of highest strength.
- The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- The EUT were measured according to the dictates of KDB 680106D01v03.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity




8. Equipment Approval Considerations

The EUT does comply with item 5.2 of KDB 680106 D01v03 as follows table;

Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operate in the frequency range 110.3 KHz - 205 KHz
Output power from each primary coil is less than or equal to 15 watts	Yes	Wireless charger output for iphone: The maximum output power of the primary coil is 15W.
The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Yes	Charging systems have three primary coils and clients that are able to detect and allow coupling only between individual pairs of coils and the coil pairs powered on at the same time.
Client device is placed directly in contact with the transmitter.	Yes	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes	Mobile exposure conditions only
The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

In all other cases, unless excluded above, an RF exposure evaluation report must be reviewed and accepted through a KDB or PBA inquiry to enable authorization of the equipment. When evaluation is required to show compliance; for example, using field strength, power density, SAR measurements or computational modeling etc., the specific authorization requirements will be determined based on the results of the RF exposure evaluation.





9. E and H field Strength

Test Modes		
Mode 1	AC/DC Adapter (12V/3A) + EUT + Phone1 (Battery Status: <1%)	Record
Mode 2	AC/DC Adapter (12V/3A) + EUT + Phone1 (Battery Status: <50%)	Record
Mode 3	AC/DC Adapter (12V/3A) + EUT + Phone1 (Battery Status: 100%)	Record
Mode 4	AC/DC Adapter (12V/3A) + EUT + Watch (Battery Status: <1%)	Record
Mode 5	AC/DC Adapter (12V/3A) + EUT + Watch (Battery Status: <50%)	Record
Mode 6	AC/DC Adapter (12V/3A) + EUT + Watch (Battery Status: 100%)	Record
Mode 7	AC/DC Adapter (12V/3A) + EUT + Phone2 (Battery Status: 100%)	Record
Mode 8	AC/DC Adapter (12V/3A) + EUT + Phone2 (Battery Status: 100%)	Record
Mode 9	AC/DC Adapter (12V/3A) + EUT + Phone2 (Battery Status: 100%)	Record
Mode 10	AC/DC Adapter (12V/3A) + EUT + Phone2 + Phone1 (Battery Status: <1%)	Record
Mode 11	AC/DC Adapter (12V/3A) + EUT + Phone2 + Phone1 (Battery Status: <50%)	Record
Mode 12	AC/DC Adapter (12V/3A) + EUT + Phone2 + Phone1 (Battery Status: 100%)	Record
Mode 13	AC/DC Adapter (12V/3A) + EUT + Phone1 + Watch + Phone2 (Battery Status: <1%)	Record
Mode 14	AC/DC Adapter (12V/3A) + EUT + Phone1 + Watch + Phone2 (Battery Status: <50%)	Record
Mode 15	AC/DC Adapter (12V/3A) + EUT + Phone1 + Watch + Phone2 (Battery Status: 100%)	Record
Note: All test modes were pre-tested, but we only recorded the worst case in this report.		

Field Strength at 15 cm from the edges surrounding the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)				50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D		
Mode 1	110.3~205.0	uT	0.125	0.136	0.136	0.134	--	--
Mode 1	110.3~205.0	A/m	0.100	0.109	0.109	0.107	0.815	1.63
Mode 1	110.3~205.0	V/m	37.588	40.888	40.920	40.349	307.0	614.0
Mode 2	110.3~205.0	uT	0.122	0.134	0.137	0.131	--	--
Mode 2	110.3~205.0	A/m	0.098	0.107	0.109	0.104	0.815	1.63
Mode 2	110.3~205.0	V/m	36.739	40.295	41.068	39.261	307.0	614.0
Mode 3	110.3~205.0	uT	0.123	0.132	0.140	0.127	--	--
Mode 3	110.3~205.0	A/m	0.098	0.105	0.112	0.102	0.815	1.63
Mode 3	110.3~205.0	V/m	36.884	39.578	42.230	38.231	307.0	614.0




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Field Strength at 20cm from the surface coils

Charging Battery Level	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)	50% Limits	Limits
			Test Position E		
Mode 1	110.3~205.0	uT	0.146	--	--
Mode 1	110.3~205.0	A/m	0.117	0.815	1.63
Mode 1	110.3~205.0	V/m	43.954	307.0	614.0
Mode 2	110.3~205.0	uT	0.141	--	--
Mode 2	110.3~205.0	A/m	0.113	0.815	1.63
Mode 2	110.3~205.0	V/m	42.458	307.0	614.0
Mode 3	110.3~205.0	uT	0.138	--	--
Mode 3	110.3~205.0	A/m	0.111	0.815	1.63
Mode 3	110.3~205.0	V/m	41.566	307.0	614.0

Field Strength at 15 cm from the edges surrounding the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)				50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D		
Mode 4	110.3~205.0	uT	0.129	0.140	0.144	0.134	--	--
Mode 4	110.3~205.0	A/m	0.104	0.112	0.115	0.107	0.815	1.63
Mode 4	110.3~205.0	V/m	38.924	42.007	43.233	40.247	307.0	614.0
Mode 5	110.3~205.0	uT	0.127	0.140	0.135	0.132	--	--
Mode 5	110.3~205.0	A/m	0.102	0.112	0.108	0.106	0.815	1.63
Mode 5	110.3~205.0	V/m	38.182	42.007	40.716	39.714	307.0	614.0
Mode 6	110.3~205.0	uT	0.123	0.133	0.135	0.127	--	--
Mode 6	110.3~205.0	A/m	0.098	0.106	0.108	0.102	0.815	1.63
Mode 6	110.3~205.0	V/m	36.857	39.957	40.479	38.206	307.0	614.0




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Field Strength at 20cm from the surface coils

Charging Battery Level	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)	50% Limits	Limits
			Test Position E		
Mode 4	110.3~205.0	uT	0.135	--	--
Mode 4	110.3~205.0	A/m	0.108	0.815	1.63
Mode 4	110.3~205.0	V/m	40.458	307.0	614.0
Mode 5	110.3~205.0	uT	0.133	--	--
Mode 5	110.3~205.0	A/m	0.106	0.815	1.63
Mode 5	110.3~205.0	V/m	39.936	307.0	614.0
Mode 6	110.3~205.0	uT	0.127	--	--
Mode 6	110.3~205.0	A/m	0.101	0.815	1.63
Mode 6	110.3~205.0	V/m	38.044	307.0	614.0

Field Strength at 15 cm from the edges surrounding the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)				50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D		
Mode 7	110.3~205.0	uT	0.129	0.134	0.144	0.128	--	--
Mode 7	110.3~205.0	A/m	0.103	0.107	0.115	0.102	0.815	1.63
Mode 7	110.3~205.0	V/m	38.873	40.258	43.342	38.387	307.0	614.0
Mode 8	110.3~205.0	uT	0.127	0.130	0.137	0.126	--	--
Mode 8	110.3~205.0	A/m	0.101	0.104	0.110	0.101	0.815	1.63
Mode 8	110.3~205.0	V/m	38.063	39.199	41.167	38.022	307.0	614.0
Mode 9	110.3~205.0	uT	0.125	0.130	0.135	0.125	--	--
Mode 9	110.3~205.0	A/m	0.100	0.104	0.108	0.100	0.815	1.63
Mode 9	110.3~205.0	V/m	37.718	39.025	40.570	37.724	307.0	614.0




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Field Strength at 20cm from the surface coils

Charging Battery Level	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)	50% Limits	Limits
			Test Position E		
Mode 7	110.3~205.0	uT	0.140	--	--
Mode 7	110.3~205.0	A/m	0.112	0.815	1.63
Mode 7	110.3~205.0	V/m	41.953	307.0	614.0
Mode 8	110.3~205.0	uT	0.136	--	--
Mode 8	110.3~205.0	A/m	0.109	0.815	1.63
Mode 8	110.3~205.0	V/m	40.858	307.0	614.0
Mode 9	110.3~205.0	uT	0.132	--	--
Mode 9	110.3~205.0	A/m	0.105	0.815	1.63
Mode 9	110.3~205.0	V/m	39.634	307.0	614.0

Note: $V/m = 10^{(((20 \lg(A/m \cdot 10^6) + 51.5) - 120) / 20)}$

Note: $A/m = uT / 1.25$

Field Strength at 15 cm from the edges surrounding the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)				50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D		
Mode 10	110.3~205.0	uT	0.130	0.140	0.144	0.131	--	--
Mode 10	110.3~205.0	A/m	0.104	0.112	0.115	0.105	0.815	1.63
Mode 10	110.3~205.0	V/m	39.049	41.969	43.393	39.535	307.0	614.0
Mode 11	110.3~205.0	uT	0.130	0.139	0.144	0.128	--	--
Mode 11	110.3~205.0	A/m	0.104	0.111	0.115	0.102	0.815	1.63
Mode 11	110.3~205.0	V/m	38.971	41.844	43.276	38.458	307.0	614.0
Mode 12	110.3~205.0	uT	0.119	0.134	0.141	0.125	--	--
Mode 12	110.3~205.0	A/m	0.096	0.108	0.113	0.100	0.815	1.63
Mode 12	110.3~205.0	V/m	35.897	40.413	42.440	37.502	307.0	614.0




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Field Strength at 20cm from the surface coils

Charging Battery Level	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)	50% Limits	Limits
			Test Position E		
Mode 10	110.3~205.0	uT	0.124	--	--
Mode 10	110.3~205.0	A/m	0.099	0.815	1.63
Mode 10	110.3~205.0	V/m	37.258	307.0	614.0
Mode 11	110.3~205.0	uT	0.123	--	--
Mode 11	110.3~205.0	A/m	0.098	0.815	1.63
Mode 11	110.3~205.0	V/m	36.884	307.0	614.0
Mode 12	110.3~205.0	uT	0.120	--	--
Mode 12	110.3~205.0	A/m	0.096	0.815	1.63
Mode 12	110.3~205.0	V/m	36.012	307.0	614.0

Note: $V/m = 10^{(((20 \lg(A/m \cdot 10^6) + 51.5) - 120) / 20)}$

Note: $A/m = uT / 1.25$

Field Strength at 15 cm from the edges surrounding the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)				50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D		
Mode 13	110.3~205.0	uT	0.126	0.139	0.140	0.132	--	--
Mode 13	110.3~205.0	A/m	0.100	0.111	0.112	0.106	0.815	1.63
Mode 13	110.3~205.0	V/m	37.748	41.717	42.203	39.733	307.0	614.0
Mode 14	110.3~205.0	uT	0.125	0.135	0.140	0.132	--	--
Mode 14	110.3~205.0	A/m	0.100	0.108	0.112	0.106	0.815	1.63
Mode 14	110.3~205.0	V/m	37.555	40.712	41.978	39.710	307.0	614.0
Mode 15	110.3~205.0	uT	0.125	0.129	0.136	0.130	--	--
Mode 15	110.3~205.0	A/m	0.100	0.103	0.108	0.104	0.815	1.63
Mode 15	110.3~205.0	V/m	37.448	38.842	40.774	39.099	307.0	614.0




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Field Strength at 20cm from the surface coils

Charging Battery Level	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)	50% Limits	Limits
			Test Position E1		
Mode 13	110.3~205.0	uT	0.142	--	--
Mode 13	110.3~205.0	A/m	0.114	0.815	1.63
Mode 13	110.3~205.0	V/m	42.831	307.0	614.0
Mode 14	110.3~205.0	uT	0.139	--	--
Mode 14	110.3~205.0	A/m	0.112	0.815	1.63
Mode 14	110.3~205.0	V/m	41.928	307.0	614.0
Mode 15	110.3~205.0	uT	0.147	--	--
Mode 15	110.3~205.0	A/m	0.117	0.815	1.63
Mode 15	110.3~205.0	V/m	44.123	307.0	614.0

Charging Battery Level	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)	50% Limits	Limits
			Test Position E2		
Mode 13	110.3~205.0	uT	0.145	--	--
Mode 13	110.3~205.0	A/m	0.116	0.815	1.63
Mode 13	110.3~205.0	V/m	43.449	307.0	614.0
Mode 14	110.3~205.0	uT	0.147	--	--
Mode 14	110.3~205.0	A/m	0.117	0.815	1.63
Mode 14	110.3~205.0	V/m	44.124	307.0	614.0
Mode 15	110.3~205.0	uT	0.139	--	--
Mode 15	110.3~205.0	A/m	0.111	0.815	1.63
Mode 15	110.3~205.0	V/m	41.786	307.0	614.0




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Charging Battery Level	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)	50% Limits	Limits
			Test Position E3		
Mode 13	110.3~205.0	uT	0.149	--	--
Mode 13	110.3~205.0	A/m	0.119	0.815	1.63
Mode 13	110.3~205.0	V/m	44.688	307.0	614.0
Mode 14	110.3~205.0	uT	0.143	--	--
Mode 14	110.3~205.0	A/m	0.115	0.815	1.63
Mode 14	110.3~205.0	V/m	43.136	307.0	614.0
Mode 15	110.3~205.0	uT	0.138	--	--
Mode 15	110.3~205.0	A/m	0.111	0.815	1.63
Mode 15	110.3~205.0	V/m	41.568	307.0	614.0

20 cm above the top surface from all simultaneous transmitting coils

Charging Battery Level	Frequency Range (kHz)	Field Strength	Measured E - Field Strength Values (V/m) Measured H - Field Strength Values (A/m)	50% Limits	Limits
			E1+E2+E3		
Mode 13	110.3~205.0	uT	0.436	--	--
Mode 13	110.3~205.0	A/m	0.349	0.815	1.63
Mode 13	110.3~205.0	V/m	130.968	307.0	614.0
Mode 14	110.3~205.0	uT	0.429	--	--
Mode 14	110.3~205.0	A/m	0.344	0.815	1.63
Mode 14	110.3~205.0	V/m	129.188	307.0	614.0
Mode 15	110.3~205.0	uT	0.424	--	--
Mode 15	110.3~205.0	A/m	0.339	0.815	1.63
Mode 15	110.3~205.0	V/m	127.477	307.0	614.0

Note: $V/m = 10^{((20 \lg(A/m \cdot 10^6) + 51.5) - 120)/20}$

Note: $A/m = uT / 1.25$




Shenzhen LCS Compliance Testing Laboratory Ltd.
 Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
 Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
 Scan code to check authenticity




10. Test Setup Photos

Test Position A - Exposure photo from side edge surface-Rear



(Mode 13-Mode 15)

Test Position B - Exposure photo from side edge surface-Left



Shenzhen LCS Compliance Testing Laboratory Ltd.


Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com


Scan code to check authenticity



Test Position C - Exposure photo from side edge surface-Front




Test Position D - Exposure photo from side edge surface-Right






Test Position E - Exposure photo from top surface (20cm)



E1



E2




Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



E3





11. Conclusion

A minimum safety distance of at 15 cm surrounding the device and 20 cm above the top surface of the device is required when the device is charging a smart phone. The detected emissions with a distance of 15 cm surrounding the device and 20 cm above the top surface of the device are below the limitations according to FCC KDB 680106 D01 Section 3. RF Exposure Requirement Clause 3.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	May 15, 2023	Initial Issue	--

.....END OF REPORT.....

