## FCC §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Report No.: RSHA240322002-00A

## **Applicable Standard**

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure										
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)						
0.3-1.34	614	1.63	*(100)	30						
1.34-30	824/f	2.19/f	*(180/f²)	30						
30-300	27.5	0.073	0.2	30						
300-1500	/	/	f/1500	30						
1500-100,000	/	/	1.0	30						

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

## **Calculated Formulary**

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$ 

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \leq 1$$

FCC Part 15.407 Page 17 of 84

Mode	Frequency Range (MHz)	Antenna Gain		<b>★Tune-up Output</b> Power		Evaluation Distance	Power Density	MPE Limit	MPE
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )	ratio
2.4G SRD	2411-2466	3.34	2.16	25	316.23	20	0.1357	1.0	0.1357
5G SRD	5180-5240	3.27	2.12	17.7	58.88	20	0.0249	1.0	0.0249
	5735-5805	2.90	1.95	26.5	446.68	20	0.1733	1.0	0.1733
5G Wi-Fi	5150-5250	3.04	2.01	13.5	22.39	20	0.0090	1.0	0.0090
	5725-5850	4.64	2.91	10.5	11.22	20	0.0065	1.0	0.0065

Report No.: RSHA240322002-00A

- For the above tune up power were declared by the manufacturer.
   SRD and Wi-Fi can transmit simultaneously, but 2.4G SRD and 5G SRD cannot transmit simultaneously.

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}}$$

 $=S_{5G\;Wi\text{-}Fi}/S_{limit\text{-}}\,_{5G\;Wi\text{-}Fi}+\,S_{5G\;SRD}/S_{limit\text{-}}\,_{5G\;SRD}$ 

=0.0090+0.1733

=0.1823

< 1.0

**Result:** The device meet FCC MPE at 20 cm distance.

FCC Part 15.407 Page 18 of 84