



FCC TEST REPORT

REPORT NO.: RF910527R02

MODEL NO.: WM302

RECEIVED: May 22, 2002

TESTED: May 23 ~ June 6 , 2002

APPLICANT: BROMAX COMMUNICATIONS, INC.

ADDRESS: No.20, Kuang Fu Road, Hsin Chu Industrial Park,
Hu Kou, Hsin Chu 303, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 73 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Lab Code: 200102-0



Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2	TEST INSTRUMENTS	9
4.1.3	TEST PROCEDURES	10
4.1.4	TEST SETUP	10
4.1.5	EUT OPERATING CONDITIONS	11
4.1.6	TEST RESULTS (A)	12
4.1.7	TEST RESULTS (B)	18
4.1.8	TEST RESULTS (C)	24
4.2	RADIATED EMISSION MEASUREMENT	30
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	30
4.2.2	TEST INSTRUMENTS	31
4.2.3	TEST PROCEDURES	32
4.2.4	TEST SETUP	33
4.2.5	EUT OPERATING CONDITIONS	33
4.2.6	TEST RESULTS (A)	34
4.2.7	TEST RESULTS (B)	39
4.2.8	TEST RESULTS (C)	44
4.3	6dB BANDWIDTH MEASUREMENT	49
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	49
4.3.2	TEST INSTRUMENTS	49
4.3.3	TEST PROCEDURE	50
4.3.4	TEST SETUP	50
4.3.5	EUT OPERATING CONDITIONS	50
4.3.6	TEST RESULTS	51
4.4	MAXIMUM PEAK OUTPUT POWER	55
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	55



4.4.2	TEST INSTRUMENTS	55
4.4.3	TEST PROCEDURES	56
4.4.4	TEST SETUP	56
4.4.5	EUT OPERATING CONDITIONS	56
4.4.6	TEST RESULTS	57
4.5	POWER SPECTRAL DENSITY MEASUREMENT	58
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	58
4.5.2	TEST INSTRUMENTS	58
4.5.3	TEST PROCEDURE	59
4.5.4	TEST SETUP	59
4.5.5	EUT OPERATING CONDITIONS	59
4.5.6	TEST RESULTS	60
4.6	BAND EDGES MEASUREMENT	64
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	64
4.6.2	TEST INSTRUMENTS	64
4.6.3	TEST PROCEDURE	64
4.6.4	EUT OPERATING CONDITION	65
4.6.5	TEST RESULTS	65
4.7	ANTENNA REQUIREMENT	68
4.7.1	STANDARD APPLICABLE	68
4.7.2	ANTENNA CONNECTED CONSTRUCTION	68
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	69
6	INFORMATION ON THE TESTING LABORATORIES	73



1 CERTIFICATION

PRODUCT : 11Mbps Wireless LAN Module
MODEL NO. : WM302
BRAND : BroMax
APPLICANT : BROMAX COMMUNICATIONS, INC.
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from May 23 to June 6, 2002, The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

CHECKED BY : Rennie Wang , DATE : June 11, 2002
Rennie Wang

APPROVED BY : Dr. Alan Lane , DATE : June 11, 2002
Dr. Alan Lane, Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission Limit: 48dBuV	PASS	Meet the requirement of limit Minimum passing margin is -3.79dBuV at 22.57MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -6.8dBuV at 4924.0MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	11Mbps Wireless LAN Module
MODEL NO.	WM302
POWER SUPPLY	5.0VDC from host equipment
MODULATION TYPE	BPSK, QPSK, CCK
RADIO TECHNOLOGY	DSSS
TRANSFER RATE	1/2/5.5/11Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	18.49dBm
ANTENNA TYPE	Dipole Antenna
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

1. There are three sets of antenna and two outer appearances provided to this EUT.
2. The details about three antennas:

	ANTENNA TYPE	ANTENNA GAIN
1	Dipole antenna	4dBi
2	Dipole antenna	2.5dBi
3	Dipole antenna	1dBi

3. For a more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided in this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. Test result (A) is for antenna 1, test result (B) is for antenna 2 and test result (C) is for antenna 3.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an 11Mbps Wireless LAN Module. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR 47 Part 15, Subpart C. (15.247)

ANSI C63.4 : 1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP01L	TW-09C748-12800-190-B220	FCC DoC APPROVED
2	MODEM	ACEEX	1414	980020503	IFAXDM1414
3	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DoC APPROVED

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.
3	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core

NOTE: All power cords of the above support units are non shielded (1.8m).

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.45 – 30	48	-

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS


DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	847793/022	Mar. 12, 2003
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	828075/003	July 19, 2002
ROHDE & SCHWARZ 200-A Four-line V-Network	ENV4200	830326/018	Oct. 25, 2002
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Dec. 2, 2002
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Dec. 2, 2002
EMCO-L.I.S.N. (for peripheral)	3825/2	90031627	July 19, 2002
Software	Cond-V2L	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C05.01	July 19, 2002
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-305	Feb. 20, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-306	Feb. 20, 2003
Shielded Room	Site 5	ADT-C05	NA
VCCI Site Registration No.	Site 5	C-1093	NA

- NOTE: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. “*”: These equipment are used for conducted telecom port test only (if tested).

4.1.3 TEST PROCEDURES

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 450 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.4 TEST SETUP



- Note:**
- Support units were connected to second LISN.
 - Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.5 EUT OPERATING CONDITIONS

- a. Connected the EUT to a computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer and the printer prints them on paper.


4.1.6 TEST RESULTS (A)

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.520	0.12	28.68	-	28.80	-	48.00	-	-19.20	-
2	0.805	0.17	23.47	-	23.64	-	48.00	-	-24.36	-
3	2.762	0.28	20.81	-	21.09	-	48.00	-	-26.91	-
4	5.258	0.44	26.37	-	26.81	-	48.00	-	-21.19	-
5	13.445	0.67	27.14	-	27.81	-	48.00	-	-20.19	-
6	19.664	0.98	30.81	-	31.79	-	48.00	-	-16.21	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.520	0.12	27.68	-	27.80	-	48.00	-	-20.20	-
2	0.688	0.15	26.12	-	26.27	-	48.00	-	-21.73	-
3	2.074	0.20	27.80	-	28.00	-	48.00	-	-20.00	-
4	3.984	0.30	23.89	-	24.19	-	48.00	-	-23.81	-
5	13.020	0.46	27.38	-	27.84	-	48.00	-	-20.16	-
6	20.363	0.79	28.97	-	29.76	-	48.00	-	-18.24	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.579	0.13	29.38	-	29.51	-	48.00	-	-18.49	-
2	1.039	0.20	20.81	-	21.01	-	48.00	-	-26.99	-
3	2.598	0.26	28.14	-	28.40	-	48.00	-	-19.60	-
4	5.199	0.44	28.35	-	28.79	-	48.00	-	-19.21	-
5	13.633	0.67	27.72	-	28.39	-	48.00	-	-19.61	-
6	19.660	0.98	30.61	-	31.59	-	48.00	-	-16.41	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (Uv)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.548	0.12	22.62	-	22.74	-	48.00	-	-25.26	-
2	0.977	0.20	24.53	-	24.73	-	48.00	-	-23.27	-
3	2.707	0.24	29.44	-	29.68	-	48.00	-	-18.32	-
4	5.066	0.32	25.71	-	26.03	-	48.00	-	-21.97	-
5	13.141	0.46	28.17	-	28.63	-	48.00	-	-19.37	-
6	19.016	0.74	30.79	-	31.53	-	48.00	-	-16.47	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.575	0.13	28.34	-	28.47	-	48.00	-	-19.53	-
2	0.927	0.19	20.62	-	20.81	-	48.00	-	-27.19	-
3	2.652	0.27	27.03	-	27.30	-	48.00	-	-20.70	-
4	5.254	0.44	28.15	-	28.59	-	48.00	-	-19.41	-
5	12.645	0.65	28.34	-	28.99	-	48.00	-	-19.01	-
6	22.570	1.10	42.15	-	43.25	-	48.00	-	-4.75	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.583	0.13	18.75	-	18.88	-	48.00	-	-29.12	-
2	0.684	0.15	16.81	-	16.96	-	48.00	-	-31.04	-
3	2.133	0.21	26.78	-	26.99	-	48.00	-	-21.01	-
4	3.691	0.28	32.53	-	32.81	-	48.00	-	-15.19	-
5	13.141	0.46	27.13	-	27.59	-	48.00	-	-20.41	-
6	19.422	0.77	31.14	-	31.91	-	48.00	-	-16.09	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




4.1.7 TEST RESULTS (B)

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.516	0.12	26.86	-	26.98	-	48.00	-	-21.02	-
2	0.688	0.15	24.06	-	24.21	-	48.00	-	-23.79	-
3	0.977	0.20	20.60	-	20.80	-	48.00	-	-27.20	-
4	3.230	0.32	29.52	-	29.84	-	48.00	-	-18.16	-
5	13.270	0.67	28.47	-	29.14	-	48.00	-	-18.86	-
6	19.633	0.98	30.88	-	31.86	-	48.00	-	-16.14	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.458	0.11	29.22	-	29.33	-	48.00	-	-18.67	-
2	0.575	0.13	29.74	-	29.87	-	48.00	-	-18.13	-
3	0.977	0.20	25.43	-	25.63	-	48.00	-	-22.37	-
4	3.168	0.26	30.66	-	30.92	-	48.00	-	-17.08	-
5	3.918	0.30	33.77	-	34.07	-	48.00	-	-13.93	-
6	12.906	0.46	32.42	-	32.88	-	48.00	-	-15.12	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.520	0.12	28.58	-	28.70	-	48.00	-	-19.30	-
2	0.809	0.17	25.09	-	25.26	-	48.00	-	-22.74	-
3	1.789	0.20	26.70	-	26.90	-	48.00	-	-21.10	-
4	3.750	0.38	30.75	-	31.13	-	48.00	-	-16.87	-
5	12.523	0.65	27.78	-	28.43	-	48.00	-	-19.57	-
6	18.984	0.94	31.64	-	32.58	-	48.00	-	-15.42	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (Uv)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.520	0.12	27.24	-	27.36	-	48.00	-	-20.64	-
2	0.805	0.17	26.88	-	27.05	-	48.00	-	-20.95	-
3	2.938	0.25	30.47	-	30.72	-	48.00	-	-17.28	-
4	3.688	0.28	32.77	-	33.05	-	48.00	-	-14.95	-
5	12.844	0.46	28.11	-	28.57	-	48.00	-	-19.43	-
6	19.242	0.75	30.65	-	31.40	-	48.00	-	-16.60	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.524	0.12	22.32	-	22.44	-	48.00	-	-25.56	-
2	0.688	0.15	23.92	-	24.07	-	48.00	-	-23.93	-
3	2.422	0.24	26.24	-	26.48	-	48.00	-	-21.52	-
4	3.633	0.36	29.16	-	29.52	-	48.00	-	-18.48	-
5	12.871	0.66	29.01	-	29.67	-	48.00	-	-18.33	-
6	19.316	0.96	31.39	-	32.35	-	48.00	-	-15.65	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.513	0.12	19.21	-	19.33	-	48.00	-	-28.67	-
2	0.688	0.15	26.48	-	26.63	-	48.00	-	-21.37	-
3	1.383	0.20	23.98	-	24.18	-	48.00	-	-23.82	-
4	2.477	0.22	29.25	-	29.47	-	48.00	-	-18.53	-
5	3.512	0.28	32.65	-	32.93	-	48.00	-	-15.07	-
6	13.016	0.46	27.64	-	28.10	-	48.00	-	-19.90	-
7	18.641	0.72	29.28	-	30.00	-	48.00	-	-18.00	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




4.1.8 TEST RESULTS (C)

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.462	0.11	31.60	-	31.71	-	48.00	-	-16.29	-
2	0.579	0.13	28.36	-	28.49	-	48.00	-	-19.51	-
3	2.652	0.27	29.57	-	29.84	-	48.00	-	-18.16	-
4	3.801	0.38	27.48	-	27.86	-	48.00	-	-20.14	-
5	13.551	0.67	28.92	-	29.59	-	48.00	-	-18.41	-
6	19.191	0.95	31.60	-	32.55	-	48.00	-	-15.45	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.571	0.13	29.06	-	29.19	-	48.00	-	-18.81	-
2	0.684	0.15	23.64	-	23.79	-	48.00	-	-24.21	-
3	3.328	0.27	31.74	-	32.01	-	48.00	-	-15.99	-
4	3.957	0.30	29.32	-	29.62	-	48.00	-	-18.38	-
5	13.027	0.46	29.68	-	30.14	-	48.00	-	-17.86	-
6	20.082	0.80	33.22	-	34.02	-	48.00	-	-13.98	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.462	0.11	31.80	-	31.91	-	48.00	-	-16.09	-
2	0.809	0.17	24.75	-	24.92	-	48.00	-	-23.08	-
3	0.981	0.20	23.41	-	23.61	-	48.00	-	-24.39	-
4	2.824	0.28	28.12	-	28.40	-	48.00	-	-19.60	-
5	5.133	0.44	28.04	-	28.48	-	48.00	-	-19.52	-
6	12.977	0.66	28.74	-	29.40	-	48.00	-	-18.60	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (Uv)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.571	0.13	26.03	-	26.16	-	48.00	-	-21.84	-
2	0.864	0.18	27.10	-	27.28	-	48.00	-	-20.72	-
3	4.023	0.30	32.60	-	32.90	-	48.00	-	-15.10	-
4	5.172	0.32	28.10	-	28.42	-	48.00	-	-19.58	-
5	13.277	0.47	28.66	-	29.13	-	48.00	-	-18.87	-
6	22.570	0.75	43.46	-	44.21	-	48.00	-	-3.79	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.520	0.12	28.61	-	28.73	-	48.00	-	-19.27	-
2	0.809	0.17	24.99	-	25.16	-	48.00	-	-22.84	-
3	2.766	0.28	26.30	-	26.58	-	48.00	-	-21.42	-
4	13.203	0.66	26.39	-	27.05	-	48.00	-	-20.95	-
5	18.809	0.93	33.05	-	33.98	-	48.00	-	-14.02	-
6	27.410	1.25	27.92	-	29.17	-	48.00	-	-18.83	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.




EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.485	0.11	8.20	-	8.31	-	48.00	-	-39.69	-
2	1.098	0.20	23.47	-	23.67	-	48.00	-	-24.33	-
3	2.070	0.20	25.62	-	25.82	-	48.00	-	-22.18	-
4	3.742	0.29	35.42	-	35.71	-	48.00	-	-12.29	-
5	13.063	0.46	28.70	-	29.16	-	48.00	-	-18.84	-
6	22.570	0.75	42.83	-	43.58	-	48.00	-	-4.42	-

NOTE:

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field Strength of Fundamental	
	uV/m	dBuV/m
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 13, 2003
* HP Preamplifier	8447D	2944A08485	Oct. 30, 2002
* HP Preamplifier	8449B	3008A01201	Dec. 06, 2002
* HP Preamplifier	8449B	3008A01292	Aug. 21, 2002
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 27, 2003
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2002
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 2, 2002
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	July 6, 2002
* EMCO Horn Antenna	3115	9312-4192	April 9, 2003
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Aug. 2, 2002
* TIMES RF cable	LMR-600	CABLE-ST5-01	Aug. 2, 2002
Open Field Test Site	Site 5	ADT-R05	July 28, 2002
VCCI Site Registration No.	Site 5	R-1039	NA

- NOTE:** 1. The measurement uncertainty is less than +/- 3.0dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
3. "*" = These equipment are used for the final measurement.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.




4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.5 EUT OPERATING CONDITIONS

Same as 4.1.5.

4.2.6 TEST RESULTS (A)

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	132.00	32.2 QP	43.50	-11.30	1.43H	357	48.51	11.16	1.24	28.71	16.31
2	176.00	27.0 QP	43.50	-16.50	1.46H	281	45.26	9.08	1.37	28.71	18.26
3	220.00	25.1 QP	46.00	-20.90	1.21H	278	42.17	10.12	1.53	28.71	17.07
4	246.00	12.3 QP	46.00	-33.70	1.62H	2	27.61	11.70	1.70	28.71	15.31
5	264.00	20.5 QP	46.00	-25.50	1.62H	254	34.59	12.89	1.73	28.71	14.09
6	308.00	24.5 QP	46.00	-21.50	1.62H	296	37.91	13.38	1.92	28.71	13.41
7	440.00	20.5 QP	46.00	-25.50	1.77H	204	30.59	16.32	2.31	28.71	10.09
8	528.00	22.8 QP	46.00	-23.20	1.81H	20	31.27	17.62	2.62	28.71	8.47
9	748.00	18.5 QP	46.00	-27.50	1.54H	358	23.73	20.14	3.34	28.71	5.23

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	132.00	31.0 QP	43.50	-12.50	1.03V	109	47.31	11.16	1.24	28.71	16.31
2	176.00	26.8 QP	43.50	-16.70	1.00V	288	45.06	9.08	1.37	28.71	18.26
3	220.00	21.0 QP	46.00	-25.00	1.16V	3	38.07	10.12	1.53	28.71	17.07
4	308.00	22.5 QP	46.00	-23.50	1.31V	221	35.91	13.38	1.92	28.71	13.41
5	440.00	20.2 QP	46.00	-25.80	1.32V	71	30.29	16.32	2.31	28.71	10.09
6	528.00	23.3 QP	46.00	-22.70	1.22V	106	31.77	17.62	2.62	28.71	8.47
7	572.00	21.4 QP	46.00	-24.60	1.22V	262	29.07	18.25	2.79	28.71	7.67
8	924.00	17.0 QP	46.00	-29.00	1.65V	3	20.99	21.00	3.71	28.71	3.99

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.



EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2412.00	101.8 PK			1.47H	188	69.60	27.11	5.10	0.00	-32.21
2	*2412.00	96.0 AV			1.47H	188	63.80	27.11	5.10	0.00	-32.21
3	4824.00	42.5 AV	54.00	-11.50	1.34H	261	38.50	31.43	7.23	34.63	-4.02
4	4824.00	51.8 PK	74.00	-22.20	1.34H	261	47.80	31.43	7.23	34.63	-4.02

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2412.00	108.6 PK			1.28V	69	76.40	27.11	5.10	0.00	-32.21
2	*2412.00	101.1 AV			1.28V	69	68.90	27.11	5.10	0.00	-32.21
3	4824.00	43.8 AV	54.00	-10.20	1.49V	250	39.80	31.43	7.23	34.63	-4.02
4	4824.00	51.6 PK	74.00	-22.40	1.49V	301	47.60	31.43	7.23	34.63	-4.02

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2437.00	101.2 PK			1.50H	141	68.80	27.33	5.08	0.00	-32.40
2	*2437.00	95.9 AV			1.50H	203	63.50	27.33	5.08	0.00	-32.40
3	4874.00	42.6 AV	54.00	-11.40	1.23H	245	38.50	31.47	7.21	34.63	-4.05
4	4874.00	50.2 PK	74.00	-23.80	1.23H	245	46.10	31.47	7.21	34.63	-4.05

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2437.00	108.2 PK			1.34V	130	75.80	27.33	5.08	0.00	-32.40
2	*2437.00	101.3 AV			1.34V	71	68.90	27.33	5.08	0.00	-32.40
3	4874.00	49.8 PK	74.00	-24.20	1.23V	3	45.70	31.47	7.21	34.63	-4.05
4	4874.00	41.9 AV	54.00	-12.10	1.23V	3	37.80	31.47	7.21	34.63	-4.05

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss.
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2462.00	100.2 PK			1.45H	3	67.80	27.33	5.08	0.00	-32.40
2	*2462.00	94.8 AV			1.45H	3	62.40	27.33	5.08	0.00	-32.40
3	4924.00	52.1 PK	74.00	-21.90	1.36H	212	48.02	31.51	7.21	34.62	-4.10
4	4924.00	43.0 AV	54.00	-11.00	1.36H	212	38.88	31.51	7.21	34.62	-4.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2462.00	108.4 PK			1.55V	6	76.00	27.33	5.08	0.00	-32.40
2	*2462.00	102.5 AV			1.55V	6	70.10	27.33	5.08	0.00	-32.40
3	4924.00	40.4 AV	54.00	-13.60	1.23V	3	36.30	31.51	7.21	34.62	-4.10
4	4924.00	50.9 PK	74.00	-23.10	1.23V	3	46.80	31.51	7.21	34.62	-4.10

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.

4.2.7 TEST RESULTS (B)

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	132.00	30.1 QP	43.50	-13.40	1.71H	136	46.41	11.16	1.24	28.71	16.31
2	176.00	25.0 QP	43.50	-18.50	1.63H	3	43.26	9.08	1.37	28.71	18.26
3	220.00	29.5 QP	46.00	-16.50	1.55H	305	46.57	10.12	1.53	28.71	17.07
4	264.00	25.1 QP	46.00	-20.90	1.00H	163	39.19	12.89	1.73	28.71	14.09
5	308.00	26.5 QP	46.00	-19.50	1.37H	247	39.91	13.38	1.92	28.71	13.41
6	352.00	16.8 QP	46.00	-29.20	1.37H	269	29.08	14.31	2.12	28.71	12.28
7	396.00	19.0 QP	46.00	-27.00	1.04H	169	29.59	15.96	2.17	28.71	10.59
8	440.00	20.0 QP	46.00	-26.00	1.26H	277	30.09	16.32	2.31	28.71	10.09
9	528.00	20.1 QP	46.00	-25.90	1.07H	230	28.57	17.62	2.62	28.71	8.48
10	748.00	21.6 QP	46.00	-24.40	1.15H	92	26.83	20.14	3.34	28.71	5.24

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.



EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY:	Bunny Yao

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	132.00	27.6 QP	43.50	-15.90	1.31H	60	43.91	11.16	1.24	28.71	16.31
2	220.00	21.7 QP	46.00	-24.30	1.70H	28	38.77	10.12	1.53	28.71	17.07
3	264.00	22.3 QP	46.00	-23.70	1.65H	163	36.39	12.89	1.73	28.71	14.09
4	308.00	21.1 QP	46.00	-24.90	1.92H	298	34.51	13.38	1.92	28.71	13.41
5	396.00	17.5 QP	46.00	-28.50	1.64H	72	28.09	15.96	2.17	28.71	10.59
6	440.00	19.9 QP	46.00	-26.10	1.68H	24	29.99	16.32	2.31	28.71	10.09
7	528.00	21.0 QP	46.00	-25.00	1.45H	137	29.47	17.62	2.62	28.71	8.47
8	572.00	18.6 QP	46.00	-27.40	1.51H	297	26.27	18.25	2.79	28.71	7.67
9	748.00	17.6 QP	46.00	-28.40	1.21H	2	22.83	20.14	3.34	28.71	5.23

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.



EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2412.00	107.0 PK			1.06H	179	74.80	27.11	5.10	0.00	-32.21
2	*2412.00	100.7 AV			1.06H	246	68.50	27.11	5.10	0.00	-32.21
3	4824.00	40.9 AV	54.00	-13.10	1.87H	0	36.90	31.43	7.23	34.63	-4.02
4	4824.00	50.3 PK	74.00	-23.70	1.87H	0	46.30	31.43	7.23	34.63	-4.02

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2412.00	104.5 PK			1.84V	189	72.30	27.11	5.10	0.00	-32.21
2	*2412.00	99.6 AV			1.84V	3	67.40	27.11	5.10	0.00	-32.21
3	4824.00	43.1 AV	54.00	-10.90	1.15V	3	39.10	31.43	7.23	34.63	-4.02
4	4824.00	50.8 PK	74.00	-23.20	1.15V	3	46.80	31.43	7.23	34.63	-4.02

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2437.00	101.3 AV			1.23H	278	68.90	27.33	5.08	0.00	-32.40
2	*2437.00	107.1 PK			1.23H	186	74.70	27.33	5.08	0.00	-32.40
3	4874.00	41.2 AV	54.00	-12.80	1.00H	225	37.10	31.47	7.21	34.63	-4.05
4	4874.00	49.8 PK	74.00	-24.20	1.00H	279	45.70	31.47	7.21	34.63	-4.05

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2437.00	104.6 PK			1.43V	194	72.20	27.33	5.08	0.00	-32.40
2	*2437.00	99.5 AV			1.43V	282	67.10	27.33	5.08	0.00	-32.40
3	4874.00	43.4 AV	54.00	-10.60	1.27V	0	39.30	31.47	7.21	34.63	-4.05
4	4874.00	50.4 PK	74.00	-23.60	1.27V	0	46.30	31.47	7.21	34.63	-4.05

NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss.
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " * " : Fundamental frequency
5. The other emission levels were very low against the limit.



EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2462.00	105.8 PK			1.42H	164	73.40	27.33	5.08	0.00	-32.40
2	*2462.00	100.2 AV			1.42H	242	67.80	27.33	5.08	0.00	-32.40
3	4924.00	42.2 AV	54.00	-11.80	1.18H	7	38.10	31.51	7.21	34.62	-4.10
4	4924.00	50.4 PK	74.00	-23.60	1.18H	1	46.30	31.51	7.21	34.62	-4.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2462.00	104.9 PK			1.18V	110	72.50	27.33	5.08	0.00	-32.40
2	*2462.00	101.0 AV			1.18V	263	68.60	27.33	5.08	0.00	-32.40
3	4924.00	44.8 AV	54.00	-9.20	1.18V	65	40.70	31.51	7.21	34.62	-4.10
4	4924.00	51.9 PK	74.00	-22.10	1.18V	20	47.80	31.51	7.21	34.62	-4.10

NOTE:

- 1 Emission level = Raw value - Correction Factor
- 2 Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
- 3 Margin value = Emission level - Limit value
- 4 " * " : Fundamental frequency
- 5 The other emission levels were very low against the limit.

4.2.8 TEST RESULTS (C)

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	132.00	27.4 QP	43.50	-16.10	1.89H	128	43.71	11.16	1.24	28.71	16.31
2	176.00	17.9 QP	43.50	-25.60	1.30H	221	36.16	9.08	1.37	28.71	18.26
3	220.00	27.4 QP	46.00	-18.60	1.18H	280	44.47	10.12	1.53	28.71	17.07
4	264.00	26.0 QP	46.00	-20.00	1.21H	177	40.09	12.89	1.73	28.71	14.09
5	308.00	25.1 QP	46.00	-20.90	1.35H	184	38.51	13.38	1.92	28.71	13.41
6	440.00	21.5 QP	46.00	-24.50	1.53H	3	31.59	16.32	2.31	28.71	10.09
7	528.00	21.9 QP	46.00	-24.10	1.60H	250	30.37	17.62	2.62	28.71	8.48
8	572.00	22.3 QP	46.00	-23.70	1.59H	109	29.97	18.25	2.79	28.71	7.68
9	748.00	17.6 QP	46.00	-28.40	1.78H	18	22.83	20.14	3.34	28.71	5.24

NOTE:

- 1 Emission level = Raw value - Correction Factor
- 2 Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
- 3 Margin value = Emission level - Limit value
- 4 The other emission levels were very low against the limit.



EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY:	Bunny Yao

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	132.00	30.3 QP	43.50	-13.20	1.35V	116	46.61	11.16	1.24	28.71	16.31
2	220.00	22.7 QP	46.00	-23.30	1.77V	122	39.77	10.12	1.53	28.71	17.07
3	264.00	28.2 QP	46.00	-17.80	1.50V	101	42.29	12.89	1.73	28.71	14.09
4	308.00	17.4 QP	46.00	-28.60	1.82V	44	30.81	13.38	1.92	28.71	13.42
5	440.00	21.3 QP	46.00	-24.70	1.13V	196	31.39	16.32	2.31	28.71	10.09
6	528.00	22.8 QP	46.00	-23.20	1.92V	78	31.27	17.62	2.62	28.71	8.47
7	572.00	23.5 QP	46.00	-22.50	1.79V	36	31.17	18.25	2.79	28.71	7.67
8	748.00	16.9 QP	46.00	-29.10	1.69V	37	22.13	20.14	3.34	28.71	5.23

NOTE:

- 1 Emission level = Raw value - Correction Factor
- 2 Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
- 3 Margin value = Emission level - Limit value
- 4 The other emission levels were very low against the limit.

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2412.00	99.8 PK			1.28H	110	67.60	27.11	5.10	0.00	-32.21
2	*2412.00	95.0 AV			1.28H	179	62.80	27.11	5.10	0.00	-32.21
3	4824.00	41.0 AV	54.00	-13.00	1.90H	60	37.00	31.43	7.23	34.63	-4.02
4	4824.00	51.4 PK	74.00	-22.60	1.90H	355	47.40	31.43	7.23	34.63	-4.02

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2412.00	104.1 PK			1.03V	149	71.90	27.11	5.10	0.00	-32.21
2	*2412.00	96.0 AV			1.03V	289	63.80	27.11	5.10	0.00	-32.21
3	4824.00	52.6 PK	74.00	-21.40	1.29V	3	48.60	31.43	7.23	34.63	-4.02
4	4824.00	47.0 AV	54.00	-7.00	1.29V	3	43.00	31.43	7.23	34.63	-4.02

NOTE:

- 1 Emission level = Raw value - Correction Factor
- 2 Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
- 3 Margin value = Emission level - Limit value
- 4 “ * ” : Fundamental frequency
- 5 The other emission levels were very low against the limit.



EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2437.00	101.2 PK			1.30H	3	68.80	27.33	5.08	0.00	-32.40
2	*2437.00	94.9 AV			1.30H	3	62.50	27.33	5.08	0.00	-32.40
3	4874.00	41.1 AV	54.00	-12.90	1.74H	356	37.00	31.47	7.21	34.63	-4.05
4	4874.00	52.5 PK	74.00	-21.50	1.74H	356	48.40	31.47	7.21	34.63	-4.05

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2437.00	105.9 PK			1.21V	12	73.50	27.33	5.08	0.00	-32.40
2	*2437.00	98.2 AV			1.21V	26	65.80	27.33	5.08	0.00	-32.40
3	4874.00	44.8 AV	54.00	-9.20	1.22V	3	40.70	31.47	7.21	34.63	-4.05
4	4874.00	53.0 PK	74.00	-21.00	1.22V	3	48.90	31.47	7.21	34.63	-4.05

NOTE:

- 1 Emission level = Raw value - Correction Factor
- 2 Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss.
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
- 3 Margin value = Emission level - Limit value
- 4 “ * ” : Fundamental frequency
- 5 The other emission levels were very low against the limit.

EUT	11Mbps Wireless LAN Module	MODEL	WM302
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 80 % RH, 1050 hPa	TESTED BY: Bunny Yao	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2462.00	93.5AV			1.30H	0	61.10	27.33	5.08	0.00	-32.40
2	*2462.00	98.4PK			1.30H	0	66.00	27.33	5.08	0.00	-32.40
3	4924.00	43.7AV	54.00	-10.3	1.85H	363	39.60	31.51	7.21	34.62	-4.10
4	4924.00	50.9PK	74.00	-23.1	1.85H	363	46.80	31.51	7.21	34.62	-4.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2462.00	105.1 PK			1.17H	355	72.70	27.33	5.08	0.00	-32.40
2	*2462.00	98.4 AV			1.17H	355	66.00	27.33	5.08	0.00	-32.40
3	4924.00	47.2 AV	54.00	-6.80	1.64H	3	43.10	31.51	7.21	34.62	-4.10
4	4924.00	52.3 PK	74.00	-21.70	1.64H	113	48.20	31.51	7.21	34.62	-4.10

NOTE:

- 1 Emission level = Raw value - Correction Factor
- 2 Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
- 3 Margin value = Emission level - Limit value
- 4 " * " : Fundamental frequency
- 5 The other emission levels were very low against the limit.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 17, 2002


NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




4.3.6 TEST RESULTS

EUT	11Mbps Wireless LAN Module	MODEL	WM302
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26 deg. C, 60%RH, 1005 hPa
TESTED BY: Steven Lu			


CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	11.60	0.5	PASS
6	2437	11.64	0.5	PASS
11	2462	11.68	0.5	PASS

CH1






CH6



CH11





4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SINGLE CHANNEL POWER METER	NRVS	100026	Feb. 21, 2003
PEAK POWER SENSOR	NRV-Z32	100013	Feb. 21, 2003


NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

The transmitter output was connected to the peak power meter.

4.4.4 TEST SETUP



4.4.5 EUT OPERATING CONDITIONS

Same as Item 4.3.5

4.4.6 TEST RESULTS

EUT	11Mbps Wireless LAN Module	MODEL	WM302
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26 deg. C, 60%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	18.49	30	PASS
6	2437	18.49	30	PASS
11	2462	18.39	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 17, 2002


NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

4.5.4 TEST SETUP



4.5.5 EUT OPERATING CONDITIONS


Same as 4.3.5

4.5.6 TEST RESULTS


EUT	11Mbps Wireless LAN Module	MODEL	WM302
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	26 deg. C, 60%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-5.60	8	PASS
6	2437	-4.99	8	PASS
11	2462	-4.95	8	PASS


CH1



CH6



CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 17, 2002

NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.




4.6.4 EUT OPERATING CONDITION


Same as Item 4.3.5

4.6.5 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE: The band edge emission plot on the following 2 pages shows 53.17dB delta between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 11 at the item 4.2.6 (Page 38) is 102.5dBuV/m, so the maximum field strength in restrict band is $102.5 - 53.17 = 49.33$ dBuV/m which is under 54 dBuV/m limit.







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole Antenna and with MMCX antenna connector. The maximum Gain of this antenna is 4dBi.


5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST





RADIATED EMISSION TEST







6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.