



REPORT No.: SZ22110114W02

TEST REPORT

APPLICANT : Thundercomm Technology Co., Ltd

PRODUCT NAME : Smart Module

MODEL NAME : C865C, C2130C, C5165C

BRAND NAME : TurboX

FCC ID : 2AOHHTURBOXC865C

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2022-11-11


TEST DATE : 2022-11-27 to 2022-12-05

ISSUE DATE : 2022-12-27

Edited by:


Zeng Xiaoying (Rapporteur)

Approved by:


Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
1.3. The Channel Number and Frequency	5
1.4. Test Standards and Results	6
1.5. Environmental Conditions	7
2. 47 CFR Part 15C Requirements	8
2.1. Antenna Requirement	8
2.2. Hopping Mechanism	8
2.3. Number of Hopping Frequency	9
2.4. Duty Cycle of Test Signal	12
2.5. Maximum Peak Conducted Output Power	13
2.6. Maximum Average Conducted Output Power	20
2.7. 20 dB Bandwidth	22
2.8. Carried Frequency Separation	29
2.9. Time of Occupancy (Dwell time)	32
2.10. Conducted Spurious Emissions	39
2.11. Conducted Emission	52
2.12. Restricted Frequency Bands	56
2.13. Radiated Emission	74
Annex A Test Uncertainty	96
Annex B Testing Laboratory Information	97

Change History		
Version	Date	Reason for change
1.0	2022-12-27	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Thundercomm Technology Co., Ltd
Applicant Address:	Building 4, No. 99, Data Valley Middle Road,Xiantao District, Yubei District Chongqing, China
Manufacturer:	Thundercomm Technology Co., Ltd
Manufacturer Address:	Building 4, No. 99, Data Valley Middle Road,Xiantao District, Yubei District Chongqing, China

1.2. Equipment Under Test (EUT) Description

Product Name:	Smart Module	
Sample No.:	1#	
Hardware Version:	DT865_DEq_LA-IOB V03	
Software Version:	FlatBuild_Turbox-QCS8250_xx.xx_la1.0.D.userdebug.202210 24.1345	
Equipment Type:	Bluetooth classic	
Bluetooth Version:	5.1	
Modulation Type:	FHSS (GFSK(1Mbps), $\pi/4$ -DQPSK(EDR 2Mbps), 8-DPSK(EDR 3Mbps))	
Operating Frequency Range:	2402MHz–2480MHz	
Antenna Information:	Antenna Type A	
	Antenna Type:	Dipole Antenna
	Antenna Gain:	2.6dBi
	Part No.:	1461531100
	Manufacturer:	MOLEX
	Antenna Type B	
	Antenna Type:	PIFA Antenna
	Antenna Gain:	1.84dBi
	Part No.:	F-0G-JV-0211-002-00
	Manufacturer:	Speed Wireless Technical Co., LTD.



Note1: This is a variant report of original report (Report No.: SZ22030287W02, FCC ID: 2AOHHTURBOXC865C). Based on the similarity between before, made the following changes:

1. A new antenna is added.
2. Change the C11201 capacitor, the role is BT power supply filter, does not change the power control, does not affect the RF.
3. Change the shelf under the shield cover.
4. Update software version number.
5. Reduce 2.4G WiFi and 5G WiFi conducted output power.

Except for the differences shown above, the other parts are the same as before. No other changes. We have evaluated those changes in restricted frequency bands and radiated emissions and added the test results for antenna B in this report.

Note2: The EUT will not sell with the antenna.

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.3. The Channel Number and Frequency

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Note 1: The black bold channels were selected for test.



1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS _{Note1}	No deviation
2	15.247(a) 15.247(h)	Hopping Mechanism	N/A	N/A	PASS _{Note1}	No deviation
3	15.247(a)	Number of Hopping Frequency	Apr. 15, 2022	Su Xiaoxian	PASS _{Note1}	No deviation
4	ANSI C63.10	Duty Cycle	Mar. 30, 2022	Su Xiaoxian	PASS _{Note1}	No deviation
5	15.247(b)	Maximum Peak Conducted Output Power	Mar. 30, 2022	Su Xiaoxian	PASS _{Note1}	No deviation
6	15.247(b)	Maximum Average Conducted Output Power	Mar. 30, 2022	Su Xiaoxian	PASS _{Note1}	No deviation
7	15.247(a)	20dB Bandwidth	Apr. 15, 2022	Su Xiaoxian	PASS _{Note1}	No deviation
8	15.247(a)	Carrier Frequency Separation	Apr. 15, 2022	Su Xiaoxian	PASS _{Note1}	No deviation
9	15.247(a)	Time of Occupancy (Dwell time)	Apr. 15, 2022	Su Xiaoxian	PASS _{Note1}	No deviation
10	15.247(d)	Conducted Spurious Emission	Apr. 15, 2022	Su Xiaoxian	PASS _{Note1}	No deviation
11	15.207	Conducted Emission	Apr. 27, 2022	Wu Zhaoling	PASS _{Note1}	No deviation
12	15.247(d)	Restricted Frequency Bands	Dec. 05, 2022	Lin Jiayong	PASS	No deviation
13	15.209, 15.247(d)	Radiated Emission	Nov. 27, 2022	Lin Jiayong	PASS	No deviation



Note1: The test results of these test items in this report refer to the test report (Report No.: SZ22030287W02).

Note 2: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013, KDB558074 D01 v05r02 and DA 00-075.

Note 3: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The Ref offset 1.5dB means the cable loss is 1.5dB.

Note 4: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 5: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2.47 CFR Part 15C Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Test Result: Compliant

Inside of the EUT has a permanently attached Dipole antenna fixed to PCB with solder. Please refer to the EUT internal photos.

2.2. Hopping Mechanism

2.2.1. Requirement

According to FCC §15.247(a)(1), a frequency hopping spread spectrum system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

According to FCC §15.247(h), the incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

2.2.2. Result: Compliant

The hopping mechanism of the EUT is in compliance with the document "**Bluetooth core specification v5.1**".


2.3. Number of Hopping Frequency

2.3.1. Requirement

According to FCC §15.247(a)(1)(iii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 15 hopping frequencies.

2.3.2. Test Description

Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Test Set through the coupler; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.3.3. Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize



2.3.4. Test Result


A. Test Verdict:

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	PASS
$\pi/4$ -DQPSK	2400 - 2483.5	79	15	PASS
8-DPSK	2400 - 2483.5	79	15	PASS

B. Test Plot:



(GFSK)



($\pi/4$ -DQPSK)



(8-DPSK)

2.4. Duty Cycle of Test Signal


2.4.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.4.2. Test Description

Test Setup:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.

2.4.3. Test Result

Test Mode	Duty Cycle (%) (D)	Duty Factor ($10 \cdot \lg[1/D]$)
GFSK	76.80	1.15
$\pi/4$ -DQPSK	77.07	1.13
8-DPSK	77.07	1.13


2.5. Maximum Peak Conducted Output Power

2.5.1. Requirement

According to FCC §15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

2.5.2. Test Description

Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Test Set through the coupler; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.



2.5.3. Test Result

GFSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	7.99	0.006	20.96	0.125	PASS
39	2441	8.81	0.008			PASS
78	2480	6.38	0.004			PASS

B. Test Plot:



(Channel 0, GFSK)



(Channel 39, GFSK)



(Channel 78, GFSK)

 $\pi/4$ -DQPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	7.57	0.006	20.96	0.125	PASS
39	2441	8.39	0.007			PASS
78	2480	5.98	0.004			PASS

B. Test Plot:

(Channel 0, $\pi/4$ -DQPSK)

(Channel 39, $\pi/4$ -DQPSK)(Channel 78, $\pi/4$ -DQPSK)



8-DPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	7.79	0.006	20.96	0.125	PASS
39	2441	8.64	0.007			PASS
78	2480	6.22	0.004			PASS

B. Test Plot:



(Channel 0, 8-DPSK)



(Channel 39, 8-DPSK)



(Channel 78, 8-DPSK)

2.6. Maximum Average Conducted Output Power


2.6.1. Requirement

According to FCC §15.247(b), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum average output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

2.6.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Test Set through the coupler; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.



2.6.3. Test Result

GFSK Mode

Channel	Frequency (MHz)	Measured	Average Power			Limit		Verdict
			Duty Factor	Duty Factor Calculated				
		dBm		dBm	W	dBm	W	
0	2402	6.65	1.15	7.80	0.006	20.96	0.125	PASS
39	2441	7.41		8.56	0.007			PASS
78	2480	5.07		6.22	0.004			PASS

$\pi/4$ -DQPSK Mode

Channel	Frequency (MHz)	Measured	Average Power			Limit		Verdict
			Duty Factor	Duty Factor Calculated				
		dBm		dBm	W	dBm	W	
0	2402	3.92	1.13	5.05	0.003	20.96	0.125	PASS
39	2441	4.81		5.94	0.004			PASS
78	2480	2.32		3.45	0.002			PASS

8-DPSK Mode

Channel	Frequency (MHz)	Measured	Average Power			Limit		Verdict
		dBm	Duty Factor	Duty Factor Calculated				
					dBm	W	dBm	
0	2402	3.89	1.13	5.02	0.003	20.96	0.125	PASS
39	2441	4.74		5.87	0.004			PASS
78	2480	2.35		3.48	0.002			PASS


2.7. 20 dB Bandwidth

2.7.1. Definition

According to FCC §15.247(a)(1), the 20 dB bandwidth is known as the 99% emission bandwidth, or 20 dB bandwidth ($10 \cdot \log 1\% = 20$ dB) taking the total RF output power.

2.7.2. Test Description

Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Test Set through the coupler; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.7.3. Test Procedure

Use the following spectrum analyzer settings:

Span = between 2 to 5 times the OBW, centered on the test channel

RBW= 1% to 5% of the OBW

VBW $\geq 3 \times$ RBW

Sweep = auto

Detector function = peak

Trace = max hold



2.7.4. Test Result

GFSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)	Result
0	2402	0.931	PASS
39	2441	0.941	PASS
78	2480	0.932	PASS

B. Test Plot:



(Channel 0, GFSK)



(Channel 39, GFSK)



(Channel 78, GFSK)

 $\pi/4$ -DQPSK Mode

A. Test Verdict:

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Result
0	2402	1.282	PASS
39	2441	1.313	PASS
78	2480	1.308	PASS

B. Test Plot:

(Channel 0, $\pi/4$ -DQPSK)

(Channel 39, $\pi/4$ -DQPSK)(Channel 78, $\pi/4$ -DQPSK)



(Channel 39, 8-DPSK)



(Channel 78, 8-DPSK)


2.8. Carried Frequency Separation

2.8.1. Definition

According to FCC §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

2.8.2. Test Description

Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Test Set through the coupler; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.8.3. Test Procedure

The EUT must have its hopping function enabled. According to DA 00-705, use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.



2.8.4. Test Result

A. Test Verdict:

Test Mode	Measured Channel Numbers	Carried Frequency Separation (MHz)	20 dB Bandwidth (MHz)	Min. Limit	Verdict
GFSK	39 and 40	1.002	0.941	two-thirds of the 20dB bandwidth	PASS
$\pi/4$ -DQPSK	39 and 40	0.999	1.313		PASS
8-DPSK	39 and 40	0.999	1.308		PASS

B. Test Plot:



(GFSK)



($\pi/4$ -DQPSK)



(8-DPSK)


2.9. Time of Occupancy (Dwell time)

2.9.1. Requirement

According to FCC §15.247(a) (1) (iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

2.9.2. Test Description

Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Test Set through the coupler; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.9.3. Test Procedure

Normal Mode:

DH1: Dwell time equal to Pulse time (ms) * (1600 / 2 / 79) * 31.6 Millisecond
DH3: Dwell time equal to Pulse time (ms) * (1600 / 4 / 79) * 31.6 Millisecond
DH5: Dwell time equal to Pulse Time (ms) * (1600 / 6 / 79) * 31.6 Millisecond

AFH Mode:

DH1: Dwell time equal to Pulse time (ms) * (800 / 2 / 20) * (0.4 * 20) Millisecond
DH3: Dwell time equal to Pulse time (ms) * (800 / 4 / 20) * (0.4 * 20) Millisecond
DH5: Dwell time equal to Pulse Time (ms) * (800 / 6 / 20) * (0.4 * 20) Millisecond.



2.9.4. Test Result

GFSK Mode


A. Test Verdict:

DH Packet	Pulse Width (ms)	Dwell Time (ms)		Limit (sec)	Verdict
		Normal Mode	AFH Mode		
DH1	0.37	118.40	59.20	0.4	PASS
DH3	1.62	259.20	129.60		PASS
DH5	2.88	307.20	153.60		PASS

B. Test Plot:



(DH1, GFSK)



(DH3, GFSK)



(DH5, GFSK)



π/4-DQPSK Mode


A. Test Verdict:

DH Packet	Pulse Width (ms)	Dwell Time (ms)		Limit (sec)	Verdict
		Normal Mode	AFH Mode		
DH1	0.38	121.60	60.80	0.4	PASS
DH3	1.64	262.40	131.20		PASS
DH5	2.88	307.20	153.60		PASS

B. Test Plot:



(DH1, π/4-DQPSK)


(DH3, $\pi/4$ -DQPSK)

(DH5, $\pi/4$ -DQPSK)



8-DPSK mode

A. Test Verdict:

DH Packet	Pulse Width (ms)	Dwell Time (ms)		Limit (sec)	Verdict
		Normal Mode	AFH Mode		
DH1	0.39	124.80	62.40	0.4	PASS
DH3	1.64	262.40	131.20		PASS
DH5	2.88	307.20	153.60		PASS


B. Test Plot:



(DH1, 8-DPSK)



(DH3, 8-DPSK)



(DH5, 8-DPSK)


2.10. Conducted Spurious Emissions

2.10.1. Requirement

According to FCC §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.10.2. Test Description

Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Test Set through the coupler; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.10.3. Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.




2.10.4. Test Result

GFSK Mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-42.22	7.57	-12.43	PASS
39	2441	-42.66	8.26	-11.74	PASS
78	2480	-41.61	5.64	-14.36	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 0, GFSK)




(Band edge, Channel 0, GFSK)




(Band edge with hopping on, Channel 0, GFSK)



(30MHz to 25GHz, Channel 39, GFSK)



(30MHz to 25GHz, Channel 78, GFSK)



(Band edge, Channel 78, GFSK)



(Band edge with hopping on, Channel 78, GFSK)




$\pi/4$ -DQPSK Mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-42.51	3.35	-16.65	PASS
39	2441	-42.54	1.89	-18.11	PASS
78	2480	-43.09	2.21	-17.79	PASS



B. Test Plot:




(30MHz to 25GHz, Channel 0, $\pi/4$ -DQPSK)


(Band edge, Channel 0, $\pi/4$ -DQPSK)

(Band edge with hopping on, Channel 0, $\pi/4$ -DQPSK)


(30MHz to 25GHz, Channel 39, $\pi/4$ -DQPSK)(30MHz to 25GHz, Channel 78, $\pi/4$ -DQPSK)


(Band edge, Channel 78, $\pi/4$ -DQPSK)


(Band edge with hopping on, Channel 78, $\pi/4$ -DQPSK)

**8-DPSK Mode****A. Test Verdict:**

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-42.07	-0.39	-20.39	PASS
39	2441	-41.52	6.50	-13.50	PASS
78	2480	-42.66	-0.14	-20.14	PASS

B. Test Plot:


(30MHz to 25GHz, Channel 0, 8-DPSK)




(Band edge, Channel 0, 8-DPSK)




(Band edge with hopping on, Channel 0, 8-DPSK)



(30MHz to 25GHz, Channel 39, 8-DPSK)



(30MHz to 25GHz, Channel 78, 8-DPSK)



(Band edge, Channel 78, 8-DPSK)



(Band edge with hopping on, Channel 78, 8-DPSK)

2.11. Conducted Emission

2.11.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5- 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.11.2. Test Description

Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.



2.11.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Adapter+PC+ BT TX

Test Voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1823	47.50	30.81	64.38	54.38	Line	PASS
2	0.2434	48.83	31.44	61.98	51.98		PASS
3	0.3073	46.55	29.48	60.04	50.04		PASS
4	0.4030	45.00	27.94	57.79	47.79		PASS
5	0.4607	49.82	31.23	56.68	46.68		PASS
6	0.8529	38.50	24.66	56.00	46.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1905	55.44	38.86	64.02	54.02	Neutral	PASS
2	0.2168	52.65	37.46	62.94	52.94		PASS
3	0.2587	53.70	39.14	61.47	51.47		PASS
4	0.3466	49.60	34.62	59.04	49.04		PASS
5	0.4555	54.97	38.97	56.77	46.77		PASS
6	0.7393	45.21	30.06	56.00	46.00		PASS


2.12. Restricted Frequency Bands

2.12.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.12.2. Test Description

Test Setup:



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Horn Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.



2.12.3. Test Procedure

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

2.12.4. Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

AT: Total correction Factor except Antenna

UR: Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

Antenna Type A


GFSK Mode

A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
0	2384.14	PK	22.74	6.74	27.20	56.68	74	PASS
0	2390.00	AV	10.02	6.74	27.20	43.96	54	PASS
78	2484.46	PK	22.03	6.74	27.20	55.97	74	PASS
78	2483.50	AV	9.08	6.74	27.20	43.02	54	PASS




B. Test Plot:



(PEAK, Channel 0, GFSK)



(AVERAGE, Channel 0, GFSK)



(PEAK, Channel 78, GFSK)



(AVERAGE, Channel 78, GFSK)




$\pi/4$ -DQPSK Mode



A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
0	2388.71	PK	22.60	6.74	27.20	56.54	74	PASS
0	2390.00	AV	10.07	6.74	27.20	44.01	54	PASS
78	2485.56	PK	21.34	6.74	27.20	55.28	74	PASS
78	2485.21	AV	10.06	6.74	27.20	44.00	54	PASS

B. Test Plot:



(PEAK, Channel 0, $\pi/4$ -DQPSK)

(AVERAGE, Channel 0, $\pi/4$ -DQPSK)(PEAK, Channel 78, $\pi/4$ -DQPSK)



(AVERAGE, Channel 78, $\pi/4$ -DQPSK)




8-DPSK Mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
0	2375.71	PK	21.47	6.74	27.20	55.41	74	PASS
0	2390.00	AV	10.05	6.74	27.20	43.99	54	PASS
78	2485.72	PK	21.54	6.74	27.20	55.48	74	PASS
78	2483.50	AV	10.20	6.74	27.20	44.14	54	PASS


B. Test Plot:




(PEAK, Channel 0, 8-DPSK)



(AVERAGE, Channel 0, 8-DPSK)



(PEAK, Channel 78, 8-DPSK)



(AVERAGE, Channel 78, 8-DPSK)




Antenna Type B

GFSK Mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBμV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
0	2362.50	PK	24.39	6.74	27.20	58.33	74	PASS
0	23899.13	AV	10.67	6.74	27.20	44.61	54	PASS
78	2486.32	PK	23.26	6.74	27.20	57.20	74	PASS
78	2483.65	AV	10.36	6.74	27.20	44.30	54	PASS


B. Test Plot:




(PEAK, Channel 0, GFSK)



(AVERAGE, Channel 0, GFSK)



(PEAK, Channel 78, GFSK)



(AVERAGE, Channel 78, GFSK)



π/4-DQPSK Mode



A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U _R (dBμV)	A _T (dB)	A _{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
0	2330.06	PK	24.09	6.74	27.20	58.03	74	PASS
0	2388.71	AV	10.74	6.74	27.20	44.68	54	PASS
78	2484.49	PK	23.45	6.74	27.20	57.39	74	PASS
78	2483.74	AV	10.32	6.74	27.20	44.26	54	PASS



B. Test Plot:

(PEAK, Channel 0, $\pi/4$ -DQPSK)(AVERAGE, Channel 0, $\pi/4$ -DQPSK)

(PEAK, Channel 78, $\pi/4$ -DQPSK)(AVERAGE, Channel 78, $\pi/4$ -DQPSK)




8-DPSK Mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
0	2348.46	PK	23.79	6.74	27.20	57.73	74	PASS
0	2390.00	AV	10.75	6.74	27.20	44.69	54	PASS
78	2487.26	PK	22.94	6.74	27.20	56.88	74	PASS
78	2483.50	AV	10.33	6.74	27.20	44.27	54	PASS


B. Test Plot:




(PEAK, Channel 0, 8-DPSK)



(AVERAGE, Channel 0, 8-DPSK)



(PEAK, Channel 78, 8-DPSK)



(AVERAGE, Channel 78, 8-DPSK)

2.13. Radiated Emission

2.13.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).


2.13.2. Test Description

Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.



2.13.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain


A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note 1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


Note 2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 3: For the frequency, which started from 18GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**Antenna Type A, GFSK Mode****Plots for Channel 0**

Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
107.600	29.42	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
341.370	29.99	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2406.933	45.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5726.200	45.48	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9141.920	45.35	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12603.840	45.90	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
108.570	28.60	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
455.830	31.25	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2411.733	46.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4977.760	45.98	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8664.520	45.81	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12683.920	45.35	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 39



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
98.870	30.03	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
328.760	29.41	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2044.800	45.37	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5599.920	45.20	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8399.640	45.64	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12135.680	46.48	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
109.540	28.77	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
575.140	32.52	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2489.600	46.05	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5184.120	44.79	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9083.400	45.61	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12834.840	45.54	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 78



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
100.810	29.48	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
353.010	29.22	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2411.733	46.55	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5880.200	46.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8584.440	45.64	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
14029.880	45.13	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
96.930	30.12	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
343.310	28.94	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2409.067	46.79	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5187.200	50.12	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8618.320	46.11	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12881.040	46.96	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


 **$\pi/4$ -DQPSK Mode**

Plots for Channel 0



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	30.92	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
339.430	28.82	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
697.360	33.45	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2240.000	45.51	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5516.760	46.14	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12345.120	46.25	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
108.570	29.40	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
559.620	32.36	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2411.733	45.35	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4691.320	45.77	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8411.960	45.35	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12908.760	45.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 39



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
110.510	29.50	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
218.180	28.30	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
563.500	33.12	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2405.867	46.83	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5667.680	45.83	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7913.000	45.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
100.810	28.89	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
559.620	31.44	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2453.867	45.53	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4515.760	45.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8535.160	46.10	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13851.240	44.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 78



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
103.720	29.79	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
350.100	29.15	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2357.867	45.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4469.560	44.54	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7909.920	44.94	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12767.080	46.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
98.870	29.53	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
328.760	27.63	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
567.380	31.45	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
4691.320	44.98	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8642.960	46.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12921.080	45.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**8-DPSK Mode**

Plots for Channel 0



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
107.600	30.18	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
340.400	29.32	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2411.200	46.55	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4537.320	45.54	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8596.760	45.75	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12619.240	46.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
99.840	29.30	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
429.640	29.88	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2413.333	45.88	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5239.560	46.06	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8618.320	46.24	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12690.080	46.83	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 39



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
99.840	29.12	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
360.770	29.84	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2404.267	46.23	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4121.520	44.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8455.080	45.35	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12151.080	46.57	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
98.870	28.96	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
571.260	32.28	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2453.333	45.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5723.120	45.55	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8384.240	45.96	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12899.520	45.87	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 78



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	29.84	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
577.080	31.26	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2413.333	46.14	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4756.000	43.89	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8914.000	45.28	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12141.840	45.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
110.510	31.22	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
577.080	34.58	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2406.933	46.16	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4709.800	45.33	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8421.200	45.91	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12890.280	46.48	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**Antenna Type B, GFSK Mode**

Plots for Channel 0



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
115.360	30.08	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
347.190	30.59	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
672.140	33.21	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
4466.480	43.73	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
6191.280	45.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12046.360	45.64	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
100.810	31.72	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
335.550	29.97	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
670.200	33.92	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
5088.640	44.85	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7937.640	45.90	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13105.880	45.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 39



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
106.630	30.53	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
345.250	30.08	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
571.260	33.01	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
5162.560	45.09	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9083.400	46.14	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
16555.480	46.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
113.420	30.21	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
331.670	30.21	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
676.020	32.34	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
5870.960	45.74	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8578.280	45.39	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12154.160	46.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 78



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	30.51	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
221.090	29.13	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
456.800	30.65	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
5683.080	45.72	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9058.760	46.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
15018.560	45.54	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
104.690	30.80	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
222.060	29.63	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
687.660	33.45	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
5076.320	45.17	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8436.600	45.39	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
16426.120	45.27	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


 **$\pi/4$ -DQPSK Mode**

Plots for Channel 0



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
111.480	30.80	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
347.190	30.42	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
707.060	33.86	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
5769.320	45.98	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9006.400	46.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13087.400	46.60	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
102.750	30.75	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
238.550	28.28	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
577.080	33.86	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
3767.320	44.05	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7999.240	46.01	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13087.400	45.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 39



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	30.78	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
474.260	31.64	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
671.170	32.48	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
5766.240	48.52	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10343.120	46.09	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12517.600	46.89	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
103.720	31.16	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
222.060	29.26	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
673.110	33.29	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
4638.960	44.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5624.560	45.80	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12520.680	46.09	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 78



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
107.600	30.59	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
342.340	30.14	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
678.930	33.51	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
4158.480	43.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9018.720	45.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12825.600	46.23	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
109.540	30.28	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
339.430	30.33	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
575.140	33.13	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
3893.600	44.23	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9021.800	45.85	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12135.680	46.48	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**8-DPSK Mode**

Plots for Channel 0



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
104.690	30.53	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
219.150	28.60	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
578.050	32.98	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
3755.000	43.81	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7977.680	45.34	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12893.360	46.87	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
98.870	30.14	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
234.670	29.49	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
576.110	32.61	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
5606.080	46.43	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8402.720	46.28	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14063.760	46.32	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 39



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
111.480	30.27	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
228.850	29.25	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
583.870	32.77	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
5590.680	45.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8488.960	45.01	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12314.320	45.66	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
105.660	30.69	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
338.460	30.84	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
700.270	33.43	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
3899.760	44.27	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9052.600	45.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12539.160	47.73	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 78



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
100.810	30.77	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
247.280	29.21	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
577.080	33.48	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
3745.760	44.37	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7882.200	46.21	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12902.600	46.57	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
109.540	30.81	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
240.490	27.61	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
577.080	33.97	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2455.467	47.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
6385.320	43.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12194.200	47.12	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)

Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test Items	Uncertainty
Number of Hopping Frequency	±5%
Peak Output Power	±2.22dB
Bandwidth	±5%
Carrier Frequency Separation	±5%
Time of Occupancy (Dwell time)	±5%
Conducted Spurious Emission	±2.77dB
Restricted Frequency Bands	±5%
Radiated Emission	±2.95dB
Conducted Emission	±2.44dB

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Bluetooth Base Station	6K00006210	MT8852B	Anritsu	2022.03.01	2023.02.28
Directional Coupler	17041703	DTO-5-30	ShangHaiHuaxiang	N/A	N/A
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2022.03.01	2023.02.28
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2022.03.03	2023.03.02
LISN	8127449	NSLK 8127	Schwarzbeck	2022.03.03	2023.03.02
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2022.07.06	2023.07.05
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2022.07.08	2023.07.07
NOTEBOOK	DF2DR A01 DPC	VOSTRO 5370	DELL	N/A	N/A
ADAPTER	OKXTTW	LA45NM140	DELL	N/A	N/A

4.3 List of Software Used

Description	Manufacturer	Software Version
Test System	Tonscend	V2.5.77.0418
Morlab EMCR V1.2	Morlab	V1.0
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

4.4 Radiated Test Equipments



Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2022.07.06	2023.07.05
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2022.05.25	2025.05.24
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2022.02.11	2025.02.10
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2022.07.13	2025.07.12
Test Antenna – Horn	BBHA9170#773	BBHA 9170	Schwarzbeck	2022.07.14	2025.07.13
Preamplifier (2GHz-18GHz)	61171/61172	S020180L3203	LUCIX CORP.	2022.07.08	2023.07.07
Preamplifier (10MHz-6GHz)	46732	S10M100L3802	LUCIX CORP.	2022.07.08	2023.07.07
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2022.07.23	2023.07.22
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-K K-0.5	Qualwave	2022.07.08	2023.07.07
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-K KF-2	Qualwave	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-N N-5	Qualwave	2022.07.08	2023.07.07
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2022.07.08	2023.07.07
Anechoic Chamber	N/A	9m*6m*6m	CRT	2020.01.06	2023.01.05

————— END OF REPORT —————