



# TEST REPORT

**No. I18D00168-SAR01**

***For***

**Client : Gemalto M2M GmbH**

**Production : EHS8**

**Model Name : EHS8**

**FCC ID: QIPEHS8**

**IC ID: 7830A-EHS8**

**Hardware Version: B2.1**

**Software Version: 04.003**

**Issued date: 2019-1-24**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of ECIT Shanghai.

**Test Laboratory:**

ECIT Shanghai, East China Institute of Telecommunications

Add: 7F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Tel: (+86)-021-63843300, E-Mail: [welcome@ecit.org.cn](mailto:welcome@ecit.org.cn)

**Revision Version**

| Report Number   | Revision | Date      | Memo                            |
|-----------------|----------|-----------|---------------------------------|
| I18D00168-SAR01 | 00       | 2019-1-24 | Initial creation of test report |

## CONTENTS

|                                                                         |           |
|-------------------------------------------------------------------------|-----------|
| <b>1. TEST LABORATORY .....</b>                                         | <b>5</b>  |
| <b>1.1. TESTING LOCATION .....</b>                                      | <b>5</b>  |
| <b>1.2. PROJECT DATA .....</b>                                          | <b>5</b>  |
| <b>1.3. SIGNATURE .....</b>                                             | <b>5</b>  |
| <b>2. CLIENT INFORMATION.....</b>                                       | <b>6</b>  |
| <b>2.1. APPLICANT INFORMATION.....</b>                                  | <b>6</b>  |
| <b>2.2. MANUFACTURER INFORMATION.....</b>                               | <b>6</b>  |
| <b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b> | <b>7</b>  |
| <b>3.1. ABOUT EUT .....</b>                                             | <b>7</b>  |
| <b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>   | <b>7</b>  |
| <b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>    | <b>7</b>  |
| <b>4. TEST RESULTS .....</b>                                            | <b>8</b>  |
| <b>4.1. RF POWER OUTPUT.....</b>                                        | <b>8</b>  |
| <b>4.2. DUTY CYCLE .....</b>                                            | <b>8</b>  |
| <b>5. REFERENCE DOCUMENTS FOR FCC .....</b>                             | <b>9</b>  |
| <b>5.1. APPLICABLE STANDARDS.....</b>                                   | <b>9</b>  |
| <b>5.2. TEST LIMITS.....</b>                                            | <b>9</b>  |
| <b>5.3. CALCULATION INFORMATION .....</b>                               | <b>10</b> |
| <b>5.4. MAX. ANTENNA GAIN CALCULATIONS.....</b>                         | <b>11</b> |
| <b>5.5. CONCLUSION FOR MAXIMUM ADMISSIBLE ANTENNA GAIN (FCC).....</b>   | <b>12</b> |
| <b>6. REFERENCE DOCUMENTS FOR IC .....</b>                              | <b>13</b> |
| <b>6.1. APPLICABLE STANDARDS.....</b>                                   | <b>13</b> |
| <b>6.2. TEST LIMITS .....</b>                                           | <b>13</b> |
| <b>6.3. CALCULATION INFORMATION .....</b>                               | <b>13</b> |
| <b>6.4. RESULT OF LTE .....</b>                                         | <b>14</b> |
| <b>6.5. MAX. ANTENNA GAIN CALCULATIONS.....</b>                         | <b>14</b> |

|      |                                                           |    |
|------|-----------------------------------------------------------|----|
| 6.6. | CONCLUSION FOR MAXIMUM ADMISSIBLE ANTENNA GAIN (IC) ..... | 15 |
| 7.   | SUMMARY .....                                             | 16 |

## 1. Test Laboratory

### 1.1. Testing Location

|               |                                                                                   |
|---------------|-----------------------------------------------------------------------------------|
| Company Name: | ECIT Shanghai, East China Institute of Telecommunications                         |
| Address:      | 7-8F, G Area, No. 668, Beijing East Road, Huangpu District, Shanghai, P. R. China |
| Postal Code:  | 200001                                                                            |
| Telephone:    | (+86)-021-63843300                                                                |
| Fax:          | (+86)-021-63843301                                                                |

### 1.2. Project Data

|                 |          |
|-----------------|----------|
| Project Leader: | Zhou Yan |
|-----------------|----------|

### 1.3. Signature



Yan Hang  
(Prepared this test report)



Fu Erliang  
(Reviewed this test report)



Zheng Zhongbin  
(Approved this test report)

## 2. Client Information

### 2.1. Applicant Information

Company Name: Gemalto M2M GmbH  
Address: Gemalto M2M GmbH, Werinherstrasse 81 81541 München,  
Germany  
Telephone: +861059378342  
Postcode: /

### 2.2. Manufacturer Information

Company Name: Gemalto M2M GmbH  
Address /Post: Gemalto M2M GmbH, Werinherstrasse 81 81541 München,  
Germany  
Telephone: +861059378342  
Postcode: /

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

|                      |                                           |
|----------------------|-------------------------------------------|
| EUT Description      | EHS8                                      |
| Model name           | EHS8                                      |
| GSM Frequency Band   | GSM850/1900                               |
| WCDMA Frequency Band | WCDMA Band II (1900) / WCDMA Band V (850) |
| Antenna Type         | External Antenna                          |
| FCC ID:              | QIPEHS8                                   |
| IC ID:               | 7830A-EHS8                                |

#### 3.2. Internal Identification of EUT used during the test

| EUT ID* | SN or IMEI | HW Version | SW Version: |
|---------|------------|------------|-------------|
| N01     | N/A        | B2.1       | 04.003      |

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

| AE ID* | Description | Model | SN  | Manufacturer |
|--------|-------------|-------|-----|--------------|
| N/A    | N/A         | N/A   | N/A | N/A          |

\*AE ID: is used to identify the test sample in the lab internally.

## 4. Test Results

### 4.1. RF Power Output

| Frequency Band               | Max power(dBm) | Highest Frame-Averaged Output Power (dBm) | Antenna Gain(dBi) |
|------------------------------|----------------|-------------------------------------------|-------------------|
| WCDMA band II (1900)         | 25             | 25                                        | 2.15              |
| WCDMA band V (850)           | 25             | 25                                        | 5.15              |
| GSM850                       | 34             | 24.97                                     | 5.15              |
| GPRS 850(GMSK, 1 Tx slot)    | 34             | 24.97                                     | 5.15              |
| GPRS 850(GMSK, 2 Tx slot)    | 31             | 24.98                                     | 5.15              |
| GPRS 850(GMSK, 3 Tx slot)    | 29             | 24.74                                     | 5.15              |
| GPRS 850(GMSK, 4 Tx slot)    | 28             | 24.99                                     | 5.15              |
| EGPRS 850(8-PSK, 1 Tx slot)  | 28             | 18.97                                     | 5.15              |
| EGPRS 850(8-PSK, 2 Tx slot)  | 25             | 18.98                                     | 5.15              |
| EGPRS 850(8-PSK, 3 Tx slot)  | 23             | 18.74                                     | 5.15              |
| EGPRS 850(8-PSK, 4 Tx slot)  | 22             | 18.99                                     | 5.15              |
| GSM1900                      | 31             | 21.97                                     | 2.15              |
| GPRS 1900(GMSK, 1 Tx slot)   | 31             | 21.97                                     | 2.15              |
| GPRS 1900(GMSK, 2 Tx slot)   | 28             | 21.98                                     | 2.15              |
| GPRS 1900(GMSK, 3 Tx slot)   | 26             | 21.74                                     | 2.15              |
| GPRS 1900(GMSK, 4 Tx slot)   | 25             | 21.99                                     | 2.15              |
| EGPRS 1900(8-PSK, 1 Tx slot) | 27             | 17.97                                     | 2.15              |
| EGPRS 1900(8-PSK, 2 Tx slot) | 24             | 17.98                                     | 2.15              |
| EGPRS 1900(8-PSK, 3 Tx slot) | 22             | 17.74                                     | 2.15              |
| EGPRS 1900(8-PSK, 4 Tx slot) | 21             | 17.99                                     | 2.15              |

### 4.2. Duty cycle

| Mode               | Duty Cycle |
|--------------------|------------|
| GSM                | 1:8.3      |
| GSM 850(1 Tx slot) | 1:8.3      |
| GSM 850(2 Tx slot) | 1:4.15     |
| GSM 850(3 Tx slot) | 1:2.77     |
| GSM 850(4 Tx slot) | 1:2.08     |
| WCDMA              | 1:1        |

## 5. Reference Documents for FCC

### 5.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

FCC CFR 47, Part 2, FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS, Oct 1,2011

Section 2.1091 Radiofrequency radiation exposure evaluation: mobile devices, June 23, 2015

### 5.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

Limits for Occupational / Controlled Exposure

| Frequency Range [MHz] | Electric Field Strength (E) [V/m] | Magnetic Field Strength (H) [A/m] | Power Density (S) [mW/cm <sup>2</sup> ] | Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S [minutes] |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|--------------------------------------------------------------------|
| 0.3 – 3.0             | 614                               | 1.63                              | (100)*                                  | 6                                                                  |
| 3.0 – 30              | 1824/f                            | 4.89/f                            | (900/f)*                                | 6                                                                  |
| 30 – 300              | 61.4                              | 0.163                             | 1.0                                     | 6                                                                  |
| 300 – 1500            | --                                | --                                | F/300                                   | 6                                                                  |
| 1500 - 100000         | --                                | --                                | 5                                       | 6                                                                  |

Limits for General Population / Uncontrolled Exposure

| Frequency Range [MHz] | Electric Field Strength (E) [V/m] | Magnetic Field Strength (H) [A/m] | Power Density (S) [mW/cm <sup>2</sup> ] | Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S [minutes] |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|--------------------------------------------------------------------|
| 0.3 – 1.34            | 614                               | 1.63                              | (100)*                                  | 30                                                                 |
| 1.34 – 30             | 824/f                             | 2.19/f                            | (180/f)*                                | 30                                                                 |
| 30 – 300              | 27.5                              | 0.073                             | 0.2                                     | 30                                                                 |
| 300 – 1500            | --                                | --                                | F/1500                                  | 30                                                                 |
| 1500 - 100000         | --                                | --                                | 1.0                                     | 30                                                                 |

Note: f=frequency in MHz; \*Plane-wave equivalent power density

For the DUT, the limits for General Population / Uncontrolled Exposure are applicable.

|                     |                                                                                                                                                                                                                                                                                                                       |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FCC: §1.1307        | Cellular Radiotelephone Service (subpart H of part 22)<br>Non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 1000 W ERP (1640 W EIRP)                                                                                                       |
| FCC §1.1307         | Personal Communications Services (part 24)<br>Broadband PCS (subpart E): non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 2000 W ERP (3280 W EIRP)                                                                                        |
| FCC §1.1310         | LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)<br>Table 1(B) Limits for General Population/Uncontrolled Exposure 300–1500 MHz: f/1500 mW/cm <sup>2</sup><br>1500–100,000 MHz: 1.0 mW/cm <sup>2</sup><br>Subject to routine evaluation is required when the device operate at frequencies of 1.5 GHz or below and their |
| FCC §2.1091         | effective radiated power (ERP) is 1.5 watts or more, or if they operate at frequencies above 1.5 GHz and their ERP is 3 watts or more.(a) Base stations are limited to 1640 watts peak equivalent isotropically radiated power (e.i.r.p.) with an antenna                                                             |
| FCC §24.232         | height up to 300 meters HAAT.<br>b) Mobile/portable stations are limited to 2 watts e.i.r.p. peak power, ...                                                                                                                                                                                                          |
| FCC §22.913         | (a) Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.                                                                                                    |
| FCC §27.50 (C )(10) | (10) Portable stations (hand-held devices) are limited to 3 watts ERP; and                                                                                                                                                                                                                                            |
| FCC §27.50(d)       | (4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band are limited to 1 watt EIRP.                                                                                                                                                                                                  |

## 5.3. Calculation Information

For conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

$$\text{Given } S = \frac{P \times G}{4\pi d^2} \quad \text{Equation 1}$$

Where

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

| Band                       | Frequency (MHz) | Highest Frame-Averaged Output Power (dBm) | Limit mW/m <sup>2</sup> | Antenna Gain (dBi) | Numeric antenna gain | Power density at 20cm | Limit mW/cm <sup>2</sup> |
|----------------------------|-----------------|-------------------------------------------|-------------------------|--------------------|----------------------|-----------------------|--------------------------|
| WCDMA band II (1900)       | 1852.4          | 25                                        | 1                       | 2.15               | 1.641                | 0.103                 | 1                        |
| WCDMA band V (850)         | 826.4           | 25                                        | 0.556                   | 5.15               | 3.273                | 0.206                 | 0.556                    |
| GPRS 850(GMSK, 4 Tx slot)  | 824.2           | 24.99                                     | 0.556                   | 5.15               | 3.273                | 0.205                 | 0.556                    |
| GPRS 1900(GMSK, 4 Tx slot) | 1850.2          | 21.99                                     | 1                       | 2.15               | 1.641                | 0.052                 | 1                        |

Note: For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band

#### 5.4. Max. Antenna gain calculations

Maximum antenna gain considerations for fixed/mobile operations for complying with limits:

| Band                       | Highest Frame-Averaged Output Power (dBm) | Limit mW/cm <sup>2</sup> | Max antenna gain at 20cm(dBi) |
|----------------------------|-------------------------------------------|--------------------------|-------------------------------|
| WCDMA band II (1900)       | 25                                        | 1                        | 12.01                         |
| WCDMA band V (850)         | 25                                        | 0.556                    | 9.46                          |
| GPRS 850(GMSK, 4 Tx slot)  | 24.99                                     | 0.556                    | 9.49                          |
| GPRS 1900(GMSK, 4 Tx slot) | 21.99                                     | 1                        | 15.04                         |

Power limit according to §2.1091 [W]:

| Band                       | Highest Frame-Averaged Output Power (dBm) | Limit (W) (ERP) | Max antenna gain at 20cm(dBi) |
|----------------------------|-------------------------------------------|-----------------|-------------------------------|
| WCDMA band II (1900)       | 25                                        | 1.5             | 8.91                          |
| WCDMA band V (850)         | 25                                        | 3               | 11.92                         |
| GPRS 850(GMSK, 4 Tx slot)  | 24.99                                     | 3               | 11.93                         |
| GPRS 1900(GMSK, 4 Tx slot) | 21.99                                     | 1.5             | 11.92                         |

Power limit according to §22.913; §24.232 [W]:

| Band                 | Highest Frame-Averaged Output Power (dBm) | Limit (W) EIRP | Max antenna gain (dBi) |
|----------------------|-------------------------------------------|----------------|------------------------|
| WCDMA band II (1900) | 25                                        | 2.0            | 8.01                   |

|                            |                                                 |                     |                           |
|----------------------------|-------------------------------------------------|---------------------|---------------------------|
| GPRS 1900(GMSK, 4 Tx slot) | 21.99                                           | 2.0                 | 11.02                     |
| Band                       | Highest<br>Frame-Averaged<br>Output Power (dBm) | Limit<br>(W)<br>ERP | Max antenna gain<br>(dBi) |
| WCDMA band V (850)         | 25                                              | 7.0                 | 15.60                     |
| GPRS 850(GMSK, 4 Tx slot)  | 24.99                                           | 7.0                 | 15.61                     |

### 5.5. Conclusion for maximum admissible antenna gain (FCC)

| Band                 | Maximum admissible antenna<br>gain (dBi) |
|----------------------|------------------------------------------|
| WCDMA band II (1900) | 8.01                                     |
| WCDMA band V (850)   | 9.46                                     |
| GSM850               | 9.49                                     |
| GSM1900              | 11.02                                    |

**Note:** Using frequency in 824~849MHz allows the use of antenna gain biggest 9.46dBi.

Using frequency in 1850~1910MHz allows the use of antenna gain biggest 8.01dBi.

## 6. Reference Documents for IC

### 6.1. Applicable Standards

RSS 102 Issue 5 :Radio Frequency (RF) Exposure Compliance of Radio communication Apparatus (All Frequency Bands)

### 6.2. Test Limits

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $22.48/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

|          |                                                                                                                                                                                                                                        |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RSS 132  | The transmitter output power shall be measured in terms of average power. The equivalent isotropically radiated power (e.i.r.p.) for mobile equipment shall not exceed 11.5 watts. Refer to SRSP-503 for base station e.i.r.p. limits. |
| SRSP-510 | 5.1.2 Mobile Stations<br>Mobile stations and hand-held portables are limited to 2 watts maximum e.i.r.p. The equipment shall employ means to limit the power to the minimum necessary for successful communication.                    |

### 6.3. Calculation Information

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;

#### 6.4. Result of EUT

The MPE limit for Occupational/Controlled Exposure is shown in the RSS 102 issue 5 section 2.5.2, can be calculated as follows:

| Frequency Band             | Highest Output Power (dBm) | Antenna Gain(dBi) | EIRP/EIP (W) | MPE limit (W) |
|----------------------------|----------------------------|-------------------|--------------|---------------|
| WCDMA band II (1900)       | 25                         | 2.15              | 0.52         | 2.24          |
| WCDMA band V (850)         | 25                         | 5.15              | 1.04         | 1.290         |
| GPRS 850(GMSK, 4 Tx slot)  | 24.99                      | 5.15              | 1.03         | 1.290         |
| GPRS 1900(GMSK, 4 Tx slot) | 21.99                      | 2.15              | 0.26         | 2.24          |

As we can see the resulted EIRP is below the MPE limit, therefore the DUT in this band is compliant with the IC rules on RF exposure.

#### 6.5. Max. Antenna gain calculations

Maximum antenna gain considerations for fixed/mobile operations for complying with limits according to RSS 102:

| Band                       | Frequency (MHz) | Highest Output Power (dBm) | MPE limit (W) | Max antenna gain at 20cm(dBi) |
|----------------------------|-----------------|----------------------------|---------------|-------------------------------|
| WCDMA band II (1900)       | 1852.4          | 25                         | 2.24          | 8.50                          |
| WCDMA band V (850)         | 826.4           | 25                         | 1.290         | 6.11                          |
| GPRS 850(GMSK, 4 Tx slot)  | 824.2           | 24.99                      | 1.290         | 6.12                          |
| GPRS 1900(GMSK, 4 Tx slot) | 1850.2          | 21.99                      | 2.24          | 11.51                         |

**Power limit according to RSS 132; SRSP-510:**

| Band                       | Highest<br>Frame-Averaged<br>Output Power (dBm) | Limit<br>(W)<br>EIRP | Max antenna gain<br>(dBi) |
|----------------------------|-------------------------------------------------|----------------------|---------------------------|
| WCDMA band II (1900)       | 25                                              | 2.0                  | 8.01                      |
| WCDMA band V (850)         | 25                                              | 11.5                 | 15.61                     |
| GPRS 850(GMSK, 4 Tx slot)  | 24.99                                           | 11.5                 | 15.62                     |
| GPRS 1900(GMSK, 4 Tx slot) | 21.99                                           | 2.0                  | 11.02                     |

**6.6. Conclusion for maximum admissible antenna gain (IC)**

| Band                       | Maximum admissible antenna<br>gain (dBi) |
|----------------------------|------------------------------------------|
| WCDMA band II (1900)       | 8.01                                     |
| WCDMA band V (850)         | 6.11                                     |
| GPRS 850(GMSK, 4 Tx slot)  | 6.12                                     |
| GPRS 1900(GMSK, 4 Tx slot) | 11.02                                    |

**Note:** Using frequency in 824~849MHz allows the use of antenna gain biggest 6.11dBi.  
Using frequency in 1850~1910MHz allows the use of antenna gain biggest 8.01dBi.

## 7. Summary

| Band                 | FCC Maximum<br>admissible antenna<br>gain (dBi) | IC Maximum<br>admissible<br>antenna gain<br>(dBi) | Total Maximum<br>admissible<br>antenna gain<br>(dBi) |
|----------------------|-------------------------------------------------|---------------------------------------------------|------------------------------------------------------|
| WCDMA band II (1900) | 8.50                                            | 8.01                                              | 8.01                                                 |
| GSM1900              | 6.11                                            | 6.11                                              | 6.11                                                 |
| WCDMA band V (850)   | 6.12                                            | 6.12                                              | 6.12                                                 |
| GSM850               | 11.51                                           | 11.02                                             | 11.02                                                |

**Note:** Using frequency in 824~849MHz allows the use of antenna gain biggest 6.12 dBi.

Using frequency in 1850~1910MHz allows the use of antenna gain biggest 8.01dBi.

**\*\*\*\*\*END OF REPORT\*\*\*\*\***