

Test report No:
NIE: 80708RAN.004A1

Assessment report

RF EXPOSURE REPORT ACCORDING TO

FCC 47 CFR Part 2.1093

FCC 47 CFR Part 1.1307

| | |
|---|--|
| (*) Identification of item under evaluation | Headunit with Display and TP, USB, BT and WLAN |
| (*) Trademark | HARMAN |
| (*) Model and /or type reference | SPACE 4 BASE 1.1A |
| (*) Other identification of the product | FCC ID : T8GSPACE4B11 IC : 6434A-SPACE4B11 HW version : DV2 SW version: R11 |
| (*) Features | Bluetooth, WLAN |
| (*) Manufacturer | Harman Becker Automotive Systems GmbH BECKER-GOERING-STR. 16; 76307 KARLSBAD GERMANY |
| Test method requested, standard | FCC 47 CFR Part 2.1093. Radiofrequency radiation exposure evaluation: portable devices. FCC 47 CFR Part 1.1307: Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared. |
| Summary | IN COMPLIANCE |
| Approved by (name / position & signature) | Manuel García Antennas Lab Technical Responsible |
| Date of issue | 2024-12-18 |
| Report template No | FAN24_02 (*) "Data provided by the client" |

Index

Competences and guarantees3

General conditions3

Data provided by the client.....3

Identification of the client.....5

Document history5

Appendix A: FCC RF Exposure assessment result6

 General description of the device under evaluation7

 Evaluation Results.....8

Appendix B: FCC RF Exposure information10

 RF Exposure determination of exemption.....11

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "General description of the device", "Other identification of the product").
2. Maximum output power, maximum antenna gain and use distance information.
3. The device under evaluation consists of a Headunit with Display and TP, USB, BT and WLAN.
4. Software version clarification cover letter.

HARMAN AUTOMOTIVE DIVISION
HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH
BECKER-GÖRING-STRASSE 16
76307 KARLSBAD, GERMANY
E-MAIL: STEFAN.BLASCHKE@HARMAN.COM



Harman Becker Automotive Systems GmbH | Postfach 2260 | 76303 Karlsbad

To whom it may concern

Karlsbad, 27.11.2024

SW-Declaration for model: SPACE 4 BASE 1.1A

Dear Ladies and Gentlemen,

we, Harman Becker Automotive Systems GmbH herewith confirm, that the product used for RED/FCC testing had the following HW/SW configuration:

Model: SPACE 4 BASE 1.1A
HW: DV2
SW: R11

Hint: On the product label you can find the SW version "SW: RB09.1.1" – this was printed in the production, but before doing the measurements the units have been updated.

In case of any question please do not hesitate and contact us. Thank you

Regards




Stefan Blaschek
Regulatory Compliance Management

Harman Infotainment Division
Harman Becker Automotive Systems GmbH
Becker-Göring-Straße 16
76307 Karlsbad
Mobile: +49 172 94 191 49
Email: stefan.blaschek@harman.com
Web: www.harman.com



CONNECTED CAR | LIFESTYLE AUDIO
PROFESSIONAL SOLUTIONS | CONNECTED SERVICES



Simon Vögele
Regulatory Compliance Management

Harman Infotainment Division
Harman Becker Automotive Systems GmbH
Becker-Göring-Straße 16
76307 Karlsbad
Mobile: +49 175 4386188
Email: simon.voegel@harman.com
Web: www.harman.com



CONNECTED CAR | LIFESTYLE AUDIO
PROFESSIONAL SOLUTIONS | CONNECTED SERVICES

Sitz der Gesellschaft: Karlsbad | Amtsgericht Mannheim: HRB-Nr. 361395

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Identification of the client

HARMAN BECKER AUTOMOTIVE SYSTEMS GMBH
76307 KARLSBAD GERMANY BECKER-GOERING-STR. 16

Document history

| Report number | Date | Description |
|----------------|------------|--|
| 80708RAN.004 | 2024-12-10 | First release |
| 80708RAN.004A1 | 2024-12-18 | Second release. The SAR reference report has been updated. This test report cancels and replaces test report num 80708RAN.004. |

Appendix A: FCC RF Exposure assessment result

General description of the device under evaluation

Table 1 shows information used for the RF Evaluation, taking into account the following declared specifications for the device:

Description and technologies: the device under evaluation consists of a Headunit with Display and Tocuh panel (TP) with the following features: USB, BT and WLAN. For RF Exposure evaluation, only transmission technologies: BT and WLAN are taken into account.

RF Exposure assessment for WLAN technology have been already evaluated through SAR tests and results and compliance are stated in report DEKRA Testing and Certification, S.A.U. test report num. 80708RAN.002. Maximum measured values will be used for simultaneous transmission calculus as part of the RF Exposure assessment.

Evaluation Distance: The device is intended for use in both extremity and body exposure conditions. According to the manufacturer, the separation distance between the radiating structures of the device and nearby users will be greater than 0 cm for extremity exposure condition and 2 cm for body exposure condition. In order to perform the assessment, a conservative evaluation distance of 0 cm for extremity exposure condition and 2 cm for body exposure condition has been used.

Maximum output power:

Values corresponding to WLAN maximum output power have been declared by the device manufacturer (maximum output power values stated in manufacturer's technical description document).

Values corresponding to conducted output power for Bluetooth have been measured and stated into DEKRA Testing and Certification, S.A.U. test report num. 80708RRF.006.

Antennas: the device supports several antennas for the BT and WLAN transmitting technologies:

- "ANT 1" antenna for Bluetooth transmissions.
- "ANT 2" antenna for Bluetooth and Wi-Fi transmissions
- "ANT 3" antenna for Bluetooth transmissions.

Maximum peak antenna gain values have been declared by the device manufacturer (maximum peak gain stated in antenna manufacturer's datasheet)

The following table shows the information provided above:

| Technology / Mode | Operating Band | Frequency under evaluation (MHz) | Maximum Conducted Output Power (dBm) | Antenna peak gain (dBi) | Maximum E.R.P. (dBm) | Maximum E.R.P. (mW) | Maximum E.I.R.P. (dBm) | Maximum E.I.R.P. (mW) |
|-------------------|----------------|----------------------------------|--------------------------------------|-------------------------|----------------------|---------------------|------------------------|-----------------------|
| Bluetooth | 2.4 GHz | 2400 - 2483.5 | 3.49 | 0.34 | 1.68 | 1.47 | 3.83 | 2.42 |
| Bluetooth | 2.4 GHz | 2400 - 2483.5 | 2.98 | -0.40 | 0.43 | 1.10 | 2.58 | 1.81 |
| Bluetooth | 2.4 GHz | 2400 - 2483.5 | 2.07 | 1.37 | 1.29 | 1.35 | 3.44 | 2.21 |
| 802.11b/g/n | 2.4 GHz | 2412 - 2484 | 15.40 | -0.40 | 12.85 | 19.28 | 15.00 | 31.62 |
| 802.11a/n/ac | U-NII-1 | 5150 - 5250 | 9.30 | -0.40 | 6.75 | 4.73 | 8.90 | 7.76 |
| 802.11a/n/ac | U-NII-3 | 5650 - 5850 | 9.30 | -0.40 | 6.75 | 4.73 | 8.90 | 7.76 |

Table 1: Equipment specifications

Evaluation Results

Determination of Exemption according to FCC 47 CFR Part 1.1307:

The evaluation for body exposure condition according to the minimum intended use distance of 2 cm will be as follow:

| Technology / Mode | Operating Band | Frequency under evaluation (MHz) | Distance (cm) | Maximum Conducted Power (mW) | § 1.1307(b)(3).i.(B) Exposure Limit (mW) | Verdict |
|-------------------|----------------|----------------------------------|---------------|------------------------------|--|---------|
| 802.11b/g/n | 2.4 GHz | 2412 - 2484 | 2.00 | 34.67 | 38.07 | Pass* |
| 802.11a/n/ac | U-NII-1 | 5150 - 5250 | 2.00 | 8.51 | 26.19 | Pass* |
| 802.11a/n/ac | U-NII-3 | 5650 - 5850 | 2.00 | 8.51 | 24.81 | Pass* |
| Bluetooth | 2.4 GHz | 2400 - 2483.5 | 2.00 | 2.24 | 38.07 | Pass |
| Bluetooth | 2.4 GHz | 2400 - 2483.5 | 2.00 | 1.99 | 38.07 | Pass |
| Bluetooth | 2.4 GHz | 2400 - 2483.5 | 2.00 | 1.61 | 38.07 | Pass |

Table 2: FCC Exemption Evaluation Result for Body exposure condition

The evaluation for extremity exposure condition according to the minimum intended use distance of 0 cm (5mm applied for the evaluation) will be as follow:

| Technology / Mode | Operating Band | Frequency under evaluation (MHz) | Distance (cm) | Maximum Conducted Power (mW) | § 1.1307(b)(3).i.(B) Exposure Limit (mW) | Verdict |
|-------------------|----------------|----------------------------------|---------------|------------------------------|--|-------------|
| 802.11b/g/n | 2.4 GHz | 2412 - 2484 | 0.50 | 34.67 | 6.78 | SAR needed* |
| 802.11a/n/ac | U-NII-1 | 5150 - 5250 | 0.50 | 8.51 | 3.73 | SAR needed* |
| 802.11a/n/ac | U-NII-3 | 5650 - 5850 | 0.50 | 8.51 | 3.42 | SAR needed* |
| Bluetooth | 2.4 GHz | 2400 - 2483.5 | 0.50 | 2.24 | 6.79 | Pass |
| Bluetooth | 2.4 GHz | 2400 - 2483.5 | 0.50 | 1.99 | 6.79 | Pass |
| Bluetooth | 2.4 GHz | 2400 - 2483.5 | 0.50 | 1.61 | 6.79 | Pass |

Table 3: FCC Exemption Evaluation Result for Extremity exposure condition

The computed value(s) for Bluetooth are below the exemption limit(s), so these modes meet the requirements stated in FCC 47 CFR Part 1.1307.

*SAR testing for Body and extremity exposure conditions for WIFI technology has been completed, and the results are stated in the test report 80708RAN.003A1.

Simultaneous transmission assessment:

The device under evaluation is able to transmit simultaneously using Bluetooth and WIFI transmitters.

Maximum measured SAR values are stated into DEKRA Testing and Certification, S.A.U. test report num. 80708RAN.003A1, therefore the most conservative approach for the evaluation of the simultaneous transmission will be:

| Simultaneous technologies and modes | Exposure condition | Result (Σ of Pout/Pmax ratios) | Verdict ($\Sigma \leq 1$) |
|--|--------------------|---|--------------------------------|
| Bluetooth 2.4 GHz + Bluetooth 2.4 GHz + Bluetooth 2.4 GHz + WIFI 5 GHz | Body | 0.89 | Pass |
| Bluetooth 2.4 GHz + Bluetooth 2.4 GHz + Bluetooth 2.4 GHz + WIFI 5 GHz | Extremity | 0.91 | Pass |

Table 4: Simultaneous Result

Appendix B: FCC RF Exposure information

RF Exposure determination of exemption

According to FCC 47 CFR §1.1307 (b)(3) Determination of exemption:

(i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2), a single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

TABLE 1 TO §1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

| RF Source frequency (MHz) | Threshold ERP (watts) |
|---------------------------|-----------------------|
| 0.3-1.34 | $1,920 R^2$. |
| 1.34-30 | $3,450 R^2/f^2$. |
| 30-300 | $3.83 R^2$. |
| 300-1,500 | $0.0128 R^2 f$. |
| 1,500-100,000 | $19.2 R^2$. |

(ii) For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P_{th}, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

P_{th,i} = the exemption threshold power (P_{th}) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERP_j = the ERP of fixed, mobile, or portable RF source j.

ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

The available maximum time-averaged power or effective radiated power (ERP), can be calculated using the following formula to assess compliance with the Exemption Limits:

$$P_{E.I.R.P.} = P_T + G_T - L_C$$

Where:

P_T = transmitter time-averaged output power (including Duty Cycle and tune-up tolerance, if applicable)

G_T = gain of the transmitting antenna

L_C = signal attenuation in the connecting cable between the transmitter and the antenna if applicable

$$P_{E.R.P.} = P_{E.I.R.P.} - 2.15 \text{ dB}$$