

RADIATED EMISSIONS DATA SHEET

DATE: 9/05/02 TESTED BY: J. Fitzgerald APPROVED BY: _____

TEST SAMPLE (model): ADEMCO Receiver 5804BD-MX

TEST METHOD: ANSI C63.4 - 1992

TEST SPECIFICATION: FCC Part 15, Subpart C

NOTES: 1) $F_c = 345$ MHz, 2) Detector = Peak, 3) Frequency range scanned to
4 GHz. Emissions not reported were more than 20 dB below the specified limit.

[Meter reading + Cable/Amp factor + Antenna factor]
20

4) Conv. reading = 10

5) Corr. reading = Conv. reading X Duty cycle

FREQUENCY (MHz)	POLARITY (V / H)	METER READING (dB uV)	CABLE/AMP FACTOR (dB)	ANTENNA FACTOR (dB/M)	CONV. READING (uV/M)	DUTY CYCLE (%)	CORR. READING (uV/M)	LIMIT @ 3M (uV/M)
	H					NONE		
30								
↓								↓
334.3		12.0	1.5	16	29.85		29.85	200
↓								↓
668.5		4.8	2.1	21.1	25.7		25.1	200
↓								↓
10029		1.0	2.85	25.2	28.34		28.34	500
↓								↓
13372		0.5	3.0	28.8	41.2		41.2	500
↓								↓
16715	V	0.11	3.7	31.2	56.29		56.29	500
↓						V		↓

®ADEMCO

Alarm Device Manufacturing Company
A Division of Pittway Corporation
165 Eileen way
Syosset, NY 11791