



FCC PART 15B REPORT

Report No: STS1412037E01

Issued for

UNNECTO HOLDING LIMITED

ROOM 1501(445),15/F., SPA CENTRE,53-55 LOCKHART ROAD,WANCHAI,HONGKONG

Product Name:	3G MOBILE PHONE
Brand Name:	unnecto M
Model No.:	U903
Series Model:	N/A
FCC ID:	2ADR3U903
Test Standard:	FCC Part 15B

Any reproduction of this document must be done in full. No single part of this document may be reprede permission from STS, All Test Data Presented in this report is only applicable to presented Test sample



Shenzhen STS Test Services Co., Ltd. 1/F, Building B, Zhuoke Science Park, Chongqing Road, Fuyong, Baoan District, Shenzhen, China TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com

Report No.: STS1412037E01



TEST RESULT CERTIFICATION

Applicant's name	UNNECTO HOLDING LIMITED
Address	ROOM 1501(445),15/F., SPA CENTRE,53-55 LOCKHART ROAD,WANCHAI,HONGKONG
Manufacture's Name	SHENZHEN UNI-ONE ELECTRONIC CO.,LTD
Address	5/F,Bldg A2,Kexing Science Park,Keyuan Rd.,Hi-Tech Park Shenzhen,P.R.China
Product description	
Product name	3G MOBILE PHONE
Band name	unnecto ™
Model and/or type reference	U903
Standards	FCC Part 15B
Test procedure	ANSI C63.4-2009
This device described above has under test (EUT) is in compliance sample identified in the report.	s been tested by STS, and the test results show that the equipment se with the FCC requirements. And it is applicable only to the tested
may be altered or revised by ST	S, personal only, and shall be noted in the revision of the document.

Date of Test

Date of performance of tests 15 Dec. 2014 ~23 Dec. 2014

Date of Issue 25 Dec. 2014

Test Result..... Pass

Testing Engineer

1

Technical Manager

mm

(Tony Liu)

(Vita Li)

Authorized Signatory :

howy

(Bovey Yang)



Table of Contents

Page

1. SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	4
1.2 MEASUREMENT UNCERTAINTY	4
2. GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 DESCRIPTION OF TEST MODES	6
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	6
2.4 DESCRIPTION OF SUPPORT UNITS	7
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	8
3. EMC EMISSION TEST	9
3.1 CONDUCTED EMISSION MEASUREMENT 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS 3.1.2 TEST PROCEDURE	9 9 10
3.1.3 DEVIATION FROM TEST STANDARD	10
3.1.4 TEST SETUP	10
3.1.6 TEST RESULTS	11
3.2 RADIATED EMISSION MEASUREMENT 3.2.1 RADIATED EMISSION LIMITS 3.2.2 TEST PROCEDURE 3.2.3 DEVIATION FROM TEST STANDARD 3.2.4 TEST SETUP 3.2.5 EUT OPERATING CONDITIONS 3.2.6 TEST RESULTS	13 13 14 14 15 16 17
4. PHOTOS OF TEST SETUP	21



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

EMISSION						
Standard Item Result Remarks						
FCC 47 CFR Part 15 Subpart B (10-1-05 Edition)	Conducted Emission	PASS	Meet Class B limit			
	Radiated Emission	PASS	Meet Class B limit			

NOTE:

(1)" unnecto [™] " denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen STS Test Services Co., Ltd. Add.: 1/F, Building 2, Zhuoke Science Park, Chongqing Road, Fuyong, Baoan District, Shenzhen, China. FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y \pm U , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $\$ k=2 , providing a level of confidence of approximately 95 % $^{\circ}$

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated (<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	3G MOBILE PHONE	
Trade Name	unnecto ™	
Model Name	U903	
Serial Model	N/A	
Model Difference	N/A	
Channel List	Please refer to the Note 2.	
Adamtan	Input:AC 100-240V,50/60Hz,180mA	
Adapter	Output:DC 5V,1000mA	
	Rated Voltage: 3.8V	
Battery	Charge Limit: 4.35V	
	capacity :1900mAh	
Hardware version number	UH09_MB_V0.1 2014-11-11	
Software versioning number	ALPS.KK1.MP1.V2.10	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.





2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	USB Model
Mode 2	MP3/MP4 Mode
Mode 3	Idle Mode

For Conducted Emission		
Final Test Mode	Description	
Mode1	USB Model	

For Radiated Emission			
Final Test Mode Description			
Mode 1	USB Model		

Note:

(1) Due to the different configuration and test, in this list only some worse mode. The worst test data of the worse modeis reported by this report.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED





2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	3G MOBILE PHONE	unnecto ™	U903	N/A	EUT
E-2	Notebook	Lenovo	B460	WB03928113	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.5m	
C-2	NO	NO	1.2m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in ^[] Length ^[] column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Universal Radio Communication Tester	R&S	CMU200	112012	2014.10.25	2015.10.24
Bilog Antenna	TESEQ	CBL6111D	34678	2014.10.25	2015.10.24
Test Cable	N/A	R-01	N/A	2014.10.25	2015.10.24
Test Cable	N/A	R-02	N/A	2014.10.25	2015.10.24
EMI Test Receiver	R&S	ESCI	101427	2014.10.25	2015.10.24
Antenna Mast	EM	SC100_1	N/A	N/A	N/A
Turn Table	EM	SC100	060531	N/A	N/A
50Ω Switch	Anritsu Corp	MP59B	6200983705	2014.07.06	2015.07.05
Spectrum Analyzer	Aglient	E4407B	MY50140340	2014.10.25	2015.10.24
Horn Antenna	Schwarbeck	BBHA 9120D	9120D-963	2014.10.25	2015.10.24
Pre-Amplifier	DASY 5	NO. WL-42W	9638	2014.10.25	2015.10.24

Radiation Test equipment

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESPI	102086	2014.10.25	2015.10.24
LISN	R&S	ENV216	101242	2014.10.25	2015.10.24
LISN	EMCO	3810/2NM	000-23625	2014.10.25	2015.10.24
Absorbing clamp	R&S	MDS-21	100668	2014.10.27	2015.10.26
Temperature & Humitidy Chamber	Mieo	HH660	N/A	2014.10.27	2015.10.26
Conduction Cable	EM	C01	N/A	2014.10.25	2015.10.24
Clamp Cable	EM	C02	N/A	2014.10.25	2015.10.24



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits

	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	Stanuaru
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.6 TEST RESULTS

EUT :	3G MOBILE PHONE	Model Name. :	U903
Temperature :	26 ℃	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter with AC 120V/60Hz	Test Mode :	Mode 1

Frequency	Reading	Correct	Result	Limit	Margin	Bomork
(MHz)	(dBuV)	Factor(dB)	(dBuV)	(dBuV)	(dB)	Remark
0.1750	25.73	10.45	36.18	64.72	-28.54	QP
0.1750	18.50	10.45	28.95	54.72	-25.77	AVG
0.3311	30.47	10.42	40.89	59.42	-18.53	QP
0.3311	23.52	10.42	33.94	49.42	-15.48	AVG
0.4938	35.76	10.40	46.16	56.10	-9.94	QP
0.4938	25.56	10.40	35.96	46.10	-10.14	AVG
0.6010	34.66	10.41	45.07	56.00	-10.93	QP
0.6010	24.44	10.41	34.85	46.00	-11.15	AVG
2.0112	26.68	10.42	37.10	56.00	-18.90	QP
2.0112	18.53	10.42	28.95	46.00	-17.05	AVG
17.7637	21.35	10.72	32.07	60.00	-27.93	QP
17.7637	13.67	10.72	24.39	50.00	-25.61	AVG



1/F, Building B, Zhuoke Science Park, Chongqing Road, Fuyong, Bao'an District, Shenzhen, China Tel: 0755-36886288 Fax: 0755-36886277 Http://www.stsapp.com E-mail: sts@stsapp.com



Report No.: STS1412037E01

EUT :	3G MOBIL	3G MOBILE PHONE		lame. :	U903	
Temperature :	26 ℃	26 ℃		e Humidity :	54%	
Pressure :	1010hPa		Phase :		N	
Test Voltage :	DC 5V from 120V/60Hz	h Adapter with A	C Test Mo	de :	Mode 1	
						1
Frequency	Reading	Correct	Result	Limit	Margin	Romark
(MHz)	(dBuV)	Factor(dB)	(dBuV)	(dBuV)	(dB)	Remark
0.4331	33.23	10.41	43.64	57.19	-13.55	QP
0.4331	19.93	10.41	30.34	47.19	-16.85	AVG
0.5420	36.13	10.41	46.54	56.00	-9.46	QP
0.5420	23.41	10.41	33.82	46.00	-12.18	AVG
0.6575	32.74	10.40	43.14	56.00	-12.86	QP
0.6575	18.48	10.40	28.88	46.00	-17.12	AVG
0.7954	33.27	10.42	43.69	56.00	-12.31	QP
0.7954	22.09	10.42	32.51	46.00	-13.49	AVG
1.3893	28.73	10.45	39.18	56.00	-16.82	QP
1.3893	16.03	10.45	26.48	46.00	-19.52	AVG
18.0992	25.40	10.75	36.15	60.00	-23.85	QP
18.0992	17.05	10.75	27.80	50.00	-22.20	AVG



Shenzhen STS Test Services Co., Ltd.

1/F, Building B, Zhuoke Science Park, Chongqing Road, Fuyong, Bao'an District, Shenzhen, China Tel: 0755-36886288 Fax: 0755-36886277 Http://www.stsapp.com E-mail: sts@stsapp.com



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 Radiated Emission Limits

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

	Class A (dBu	ıV/m) (at 3M)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54
Notoo				

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



Report No.: STS1412037E01

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier harmonic(Peak/AV)
RB / VB (emission in restricted	
band)	

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz/RB 120kHz for QP

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 1 meter above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 1 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD No deviation



3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





Page 16 of 22

(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.





3.2.6 TEST RESULTS

Below 30MHz

EUT :	3G MOBILE PHONE	Model Name. :	U903			
Temperature :	20 ℃	Relative Humidity :	48%			
Pressure :	1010 hPa	Polarization :				
Test Voltage :	DC 5V from Adapter AC 120V/60Hz					
Test Mode :	Mode 1					

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



Shenzhen STS Test Services Co., Ltd.



Between 30MHz – 1000 MHz

-						
EUT :	3G MOBILE PHONE	Model Name. :	U903			
Temperature :	20 ℃	Relative Humidity :	48%			
Pressure :	1010 hPa	Polarization :	Horizontal			
Test Voltage :	DC 5V from Adapter AC 120V/60Hz					
Test Mode :	Mode 1					

Frequency	Reading	Correct	Result	Result Limit		Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
31.2893	6.90	18.29	25.19	40.00	-14.81	QP
61.1316	11.81	5.71	17.52	40.00	-22.48	QP
95.0930	7.21	10.31	17.52	43.50	-25.98	QP
181.2834	9.90	10.41	20.31	43.50	-23.19	QP
261.0583	7.75	15.36	23.11	46.00	-22.89	QP
400.4320	8.25	18.84	27.09	46.00	-18.91	QP

Remark:





Report No.: STS1412037E01

EUT :	3G MOBILE PHONE	Model Name. :	U903			
Temperature :20 °CRelative Humidity :		Relative Humidity :	48%			
Pressure :	essure : 1010 hPa Polarization :		Vertical			
Test Voltage :	DC 5V from Adapter AC 120V/60Hz					
Test Mode :	Mode 1					

Frequency	Reading	Correct	Result	Limit	Margin	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
30.0000	15.61	18.95	34.56	40.00	-5.44	QP
39.4371	20.54	14.10	34.64	40.00	-5.36	QP
99.8777	10.12	10.90	21.02	43.50	-22.48	QP
136.9391	10.01	12.86	22.87	43.50	-20.63	QP
168.4138	11.22	11.01	22.23	43.50	-21.27	QP
375.9385	9.13	17.63	26.76	46.00	-19.24	QP

Remark:







Above 1GHz

The worst test data above 1 GHz was showed as thefollow:

EUT :	3G MOBILE PHONE	Model Name. :	U903				
Temperature :	20 ℃	Relative Humidity :	48%				
Pressure :	1010 hPa	Test Mode :	Mode 1				
Test Voltage : DC 5V from Adapter AC 120V/60Hz							

Freq.	Ant. Pol	Peak	AV	Ant./CL	∧ cti	Actual Ec		AV	Peak	AV
(MHz)	H/V	Reading	Reading	CF	Actual FS		Limit	Limit	margin	margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)
					(dBuV/m)	(dBuV/m)				
1097.22	Н	57.31	41.32	5.15	62.46	46.47	74	54	-11.54	-7.53
2866.4	Н	52.33	38.24	9.45	61.78	47.69	74	54	-12.22	-6.31
N/A										
1069.22	V	52.18	37.55	5.15	57.33	42.7	74	54	-16.67	-11.3
2896.40	V	49.36	32.14	9.45	58.81	41.59	74	54	-15.19	-12.41
N/A										

Notes:

- 1. Measuring frequencies from 1 GHz to 6GHz.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode of the emission shown in Actual FS column.
- 3. The frequency that above 3GHz is mainly from the environment noise.





4. PHOTOS OF TEST SETUP



Page 21 of 22

Above 1GHz



Shenzhen STS Test Services Co., Ltd.

1/F, Building B, Zhuoke Science Park, Chongqing Road, Fuyong, Bao'an District, Shenzhen,China Tel: 0755-36886288 Fax: 0755-36886277 Http://www.stsapp.com E-mail: sts@stsapp.com



Page 22 of 22

Conducted Measurement Photos





Shenzhen STS Test Services Co., Ltd.

1/F, Building B, Zhuoke Science Park, Chongqing Road, Fuyong, Bao'an District, Shenzhen, China Tel: 0755-36886288 Fax: 0755-36886277 Http://www.stsapp.com E-mail: sts@stsapp.com