

RF EXPOSURE REPORT

for

Model Number: MS49SF2
MS49S1, MS49SF5, MS49series

FCC ID: 2ABU6-MS49SF2

Prepared for : Shenzhen Minew Technologies Co., Ltd
3th Floor, I Building, Gangzhilong Science Park, Qinglong Road,
Address : Longhua District, Shenzhen City, China

Prepared by : Shenzhen BCTC Technology Co., Ltd.
Address : No.101,Yousong Road, Longhua New District,
Shenzhen,China

1. RF EXPOSURE EVALUATION

Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V06, FCC 47CFR § 2.1093 the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right]$$

* $[\sqrt{f(\text{GHz})}]$

	tune up power tolerance (dBm)	Maximum Tune up output power (dBm)	max. output power(mW)	Separation distance mm	RF exposure
GFSK	1 ± 1	2	1.58	5	0.49

The Max RF exposure is 0.49.

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion:

So no SAR is required.