

FCC §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart subpart 1.1310 and 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:**Model: L1563****2.4G Wi-Fi&BLE&BT:**

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412-2462	2.19	1.66	25.00	251.19	20	0.0829	1.0
802.11g		2.19	1.66	24.00	100.00	20	0.0330	1.0
802.11n-HT20		2.19	1.66	20.00	79.43	20	0.0262	1.0
802.11n-HT40	2422-2452	2.19	1.66	19.00	316.23	20	0.1044	1.0
BLE(1Mbps)	2402-2480	2.19	1.66	-0.50	0.89	20	0.0003	1.0
BLE(2Mbps)	2402-2480	2.19	1.66	-0.50	0.89	20	0.0003	1.0
BT	2402-2480	2.19	1.66	10.00	10.00	20	0.0033	1.0

GSM:

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
GPRS 850	824-849	1.46	1.40	27.50	562.34	20	0.1566	0.55
EGPRS 850	824-849	1.46	1.40	19.74	94.19	20	0.0262	0.55
GPRS 1900	1850-1910	2.23	1.67	23.50	223.87	20	0.0744	1.00
EGPRS 1900	1850-1910	2.23	1.67	20.24	105.68	20	0.0351	1.00

Note 1:

GPRS 850: Tune-up maximum output power with 1 slot is 33.50 dBm, 2 slots is 33.00 dBm, 3 slots is 31.50 dBm, 4 slots is 30.50 dBm, so the tune-up time based Ave. power compared to slotted Ave. power is 27.50dBm.

EGPRS 850: Tune-up maximum output power with 1 slot is 27.00 dBm, 2 slots is 25.50 dBm, 3 slots is 24.00 dBm, 4 slots is 22.50 dBm, so the tune-up time based Ave. power compared to slotted Ave. power is 19.74dBm.

GPRS 1900: Tune-up maximum output power with 1 slot is 29.50 dBm, 2 slots is 28.50 dBm, 3 slots is 27.50 dBm, 4 slots is 26.50 dBm, so the tune-up time based Ave. power compared to slotted Ave. power is 23.50 dBm.

EGPRS 1900: Tune-up maximum output power with 1 slot is 26.50 dBm, 2 slots is 25.50 dBm, 3 slots is 24.50 dBm, 4 slots is 22.50 dBm, so the tune-up time based Ave. power compared to slotted Ave. power is 20.24 dBm.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.26 dB	-3 dB

5G Wi-Fi/WCDMA/LTE:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11a	5150~5250	0.05	1.01	18.50	70.79	20	0.0142	1.0
	5725~5850	0.05	1.01	19.00	79.43	20	0.0160	1.0
802.11ac20	5150~5250	0.05	1.01	21.00	125.89	20	0.0253	1.0
	5725~5850	0.05	1.01	22.00	158.49	20	0.0318	1.0
802.11n20	5150~5250	0.05	1.01	21.50	141.25	20	0.0284	1.0
	5725~5850	0.05	1.01	22.00	158.49	20	0.0318	1.0
802.11ac40	5150~5250	0.05	1.01	15.50	35.48	20	0.0071	1.0
	5725~5850	0.05	1.01	21.00	125.89	20	0.0253	1.0
802.11n40	5150~5250	0.05	1.01	15.50	35.48	20	0.0071	1.0
	5725~5850	0.05	1.01	22.00	158.49	20	0.0318	1.0
802.11ac80	5150~5250	0.05	1.01	11.00	12.59	20	0.0025	1.0
	5725~5850	0.05	1.01	21.50	141.25	20	0.0284	1.0
WCDMA Band II	1850-1910	2.23	1.67	22.50	177.83	20	0.0591	1.0
WCDMA Band V	824-849	1.46	1.40	22.50	177.83	20	0.0495	0.55
LTE Band 2	1850-1910	2.23	1.67	23.50	223.87	20	0.0744	1.0
LTE Band 4	1710-1755	2.23	1.67	23.00	199.53	20	0.0663	1.0
LTE Band 5	824-849	1.46	1.40	23.00	199.53	20	0.0556	0.55
LTE Band 7	2500-2570	2.03	1.60	22.50	177.83	20	0.0566	1.0
LTE Band 38	2570-2620	2.03	1.60	22.50	177.83	20	0.0566	1.0
LTE Band 40 Lower	2305-2315	2.03	1.60	22.50	177.83	20	0.0566	1.0
LTE Band 40 Upperr	2350-2360	2.03	1.60	22.50	177.83	20	0.0566	1.0
LTE Band 41	2555-2655	2.03	1.60	22.50	177.83	20	0.0566	1.0

Note:

1. For the above tune up power were declared by the manufacturer.
2. Wi-Fi and BT/BLE cannot transmit simultaneously.
3. For 802.11b, 802.11g, 802.11a, the tune-up power is base on SISO mode
For 802.11ac20/n20/n40/ac40/ac80, the tune-up power is base on MIMO mode
4. Wi-Fi & GPRS/WCDMA/LTE or BT/BLE & GPRS/WCDMA/LTE can transmit simultaneously; the worst condition is 2.4G Wi-Fi & GPRS 850 as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0829/1.00 + 0.1566/0.55 = 0.3676 < 1.0$$

Conclusion: The device meets MPE at distance 20cm.

Model: L1573**2.4G Wi-Fi&BLE&BT:**

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412-2462	0.66	1.16	25.00	316.23	20	0.0730	1.0
802.11g		0.66	1.16	24.00	251.19	20	0.0580	1.0
802.11n-HT20		0.66	1.16	20.00	100.00	20	0.0231	1.0
802.11n-HT40	2422-2452	0.66	1.16	19.00	79.43	20	0.0183	1.0
BLE(1Mbps)	2402-2480	0.19	1.04	-0.50	0.89	20	0.0002	1.0
BLE(2Mbps)	2402-2480	0.19	1.04	-0.50	0.89	20	0.0002	1.0
BT	2402-2480	0.19	1.04	10.00	10.00	20	0.0021	1.0

GSM:

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
GPRS 850	824-849	1.24	1.33	27.50	562.34	20	0.1488	0.55
EGPRS 850	824-849	1.24	1.33	19.74	94.19	20	0.0249	0.55
GPRS 1900	1850-1910	1.22	1.32	23.50	223.87	20	0.0588	1.00
EGPRS 1900	1850-1910	1.22	1.32	20.24	105.68	20	0.0277	1.00

Note 1:

GPRS 850: Tune-up maximum output power with 1 slot is 33.50 dBm, 2 slots is 33.00 dBm, 3 slots is 31.50 dBm, 4 slots is 30.50 dBm, so the tune-up time based Ave. power compared to slotted Ave. power is 27.50dBm.

EGPRS 850: Tune-up maximum output power with 1 slot is 27.00 dBm, 2 slots is 25.50 dBm, 3 slots is 24.00 dBm, 4 slots is 22.50 dBm, so the tune-up time based Ave. power compared to slotted Ave. power is 19.74dBm.

GPRS 1900: Tune-up maximum output power with 1 slot is 29.50 dBm, 2 slots is 28.50 dBm, 3 slots is 27.50 dBm, 4 slots is 26.50 dBm, so the tune-up time based Ave. power compared to slotted Ave. power is 23.50 dBm.

EGPRS 1900: Tune-up maximum output power with 1 slot is 26.50 dBm, 2 slots is 25.50 dBm, 3 slots is 24.50 dBm, 4 slots is 22.50 dBm, so the tune-up time based Ave. power compared to slotted Ave. power is 20.24 dBm.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.26 dB	-3 dB

5G Wi-Fi/WCDMA/LTE:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11a	5150~5250	1.57	1.44	18.50	70.79	20	0.0203	1.0
	5725~5850	-0.79	0.83	19.00	79.43	20	0.0131	1.0
802.11ac20	5150~5250	1.57	1.44	21.00	125.89	20	0.0361	1.0
	5725~5850	-0.79	0.83	22.00	158.49	20	0.0262	1.0
802.11n20	5150~5250	1.57	1.44	21.50	141.25	20	0.0405	1.0
	5725~5850	-0.79	0.83	22.00	158.49	20	0.0262	1.0
802.11ac40	5150~5250	1.57	1.44	15.50	35.48	20	0.0102	1.0
	5725~5850	-0.79	0.83	21.00	125.89	20	0.0208	1.0
802.11n40	5150~5250	1.57	1.44	15.50	35.48	20	0.0102	1.0
	5725~5850	-0.79	0.83	22.00	158.49	20	0.0262	1.0
802.11ac80	5150~5250	1.57	1.44	11.00	12.59	20	0.0036	1.0
	5725~5850	-0.79	0.83	21.50	141.25	20	0.0233	1.0
WCDMA Band II	1850-1910	1.22	1.32	22.50	177.83	20	0.0467	1.0
WCDMA Band V	824-849	1.24	1.33	22.50	177.83	20	0.0470	0.55
LTE Band 2	1850-1910	1.22	1.32	23.50	223.87	20	0.0588	1.0
LTE Band 4	1710-1755	2.19	1.66	23.00	199.53	20	0.0659	1.0
LTE Band 5	824-849	1.24	1.33	23.00	199.53	20	0.0528	0.55
LTE Band 7	2500-2570	2.17	1.65	22.50	177.83	20	0.0584	1.0
LTE Band 38	2570-2620	1.47	1.40	22.50	177.83	20	0.0495	1.0
LTE Band 40 Lower	2305-2315	2.06	1.61	22.50	177.83	20	0.0570	1.0
LTE Band 40 Upperr	2350-2360	2.49	1.77	22.50	177.83	20	0.0626	1.0
LTE Band 41	2555-2655	1.47	1.40	22.50	177.83	20	0.0495	1.0

Note:

1. For the above tune up power were declared by the manufacturer.
2. Wi-Fi and BT/BLE cannot transmit simultaneously.
3. For 802.11b, 802.11g, 802.11a, the tune-up power is base on SISO mode
For 802.11ac20/n20/n40/ac40/ac80, the tune-up power is base on MIMO mode
4. Wi-Fi & GPRS/WCDMA/LTE or BT/BLE & GPRS/WCDMA/LTE can transmit simultaneously; the worst condition is 2.4G Wi-Fi & GPRS 850 as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0730/1.00 + 0.1488/0.55 = 0.3436 < 1.0$$

Conclusion: The device meets MPE at distance 20cm.