

FCC TEST REPORT

For

Shen Zhen Simagic Technology Co., Limited

Direct drive force-feedback simwheel

Test Model: M10-SR

Additional Model No.: Please Refer to Page 6

Prepared for : Shen Zhen Simagic Technology Co., Limited
Address : No.302, building 7, DCC cultural and creative park, No. 95,
Pingxin North Road, shangmugu community, Pinghu street,
Longgang District, Shenzhen

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing
Street, Baoan District, Shenzhen, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 27, 2020
Number of tested samples : 1
Serial number : Prototype
Date of Test : May 27, 2020 ~ June 03, 2020
Date of Report : June 05, 2020

**FCC TEST REPORT
FCC CFR 47 PART 18**

Report Reference No. : **LCS200509061AEB**

Date Of Issue : June 05, 2020

Testing Laboratory Name..... : **Shenzhen LCS Compliance Testing Laboratory Ltd.**

Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China

Testing Location/ Procedure : Full application of Harmonised standards
 Partial application of Harmonised standards
 Other standard testing method

Applicant's Name : **Shen Zhen Simagic Technology Co.,Limited**

Address : No.302, building 7, DCC cultural and creative park, No. 95, Pingxin North Road, shangmugu community, Pinghu street, Longgang District, Shenzhen

Test Specification

Standard..... : FCC CFR 47 PART 18

Test Report Form No...... : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : **Direct drive force-feedback simwheel**

Trade Mark : N/A

Test Model..... : M10-SR

Power Supply : Input: AC 100-240V, 50-60Hz, 240W
 Output : DC 24V, 10A


Result : **Positive**

Compiled by:



Jayden Zhuo/ Administrators

Supervised by:



Jin Wang/ Technique principal

Approved by:



Gavin Liang/ Manager

FCC TEST REPORT

| | |
|---|---------------------------------------|
| Test Report No. : LCS200509061AEB | <u>June 05, 2020</u> Date of issue |
|---|---------------------------------------|

| |
|---|
| Test Model..... : M10-SR EUT..... : Direct drive force-feedback simwheel |
| Applicant..... : Shen Zhen Simagic Technology Co.,Limited No.302, building 7, DCC cultural and creative park, No. 95, Address..... : Pingxin North Road, shangmugu community, Pinghu street, Longgang District, Shenzhen Telephone..... : / Fax..... : / |
| Manufacturer..... : Shen Zhen Simagic Technology Co.,Limited No.302, building 7, DCC cultural and creative park, No. 95, Address..... : Pingxin North Road, shangmugu community, Pinghu street, Longgang District, Shenzhen Telephone..... : / Fax..... : / |
| Factory..... : Shen Zhen Simagic Technology Co.,Limited No.302, building 7, DCC cultural and creative park, No. 95, Address..... : Pingxin North Road, shangmugu community, Pinghu street, Longgang District, Shenzhen Telephone..... : / Fax..... : / |

| | |
|--------------------|-----------------|
| Test Result | Positive |
|--------------------|-----------------|

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

| Revision | Issue Date | Revisions | Revised By |
|----------|---------------|---------------|-------------|
| 000 | June 05, 2020 | Initial Issue | Gavin Liang |
| | | | |
| | | | |

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. GENERAL INFORMATION..... | 6 |
| 1.1 Description of Device (EUT)..... | 6 |
| 1.2 Support equipment List..... | 6 |
| 1.3 External I/O Cable | 6 |
| 1.4 Description of Test Facility | 7 |
| 1.5 Statement of the Measurement Uncertainty | 7 |
| 1.6 Measurement Uncertainty | 7 |
| 1.7 Description of Test Modes..... | 8 |
| 2. TEST METHODOLOGY | 9 |
| 2.1 EUT Configuration | 9 |
| 2.2 EUT Exercise..... | 9 |
| 2.3 General Test Procedures..... | 9 |
| 2.3.1 Conducted Emissions | 9 |
| 2.3.2 Radiated Emissions | 9 |
| 3. SYSTEM TEST CONFIGURATION..... | 10 |
| 3.1 Justification | 10 |
| 3.2 EUT Exercise Software..... | 10 |
| 3.3 Special Accessories | 10 |
| 3.4 Block Diagram/Schematics | 10 |
| 3.5 Equipment Modifications..... | 10 |
| 3.6 Test Setup..... | 10 |
| 4. SUMMARY OF TEST EQUIPMENT | 11 |
| 5. SUMMARY OF TEST RESULT..... | 12 |
| 6. POWER LINE CONDUCTED MEASUREMENT..... | 13 |
| 7. RADIATED EMISSION MEASUREMENT..... | 16 |
| 7.1. Block Diagram of Test Setup | 16 |
| 7.2. Radiated Emission Limit | 17 |
| 7.3. EUT Configuration on Measurement | 17 |
| 7.4. Operating Condition of EUT | 17 |
| 7.5. Measuring Setting..... | 17 |
| 7.6. Test Procedure..... | 18 |
| 7.7. Test Results..... | 19 |
| 8. PHOTOGRAPHS OF TEST SETUP..... | 23 |
| 9. EXTERNAL PHOTOGRAPHS OF THE EUT..... | 23 |
| 10. INTERNAL PHOTOGRAPHS OF THE EUT..... | 23 |

1. GENERAL INFORMATION

1.1 Description of Device (EUT)

EUT : Direct drive force-feedback simwheel

Test Model : M10-SR

Additional Model No : M10-SDC, M10-GT4, M10-GT4C, M10

Model Declaration : PCB board, structure and internal of these model(s) are the same,
: So no additional models were tested

Power Supply : Input: AC 100-240V, 50-60Hz, 240W
: Output : DC 24V, 10A

Hardware Version : V1.1

Software Version : 4031

2.4G Emission:

Frequency Range : 2402MHz-2480MHz

Channel Number : 40

Modulation Type : GFSK

Antenna Description : PCB Antenna, 0dBi

2.4G Receive:

Frequency Range : 2402MHz-2480MHz

Channel Number : 40

Modulation Type : GFSK

Antenna Description : PCB Antenna, 0dBi

Wireless Charging :

Operating Frequency : 110.0~205.0KHz

Modulation Type : Continuous Wave

Antenna Type : Coil Antenna, 0dBi

1.2 Support equipment List

| Manufacturer | Description | Model | Serial Number | Certificate |
|--------------|-------------|-------|---------------|-------------|
| --- | --- | --- | --- | --- |

1.3 External I/O Cable

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-------|
| --- | --- | --- |

1.4 Description of Test Facility

- FCC Registration Number is 254912.
- Industry Canada Registration Number is 9642A.
- EMSD Registration Number is ARCB0108.
- UL Registration Number is 100571-492.
- TUV SUD Registration Number is SCN1081.
- TUV RH Registration Number is UA 50296516-001.
- NVLAP Accreditation Code is 600167-0.
- FCC Designation Number is CN5024.
- CAB identifier: CN0071

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6 Measurement Uncertainty

| Test Item | Frequency Range | Uncertainty | Note |
|------------------------|-----------------|-------------|------|
| Radiation Uncertainty | 9KHz~30MHz | 3.10dB | (1) |
| | 30MHz~200MHz | 2.96dB | (1) |
| | 200MHz~1000MHz | 3.10dB | (1) |
| | 1GHz~26.5GHz | 3.80dB | (1) |
| | 26.5GHz~40GHz | 3.90dB | (1) |
| Conduction Uncertainty | 150kHz~30MHz | 1.63dB | (1) |
| Power disturbance | 30MHz~300MHz | 1.60dB | (1) |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7 Description of Test Modes

Equipment under test was operated during the measurement under the following conditions:

Charging and communication mode

Modulation Type: CW (Continuous Wave)

| Test Modes | | |
|------------|--|------------|
| Mode 1 | AC/DC Adapter (5V/2.4A) + EUT+ Mobile Phone (Battery Status: <1%) | Record |
| Mode 2 | AC/DC Adapter (5V/2.4A) + EUT+ Mobile Phone (Battery Status: <50%) | Pre-tested |
| Mode 3 | AC/DC Adapter (5V/2.4A) + EUT+ Mobile Phone (Battery Status: 100%) | Pre-tested |
| Mode 4 | PC Charger + EUT+ Mobile Phone (Battery Status: <1%) | Pre-tested |
| Mode 5 | PC Charger + EUT+ Mobile Phone (Battery Status: <50%) | Pre-tested |
| Mode 6 | PC Charger + EUT+ Mobile Phone (Battery Status: 100%) | Pre-tested |

Note: All test modes were pre-tested, but we only recorded the worst case in this report.

For AC conducted emission, pre-test at both AC 120V/60Hz and AC 240V/50Hz, recorded worst case;

For AC conducted emission, pre-test at both AC charge from power adapter modes, recorded worst case.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with MP-5, and FCC CFR PART 18.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT was operated in the charging and compunction mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 18.305 and 18.307 under the FCC Rules Part 18.

2.3 General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in FCC MP-5 for Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in FCC MP-5 for radiated emission.

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a normal condition.

3.2 EUT Exercise Software

N/A.

3.3 Special Accessories

N/A.

3.4 Block Diagram/Schematics

Please refer to the related document.

3.5 Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6 Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST EQUIPMENT

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|--------------------------|----------------|--------------|-----------------|------------|------------|
| 1 | MXA Signal Analyzer | Agilent | N9020A | MY49100040 | 2019-06-11 | 2020-06-10 |
| 2 | SPECTRUM ANALYZER | R&S | FSP40 | 100503 | 2019-11-14 | 2020-11-13 |
| 3 | 3m Semi Anechoic Chamber | SIDT FRANKONIA | SAC-3M | 03CH03-HY | 2019-06-12 | 2020-06-11 |
| 4 | Positioning Controller | MF | MF-7082 | / | 2019-06-12 | 2020-06-11 |
| 5 | EMI Test Software | EZ | EZ-EMC | / | N/A | N/A |
| 6 | EMI Test Receiver | R&S | ESR 7 | 101181 | 2019-06-12 | 2020-06-11 |
| 7 | Active Loop Antenna | SCHWARZBECK | FMZB 1519B | 00005 | 2018-07-26 | 2021-07-25 |
| 8 | By-log Antenna | SCHWARZBECK | VULB9163 | 9163-470 | 2018-07-26 | 2021-07-25 |
| 9 | Horn Antenna | SCHWARZBECK | BBHA 9120D | 9120D-1925 | 2018-07-02 | 2021-07-01 |
| 10 | RF Cable-R03m | Jye Bao | RG142 | CB021 | 2019-06-12 | 2020-06-11 |
| 11 | RF Cable-HIGH | SUHNER | SUCOFLEX 106 | 03CH03-HY | 2019-06-12 | 2020-06-11 |
| 12 | EMI Test Receiver | R&S | ESPI | 101840 | 2019-06-11 | 2020-06-10 |
| 13 | Artificial Mains | R&S | ENV216 | 101288 | 2019-06-12 | 2020-06-11 |
| 14 | 10dB Attenuator | SCHWARZBECK | MTS-IMP-136 | 261115-001-0032 | 2019-06-11 | 2020-06-10 |

Note: All equipment is calibrated through CHINA CEPREI LABORATORY and GUANGZHOU LISAI CALIBRATION AND TEST CO., LTD.

5. SUMMARY OF TEST RESULT


| Test Item | FCC Rule No. | Temperature conditions | Power source conditions | C | NC | NA | NP | Remark |
|-----------------------|--------------|------------------------|-------------------------|-------------------------------------|--------------------------|--------------------------|--------------------------|--------|
| Radiated Emission | §18.305 (b) | Nominal | Nominal | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| AC conducted emission | §18.307 (a) | Nominal | Nominal | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |

Remark: The measurement uncertainty is not included in the test result.

N/A – Not Applicable!!!

6. POWER LINE CONDUCTED MEASUREMENT

6.1. Block Diagram of Test Setup



6.2. Standard Applicable

According to §18.307 (b): For all other part 18 consumer devices which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dBµV) | |
|-----------------------|---------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

6.3 Test Results


PASS

The test data please refer to following page.

| | | | |
|---------------|--------|----------------|----------|
| Temperature | 23.3°C | Humidity | 53.7% |
| Test Engineer | Qu Xin | Configurations | Transmit |


AC Power Line Conducted Emission (Power input to adapter @ AC 120V/60Hz (Worst Case))

Line



| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|-----------------|----------------|--------------|---------------|--------------|-------------|--------|
| 1 | 0.1500 | 33.23 | 19.14 | 52.37 | 66.00 | -13.63 | QP |
| 2 | 0.1500 | 6.76 | 19.14 | 25.90 | 56.00 | -30.10 | AVG |
| 3 | 0.2535 | 13.68 | 19.23 | 32.91 | 61.64 | -28.73 | QP |
| 4 | 0.3217 | -0.12 | 19.29 | 19.17 | 49.66 | -30.49 | AVG |
| 5 | 0.9375 | 9.24 | 19.29 | 28.53 | 56.00 | -27.47 | QP |
| 6 | 0.9825 | -0.05 | 19.27 | 19.22 | 46.00 | -26.78 | AVG |
| 7 | 2.8095 | 6.01 | 19.46 | 25.47 | 56.00 | -30.53 | QP |
| 8 | 2.8095 | 2.01 | 19.46 | 21.47 | 46.00 | -24.53 | AVG |
| 9 | 8.6730 | 11.11 | 19.65 | 30.76 | 60.00 | -29.24 | QP |
| 10 | 8.8979 | -4.61 | 19.66 | 15.05 | 50.00 | -34.95 | AVG |
| 11 | 29.0085 | 11.91 | 20.12 | 32.03 | 60.00 | -27.97 | QP |
| 12 | 29.2380 | -4.55 | 20.12 | 15.57 | 50.00 | -34.43 | AVG |

Neutral




| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|-----------------|----------------|--------------|---------------|--------------|-------------|--------|
| 1 | 0.1500 | 33.44 | 19.14 | 52.58 | 66.00 | -13.42 | QP |
| 2 | 0.1516 | 5.01 | 19.14 | 24.15 | 55.91 | -31.76 | AVG |
| 3 | 0.3885 | 12.43 | 19.31 | 31.74 | 58.10 | -26.36 | QP |
| 4 | 0.4110 | 7.24 | 19.32 | 26.56 | 47.63 | -21.07 | AVG |
| 5 | 0.9375 | 8.97 | 19.29 | 28.26 | 56.00 | -27.74 | QP |
| 6 | 0.9555 | -4.54 | 19.29 | 14.75 | 46.00 | -31.25 | AVG |
| 7 | 2.8095 | 6.17 | 19.46 | 25.63 | 56.00 | -30.37 | QP |
| 8 | 2.8590 | -5.75 | 19.46 | 13.71 | 46.00 | -32.29 | AVG |
| 9 | 9.0014 | 7.07 | 19.66 | 26.73 | 60.00 | -33.27 | QP |
| 10 | 9.0014 | -5.03 | 19.66 | 14.63 | 50.00 | -35.37 | AVG |
| 11 | 19.3380 | 14.11 | 20.31 | 34.42 | 60.00 | -25.58 | QP |
| 12 | 19.7520 | -0.22 | 20.30 | 20.08 | 50.00 | -29.92 | AVG |
| 13 | 29.0085 | 9.24 | 20.12 | 29.36 | 50.00 | -20.64 | AVG |
| 14 | 29.2380 | -2.97 | 20.12 | 17.15 | 50.00 | -32.85 | AVG |


***Note: Pre-scan all modes and recorded the worst case results in this report.

7. RADIATED EMISSION MEASUREMENT


7.1. Block Diagram of Test Setup



Below 30MHz



Below 1GHz



Above 1GHz

7.2. Radiated Emission Limit

Except as provided elsewhere in this Subpart 18.305 (b), the field strength levels of emissions which lie outside the bands specified in §18.301, unless otherwise indicated, shall not exceed the following table:

| Frequency MHz | Distance Meters | Field Strengths Limit | |
|------------------|--------------------|-----------------------|------------|
| | | dB μ V/m | Remark |
| 0.009~30MHz | 3 | 103.5 | Quasi-peak |
| 30~88 | 3 | 40.0 | Quasi-peak |
| 88~216 | 3 | 43.5 | Quasi-peak |
| 216~960 | 3 | 46.0 | Quasi-peak |
| 960~1000 | 3 | 54.0 | Quasi-peak |

Remark:

(1) Emission level dB μ V/m for 0.009~30MHz = 20log (25) + 40log (300/3) dB μ V/m;

(2) Calculated according FCC 18.305.

(3) The smaller limit shall apply at the cross point between two frequency bands.

(4) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

7.3. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

(1) Setup the EUT as shown in Section 4.1.

(2) Let the EUT work in worst test mode (Mode 1) and measure it.

7.5. Measuring Setting

The following table is the setting of spectrum analyzer and receiver.

| Receiver Parameter | Setting |
|------------------------|---------------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP/Average |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP/Average |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 100kHz for QP |

7.6. Test Procedure

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

7.7. Test Results


PASS.

Only report the worst test data (Mode 1) in test report;

The test data please refer to following page:

| | | | |
|---------------|--------|----------------|----------|
| Temperature | 24.6°C | Humidity | 54.1% |
| Test Engineer | Qu Xin | Configurations | Transmit |

0.009 MHz – 30 MHz




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1 * | 0.0162 | 73.95 | 0.24 | 74.19 | 103.50 | -29.31 | QP |
| 2 | 0.2060 | 60.37 | 0.24 | 60.61 | 103.50 | -42.89 | QP |
| 3 | 0.6416 | 59.44 | 0.25 | 59.69 | 103.50 | -43.81 | QP |
| 4 | 0.9470 | 59.73 | 0.26 | 59.99 | 103.50 | -43.51 | QP |
| 5 | 4.9952 | 41.36 | 0.28 | 41.64 | 103.50 | -61.86 | QP |
| 6 | 20.6570 | 42.87 | 0.30 | 43.17 | 103.50 | -60.33 | QP |

Remark: Measured at antenna position 0 degree and 90 degree, recorded worst case at 0 degree.


Below 1GHz

Horizontal



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1 | 49.5328 | 35.18 | -16.40 | 18.78 | 40.00 | -21.22 | QP |
| 2 | 63.7588 | 40.98 | -18.92 | 22.06 | 40.00 | -17.94 | QP |
| 3 | 112.1305 | 46.38 | -18.75 | 27.63 | 43.50 | -15.87 | QP |
| 4 | 138.3873 | 49.89 | -21.93 | 27.96 | 43.50 | -15.54 | QP |
| 5 * | 170.1948 | 57.39 | -20.70 | 36.69 | 43.50 | -6.81 | QP |
| 6 | 298.2681 | 43.48 | -15.69 | 27.79 | 46.00 | -18.21 | QP |

Vertical



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1 | 41.1320 | 35.40 | -17.20 | 18.20 | 40.00 | -21.80 | QP |
| 2 | 59.8588 | 38.36 | -17.96 | 20.40 | 40.00 | -19.60 | QP |
| 3 * | 173.2051 | 59.38 | -20.53 | 38.85 | 43.50 | -4.65 | QP |
| 4 | 233.3487 | 52.11 | -17.26 | 34.85 | 46.00 | -11.15 | QP |
| 5 | 355.4273 | 41.05 | -14.30 | 26.75 | 46.00 | -19.25 | QP |
| 6 | 900.1474 | 33.03 | -5.62 | 27.41 | 46.00 | -18.59 | QP |

8. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files for Test Setup Photos of the EUT.

9. EXTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

10. INTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----