

FCC Test Report

Applicant : Shenzhen Qianyan Technology LTD

Address :
No. 3301, Block C, Section 1, Chuangzhi
Yuncheng Building, Liuxian Avenue, Xili
Community, Xili Street, Nanshan District,
Shenzhen, 518000, China

Product Name : Govee Smart TV Backlight 3S

Report Date : Feb. 26, 2024



Shenzhen Anbotek Compliance Laboratory Limited

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com

Code: AB-RF-05-b



Hotline

400-003-0500

www.anbotek.com.cn



Contents

1. General Information	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	7
1.4. Description of Test Configuration	8
1.5. Description Of Test Setup	9
1.6. Test Equipment List	10
1.7. Measurement Uncertainty	11
1.8. Description of Test Facility	11
1.9. Disclaimer	12
2. Summary of Test Results	13
3. Conducted Emission Test	14
3.1. Test Standard and Limit	14
3.2. Test Setup	14
3.3. Test Procedure	14
3.4. Test Data	14
4. Radiation Spurious Emission and Band Edge	19
4.1. Test Standard and Limit	19
4.2. Test Setup	19
4.3. Test Procedure	20
4.4. Test Data	21
5. Maximum Peak Output Power Test	32
5.1. Test Standard and Limit	32
5.2. Test Setup	32
5.3. Test Procedure	32
5.4. Test Data	32
6. Antenna Requirement	33
6.1. Test Standard and Requirement	33
6.2. Antenna Connected Construction	33
APPENDIX I -- TEST SETUP PHOTOGRAPH	34
APPENDIX II -- EXTERNAL PHOTOGRAPH	34
APPENDIX III -- INTERNAL PHOTOGRAPH	34



TEST REPORT

Applicant : Shenzhen Qianyan Technology LTD

Manufacturer : Shenzhen Qianyan Technology LTD

Product Name : Govee Smart TV Backlight 3S

Test Model No. : H6098

Reference Model No. : H6098B, H6098C

Trade Mark : Govee

Rating(s) : Input: 12V $\equiv$ 2A, 12V $\equiv$ 3A

Test Standard(s) : **FCC Part15 Subpart C, Section 15.247**

Test Method(s) : **ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Jan. 26, 2024

Date of Test

Jan. 26 ~ Feb. 01, 2024

Prepared By

Nian xiu Chen

(Nianxiu Chen)

Approved & Authorized Signer

Edward Pan

(Edward Pan)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Feb. 26, 2024

Note:

This is a Class II application which was based on the original report 18220WC30196901. The difference between the original device and current one described as following:

1. Add model H6098B, H6098C
2. Add the adapter, lamp length and camera length of model H6098.

The changes are not related with the other RF parameters, only conducted emission and radiation spurious emission were retested.



1. General Information

1.1. Client Information

Applicant	:	Shenzhen Qianyan Technology LTD
Address	:	No. 3301, Block C, Section 1, Chuangzhi Yuncheng Building, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China
Manufacturer	:	Shenzhen Qianyan Technology LTD
Address	:	No. 3301, Block C, Section 1, Chuangzhi Yuncheng Building, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China

1.2. Description of Device (EUT)

Product Name	:	Govee Smart TV Backlight 3S
Test Model No.	:	H6098
Reference Model No.	:	H6098B, H6098C (Note: The model differences please refer to page 6, based on the model differences, we prepare "H6098" for conducted emission and radiation spurious emission testing.)
Trade Mark	:	Govee
Test Power Supply	:	AC 120V, 60Hz for Adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
RF Specification		
Operation Mode	:	☒ BT BLE
Support Rate	:	☒ 1Mbps ☐ 2Mbps
Operation Frequency	:	2402~2480MHz
Number of Channel	:	40 Channels
Modulation Type	:	GFSK
Antenna Type	:	PCB Antenna
Antenna Gain(Peak)	:	3.18dBi
Remark: (1) All of the RF specification are provided by customer. (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		



Model differences:

Product Name	Model No.	Length of light string	Camera	Adapter	Differences
Govee Smart TV Backlight 3S	H6098	3.6m	96mm	Model: BI24G-120200-AdU Input: 100-240V~ 50/60Hz 0.8A Output: 12V= 2A	Same with Original
	H6098	3.6m	96mm	Model: YXTG24US-1202000 Input: 100-240V~ 50/60Hz 0.8A Output: 12V= 2A 24W	Only power adapter is different from Original H6098
	H6098	5m	135m	Model: YXTG36US-1203000 Input: 100-240V~ 1.0A Max 50/60Hz Output: 12V= 3.0A 36.0W	Only the model name and camera, Product Name are different from Original H6099
	H6098	5m	135m	Model: BI36GL-120300-AdU Input: 100-240V~ 50/60Hz 1A Output: 12V= 3A	Only power adapter, lamp length and camera length are different Original H6098
	H6098B	3.6m	96mm	Model: BI24G-120200-AdU Input: 100-240V~ 50/60Hz 0.8A Output: 12V= 2A	Only the model name is different from new H6098
	H6098B	3.6m	96mm	Model: YXTG24US-1202000 Input: 100-240V~ 50/60Hz 0.8A Output: 12V= 2A 24W	Only the model name is different from new H6098
	H6098C	5m	135mm	Model: YXTG36US-1203000 Input: 100-240V~ 1.0A Max 50/60Hz Output: 12V= 3.0A 36.0W	Only the model name is different from new H6098
	H6098C	5m	135mm	Model: BI36GL-120300-AdU Input: 100-240V~ 50/60Hz 1A Output: 12V= 3A	Only the model name is different from new H6098



1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
--	--



1.4. Description of Test Configuration



Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	2402	09	2420	18	2438	27	2456	36	2474
01	2404	10	2422	19	2440	28	2458	37	2476
02	2406	11	2424	20	2442	29	2460	38	2478
03	2408	12	2426	21	2444	30	2462	39	2480
04	2410	13	2428	22	2446	31	2464		
05	2412	14	2430	23	2448	32	2466		
06	2414	15	2432	24	2450	33	2468		
07	2416	16	2434	25	2452	34	2470		
08	2418	17	2436	26	2454	35	2472		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with channel 0, 19 and 39.



1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 12, 2023	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2023	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 12, 2023	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 12, 2023	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 12, 2023	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G -45	SKET-PA-002	Oct. 12, 2023	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 12, 2023	1 Year
10.	Horn Antenna	A-INFO	LB-180400- KF	J211060628	Oct. 12, 2023	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Oct. 12, 2023	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 12, 2023	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 12, 2023	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 12, 2023	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 20, 2023	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 16, 2023	1 Year
18.	Power Meter	Agilent	N1914A	MY50001102	Oct. 20, 2023	1 Year
19.	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	101792	May. 26, 2023	1 Year



1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.8dB
Occupied Bandwidth	925Hz
Conducted Output Power	0.76dB
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.78dB; 6G-18GHz: 4.88dB 18G-40GHz: 5.68dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.



1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark:(1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.

AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.




Report No.: 18220WC40018901

FCC ID: 2A7VD-H6099

Page 15 of 34

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 2402MHz
Test Specification: AC 120V, 60Hz for Adapter
Comment: Live Line
Temp.(°C)/Hum.(%RH): 21.4°C/52%RH
Test Model: H6098 (with adapter YXTG24US-1202000)




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.4820	14.46	19.07	33.53	46.30	-12.77	AVG	
2	0.6740	13.11	19.03	32.14	46.00	-13.86	AVG	
3	1.9620	30.17	18.96	49.13	56.00	-6.87	QP	
4	2.8340	30.07	19.02	49.09	56.00	-6.91	QP	
5	4.3540	18.33	18.88	37.21	46.00	-8.79	AVG	
6	9.3420	23.00	18.80	41.80	50.00	-8.20	AVG	
7	10.7140	20.48	18.80	39.28	50.00	-10.72	AVG	
8	12.4740	34.71	18.81	53.52	60.00	-6.48	QP	
9	13.0740	17.40	18.83	36.23	50.00	-13.77	AVG	
10	9.4420	37.43	18.80	56.23	60.00	-3.77	QP	
11	10.4540	35.32	18.79	54.11	60.00	-5.89	QP	
12	4.2700	30.23	18.89	49.12	56.00	-6.88	QP	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 2402MHz
Test Specification: AC 120V, 60Hz for Adapter
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 21.4°C/52%RH
Test Model: H6098 (with adapter YXTG24US-1202000)




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.5020	30.49	19.08	49.57	56.00	-6.43	QP	
2	0.5580	30.78	19.07	49.85	56.00	-6.15	QP	
3	0.5580	12.47	19.07	31.54	46.00	-14.46	AVG	
4	0.7140	12.09	19.02	31.11	46.00	-14.89	AVG	
5	1.5060	30.42	18.96	49.38	56.00	-6.62	QP	
6	4.1660	15.79	18.90	34.69	46.00	-11.31	AVG	
7	9.5620	24.36	18.79	43.15	50.00	-6.85	AVG	
8	10.8220	21.29	18.80	40.09	50.00	-9.91	AVG	
9	14.1820	18.60	18.84	37.44	50.00	-12.56	AVG	
10	8.7260	34.74	18.80	53.54	60.00	-6.46	QP	
11	10.0260	37.58	18.79	56.37	60.00	-3.63	QP	
12	4.1940	28.98	18.90	47.88	56.00	-8.12	QP	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 2402MHz
Test Specification: AC 120V, 60Hz for Adapter
Comment: Live Line
Temp.(°C)/Hum.(%RH): 21.4°C/52%RH
Test Model: H6098 (with adapter BI36GL-120300-AdU)




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1740	33.76	17.83	51.59	64.76	-13.17	QP	
2	0.6060	29.55	17.87	47.42	56.00	-8.58	QP	
3	0.6060	21.86	17.87	39.73	46.00	-6.27	AVG	
4	1.4540	14.76	17.86	32.62	46.00	-13.38	AVG	
5	1.4819	31.14	17.86	49.00	56.00	-7.00	QP	
6	1.8060	29.61	17.86	47.47	56.00	-8.53	QP	
7	1.8060	14.42	17.86	32.28	46.00	-13.72	AVG	
8	2.1099	23.88	17.85	41.73	56.00	-14.27	QP	
9	3.1940	22.66	17.85	40.51	56.00	-15.49	QP	
10	3.3900	13.59	17.85	31.44	46.00	-14.56	AVG	
11	4.5020	11.96	17.86	29.82	46.00	-16.18	AVG	
12	6.4060	14.45	17.89	32.34	50.00	-17.66	AVG	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 2402MHz
Test Specification: AC 120V, 60Hz for Adapter
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 21.4°C/52%RH
Test Model: H6098 (with adapter BI36GL-120300-AdU)



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1740	22.80	17.83	40.63	54.76	-14.13	AVG	
2	0.2819	34.01	17.84	51.85	60.76	-8.91	QP	
3	0.3620	18.43	17.82	36.25	48.68	-12.43	AVG	
4	0.5940	31.10	17.86	48.96	56.00	-7.04	QP	
5	0.6020	23.92	17.87	41.79	46.00	-4.21	AVG	
6	1.0140	30.41	17.86	48.27	56.00	-7.73	QP	
7	1.4260	15.73	17.86	33.59	46.00	-12.41	AVG	
8	1.4860	30.44	17.86	48.30	56.00	-7.70	QP	
9	1.8020	13.68	17.86	31.54	46.00	-14.46	AVG	
10	1.8540	29.35	17.85	47.20	56.00	-8.80	QP	
11	2.1619	10.67	17.85	28.52	46.00	-17.48	AVG	
12	2.2060	25.39	17.85	43.24	56.00	-12.76	QP	



4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.



For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 3MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

For average measurement:

–VBW=3*RBW, Detector= RMS, When duty cycle is no less than 98 percent

–VBW=3*RBW, Detector= RMS, When duty cycle is less than 98 percent and dutycycle is constant, average=peak level+correction factor($20\log(\text{duty cycle})$).

–VBW $\geq 1/T$, when duty cycle is less than 98 percent and dutycycle is not constant, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.4 duty cycle.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.



Report No.: 18220WC40018901

FCC ID: 2A7VD-H6099

Page 22 of 34

Test Results (30~1000MHz)


Test Mode: 2402MHz

Power Source: AC 120V, 60Hz for Adapter

Polarization: Horizontal

Temp.(°C)/Hum.(%RH): 20.1°C/49%RH

Test Model: H6098 (with adapter YXTG24US-1202000)



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	71.0803	45.00	-21.65	23.35	40.00	-16.65	QP			
2	98.1419	40.59	-17.20	23.39	43.50	-20.11	QP			
3	126.3286	44.81	-20.35	24.46	43.50	-19.04	QP			
4	147.4036	47.79	-21.18	26.61	43.50	-16.89	QP			
5	181.9202	48.26	-19.24	29.02	43.50	-14.48	QP			
6	237.4760	46.78	-16.59	30.19	46.00	-15.81	QP			



Test Results (30~1000MHz)

Test Mode: 2402MHz

Power Source: AC 120V, 60Hz for Adapter

Polarization: Vertical

Temp.(°C)/Hum.(%RH): 20.1°C/49%RH

Test Model: H6098 (with adapter YXTG24US-1202000)



No.	Freq. (MHz)	Reading (dBuV)	Factor (°)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	34.2760	50.57	-18.04	32.53	40.00	-7.47	QP			
2	55.2207	46.79	-17.44	29.35	40.00	-10.65	QP			
3	68.1514	44.25	-20.92	23.33	40.00	-16.67	QP			
4	104.5361	36.53	-17.54	18.99	43.50	-24.51	QP			
5	151.5972	48.33	-21.02	27.31	43.50	-16.19	QP			
6	221.3921	44.02	-17.27	26.75	46.00	-19.25	QP			



Report No.: 18220WC40018901

FCC ID: 2A7VD-H6099

Page 24 of 34

Test Results (30~1000MHz)


Test Mode: 2402MHz

Power Source: AC 120V, 60Hz for Adapter

Polarization: Horizontal

Temp.(°C)/Hum.(%RH): 20.1°C/49%RH

Test Model: H6098 (with adapter BI36GL-120300-AdU)



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	71.0803	48.65	-21.65	27.00	40.00	-13.00	QP			
2	98.1419	47.13	-17.20	29.93	43.50	-13.57	QP			
3	125.4457	51.41	-20.24	31.17	43.50	-12.33	QP			
4	162.6106	54.23	-20.38	33.85	43.50	-9.65	QP			
5	210.7860	51.19	-17.73	33.46	43.50	-10.04	QP			
6	332.5187	41.45	-14.05	27.40	46.00	-18.60	QP			



Test Results (30~1000MHz)

Test Mode: 2402MHz

Power Source: AC 120V, 60Hz for Adapter

Polarization: Vertical

Temp.(°C)/Hum.(%RH): 20.1°C/49%RH

Test Model: H6098 (with adapter BI36GL-120300-AdU)



No.	Freq. (MHz)	Reading (dBUV)	Factor ()	Result (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	32.1795	51.22	-18.04	33.18	40.00	-6.82	QP			
2	65.8031	48.82	-19.99	28.83	40.00	-11.17	QP			
3	98.1419	44.91	-17.20	27.71	43.50	-15.79	QP			
4	160.3456	56.66	-20.51	36.15	43.50	-7.35	QP			
5	327.8873	37.65	-14.17	23.48	46.00	-22.52	QP			
6	574.6258	33.75	-8.85	24.90	46.00	-21.10	QP			



Test Results (1GHz-25GHz)

Test Model: H6098 (with adapter YXTG24US-1202000)

Test Mode: CH00

Test channel: Lowest

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	27.02	15.27	42.29	74.00	-31.71	Vertical
7206.00	27.33	18.09	45.42	74.00	-28.58	Vertical
9608.00	27.69	23.76	51.45	74.00	-22.55	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	26.81	15.27	42.08	74.00	-31.92	Horizontal
7206.00	27.32	18.09	45.41	74.00	-28.59	Horizontal
9608.00	27.50	23.76	51.26	74.00	-22.74	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	15.29	15.27	30.56	54.00	-23.44	Vertical
7206.00	16.38	18.09	34.47	54.00	-19.53	Vertical
9608.00	17.16	23.76	40.92	54.00	-13.08	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	15.14	15.27	30.41	54.00	-23.59	Horizontal
7206.00	16.35	18.09	34.44	54.00	-19.56	Horizontal
9608.00	17.01	23.76	40.77	54.00	-13.23	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test Mode: CH19			Test channel: Middle			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	26.57	15.42	41.99	74.00	-32.01	Vertical
7320.00	27.30	18.02	45.32	74.00	-28.68	Vertical
9760.00	27.19	23.80	50.99	74.00	-23.01	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	26.62	15.42	42.04	74.00	-31.96	Horizontal
7320.00	27.19	18.02	45.21	74.00	-28.79	Horizontal
9760.00	27.22	23.80	51.02	74.00	-22.98	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	15.38	15.42	30.80	54.00	-23.20	polarization
7320.00	16.24	18.02	34.26	54.00	-19.74	Vertical
9760.00	17.01	23.80	40.81	54.00	-13.19	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	15.25	15.42	30.67	54.00	-23.33	Vertical
7320.00	16.70	18.02	34.72	54.00	-19.28	Horizontal
9760.00	17.31	23.80	41.11	54.00	-12.89	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test Mode: CH39			Test channel: Highest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	26.70	15.58	42.28	74.00	-31.72	Vertical
7440.00	27.46	17.93	45.39	74.00	-28.61	Vertical
9920.00	27.89	23.83	51.72	74.00	-22.28	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	26.76	15.58	42.34	74.00	-31.66	Horizontal
7440.00	27.40	17.93	45.33	74.00	-28.67	Horizontal
9920.00	27.60	23.83	51.43	74.00	-22.57	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	16.50	15.58	32.08	54.00	-21.92	Vertical
7440.00	17.51	17.93	35.44	54.00	-18.56	Vertical
9920.00	17.66	23.83	41.49	54.00	-12.51	Vertical
12400.00	*			54.00		Vertical
14880.00	*			54.00		Vertical
4960.00	16.43	15.58	32.01	54.00	-21.99	Horizontal
7440.00	17.50	17.93	35.43	54.00	-18.57	Horizontal
9920.00	17.46	23.83	41.29	54.00	-12.71	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

1.Result =Reading + Factor

2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.



Test Results (1GHz-25GHz)

Test Model: H6098 (with adapter BI36GL-120300-AdU)

Test Mode: CH00

Test channel: Lowest

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	26.95	15.27	42.22	74.00	-31.78	Vertical
7206.00	27.28	18.09	45.37	74.00	-28.63	Vertical
9608.00	27.61	23.76	51.37	74.00	-22.63	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	26.75	15.27	42.02	74.00	-31.98	Horizontal
7206.00	27.24	18.09	45.33	74.00	-28.67	Horizontal
9608.00	27.47	23.76	51.23	74.00	-22.77	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	15.22	15.27	30.49	54.00	-23.51	Vertical
7206.00	16.33	18.09	34.42	54.00	-19.58	Vertical
9608.00	17.08	23.76	40.84	54.00	-13.16	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	15.08	15.27	30.35	54.00	-23.65	Horizontal
7206.00	16.27	18.09	34.36	54.00	-19.64	Horizontal
9608.00	16.98	23.76	40.74	54.00	-13.26	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test Mode: CH19			Test channel: Middle			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	26.50	15.42	41.92	74.00	-32.08	Vertical
7320.00	27.25	18.02	45.27	74.00	-28.73	Vertical
9760.00	27.11	23.80	50.91	74.00	-23.09	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	26.56	15.42	41.98	74.00	-32.02	Horizontal
7320.00	27.11	18.02	45.13	74.00	-28.87	Horizontal
9760.00	27.19	23.80	50.99	74.00	-23.01	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	15.31	15.42	30.73	54.00	-23.27	polarization
7320.00	16.19	18.02	34.21	54.00	-19.79	Vertical
9760.00	16.93	23.80	40.73	54.00	-13.27	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	15.19	15.42	30.61	54.00	-23.39	Vertical
7320.00	16.62	18.02	34.64	54.00	-19.36	Horizontal
9760.00	17.28	23.80	41.08	54.00	-12.92	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test Mode: CH39			Test channel: Highest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	26.63	15.58	42.21	74.00	-31.79	Vertical
7440.00	27.41	17.93	45.34	74.00	-28.66	Vertical
9920.00	27.81	23.83	51.64	74.00	-22.36	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	26.70	15.58	42.28	74.00	-31.72	Horizontal
7440.00	27.32	17.93	45.25	74.00	-28.75	Horizontal
9920.00	27.57	23.83	51.40	74.00	-22.60	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	16.43	15.58	32.01	54.00	-21.99	Vertical
7440.00	17.46	17.93	35.39	54.00	-18.61	Vertical
9920.00	17.58	23.83	41.41	54.00	-12.59	Vertical
12400.00	*			54.00		Vertical
14880.00	*			54.00		Vertical
4960.00	16.37	15.58	31.95	54.00	-22.05	Horizontal
7440.00	17.42	17.93	35.35	54.00	-18.65	Horizontal
9920.00	17.43	23.83	41.26	54.00	-12.74	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

1.Result =Reading + Factor

2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.




5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W (30dBm)

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW $\geq$ DTS bandwidth.
2. Set the VBW $\geq 3 \times$ RBW.
3. Set the span $\geq 3 \times$ RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data

Pass

Note: For pre-scan, the result is equal to original, so the original data is referenced.

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-2.59	≤ 30	PASS
		2440	-2.72	≤ 30	PASS
		2480	-3.26	≤ 30	PASS



6. Antenna Requirement

6.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

6.2. Antenna Connected Construction

The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is 3.18dBi . It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

