



Report No.: HKEM220900091602

Page: 1 of 68

TEST REPORT

Application No.: HKEM2209000916AT
Applicant: VTech Telecommunications Ltd.
Address of Applicant: 23/F., Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, Hong Kong
Equipment Under Test (EUT):
EUT Name: Pan & Tilt Video Monitor
Model No.: VM901 BU, VM901-2 BU, VM901-ab BU, VM901HD BU, VM901-2HD BU, VM901-0HD BU
Additional Model: Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.
FCC ID: EW780-1957-00C
IC: 1135B-80195700D
HVIN: 35-400344BUC
Standard(s) : CFR 47 FCC Part 15, Subpart C
RSS-247 Issue 2
RSS-Gen Issue 5
Date of Receipt: 2022-09-26
Date of Test: 2022-09-26 to 2022-10-14
Date of Issue: 2022-10-18

| | |
|---------------------|--|
| Test Result: | The submitted sample was found to comply with the test requirement |
|---------------------|--|

Law Man Kit
EMC Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request and accessible at <http://www.sgs.com/en/Terms-and-conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. The document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

| Revision Record | | | |
|-----------------|------|-------------------|--------|
| Revision No. | Date | Report superseded | Remark |
| | | | |
| | | | |
| | | | |

| | | | |
|--------------------------|--|---|------------------|
| Authorized for issue by: | | | |
| | |  | |
| | | Panny Leung /Project Engineer | Date: 2022-10-17 |
| | |  | |
| | | Law Man Kit /Reviewer | Date: 2022-10-18 |

2 Test Summary

| Radio Spectrum Technical Requirement | | | | |
|--------------------------------------|----------------------------------|--------|---|--------|
| Item | Standard | Method | Requirement | Result |
| Antenna Requirement | 47 CFR Part 15, Subpart C 15.247 | N/A | 47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4) | Pass |

| Radio Spectrum Matter Part | | | | |
|---|----------------------------------|--|--|--------|
| Item | Standard | Method | Requirement | Result |
| Conducted Disturbance at AC Power Line(150kHz-30MHz) | 47 CFR Part 15, Subpart C 15.207 | ANSI C63.10: 2013 Section 6.2 | 47 CFR FCC Part 15, Subpart C 15.207 | Pass |
| Minimum 6dB Bandwidth | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 11.8.1 | 47 CFR Part 15, Subpart C 15.247a(2) | Pass |
| Conducted Peak Output Power | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 11.9.2.3 | 47 CFR Part 15, Subpart C 15.247(b)(3) | Pass |
| Power Spectrum Density | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 11.10.2 | 47 CFR Part 15, Subpart C 15.247(e) | Pass |
| Conducted Band Edges Measurement | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 11.13.3.2 | 47 CFR Part 15, Subpart C 15.247(d) | Pass |
| Conducted Spurious Emissions | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 11.11 | 47 CFR Part 15, Subpart C 15.247(d) | Pass |
| Radiated Emissions which fall in the restricted bands | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 6.10.5 | 47 CFR Part 15, Subpart C 15.209 & 15.247(d) | Pass |
| Radiated Spurious Emissions | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 6.4,6.5,6.6 | 47 CFR Part 15, Subpart C 15.209 & 15.247(d) | Pass |

| Radio Spectrum Technical Requirement | | | | |
|--------------------------------------|----------------------------|--------|---------------------|--------|
| Item | Standard | Method | Requirement | Result |
| Antenna Requirement | RSS-Gen Issue 5, Amdt 2021 | N/A | RSS-Gen Section 6.8 | Pass |

| Radio Spectrum Matter Part | | | | |
|---|--------------------------------|------------------------------------|------------------------|--------|
| Item | Standard | Method | Requirement | Result |
| Conducted Emissions at AC Power Line (150kHz-30MHz) | RSS-Gen Issue 5: Amdt 2021 | ANSI C63.10 (2013) Section 6.2 | RSS-Gen Section 8.8 | Pass |
| 99% Bandwidth | RSS-Gen Issue 5: Amdt 2021 | ANSI C63.10 Section 6.9.3 | RSS-Gen Section 6.7 | Pass |
| Minimum 6dB Bandwidth | RSS-247 Issue 2, February 2017 | ANSI C63.10 (2013) Section 11.8.1 | RSS-247 Section 5.2(a) | Pass |
| Conducted Peak Output Power | RSS-247 Issue 2, February 2017 | ANSI C63.10 (2013) Section 11.9.1 | RSS-247 Section 5.4(d) | Pass |
| Power Spectrum Density | RSS-247 Issue 2, February 2017 | ANSI C63.10 (2013) Section 11.10.2 | RSS-247 Clause 5.2(b) | Pass |

| Radio Spectrum Matter Part | | | | |
|---|--------------------------------|--|--|--------|
| Item | Standard | Method | Requirement | Result |
| Conducted Band Edges Measurement | RSS-247 Issue 2, February 2017 | ANSI C63.10 (2013) Section 11.12 | RSS-247 Section 5.5 | Pass |
| Spurious Emissions | RSS-247 Issue 2, February 2017 | ANSI C63.10 (2013) Section 11.11 | RSS-247 Section 5.5 | Pass |
| Radiated Emissions which fall in the restricted bands | RSS-Gen Issue 5: Amdt 2021 | ANSI C63.10 (2013) Section 6.4&6.5&6.6 | RSS-247 Section Section 3.3 & RSS-Gen Section 8.10 | Pass |
| Frequency stability | RSS-247 Issue 2, February 2017 | RSS-Gen Section 6.11 | RSS-Gen Section 8.11 | Pass |

Note: Frequency stability requested in RSS GEN Section 8.1.1 has been complied since the result of band edge can demonstrate.

Declaration of EUT Family Grouping:

VM901 BU, VM901-2 BU, VM901-ab BU, VM901HD BU, VM901-2HD BU, VM901-0HD BU

These models are identical in electronics/electrical designs, including software & firmware, construction design/Physical design/enclosure and PCB layout. The only difference between these models is the model numbers for marketing purpose. Thus, only the model VM901 BU was tested in this report.

Abbreviation:

Tx: In this whole report Tx (or tx) means Transmitter.
Rx: In this whole report Rx (or rx) means Receiver.
RF: In this whole report RF means Radiated Frequency.
CH: In this whole report CH means channel.
Volt: In this whole report Volt means Voltage.
Temp: In this whole report Temp means Temperature.
Humid: In this whole report Humid means humidity.
Press: In this whole report Press means Pressure.
N/A: In this whole report not application.

3 Contents

| | Page |
|---|-----------|
| 1 COVER PAGE | 1 |
| 2 TEST SUMMARY | 3 |
| 3 CONTENTS | 5 |
| 4 GENERAL INFORMATION | 7 |
| 4.1 DETAILS OF E.U.T. | 7 |
| 4.2 DESCRIPTION OF SUPPORT UNITS | 8 |
| 4.3 MEASUREMENT UNCERTAINTY | 8 |
| 4.4 TEST LOCATION | 9 |
| 4.5 TEST FACILITY | 9 |
| 4.6 DEVIATION FROM STANDARDS | 9 |
| 4.7 ABNORMALITIES FROM STANDARD CONDITIONS | 9 |
| 5 EQUIPMENT LIST | 10 |
| 6 RADIO SPECTRUM TECHNICAL REQUIREMENT | 12 |
| 6.1 ANTENNA REQUIREMENT | 12 |
| 6.1.1 Test Requirement: | 12 |
| 6.1.2 Conclusion | 12 |
| 7 RADIO SPECTRUM MATTER TEST RESULTS | 13 |
| 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) | 13 |
| 7.1.1 E.U.T. Operation | 14 |
| 7.1.2 Test Setup Diagram | 14 |
| 7.1.3 Measurement Procedure and Data | 14 |
| 7.2 99% BANDWIDTH | 17 |
| 7.2.1 E.U.T. Operation | 17 |
| 7.2.2 Test Setup Diagram | 17 |
| 7.2.3 Measurement Procedure and Data | 17 |
| 7.3 MINIMUM 6dB BANDWIDTH | 18 |
| 7.3.1 E.U.T. Operation | 18 |
| 7.3.2 Test Setup Diagram | 18 |
| 7.3.3 Measurement Procedure and Data | 18 |
| 7.4 CONDUCTED PEAK OUTPUT POWER | 19 |
| 7.4.1 E.U.T. Operation | 19 |
| 7.4.2 Test Setup Diagram | 19 |
| 7.4.3 Measurement Procedure and Data | 19 |
| 7.5 POWER SPECTRUM DENSITY | 20 |
| 7.5.1 E.U.T. Operation | 20 |
| 7.5.2 Test Setup Diagram | 20 |
| 7.5.3 Measurement Procedure and Data | 20 |
| 7.6 CONDUCTED BAND EDGES MEASUREMENT | 21 |
| 7.6.1 E.U.T. Operation | 23 |
| 7.6.2 Test Setup Diagram | 23 |
| 7.6.3 Measurement Procedure and Data | 23 |
| 7.7 CONDUCTED SPURIOUS EMISSIONS | 24 |
| 7.7.1 E.U.T. Operation | 24 |
| 7.7.2 Test Setup Diagram | 24 |
| 7.7.3 Measurement Procedure and Data | 24 |



| | | |
|-------|--|-----------|
| 7.8 | RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS..... | 25 |
| 7.8.1 | <i>E.U.T. Operation.....</i> | 25 |
| 7.8.2 | <i>Test Setup Diagram.....</i> | 25 |
| 7.8.3 | <i>Measurement Procedure and Data.....</i> | 26 |
| 7.9 | RADIATED SPURIOUS EMISSIONS | 28 |
| 7.9.1 | <i>E.U.T. Operation.....</i> | 29 |
| 7.9.2 | <i>Test Setup Diagram.....</i> | 29 |
| 7.9.3 | <i>Measurement Procedure and Data.....</i> | 30 |
| 8 | PHOTOGRAPHS | 40 |
| 9 | APPENDIX..... | 41 |
| 9.1 | 99% BANDWIDTH | 41 |
| 9.2 | MINIMUM EMISSION BANDWIDTH 6 dB | 47 |
| 9.3 | RF OUTPUT POWER | 53 |
| 9.4 | BAND EDGE | 60 |
| 9.5 | CONDUCTED SPURIOUS EMISSION | 67 |

4 General Information

4.1 Details of E.U.T.

| | |
|----------------------|--|
| Power supply: | Adaptor Model: VT05EUS05100 Input: AC 100 V - 240 V, 50/60 Hz, 0.15 A Output: DC 5.0 V, 1.0 A |
| Test voltage: | AC 120 V |
| Cable: | Power Cable: 140 cm unshielded 2-wire DC cable |
| Antenna Gain: | 2 dBi |
| Antenna Type: | Dipole |
| Channel Spacing: | 5MHz |
| Modulation Type: | 802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK) |
| Data rate: | 802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11 Mbps 802.11g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n: 6.5Mbps, 13Mbps, 19.5Mbps, 26Mbps, 39Mbps, 52Mbps, 58.5Mbps, 65Mbps |
| Number of Channels: | 802.11b/g/n(HT20):11 |
| Operation Frequency: | 802.11b/g/n(HT20): 2412MHz to 2462MHz |
| Tested Channels: | 2412MHz, 2437MHz, 2462MHz |
| Version code: | T31N |
| Series number: | A1 |
| Hardware Version: | 35-400344BUC |
| Software Version: | V4.0.4.0 |
| | Remark: Power level setting was not adjustable and fixed default through SW Version. |

Frequency List

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|----------|-----------------|----------|-----------------|-----------|-----------------|
| 1 | 2412 | 5 | 2432 | 9 | 2452 |
| 2 | 2417 | 6 | 2437 | 10 | 2457 |
| 3 | 2422 | 7 | 2442 | 11 | 2462 |
| 4 | 2427 | 8 | 2447 | | |

Remark: 1. Testing Channels are highlighted in **bold**.

4.2 Description of Support Units

The EUT has been tested with corresponding accessories as below:

Supplied by client

| Description | Manufacturer | Model No. | SN/Certificate NO |
|---------------|-------------------|-------------------|-------------------|
| Test Software | MicroRidge System | Version 3.0.0.108 | N/A |

Supplied by SGS:

| Description | Manufacturer | Model No. | SN/Certificate NO |
|-----------------|--------------|-----------|-------------------|
| NoteBook (EMC4) | Dell | P75F | N/A |

4.3 Measurement Uncertainty

RF

| No. | Item | Measurement Uncertainty |
|-----|--|---------------------------|
| 1 | Conducted disturbance | 2.8dB (150kHz to 30MHz) |
| 2 | Radio Frequency | $\pm 7.25 \times 10^{-8}$ |
| 3 | Duty cycle | $\pm 0.37\%$ |
| 4 | Occupied Bandwidth | $\pm 3\%$ |
| 5 | RF conducted power (30MHz-40GHz) | 1.7dB |
| 6 | RF power density | 1.7dB |
| 7 | Conducted Spurious emissions | 1.7dB |
| 8 | RF Radiated power & Radiated Spurious emission test | 4.7dB (30MHz-1GHz) |
| | | 4.7dB (1GHz-6GHz) |
| | | 4.7dB (6GHz-18GHz) |
| | | 5.7dB (18GHz-40GHz) |
| 9 | Temperature test | $\pm 1^\circ\text{C}$ |
| 10 | Humidity test | $\pm 3\%$ |
| 11 | Supply voltages | $\pm 1.5\%$ |
| 12 | Time | $\pm 3\%$ |

Remark:

The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

According to decision rule based on Clause 4.2 of CISPR 16-4-2, the EUT complied with the standards specified above.

4.4 Test Location

All tests were performed at:

SGS Hong Kong Limited

Unit 2 and 3, G/F, Block A, Po Lung Centre,

11 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong

Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **IAS Accreditation (Lab Code: TL-817)**

SGS Hong Kong Limited has met the requirements of AC89, IAS Accreditation Criteria for Testing Laboratories, and has demonstrated compliance with ISO/IEC Standard 17025:2017, General requirements for the competence of testing and calibration laboratories. This organization is accredited to provide the services specified in the scope of accreditation maintained on the IAS website (www.iasonline.org).

The report must not be used by the client to claim product certification, approval, or endorsement by IAS, NIST, or any agency of the Federal Government.

- **FCC Recognized Accredited Test Firm(CAB Registration No.: 514599)**

SGS Hong Kong Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0015, Test Firm Registration Number: 514599.

- **Industry Canada (Site Registration No.: 26103; CAB Identifier No.: HK0015)**

SGS Hong Kong Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0015, Site Registration Number: 26103.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

Minimum 6dB Bandwidth, Conducted Peak Output Power, Power Spectrum Density, Conducted Band Edges Measurement, Conducted Spurious Emissions

| Equipment | Manufacturer | Model No | Inventory No | Cal Date | Cal Due Date |
|----------------------------------|-----------------|-----------------|--------------|------------|--------------|
| SMBV100A VECTOR SIGNAL GENERATOR | Rohde & Schwarz | SMBV100A | E234 | 2022/08/17 | 2023/08/16 |
| FSV40 SIGNAL ANALYZER 40GHz | Rohde & Schwarz | FSV40 | E235 | 2022/08/17 | 2023/08/16 |
| Wireless Conn. Tester (CMW) | Rohde & Schwarz | CMW270 | E240 | 2022/08/20 | 2023/08/19 |
| OSP | Rohde & Schwarz | OSP-B157W8 | E242 | 2022/04/20 | 2023/04/19 |
| Cable | Rohde & Schwarz | J12J103539-00-2 | E239 | 2022/09/17 | 2023/09/16 |
| WMS32 Test Software | R&S | Version 10 | N/A | -- | -- |

Conducted Emissions at Mains Terminals (150kHz-30MHz)

| Equipment | Manufacturer | Model No | Inventory No | Cal Date | Cal Due Date |
|----------------------------------|-----------------|----------------------|--------------|------------|--------------|
| EMI Test Receiver 9kHz to 3.6GHz | Rohde & Schwarz | ESR3 / 102326 | E231 | 2022/08/17 | 2023/08/16 |
| Artificial Mains Network (LISN) | Schwarzbeck | NSLK 8127 / 8127312 | E005 | 2022/04/13 | 2023/04/12 |
| Impulse Limiter | Rohde & Schwarz | ESH-3-Z2 / 357881052 | E028 | 2022/07/15 | 2023/07/14 |
| EMC32 Test Software | R&S | Version 10 | N/A | -- | -- |

Radiated Spurious Emissions (30MHz-1GHz)

| Equipment | Manufacturer | Model No | Inventory No | Cal Date | Cal Due Date |
|---|-----------------|---------------|--------------|------------|--------------|
| 3m Semi-Anechoic Chamber | ChamPro | N/A | E229 | 2022/08/08 | 2023/08/07 |
| Coaxial Cable | SGS | N/A | E167 | 2022/07/15 | 2023/07/14 |
| EMI Test Receiver 9kHz to 7GHz | Rohde & Schwarz | ESR7 / 102298 | E314 | 2022/06/29 | 2023/06/28 |
| TRILOG Super Broadb. Test Antenna, (25) 30-1000 MHz | Schwarzbeck | 9168-1110 | E264 | 2021/10/18 | 2023/10/17 |
| EMC32 Test software | Rohde & Schwarz | Version 10 | N/A | N/A | N/A |
| Boresight Mast Controller | ChamPro | AM-BS-4500-E | E237 | N/A | N/A |
| Turntable with Controller | ChamPro | EM1000 | E238 | N/A | N/A |

| Radiated Spurious Emissions (above 1GHz) | | | | | |
|---|---------------------|------------------------------|---------------------|-----------------|---------------------|
| Equipment | Manufacturer | Model No | Inventory No | Cal Date | Cal Due Date |
| 3m Semi-Anechoic Chamber | ChamPro | N/A | E229 | 2022/08/08 | 2023/08/07 |
| Coaxial Cable | SGS | N/A | E167 | 2022/07/15 | 2023/07/14 |
| EMI Test Receiver 9kHz to 7GHz | Rohde & Schwarz | ESR7 / 102298 | E314 | 2022/06/29 | 2023/06/28 |
| TRILOG Super Broadb. Test Antenna, (25) 30-1000 MHz | Schwarzbeck | 9168-1110 | E264 | 2021/10/18 | 2023/10/17 |
| Signal and Spectrum Analyzer 2Hz - 26.5GHz | Rohde & Schwarz | FSW26 | E296 | 2022/09/17 | 2023/09/16 |
| Horn Antenna 1 - 18GHz | Schwarzbeck | BBHA9120D | E211 | 2022/03/03 | 2024/03/02 |
| Horn Antenna 15 - 40GHz | Schwarzbeck | BBHA9170 | E212 | 2022/03/16 | 2024/03/15 |
| Preamplifier 33dB, 1 - 18GHz | Schwarzbeck | BBV9718 | E214 | 2022/01/20 | 2023/01/19 |
| Preamplifier 33dB, 18 - 26.5GHz | Schwarzbeck | BBV9719 | E215 | 2022/09/17 | 2023/09/16 |
| Broadband Coaxial Preamplifier typ. 30 dB, 18-40GHz | Schwarzbeck | BBV 9721 | E266 | 2022/09/17 | 2023/09/16 |
| Band Reject Filter 2.4 -2.5GHz | MICRO-TRONICS | BRM50702 | E324 | 2022/09/17 | 2023/09/16 |
| RF cable SMA to SMA 10000mm | HUBER+SUHNER | SF104- 26.5/2*11SMA 45 | E207-1 | 2022/09/17 | 2023/09/16 |
| Boresight Mast Controller | ChamPro | AM-BS-4500-E | E237 | N/A | N/A |
| Turntable with Controller | ChamPro | EM1000 | E238 | N/A | N/A |

| General used equipment | | | | | |
|--|----------------------------------|-----------------|---------------------|-----------------|---------------------|
| Equipment | Manufacturer | Model No | Inventory No | Cal Date | Cal Due Date |
| Digital temperature & humidity data logger | SATO | SK-L200TH II | E232 | 2022/08/16 | 2023/08/15 |
| Electronic Digital Thermometer with Hygrometer | nil | 2074/2075 | E159 | 2022/08/16 | 2023/08/15 |
| Barometer with digital thermometer | SATO | 7612-00 | E218 | 2022/03/29 | 2023/03/28 |
| Conditional Chamber | Zhong Zhi Testing Instruments | CZ-E-608D | E216 | 2022/08/17 | 2023/08/16 |

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

FCC Part 15 Subpart C Section 15.247 & 15.203

RSS-Gen Section 8.3

6.1.2 Conclusion

Standard Requirement:

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2 dBi.

Photo of antenna refer to Appendix – Internal photo.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207, RSS-Gen Section 8.8
Test Method: ANSI C63.10 (2013) Section 6.2
Limit:

| Frequency of emission(MHz) | Conducted limit(dBμV) | |
|---|-----------------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |
| *Decreases with the logarithm of the frequency. | | |

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 23.0 °C Humidity: 52.0 % RH

Test mode a :TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)..11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

Only the data of worst case is recorded in the report.

7.1.2 Test Setup Diagram




7.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Mode:a (802.11b);
Line: Live Line


Full Spectrum



| Frequency (MHz) | QuasiPeak (dBμV) | Average (dBμV) | Limit (dBμV) | Margin (dB) | Corr. (dB) | Result |
|--------------------|---------------------|-------------------|-----------------|----------------|---------------|--------|
| 0.426000 | --- | 31.6 | 47.3 | 15.7 | 10.9 | Pass |
| 0.434000 | --- | 25.0 | 47.2 | 22.2 | 10.9 | Pass |
| 0.790000 | --- | 24.6 | 46.0 | 21.4 | 10.7 | Pass |
| 1.742000 | --- | 20.3 | 46.0 | 25.7 | 10.4 | Pass |
| 4.050000 | 30.3 | --- | 56.0 | 25.7 | 10.3 | Pass |
| 4.426000 | --- | 23.9 | 46.0 | 22.1 | 10.3 | Pass |
| 4.594000 | 31.5 | --- | 56.0 | 24.6 | 10.3 | Pass |
| 4.646000 | 31.9 | --- | 56.0 | 24.1 | 10.3 | Pass |
| 4.742000 | 31.8 | --- | 56.0 | 24.2 | 10.3 | Pass |
| 4.838000 | 31.6 | --- | 56.0 | 24.4 | 10.3 | Pass |
| 4.850000 | --- | 24.3 | 46.0 | 21.7 | 10.3 | Pass |
| 4.946000 | 30.4 | --- | 56.0 | 25.6 | 10.3 | Pass |

Mode: a(802.11b);
Line: Neutral Line

Full Spectrum



| Frequency (MHz) | QuasiPeak (dBμV) | Average (dBμV) | Limit (dBμV) | Margin (dB) | Corr. (dB) | Result |
|-----------------|------------------|----------------|--------------|-------------|------------|--------|
| 2.210000 | --- | 26.9 | 46.0 | 19.1 | 10.3 | Pass |
| 2.706000 | --- | 27.0 | 46.0 | 19.0 | 10.3 | Pass |
| 2.742000 | 36.3 | --- | 56.0 | 19.7 | 10.3 | Pass |
| 3.386000 | 36.8 | --- | 56.0 | 19.2 | 10.3 | Pass |
| 3.446000 | --- | 27.3 | 46.0 | 18.7 | 10.3 | Pass |
| 3.518000 | --- | 26.6 | 46.0 | 19.4 | 10.3 | Pass |
| 3.578000 | --- | 26.9 | 46.0 | 19.1 | 10.3 | Pass |
| 3.690000 | 37.0 | --- | 56.0 | 19.0 | 10.3 | Pass |
| 3.690000 | --- | 27.4 | 46.0 | 18.7 | 10.3 | Pass |
| 4.030000 | 37.0 | --- | 56.0 | 19.1 | 10.3 | Pass |
| 4.130000 | 36.6 | --- | 56.0 | 19.4 | 10.3 | Pass |
| 4.330000 | 36.7 | --- | 56.0 | 19.3 | 10.3 | Pass |

7.2 99% Bandwidth

Test Requirement RSS-Gen Section 6.6
Test Method: ANSI C63.10 Section 6.9.3

7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 22.5 °C Humidity: 53.0 % RH

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

Only the data of worst case is recorded in the report.

7.2.2 Test Setup Diagram



7.2.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

7.3 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
 Test Method: ANSI C63.10 (2013) Section 11.8.1
 Limit: ≥ 500 kHz

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 22.5 °C Humidity: 53.0 % RH

Test mode b:TX mode_ Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)..11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

Only the data of worst case is recorded in the report.

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

7.4 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247 (b)(1) & 15.247(b)(3), RSS-247 Section 5.4(b)

Test Method: ANSI C63.10 (2013) Section 7.8.5


7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C Humidity: 53.0 % RH

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

7.5 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e), RSS-247 Clause 5.2(b)
 Test Method: ANSI C63.10 (2013) Section 11.10.2
 Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 22.5 °C Humidity: 53.0 % RH

Test mode b:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

Only the data of worst case is recorded in the report.

7.5.2 Test Setup Diagram



7.5.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix



7.6 Conducted Band Edges Measurement

| | |
|------------------|---|
| Test Requirement | 47 CFR Part 15, Subpart C 15.247 (d), RSS-247 Section 5.5 |
| Test Method: | ANSI C63.10 (2013) Section 7.8.6 |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)) |

FCC Part 15 C Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|----------------------------|-----------------------|-----------------|---------------|
| 0.090 - 0.110 | 16.42 - 16.423 | 399.9 - 410 | 4.5 - 5.15 |
| ¹ 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614 | 5.35 - 5.46 |
| 2.1735 - 2.1905 | 16.80425 - 16.80475 | 960 - 1240 | 7.25 - 7.75 |
| 4.125 - 4.128 | 25.5 - 25.67 | 1300 - 1427 | 8.025 - 8.5 |
| 4.17725 - 4.17775 | 37.5 - 38.25 | 1435 - 1626.5 | 9.0 - 9.2 |
| 4.20725 - 4.20775 | 73 - 74.6 | 1645.5 - 1646.5 | 9.3 - 9.5 |
| 6.215 - 6.218 | 74.8 - 75.2 | 1660 - 1710 | 10.6 - 12.7 |
| 6.26775 - 6.26825 | 108 - 121.94 | 1718.8 - 1722.2 | 13.25 - 13.4 |
| 6.31175 - 6.31225 | 123 - 138 | 2200 - 2300 | 14.47 - 14.5 |
| 8.291 - 8.294 | 149.9 - 150.05 | 2310 - 2390 | 15.35 - 16.2 |
| 8.362 - 8.366 | 156.52475 - 156.52525 | 2483.5 - 2500 | 17.7 - 21.4 |
| 8.37625 - 8.38675 | 156.7 - 156.9 | 2655 - 2900 | 22.01 - 23.12 |
| 8.41425 - 8.41475 | 162.0125 - 167.17 | 3260 - 3267 | 23.6 - 24.0 |
| 12.29 - 12.293 | 167.72 - 173.2 | 3332 - 3339 | 31.2 - 31.8 |
| 12.51975 - 12.52025 | 240 - 285 | 3345.8 - 3358 | 36.43 - 36.5 |
| 12.57675 - 12.57725 | 322 - 335.4 | 3600 - 4400 | |
| 13.36 - 13.41 | | | |

RSS-Gen Section 8.10 Restricted bands of operation.

Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

(a) The transmit frequency, including fundamental components of modulation, of licence-exempt radio

apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, *Emergency Position Indicating Radio Beacons (EPIRB)*, *Emergency Locator Transmitters (ELT)*, *Personal Locator Beacons (PLB)*, and *Maritime Survivor Locator Devices (MSLD)*.

(b) Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.

(c) Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

| Table 7 – Restricted frequency bands* MHz | MHz | GHz |
|---|-----------------------|---|
| 0.090 - 0.110 | 149.9 - 150.05 | 9.0 - 9.2 |
| 0.495 - 0.505 | 156.52475 - 156.52525 | 9.3 - 9.5 |
| 2.1735 - 2.1905 | 156.7 - 156.9 | 10.6 - 12.7 |
| 3.020 - 3.026 | 162.0125 - 167.17 | 13.25 - 13.4 |
| 4.125 - 4.128 | 167.72 - 173.2 | 14.47 - 14.5 |
| 4.17725 - 4.17775 | 240 - 285 | 15.35 - 16.2 |
| 4.20725 - 4.20775 | 322 - 335.4 | 17.7 - 21.4 |
| 5.677 - 5.683 | 399.9 - 410 | 22.01 - 23.12 |
| 6.215 - 6.218 | 608 - 614 | 23.6 - 24.0 |
| 6.26775 - 6.26825 | 960 - 1427 | 31.2 - 31.8 |
| 6.31175 - 6.31225 | 1435 - 1626.5 | 36.43 - 36.5 |
| 8.291 - 8.294 | 1645.5 - 1646.5 | Above 38.6 |
| 8.362 - 8.366 | 1660 - 1710 | * Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs. |
| 8.37625 - 8.38675 | 1718.8 - 1722.2 | |
| 8.41425 - 8.41475 | 2200 - 2300 | |
| 12.29 - 12.293 | 2310 - 2390 | |
| 12.51975 - 12.52025 | 2483.5 - 2500 | |
| 12.57675 - 12.57725 | 2655 - 2900 | |
| 13.36 - 13.41 | 3260 - 3267 | |
| 16.42 - 16.423 | 3332 - 3339 | |
| 16.69475 - 16.69525 | 3345.8 - 3358 | |
| 16.80425 - 16.80475 | 3500 - 4400 | |
| 25.5 - 25.67 | 4500 - 5150 | |
| 37.5 - 38.25 | 5350 - 5460 | |
| 73 - 74.6 | 7250 - 7750 | |
| 74.8 - 75.2 | 8025 - 8500 | |
| 108 - 138 | -- | |


7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C Humidity: 53.0 % RH

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

7.6.2 Test Setup Diagram



7.6.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix


7.7 Conducted Spurious Emissions

| | |
|------------------|---|
| Test Requirement | 47 CFR Part 15, Subpart C 15.247 (d), RSS-247 Section 5.5 |
| Test Method: | ANSI C63.10 (2013) Section 7.8.8 |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required. |

7.7.1 E.U.T. Operation

| | |
|------------------------|---|
| Operating Environment: | |
| Temperature: | 22.5 °C Humidity: 53.0 % RH |
| Test mode | a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20). |

7.7.2 Test Setup Diagram



7.7.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

7.8 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d), Section 3.3 & RSS-Gen Section 8.9
Test Method: ANSI C63.10 (2013) Section 6.10.5
Limit:

Table 5 – General field strength limits at frequencies above 30 MHz

| Frequency (MHz) | Field strength ($\mu\text{V/m}$ at 3 m) |
|-----------------|--|
| 30 – 88 | 100 |
| 88 – 216 | 150 |
| 216 – 960 | 200 |
| Above 960 | 500 |

Table 6 – General field strength limits at frequencies below 30 MHz

| Frequency | Magnetic field strength (H-Field) ($\mu\text{A/m}$) | Measurement distance (m) |
|----------------|---|--------------------------|
| 9 - 490 kHz 1 | $6.37/F$ (F in kHz) | 300 |
| 490 - 1705 kHz | $63.7/F$ (F in kHz) | 30 |
| 1.705 - 30 MHz | 0.08 | 30 |

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

7.8.1 E.U.T. Operation


Operating Environment:

Temperature: 21.0 °C Humidity: 55.0 % RH

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

Only the data of worst case is recorded in the report.

7.8.2 Test Setup Diagram



7.8.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Worse test result as shown below:

Mode: 802.11b

| Frequency (MHz) | Antenna Polarization | Emission Level (dB μ V/m) | | Limit (dB μ V/m) | | Result |
|--------------------|-------------------------|-------------------------------|---------|----------------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 2390.000 | V | 52.6 | 36.5 | 74.0 | 54.0 | Pass |
| 2483.500 | V | 55.3 | 42.1 | 74.0 | 54.0 | Pass |

Mode: 802.11g

| Frequency (MHz) | Antenna Polarization | Emission Level (dB μ V/m) | | Limit (dB μ V/m) | | Result |
|--------------------|-------------------------|-------------------------------|---------|----------------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 2390.000 | V | 58.5 | 45.5 | 74.0 | 54.0 | Pass |
| 2483.500 | V | 59.7 | 46.3 | 74.0 | 54.0 | Pass |

Mode: 802.11n20

| Frequency (MHz) | Antenna Polarization | Emission Level (dB μ V/m) | | Limit (dB μ V/m) | | Result |
|--------------------|-------------------------|-------------------------------|---------|----------------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 2390.000 | V | 58.5 | 45.5 | 74.0 | 54.0 | Pass |
| 2483.500 | V | 59.0 | 46.2 | 74.0 | 54.0 | Pass |

7.9 Radiated Spurious Emissions

Test Requirement Section 3.3 & RSS-Gen Section 8.9
Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6
Limit:

Table 5 – General field strength limits at frequencies above 30 MHz

| Frequency (MHz) | Field strength ($\mu\text{V/m}$ at 3 m) |
|--------------------|---|
| 30 – 88 | 100 |
| 88 – 216 | 150 |
| 216 – 960 | 200 |
| Above 960 | 500 |

Table 6 – General field strength limits at frequencies below 30 MHz

| Frequency | Magnetic field strength (H-Field) ($\mu\text{A/m}$) | Measurement distance (m) |
|----------------|--|-----------------------------|
| 9 - 490 kHz 1 | $6.37/F$ (F in kHz) | 300 |
| 490 - 1705 kHz | $63.7/F$ (F in kHz) | 30 |
| 1.705 - 30 MHz | 0.08 | 30 |

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

7.9.1 E.U.T. Operation


Operating Environment:

Temperature: 21.0 °C Humidity: 55.0 % RH

Test mode a:TX mode Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

Only the data of worst case is recorded in the report.

7.9.2 Test Setup Diagram



7.9.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 40GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

802.11b


Radiated emission below 1GHz

Horizontal (the worst plot is shown below)



| Frequency (MHz) | QuasiPeak (dBμV/m) | Pol. | Corr. (dB/m) | Margin (dB) | Limit (dBμV/m) | Result |
|--------------------|-----------------------|------|-----------------|----------------|-------------------|--------|
| 173.492500 | 28.8 | H | 13.8 | 14.7 | 43.5 | Pass |
| 271.285000 | 44.0 | H | 13.8 | 2.0 | 46.0 | Pass |
| 374.342500 | 27.0 | H | 16.8 | 19.0 | 46.0 | Pass |
| 399.985000 | 35.0 | H | 17.4 | 11.0 | 46.0 | Pass |
| 421.240000 | 30.4 | H | 17.9 | 15.6 | 46.0 | Pass |
| 444.542500 | 25.4 | H | 18.6 | 20.6 | 46.0 | Pass |

Vertical (the worst plot is shown below)



| Frequency (MHz) | QuasiPeak (dBμV/m) | Pol. | Corr. (dB/m) | Margin (dB) | Limit (dBμV/m) | Result |
|--------------------|-----------------------|------|-----------------|----------------|-------------------|--------|
| 40.600000 | 28.3 | V | 13.8 | 11.7 | 40.0 | Pass |
| 112.457500 | 28.4 | V | 11.4 | 15.1 | 43.5 | Pass |
| 269.432500 | 34.9 | V | 13.7 | 11.1 | 46.0 | Pass |
| 421.240000 | 31.4 | V | 17.9 | 14.7 | 46.0 | Pass |
| 444.640000 | 31.5 | V | 18.6 | 14.5 | 46.0 | Pass |
| 538.240000 | 32.0 | V | 20.3 | 14.0 | 46.0 | Pass |

Above 1GHz

Channel:Low

| Frequency (MHz) | Antenna Polarization | Emission Level (dB μ V/m) | | Limit (dB μ V/m) | | Result |
|--------------------|-------------------------|-------------------------------|---------|----------------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 4983.464 | V | 54.7 | 37.6 | 74.0 | 54.0 | Pass |
| 5316.785 | V | 55.1 | 32.6 | 74.0 | 54.0 | Pass |
| 5987.678 | V | 49.1 | / | 74.0 | 54.0 | Pass |
| 7175.250 | H | 53.6 | / | 74.0 | 54.0 | Pass |
| 9790.214 | H | 54.2 | 40.5 | 74.0 | 54.0 | Pass |
| 12158.678 | H | 58.7 | 44.4 | 74.0 | 54.0 | Pass |

Channel:Middle

| Frequency (MHz) | Antenna Polarization | Emission Level (dB μ V/m) | | Limit (dB μ V/m) | | Result |
|--------------------|-------------------------|-------------------------------|---------|----------------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 4985.285 | H | 54.0 | 37.2 | 74.0 | 54.0 | Pass |
| 4997.428 | V | 55.3 | 37.7 | 74.0 | 54.0 | Pass |
| 8661.535 | V | 53.7 | / | 74.0 | 54.0 | Pass |
| 9779.892 | H | 53.0 | / | 74.0 | 54.0 | Pass |
| 12170.214 | V | 58.1 | 44.5 | 74.0 | 54.0 | Pass |
| 12180.535 | H | 58.3 | 44.4 | 74.0 | 54.0 | Pass |


Channel: High

| Frequency (MHz) | Antenna Polarization | Emission Level (dB μ V/m) | | Limit (dB μ V/m) | | Result |
|--------------------|-------------------------|-------------------------------|---------|----------------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 4923.964 | V | 57.4 | 52.8 | 74.0 | 54.0 | Pass |
| 4985.285 | H | 54.4 | 37.5 | 74.0 | 54.0 | Pass |
| 4996.821 | V | 55.2 | 38.2 | 74.0 | 54.0 | Pass |
| 5316.178 | V | 55.7 | 33.1 | 74.0 | 54.0 | Pass |
| 9859.428 | H | 53.4 | / | 74.0 | 54.0 | Pass |
| 12275.857 | H | 57.6 | 44.1 | 74.0 | 54.0 | Pass |

802.11g


Radiated emission below 1GHz

Horizontal (the worst plot is shown below)



| Frequency (MHz) | QuasiPeak (dBμV/m) | Pol. | Corr. (dB/m) | Margin (dB) | Limit (dBμV/m) | Result |
|--------------------|-----------------------|------|-----------------|----------------|-------------------|--------|
| 272.162500 | 43.5 | H | 13.9 | 2.5 | 46.0 | Pass |
| 350.942500 | 26.8 | H | 16.1 | 19.2 | 46.0 | Pass |
| 374.342500 | 27.5 | H | 16.8 | 18.5 | 46.0 | Pass |
| 399.985000 | 34.2 | H | 17.4 | 11.8 | 46.0 | Pass |
| 421.142500 | 27.7 | H | 17.9 | 18.3 | 46.0 | Pass |
| 444.640000 | 28.9 | H | 18.6 | 17.1 | 46.0 | Pass |

Vertical (the worst plot is shown below)



| Frequency (MHz) | QuasiPeak (dBμV/m) | Pol. | Corr. (dB/m) | Margin (dB) | Limit (dBμV/m) | Result |
|--------------------|-----------------------|------|-----------------|----------------|-------------------|--------|
| 40.892500 | 25.3 | V | 13.8 | 14.7 | 40.0 | Pass |
| 112.457500 | 29.3 | V | 11.4 | 14.2 | 43.5 | Pass |
| 271.675000 | 37.2 | V | 13.8 | 8.8 | 46.0 | Pass |
| 399.985000 | 33.4 | V | 17.4 | 12.6 | 46.0 | Pass |
| 421.240000 | 31.4 | V | 17.9 | 14.6 | 46.0 | Pass |
| 538.240000 | 32.0 | V | 20.3 | 14.0 | 46.0 | Pass |

Above 1GHz

Channel:Low

| Frequency (MHz) | Antenna Polarization | Emission Level (dBμV/m) | | Limit (dBμV/m) | | Result |
|--------------------|-------------------------|-------------------------|---------|----------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 4990.142 | H | 53.1 | / | 74.0 | 54.0 | Pass |
| 4993.785 | V | 55.2 | 38.4 | 74.0 | 54.0 | Pass |
| 7109.678 | H | 52.8 | / | 74.0 | 54.0 | Pass |
| 9577.107 | V | 52.4 | / | 74.0 | 54.0 | Pass |
| 9662.107 | H | 52.9 | / | 74.0 | 54.0 | Pass |
| 12154.428 | H | 57.4 | 44.3 | 74.0 | 54.0 | Pass |

Channel:Middle

| Frequency (MHz) | Antenna Polarization | Emission Level (dBμV/m) | | Limit (dBμV/m) | | Result |
|--------------------|-------------------------|-------------------------|---------|----------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 4996.821 | V | 55.2 | 37.9 | 74.0 | 54.0 | Pass |
| 7225.035 | V | 53.0 | / | 74.0 | 54.0 | Pass |
| 7313.678 | H | 53.2 | / | 74.0 | 54.0 | Pass |
| 9784.142 | H | 53.8 | / | 74.0 | 54.0 | Pass |
| 9802.964 | V | 53.5 | / | 74.0 | 54.0 | Pass |
| 12135.000 | H | 57.7 | 44.3 | 74.0 | 54.0 | Pass |


Channel: High

| Frequency (MHz) | Antenna Polarization | Emission Level (dBμV/m) | | Limit (dBμV/m) | | Result |
|--------------------|-------------------------|-------------------------|---------|----------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 4921.535 | V | 53.7 | / | 74.0 | 54.0 | Pass |
| 4987.107 | H | 52.9 | / | 74.0 | 54.0 | Pass |
| 4989.535 | V | 54.9 | 38.0 | 74.0 | 54.0 | Pass |
| 9785.357 | H | 54.0 | 40.4 | 74.0 | 54.0 | Pass |
| 9805.392 | V | 53.1 | / | 74.0 | 54.0 | Pass |
| 12255.214 | H | 56.9 | 44.2 | 74.0 | 54.0 | Pass |

802.11n20


Radiated emission below 1GHz

Horizontal (the worst plot is shown below)



| Frequency (MHz) | QuasiPeak (dBμV/m) | Pol. | Corr. (dB/m) | Margin (dB) | Limit (dBμV/m) | Result |
|--------------------|-----------------------|------|-----------------|----------------|-------------------|--------|
| 270.407500 | 43.0 | H | 13.8 | 3.0 | 46.0 | Pass |
| 327.542500 | 27.1 | H | 15.7 | 18.9 | 46.0 | Pass |
| 350.942500 | 27.1 | H | 16.1 | 18.9 | 46.0 | Pass |
| 374.342500 | 26.6 | H | 16.8 | 19.4 | 46.0 | Pass |
| 399.985000 | 35.2 | H | 17.4 | 10.8 | 46.0 | Pass |
| 421.142500 | 28.0 | H | 17.9 | 18.0 | 46.0 | Pass |

Vertical (the worst plot is shown below)



| Frequency (MHz) | QuasiPeak (dBμV/m) | Pol. | Corr. (dB/m) | Margin (dB) | Limit (dBμV/m) | Result |
|-----------------|--------------------|------|--------------|-------------|----------------|--------|
| 41.965000 | 24.3 | V | 13.9 | 15.7 | 40.0 | Pass |
| 112.457500 | 29.4 | V | 11.4 | 14.1 | 43.5 | Pass |
| 271.772500 | 36.2 | V | 13.8 | 9.8 | 46.0 | Pass |
| 421.142500 | 28.3 | V | 17.9 | 17.7 | 46.0 | Pass |
| 444.542500 | 27.2 | V | 18.6 | 18.8 | 46.0 | Pass |
| 538.142500 | 29.7 | V | 20.3 | 16.3 | 46.0 | Pass |

Above 1GHz

Channel:Low

| Frequency (MHz) | Antenna Polarization | Emission Level (dBμV/m) | | Limit (dBμV/m) | | Result |
|--------------------|-------------------------|-------------------------|---------|----------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 4990.750 | V | 53.3 | / | 74.0 | 54.0 | Pass |
| 4996.214 | H | 54.9 | 37.7 | 74.0 | 54.0 | Pass |
| 9648.142 | H | 54.6 | 41.7 | 74.0 | 54.0 | Pass |
| 10875.785 | V | 58.8 | 45.3 | 74.0 | 54.0 | Pass |
| 12041.500 | V | 57.3 | 43.7 | 74.0 | 54.0 | Pass |
| 12118.000 | H | 57.4 | 43.9 | 74.0 | 54.0 | Pass |

Channel:Middle

| Frequency (MHz) | Antenna Polarization | Emission Level (dBμV/m) | | Limit (dBμV/m) | | Result |
|--------------------|-------------------------|-------------------------|---------|----------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 4987.107 | H | 54.4 | 37.5 | 74.0 | 54.0 | Pass |
| 4988.928 | V | 54.2 | 37.0 | 74.0 | 54.0 | Pass |
| 7211.678 | V | 53.3 | / | 74.0 | 54.0 | Pass |
| 7336.142 | H | 52.7 | / | 74.0 | 54.0 | Pass |
| 9711.892 | H | 52.9 | / | 74.0 | 54.0 | Pass |
| 12093.714 | H | 57.5 | 43.9 | 74.0 | 54.0 | Pass |

Channel: High

| Frequency (MHz) | Antenna Polarization | Emission Level (dBμV/m) | | Limit (dBμV/m) | | Result |
|--------------------|-------------------------|-------------------------|---------|----------------|---------|--------|
| | | Peak | Average | Peak | Average | |
| 4979.821 | V | 54.0 | 35.9 | 74.0 | 54.0 | Pass |
| 4991.357 | H | 54.4 | 37.6 | 74.0 | 54.0 | Pass |
| 7357.392 | H | 52.7 | / | 74.0 | 54.0 | Pass |
| 8676.714 | V | 53.0 | / | 74.0 | 54.0 | Pass |
| 9320.892 | H | 53.9 | / | 74.0 | 54.0 | Pass |
| 11544.857 | H | 57.2 | 43.9 | 74.0 | 54.0 | Pass |



Report No.: HKEM220900091602
Page: 40 of 68

8 Photographs

Remark: Photos refer to Appendix: External Photo, Internal Photo, and Setup Photo


9 Appendix

9.1 99% Bandwidth


802.11b:


| DUT Frequency (MHz) | Bandwidth (MHz) | Limit Min (MHz) | Limit Max (MHz) | Band Edge Left (MHz) | Band Edge Right (MHz) |
|---------------------|-----------------|-----------------|-----------------|----------------------|-----------------------|
| 2412.000000 | 13.200000 | --- | --- | 2405.350000 | 2418.550000 |
| 2437.000000 | 13.400000 | --- | --- | 2430.250000 | 2443.650000 |
| 2462.000000 | 13.300000 | --- | --- | 2455.450000 | 2468.750000 |

99 % Bandwidth



99 % Bandwidth





Measurement


| Setting | Instrument Value | Target Value |
|-----------------------|------------------|--------------------|
| Span | 40.000 MHz | 40.000 MHz |
| RBW | 200.000 kHz | ≥ 200.000 kHz |
| VBW | 1.000 MHz | ≥ 600.000 kHz |
| SweepPoints | 400 | ~ 400 |
| SweepTime | 47.266 μ s | AUTO |
| Reference Level | 0.000 dBm | 0.000 dBm |
| Attenuation | 20.000 dB | AUTO |
| Detector | MaxPeak | MaxPeak |
| SweepCount | 100 | 100 |
| Filter | 3 dB | 3 dB |
| Trace Mode | Max Hold | Max Hold |
| SweepType | FFT | AUTO |
| Preamplifier | off | off |
| Stablemode | Trace | Trace |
| Stablevalue | 0.30 dB | 0.30 dB |
| Run | 8 / max. 150 | max. 150 |
| Stable | 3 / 3 | 3 |
| Max Stable Difference | 0.06 dB | 0.30 dB |

Remark: Cable loss 0.8dB was considered and set in system configuration.


802.11g:


| DUT Frequency (MHz) | Bandwidth (MHz) | Limit Min (MHz) | Limit Max (MHz) | Band Edge Left (MHz) | Band Edge Right (MHz) |
|---------------------|-----------------|-----------------|-----------------|----------------------|-----------------------|
| 2412.000000 | 16.700000 | --- | --- | 2403.550000 | 2420.250000 |
| 2437.000000 | 16.700000 | --- | --- | 2428.650000 | 2445.350000 |
| 2462.000000 | 16.700000 | --- | --- | 2453.650000 | 2470.350000 |

99 % Bandwidth



99 % Bandwidth





Measurement


| Setting | Instrument Value | Target Value |
|-----------------------|------------------|--------------------|
| Span | 40.000 MHz | 40.000 MHz |
| RBW | 200.000 kHz | ≥ 200.000 kHz |
| VBW | 1.000 MHz | ≥ 600.000 kHz |
| SweepPoints | 400 | ~ 400 |
| SweepTime | 47.266 μ s | AUTO |
| Reference Level | 0.000 dBm | 0.000 dBm |
| Attenuation | 20.000 dB | AUTO |
| Detector | MaxPeak | MaxPeak |
| SweepCount | 100 | 100 |
| Filter | 3 dB | 3 dB |
| Trace Mode | Max Hold | Max Hold |
| SweepType | FFT | AUTO |
| Preamplifier | off | off |
| Stablemode | Trace | Trace |
| Stablevalue | 0.30 dB | 0.30 dB |
| Run | 24 / max. 150 | max. 150 |
| Stable | 3 / 3 | 3 |
| Max Stable Difference | 0.10 dB | 0.30 dB |

Remark: Cable loss 0.8dB was considered and set in system configuration.


802.11n20:


| DUT Frequency (MHz) | Bandwidth (MHz) | Limit Min (MHz) | Limit Max (MHz) | Band Edge Left (MHz) | Band Edge Right (MHz) |
|---------------------|-----------------|-----------------|-----------------|----------------------|-----------------------|
| 2412.000000 | 17.700000 | --- | --- | 2403.150000 | 2420.850000 |
| 2437.000000 | 17.700000 | --- | --- | 2428.150000 | 2445.850000 |
| 2462.000000 | 17.700000 | --- | --- | 2453.150000 | 2470.850000 |

99 % Bandwidth



99 % Bandwidth





Measurement

| Setting | Instrument Value | Target Value |
|-----------------------|------------------|--------------------|
| Span | 40.000 MHz | 40.000 MHz |
| RBW | 200.000 kHz | ≥ 200.000 kHz |
| VBW | 1.000 MHz | ≥ 600.000 kHz |
| SweepPoints | 400 | ~ 400 |
| SweepTime | 47.266 μ s | AUTO |
| Reference Level | 0.000 dBm | 0.000 dBm |
| Attenuation | 20.000 dB | AUTO |
| Detector | MaxPeak | MaxPeak |
| SweepCount | 100 | 100 |
| Filter | 3 dB | 3 dB |
| Trace Mode | Max Hold | Max Hold |
| SweepType | FFT | AUTO |
| Preamp | off | off |
| Stablemode | Trace | Trace |
| Stablevalue | 0.30 dB | 0.30 dB |
| Run | 19 / max. 150 | max. 150 |
| Stable | 3 / 3 | 3 |
| Max Stable Difference | 0.19 dB | 0.30 dB |


Remark: Cable loss 0.8dB was considered and set in system configuration.

9.2 Minimum Emission Bandwidth 6 dB


802.11b:


| DUT Frequency (MHz) | Bandwidth (MHz) | Limit Min (MHz) | Limit Max (MHz) | Band Edge Left (MHz) | Band Edge Right (MHz) |
|---------------------|-----------------|-----------------|-----------------|----------------------|-----------------------|
| 2412.000000 | 8.600000 | --- | --- | 2407.425000 | 2416.025000 |
| 2437.000000 | 9.100000 | --- | --- | 2432.425000 | 2441.525000 |
| 2462.000000 | 7.650000 | --- | --- | 2458.375000 | 2466.025000 |

6 dB Bandwidth



6 dB Bandwidth





Measurement


| Setting | Instrument Value | Target Value |
|-----------------------|------------------|--------------|
| Span | 40.000 MHz | 40.000 MHz |
| RBW | 100.000 kHz | 100.000 kHz |
| VBW | 300.000 kHz | 300.000 kHz |
| SweepPoints | 800 | ~ 800 |
| SweepTime | 94.922 μ s | AUTO |
| Reference Level | 10.000 dBm | 10.000 dBm |
| Attenuation | 30.000 dB | AUTO |
| Detector | MaxPeak | MaxPeak |
| SweepCount | 100 | 100 |
| Filter | 3 dB | 3 dB |
| Trace Mode | Max Hold | Max Hold |
| SweepType | FFT | AUTO |
| Preamplifier | off | off |
| Stablemode | Trace | Trace |
| Stablevalue | 0.50 dB | 0.50 dB |
| Run | 10 / max. 150 | max. 150 |
| Stable | 5 / 5 | 5 |
| Max Stable Difference | 0.11 dB | 0.50 dB |

Remark: Cable loss 0.8dB was considered and set in system configuration.


802.11g:


| DUT Frequency (MHz) | Bandwidth (MHz) | Limit Min (MHz) | Limit Max (MHz) | Band Edge Left (MHz) | Band Edge Right (MHz) |
|---------------------|-----------------|-----------------|-----------------|----------------------|-----------------------|
| 2412.000000 | 16.400000 | --- | --- | 2403.775000 | 2420.175000 |
| 2437.000000 | 16.400000 | --- | --- | 2428.775000 | 2445.175000 |
| 2462.000000 | 16.400000 | --- | --- | 2453.775000 | 2470.175000 |

6 dB Bandwidth



6 dB Bandwidth





Measurement


| Setting | Instrument Value | Target Value |
|-----------------------|------------------|---------------|
| Span | 40.000 MHz | 40.000 MHz |
| RBW | 100.000 kHz | ~ 100.000 kHz |
| VBW | 300.000 kHz | ~ 300.000 kHz |
| SweepPoints | 800 | ~ 800 |
| SweepTime | 94.922 μ s | AUTO |
| Reference Level | 0.000 dBm | 0.000 dBm |
| Attenuation | 20.000 dB | AUTO |
| Detector | MaxPeak | MaxPeak |
| SweepCount | 100 | 100 |
| Filter | 3 dB | 3 dB |
| Trace Mode | Max Hold | Max Hold |
| SweepType | FFT | AUTO |
| Preamplifier | off | off |
| Stablemode | Trace | Trace |
| Stablevalue | 0.50 dB | 0.50 dB |
| Run | 20 / max. 150 | max. 150 |
| Stable | 5 / 5 | 5 |
| Max Stable Difference | 0.14 dB | 0.50 dB |

Remark: Cable loss 0.8dB was considered and set in system configuration.


802.11n20:


| DUT Frequency (MHz) | Bandwidth (MHz) | Limit Min (MHz) | Limit Max (MHz) | Band Edge Left (MHz) | Band Edge Right (MHz) |
|---------------------|-----------------|-----------------|-----------------|----------------------|-----------------------|
| 2412.000000 | 17.650000 | --- | --- | 2403.175000 | 2420.825000 |
| 2437.000000 | 17.600000 | --- | --- | 2428.175000 | 2445.775000 |
| 2462.000000 | 17.400000 | --- | --- | 2453.425000 | 2470.825000 |

6 dB Bandwidth



6 dB Bandwidth





Measurement

| Setting | Instrument Value | Target Value |
|-----------------------|------------------|---------------|
| Span | 40.000 MHz | 40.000 MHz |
| RBW | 100.000 kHz | ~ 100.000 kHz |
| VBW | 300.000 kHz | ~ 300.000 kHz |
| SweepPoints | 800 | ~ 800 |
| SweepTime | 94.922 μ s | AUTO |
| Reference Level | 0.000 dBm | 0.000 dBm |
| Attenuation | 20.000 dB | AUTO |
| Detector | MaxPeak | MaxPeak |
| SweepCount | 100 | 100 |
| Filter | 3 dB | 3 dB |
| Trace Mode | Max Hold | Max Hold |
| SweepType | FFT | AUTO |
| Preamplifier | off | off |
| Stablemode | Trace | Trace |
| Stablevalue | 0.50 dB | 0.50 dB |
| Run | 14 / max. 150 | max. 150 |
| Stable | 5 / 5 | 5 |
| Max Stable Difference | 0.43 dB | 0.50 dB |

Remark: Cable loss 0.8dB was considered and set in system configuration.

9.3 RF output power


| Operation Mode | DUT Frequency (MHz) | Limit Max (dBm) | Gated Level (dBm) | Result |
|----------------|---------------------|-----------------|-------------------|--------|
| 802.11b | 2412.000000 | 30.0 | 14.7 | PASS |
| 802.11b | 2437.000000 | 30.0 | 13.8 | PASS |
| 802.11b | 2462.000000 | 30.0 | 14.5 | PASS |
| 802.11g | 2412.000000 | 30.0 | 11.9 | PASS |
| 802.11g | 2437.000000 | 30.0 | 10.7 | PASS |
| 802.11g | 2462.000000 | 30.0 | 12.0 | PASS |
| 802.11n20 | 2412.000000 | 30.0 | 11.8 | PASS |
| 802.11n20 | 2437.000000 | 30.0 | 10.5 | PASS |
| 802.11n20 | 2462.000000 | 30.0 | 11.9 | PASS |

Remark:

Cable loss 0.8dB was considered and set in system configuration.


(only the plot of the worst case is shown for each mode)

802.11b:



802.11g:


Gated Trace



— Gated Trace — Overall — Limit

802.11n20:

Gated Trace




— Gated Trace — Overall — Limit

Power Spectral Density

802.11b:


| DUT Frequency (MHz) | Frequency (MHz) | PSD (dBm) | Limit Max (dBm) | Result |
|---------------------|-----------------|-----------|-----------------|--------|
| 2412.000000 | 2411.475000 | 5.884 | 8.0 | PASS |
| 2437.000000 | 2437.475000 | 4.763 | 8.0 | PASS |
| 2462.000000 | 2462.975000 | 5.360 | 8.0 | PASS |

Peak Power Spectral Density




— Limit — Sum Level ◆ PSD

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Peak Power Spectral Density




802.11g:

| DUT Frequency (MHz) | Frequency (MHz) | PSD (dBm) | Limit Max (dBm) | Result |
|---------------------|-----------------|-----------|-----------------|--------|
| 2412.000000 | 2419.475000 | -0.447 | 8.0 | PASS |
| 2437.000000 | 2444.475000 | -1.682 | 8.0 | PASS |
| 2462.000000 | 2469.475000 | -0.130 | 8.0 | PASS |


Peak Power Spectral Density



Peak Power Spectral Density




Peak Power Spectral Density




802.11n20:

| DUT Frequency (MHz) | Frequency (MHz) | PSD (dBm) | Limit Max (dBm) | Result |
|---------------------|-----------------|-----------|-----------------|--------|
| 2412.000000 | 2410.725000 | -0.397 | 8.0 | PASS |
| 2437.000000 | 2430.725000 | -1.729 | 8.0 | PASS |
| 2462.000000 | 2469.475000 | -0.198 | 8.0 | PASS |


Peak Power Spectral Density



Peak Power Spectral Density



Peak Power Spectral Density




Measurement

| Setting | Instrument Value | Target Value |
|-----------------------|------------------|--------------------|
| Span | 30.000 MHz | 30.000 MHz |
| RBW | 100.000 kHz | ≤ 100.000 kHz |
| VBW | 300.000 kHz | ≥ 300.000 kHz |
| SweepPoints | 600 | ~ 600 |
| Sweptime | 12.000 ms | 12.000 ms |
| Reference Level | 0.000 dBm | 0.000 dBm |
| Attenuation | 20.000 dB | AUTO |
| Detector | RMS | RMS |
| SweepCount | 1 | 1 |
| Filter | 3 dB | 3 dB |
| Trace Mode | Max Hold | Max Hold |
| SweepType | Sweep | Sweep |
| Preamplifier | off | off |
| Stablemode | Trace | Trace |
| Stablevalue | 0.50 dB | 0.50 dB |
| Run | 45 / max. 150 | max. 150 |
| Stable | 3 / 3 | 3 |
| Max Stable Difference | 0.30 dB | 0.50 dB |

Remark: Cable loss 0.8dB was considered and set in system configuration.

9.4 Band Edge

802.11b Band Edge Low




Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2399.475000 | -43.2 | 20.8 | -22.4 | PASS |
| 2399.975000 | -43.4 | 21.0 | -22.4 | PASS |
| 2399.525000 | -44.7 | 22.3 | -22.4 | PASS |
| 2399.925000 | -44.9 | 22.5 | -22.4 | PASS |
| 2399.225000 | -45.0 | 22.6 | -22.4 | PASS |
| 2399.675000 | -45.0 | 22.6 | -22.4 | PASS |
| 2399.375000 | -45.1 | 22.7 | -22.4 | PASS |
| 2399.175000 | -45.1 | 22.7 | -22.4 | PASS |
| 2399.275000 | -45.2 | 22.8 | -22.4 | PASS |
| 2399.725000 | -45.2 | 22.8 | -22.4 | PASS |
| 2397.275000 | -45.2 | 22.9 | -22.4 | PASS |
| 2397.225000 | -45.3 | 22.9 | -22.4 | PASS |
| 2399.125000 | -45.3 | 22.9 | -22.4 | PASS |
| 2399.425000 | -45.3 | 22.9 | -22.4 | PASS |
| 2399.575000 | -45.3 | 23.0 | -22.4 | PASS |

Remark: Limit = Inband peak - 30dB

802.11b Band Edge High




Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2492.675000 | -45.9 | 23.5 | -22.4 | PASS |
| 2494.825000 | -46.1 | 23.7 | -22.4 | PASS |
| 2497.425000 | -46.2 | 23.8 | -22.4 | PASS |
| 2494.875000 | -46.2 | 23.8 | -22.4 | PASS |
| 2487.075000 | -46.3 | 23.9 | -22.4 | PASS |
| 2492.625000 | -46.4 | 24.0 | -22.4 | PASS |
| 2487.725000 | -46.4 | 24.0 | -22.4 | PASS |
| 2496.475000 | -46.5 | 24.1 | -22.4 | PASS |
| 2487.125000 | -46.5 | 24.1 | -22.4 | PASS |
| 2488.125000 | -46.6 | 24.2 | -22.4 | PASS |
| 2497.475000 | -46.6 | 24.2 | -22.4 | PASS |
| 2496.625000 | -46.6 | 24.2 | -22.4 | PASS |
| 2497.375000 | -46.7 | 24.3 | -22.4 | PASS |
| 2484.275000 | -46.7 | 24.3 | -22.4 | PASS |
| 2485.525000 | -46.7 | 24.3 | -22.4 | PASS |

Remark: Limit = Inband peak - 30dB

802.11g Band Edge Low




Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2399.975000 | -37.9 | 9.5 | -28.4 | PASS |
| 2399.875000 | -38.6 | 10.3 | -28.4 | PASS |
| 2399.825000 | -39.3 | 10.9 | -28.4 | PASS |
| 2399.925000 | -39.5 | 11.2 | -28.4 | PASS |
| 2399.725000 | -39.8 | 11.4 | -28.4 | PASS |
| 2399.775000 | -40.8 | 12.5 | -28.4 | PASS |
| 2399.475000 | -41.5 | 13.2 | -28.4 | PASS |
| 2399.525000 | -41.6 | 13.2 | -28.4 | PASS |
| 2399.675000 | -41.6 | 13.3 | -28.4 | PASS |
| 2399.625000 | -41.7 | 13.3 | -28.4 | PASS |
| 2399.575000 | -41.7 | 13.4 | -28.4 | PASS |
| 2399.375000 | -41.9 | 13.5 | -28.4 | PASS |
| 2399.325000 | -41.9 | 13.6 | -28.4 | PASS |
| 2399.425000 | -42.0 | 13.6 | -28.4 | PASS |
| 2399.175000 | -42.1 | 13.7 | -28.4 | PASS |

Remark: Limit = Inband peak - 30dB

802.11g Band Edge High




Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2490.175000 | -45.3 | 17.3 | -28.0 | PASS |
| 2490.225000 | -45.7 | 17.7 | -28.0 | PASS |
| 2486.425000 | -46.0 | 18.0 | -28.0 | PASS |
| 2486.375000 | -46.1 | 18.1 | -28.0 | PASS |
| 2490.125000 | -46.3 | 18.3 | -28.0 | PASS |
| 2486.625000 | -46.5 | 18.5 | -28.0 | PASS |
| 2486.525000 | -46.5 | 18.5 | -28.0 | PASS |
| 2494.225000 | -46.6 | 18.6 | -28.0 | PASS |
| 2493.475000 | -46.6 | 18.6 | -28.0 | PASS |
| 2493.525000 | -46.6 | 18.6 | -28.0 | PASS |
| 2486.475000 | -46.7 | 18.7 | -28.0 | PASS |
| 2486.025000 | -46.7 | 18.7 | -28.0 | PASS |
| 2485.975000 | -46.7 | 18.7 | -28.0 | PASS |
| 2487.275000 | -46.9 | 18.9 | -28.0 | PASS |
| 2487.375000 | -46.9 | 18.9 | -28.0 | PASS |

Remark: Limit = Inband peak - 30dB

802.11n20 Band Edge Low

Band Edge




Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2399.975000 | -36.6 | 8.2 | -28.4 | PASS |
| 2399.925000 | -37.9 | 9.4 | -28.4 | PASS |
| 2399.475000 | -38.6 | 10.2 | -28.4 | PASS |
| 2399.525000 | -38.9 | 10.4 | -28.4 | PASS |
| 2399.875000 | -38.9 | 10.5 | -28.4 | PASS |
| 2399.725000 | -39.1 | 10.7 | -28.4 | PASS |
| 2399.775000 | -39.4 | 11.0 | -28.4 | PASS |
| 2399.825000 | -40.1 | 11.6 | -28.4 | PASS |
| 2399.625000 | -40.1 | 11.7 | -28.4 | PASS |
| 2399.675000 | -40.3 | 11.9 | -28.4 | PASS |
| 2399.575000 | -40.4 | 12.0 | -28.4 | PASS |
| 2399.425000 | -41.1 | 12.7 | -28.4 | PASS |
| 2399.325000 | -42.4 | 13.9 | -28.4 | PASS |
| 2399.375000 | -42.4 | 14.0 | -28.4 | PASS |
| 2399.175000 | -42.5 | 14.1 | -28.4 | PASS |

Remark: Limit = Inband peak - 30dB

802.11n20 Band Edge High

Band Edge



Measurements

| Frequency (MHz) | Level (dBm) | Margin (dB) | Limit (dBm) | Result |
|-----------------|-------------|-------------|-------------|--------|
| 2486.925000 | -45.8 | 17.7 | -28.1 | PASS |
| 2486.975000 | -46.1 | 17.9 | -28.1 | PASS |
| 2497.625000 | -46.1 | 18.0 | -28.1 | PASS |
| 2498.675000 | -46.2 | 18.1 | -28.1 | PASS |
| 2497.675000 | -46.2 | 18.1 | -28.1 | PASS |
| 2489.275000 | -46.2 | 18.1 | -28.1 | PASS |
| 2498.725000 | -46.3 | 18.2 | -28.1 | PASS |
| 2494.125000 | -46.3 | 18.2 | -28.1 | PASS |
| 2484.825000 | -46.4 | 18.2 | -28.1 | PASS |
| 2484.725000 | -46.4 | 18.3 | -28.1 | PASS |
| 2496.975000 | -46.4 | 18.3 | -28.1 | PASS |
| 2484.675000 | -46.4 | 18.3 | -28.1 | PASS |
| 2489.225000 | -46.5 | 18.4 | -28.1 | PASS |
| 2494.075000 | -46.6 | 18.5 | -28.1 | PASS |
| 2488.725000 | -46.6 | 18.5 | -28.1 | PASS |

Remark: Limit = Inband peak - 30dB

Measurement setting


| Setting | Instrument Value | Target Value |
|-----------------------|------------------|--------------------|
| RBW | 100.000 kHz | ≤ 100.000 kHz |
| VBW | 300.000 kHz | ≥ 300.000 kHz |
| SweepPoints | 1670 | ~ 1670 |
| SweepTime | 1.670 ms | AUTO |
| Reference Level | 0.000 dBm | 0.000 dBm |
| Attenuation | 20.000 dB | AUTO |
| Detector | MaxPeak | MaxPeak |
| SweepCount | 100 | 100 |
| Filter | 3 dB | 3 dB |
| Trace Mode | Max Hold | Max Hold |
| SweepType | Sweep | AUTO |
| Preamp | off | off |
| Stablemode | Trace | Trace |
| Stablevalue | 0.50 dB | 0.50 dB |
| Run | 9 / max. 150 | max. 150 |
| Stable | 3 / 3 | 3 |
| Max Stable Difference | 0.18 dB | 0.50 dB |

Remark: Cable loss 0.8dB was considered and set in system configuration.


9.5 Conducted spurious emission

Only the worst case is shown for each mode

802.11b




802.11g



802.11n20

Spurious



— Limit — Sum Level — Threshold × Critical × Final Critical

Limit=Inband peak-30dB

Pre Measurement 1

| Setting | Instrument Value | Target Value |
|-----------------------|------------------|----------------|
| RBW | 100.000 kHz | <= 100.000 kHz |
| VBW | 300.000 kHz | >= 300.000 kHz |
| SweepPoints | 2601 | ~ 2601 |
| SweepTime | 23.700 ms | AUTO |
| Reference Level | -10.000 dBm | -30.000 dBm |
| Attenuation | 20.000 dB | AUTO |
| Detector | MaxPeak | MaxPeak |
| SweepCount | 3 | 3 |
| Filter | 3 dB | 3 dB |
| Trace Mode | Max Hold | Max Hold |
| SweepType | Sweep | AUTO |
| Preamplifier | off | off |
| Stablemode | Trace | Trace |
| Stablevalue | 0.50 dB | 0.50 dB |
| Run | 8 / max. 40 | max. 40 |
| Stable | 3 / 3 | 3 |
| Max Stable Difference | 0.00 dB | 0.50 dB |

Remark: Cable loss 0.8dB was considered and set in system configuration.

- End of the Report -