

ST TECHA

# **RF Exposure evaluation**

Product Name	:	AXON 3 STUDIO REFERENCE MONITOR
Brand Name	:	NUX
Model	:	NFM-03
Series Model	:	N/A
FCC ID	:	2BCVT-NFM-03
Applicant	:	Cherub Technology Co., Ltd.
Address	:	No.10, Keji 9th Road, Tangjiawan Town, Zhuhai High-tech Zone, Zhuhai, Guangdong, China, 519080
Manufacturer	:	Cherub Technology Co., Ltd.
Address	:	No.10, Keji 9th Road, Tangjiawan Town, Zhuhai High-tech Zone, Zhuhai, Guangdong, China, 519080
Standard(s)	:	47CFR §1.1310, 47CFR §2.1091 KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt	:	Mar. 20, 2025
Date of Test	:	Mar. 20, 2025~ Apr. 03, 2025
Issued Date	:	Apr. 03, 2025

Issued By:

#### Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street,

Bao'an District, Shenzhen, Guangdong, China

Tel.: +86 0755-230967639 Fax.: +86 0755-230967639

Reviewed by:	Jeon Yi	Approved by:	Sean She	
	Leon.yi		Sean She	* TESTREPOR

Note: This device has been tested and found to comply with the standard(s) listed, this test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory. This report shall not be reproduced except in full, without the written approval of Guangdong Asia Hongke Test Technology Limited. If there is a need to alter or revise this document, the right belongs to Guangdong Asia Hongke Test Technology Limited, and it should give a prior written notice of the revision document. This test report must not be used by the client to claim product endorsement.

#### Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.



#### **Report Revise Record**

Report Version	Issued Date	Notes
M1	Apr. 03, 2025	Initial Release



## Contents

GEN	ERAL INFORMATION	.4
1.1 1.2	Environmental conditions General Description of EUT	.4 .4
1.3	TEST FACILITY	.5
1.4	MEASUREMENT UNCERTAINTY	.5
MET	HOD OF MEASUREMENT	.6
2.1	Applicable Standard	.6
2.2	LIMIT	.6
2.3	MPE CALCULATION METHOD	.7
2.4	ANTENNA INFORMATION	.7
2.5	MANUFACTURING TOLERANCE	.7
2.6	STANDALONE MPE RESULT	.8
2.7	CONCLUSION	.8
	GEN 1.1 1.2 1.3 1.4 MET 2.1 2.2 2.3 2.4 2.5 2.6 2.7	GENERAL INFORMATION   1.1 ENVIRONMENTAL CONDITIONS.   1.2 GENERAL DESCRIPTION OF EUT   1.3 TEST FACILITY   1.4 MEASUREMENT UNCERTAINTY   METHOD OF MEASUREMENT   2.1 APPLICABLE STANDARD   2.2 LIMIT.   2.3 MPE CALCULATION METHOD   2.4 ANTENNA INFORMATION   2.5 MANUFACTURING TOLERANCE   2.6 STANDALONE MPE RESULT   2.7 CONCLUSION



## **1 GENERAL INFORMATION**

## **1.1 Environmental conditions**

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

## 1.2 General Description of EUT

Product Name:	AXON 3 STUDIO REFERENCE MONITOR		
Model/Type reference:	NFM-03		
Serial Model:	N/A		
Power Rating:	N/A		
Adapter information:	DC 24 V 2.5A 60W from adapter		
Hardware Version:	N/A		
Software Version:	N/A		
Sample(s) Status:	AiTSZ-250320047-1(Normal sample) AiTSZ-250320047-2(Engineer sample)		
Bluetooth :			
Supported type:	Bluetooth BR/EDR		
Modulation:	GFSK, π/4DQPSK, 8DPSK		
Operation frequency:	2402MHz~2480MHz		
Channel number:	79		
Channel separation:	1MHz		
Antenna type:	PCB antenna		
Antenna gain:	1.54dBi		
Bluetooth LE:			
Supported type:	Bluetooth BLE 1M		
Modulation:	GFSK		
Operation frequency:	2402MHz~2480MHz		
Channel number:	40		
Channel separation:	2MHz		
Antenna type:	PCB antenna		
Antenna gain:	1.54dBi		
<b>Remark:</b> The above DUT's information was declared by manufacturer. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.			



## 1.3 Test Facility

#### **Test Laboratory:**

#### Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

The test facility is recognized, certified or accredited by the following organizations:

#### FCC-Registration No.: 251906 Designation Number: CN1376

Guangdong Asia Hongke Test Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

#### IC — Registration No.: 31737 CAB identifier: CN0165

The 3m Semi-anechoic chamber of Guangdong Asia Hongke Test Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 31737

#### A2LA-Lab Cert. No.: 7133.01

Guangdong Asia Hongke Test Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

### **1.4 Measurement uncertainty**

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Guangdong Asia Hongke Test Technology Limited's quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Asia Hongke laboratory is reported:

Test	Measurement Uncertainty	Notes
Power Line Conducted Emission	150KHz~30MHz ±1.20 dB	(1)
Radiated Emission	9KHz~30Hz ±3.10dB	(1)
Radiated Emission	9KHz~1GHz ±3.75dB	(1)
Radiated Emission	1GHz~18GHz ±3.88 dB	(1)
Radiated Emission	18GHz-40GHz ±3.88dB	(1)
RF power, conducted	30MHz~6GHz ±0.16dB	(1)
RF power density, conducted	±0.24dB	(1)
Spurious emissions, conducted	±0.21dB	(1)
Temperature	±1°C	(1)
Humidity	±3%	(1)
DC and low frequency voltages	±1.5%	(1)
Time	±2%	(1)
Duty cycle	±2%	(1)
Bandwidth	±1.5 x10 <sup>-6</sup>	(1)

The report uncertainty of measurement  $y \pm U$ , where expended uncertainty U is based on a standard uncertainty Multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.



## 2 Method of measurement

## 2.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures

## 2.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure						
Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time		
Range(MHz)	Strength(V/m)	Strength(A/m)	(mW/cm²)	(minute)		
Limits for Occupational/Controlled Exposure						
0.3 – 3.0	614	1.63	(100) *	6		
3.0 - 30	1842/f	4.89/f	(900/f)*	6		
30 – 300	61.4	0.163	1.0	6		
300 – 1500	1	1	f/300	6		
1500 – 100,000	/	/	5	6		

#### Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time		
Range(MHz)	Strength(V/m) Strength(A/m) (mW/cm <sup>2</sup> )		(mW/cm <sup>2</sup> )	(minute)		
	Limits for Occupational/Controlled Exposure					
0.3 - 3.0	614	1.63	(100) *	30		
3.0 – 30	824/f	2.19/f	(180/f)*	30		
30 – 300	27.5	0.073	0.2	30		
300 – 1500	/	/	f/1500	30		
1500 - 100,000	/	/	1.0	30		

F=frequency in MHz

\*=Plane-wave equivalent power density





## 2.3 MPE Calculation Method

Predication of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

#### S=PG/4πR<sup>2</sup>

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

8

## 2.4 Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Antenna	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
BT	/	PCB Antenna	1.54dBi	2400-2500MHz
BLE	/	PCB Antenna	1.54dBi	2400-2500MHZ

## 2.5 Manufacturing Tolerance

Frequency	BT(Peak) - GFSK				
(MHz)	2402	2441	2480		
Target (dBm)	0.0	1.0	0.0		
Tolerance ± (dB)	1.0	1.0	1.0		
Frequency		BT(Peak) - Pi/4DQPSK			
(MHz)	2402	2441	2480		
Target (dBm)	0.5	1.0	0.5		
Tolerance ± (dB)	1.0	1.0	1.0		
Frequency		BT(Peak) - 8DPSK			
(MHz)	2402	2441	2480		
Target (dBm)	0.5	0.5	0.0		
Tolerance ± (dB)	1.0	1.0	1.0		
Frequency	BLE(Peak) - GFSK				
(MHz)	2402	2440	2480		
Target (dBm)	-5.0	-5.0	-5.0		
Tolerance ± (dB)	1.0	1.0	1.0		



### 2.6 Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, r = 20cm, as well as the gain of the used antenna is refer to section 4, the RF power density can be obtained.

Modulation Type	Output power with tune_up		Antenna Gain	Antenna Gain (linear)	MPE	MPE Limits
	dBm	mW	(dBi)	(initial)	(	(mW/cm2)
2.4G BT	2.0	1.58	1.54	1.4256	0.0004	1
2.4G BLE	-4.0	0.40	1.54	1.4256	0.0001	1

Remark:

1. Output power (Peak) including turn-up tolerance;

2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

## 2.7 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.