

Test Report

Product	Digital Video Conference System with WLAN and BT
Name and address of the applicant	Cisco Systems, Inc. 170 West Tasman Drive San Jose, CA 95134, USA
Name and address of the manufacturer	Cisco Systems, Inc. 170 West Tasman Drive San Jose, CA 95134, USA
Model	TTC60-21
Rating	Mains (100-240V 50/60 Hz, 1.8A – 0.8A)
Trademark	Cisco
Serial number	/
Additional information	Bluetooth, 802.11a/b/g/n/ac
Tested according to	FCC Part 15.247 Digital Transmission Systems Industry Canada RSS-247, Issue 2 Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
Order number	312072
Tested in period	2017.02.2 to 2017.03.09 and 2017.03.20
Issue date	2017.04.18
Name and address of the testing laboratory	 Instituttveien 6 Kjeller, Norway FCC No: 994405 IC OATS: 2040D-1 TEL: +47 22 96 03 30 FAX: +47 22 96 05 50
 Prepared by [Frode Sveinsen]  Approved by [G.Suwanthakumar]	
This report shall not be reproduced except in full without the written approval of Nemko. Opinions and interpretations expressed within this report are not part of the current accreditation. This report was originally distributed electronically with digital signatures. For more information contact Nemko.	

CONTENTS

1	INFORMATION	3
1.1	Test Item	3
1.2	Normal test condition	3
1.3	Test Engineer(s)	3
1.4	Description of modification for Modification Filing	4
1.5	Family List Rational	4
1.6	Antenna Requirement	4
1.7	Worst-Case Configuration and Mode	4
1.8	On Time and Duty Cycle Factors	4
1.9	Antenna Gain	4
1.10	Comments	4
2	TEST REPORT SUMMARY	5
2.1	General	5
2.2	Test Summary	6
3	TEST RESULTS	7
3.1	Power Line Conducted Emissions	7
3.2	Spurious Emissions (Radiated)	8
3.3	Radiated Emissions, 30 – 1000 MHz	15
3.4	Radiated Emissions, 1-25 GHz	17
4	Measurement Uncertainty	45
5	LIST OF TEST EQUIPMENT	46
6	BLOCK DIAGRAM	47
6.1	Power Line Conducted Emission	47
6.2	Test Site Radiated Emission	47

1 INFORMATION

1.1 Test Item

Name :	Cisco
Model/version :	TTC60-21
FCC ID :	LDK60211476
Industry Canada ID :	2461N-60211476
Serial number :	/
Hardware identity and/or version:	Rev. D
Software identity and/or version :	S01828-1.1.0 574512d, CE9.1.x
Frequency Range :	2412 – 2462 MHz
Number of Channels :	11
Operating Modes :	802.11b 802.11g 802.11n (HT20) (HT40 mode is disabled)
Type of Modulation :	Digital (DSSS, OFDM)
Rated Output Power :	802.11b: 0.060 W (Conducted) 802.11g: 0.045 W (Conducted) 802.11n: 0.051 W (Conducted)
Antenna Connector :	Internal Antennas connected to PCB with U-FL connector
Antenna Diversity Supported :	Yes
Smart Antennas System :	MIMO
Power Supply :	Mains (Integral Power Supply)

Description of Test Item

The EUT is a digital video encoder/decoder with WiFi and Bluetooth transceivers. The WiFi and Bluetooth transceivers are contained in a module with single modular certification (FCC ID: VOB-P2180), however the antennas used in this EUT are not certified.

1.2 Normal test condition

Temperature:	22.3 – 23.7 °C
Relative humidity:	30 - 57 %
Normal test voltage:	120 V AC

The values are the limit registered during the test period.

1.3 Test Engineer(s)

Frode Sveinsen
Kristian Osvoll (Power Line Conducted Test)

1.4 Description of modification for Modification Filing

Not applicable.

1.5 Family List Rational

Not Applicable.

1.6 Antenna Requirement

Is the antenna detachable?

☒ Yes ☐ No

If detachable, is the antenna connector non-standard?

☒ Yes ☐ No

Type of antenna connector: U-FL (The antennas are internal with connector on the PCB)

Ref. FCC §15.203

1.7 Worst-Case Configuration and Mode

Radiated Emissions and Power Line Conducted Emissions were performed with the EUT set to transmit at the channel with the highest output power as worst-case scenario. HT40 mode has been disabled in this EUT.

The worst case data rates were:

802.11b mode: 1 Mbps
802.11g mode: 6 Mbps
802.11n HT20 mode: MCS0

1.8 On Time and Duty Cycle Factors

Mode	On Time Burst (ms)	Period (msec)	Duty Cycle (linear)	Duty Cycle Correction: Power (dB)	Duty Cycle Correction: Voltage (dB)
802.11b	8.600	8.695	0.989	0.05	0.10
802.11g	1.425	1.536	0.928	0.33	0.65
802.11n HT20 CDD 2TX	0.692	0.793	0.872	0.59	1.18

The results above are from UL report no. 15U21878-E3V2

1.9 Antenna Gain

The EUT has two antennas that are connected to the main PCB with a cable and connector. The values below are the antenna gain values provided by the manufacturer:

Frequency (MHz)	Max Gain Ant #0 (dBi)	Max Gain Ant #1 (dBi)
2400	2.2	2.1
2420	2.6	2.1
2440	3.3	2.4
2450	3.7	2.5
2460	3.9	2.4
2480	3.9	2.3

1.10 Comments

This report covers only limited radiated tests to show compliance with the new antenna in this EUT. All other radio tests for 2.4GHz WLAN are covered by UL reports no. 15U21878-E3V2.

All ports were populated during spurious emission measurements.

2 TEST REPORT SUMMARY

2.1 General

All measurements are traceable to national standards.

The tests were performed for demonstrating compliance with FCC CFR 47 Part 15, paragraph 15.247 and Industry Canada RSS-247 Issue 2.

Tests were performed in accordance with ANSI C63.4-2014 and ANSI C63.10-2013.

Radiated tests were performed in a semi-anechoic chamber at measuring distances of 3m and 10m.

A description of the test facility is on file with the FCC and ISSED.

☒ New Submission

☒ Production Unit

☐ Class II Permissive Change

☐ Pre-production Unit

DTS Equipment Code

☐ Family Listing



THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.

2.2 Test Summary

Name of test	FCC Part 15 reference	RSS-247 Issue 2, RSS-GEN Issue 4 reference	Result
Supply Voltage Variations	15.31(e)	6.11 (RSS-GEN)	Complies ¹
Antenna Requirement	15.203	8.3 (RSS-GEN)	Complies
Power Line Conducted Emission	15.107(a) 15.207(a)	8.8 (RSS-GEN)	Complies
Occupied Bandwidth	N/A	6.6 (RSS-GEN)	Complies ¹
Minimum 6 dB Bandwidth	15.247(a)(2)	5.2 (1) (RSS-247)	Complies ¹
Peak Power Output	15.247(b)	5.4 (RSS-247)	Complies
Power Spectral Density	15.247(d)	5.2 (2) (RSS-247)	Complies ¹
Spurious Emissions (Antenna Conducted)	15.247(c)	5.5 (RSS-247)	Complies ¹
Spurious Emissions (Radiated)	15.247(c) 15.109(a) 15.209(a)	5.5 (RSS-247) 6.13 (RSS-GEN) 8.9 (RSS-GEN)	Complies

¹ Covered by UL Test Report no. 15U21878-E3V2 (FCC ID: VOB-P2180)

3 TEST RESULTS

3.1 Power Line Conducted Emissions

FCC Part 15.207 (a)

ISED RSS-GEN Issue 4, Clause 8.8

Test Performed By: Kristian Osvoll

Date of Test: 20-March-2017

Measurement procedure: ANSI C63.4-2014 using 50 μ H/50 ohms LISN.


Test Results: Complies.

Measurement Data: See attached graph, (Peak detector).

Highest measured value (L1 and N):

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	PE	Corr. (dB)
0.252	---	47.79	51.69	3.90	1000.0	9.000	N	GND	10.1
0.254	---	47.16	51.63	4.47	1000.0	9.000	N	GND	10.1
12.588	---	40.61	50.00	9.39	1000.0	9.000	N	GND	10.3
17.692	---	39.74	50.00	10.26	1000.0	9.000	L1	GND	10.6
18.244	---	38.25	50.00	11.75	1000.0	9.000	N	GND	10.5
24.076	---	41.53	50.00	8.47	1000.0	9.000	L1	GND	10.7
24.808	---	38.76	50.00	11.24	1000.0	9.000	L1	GND	10.7

Full Spectrum



3.2 Spurious Emissions (Radiated)

Para. No.: 15.247 (c)

ISED RSS-247 Issue 2

Test Results: Complies

Measurement Data:

Peak Detector:

Modulation and Bitrate	Measured field strength (dBμV/m)		Limit	Margin	
	2390 MHz	2483.5 MHz	dB	dB	
802.11b, 11 Mbps	50.3	57.5	74	23.7	16.5
802.11g, 6 Mbps	54.2	60.3	74	19.8	13.7
802.11n, MCS0	59.7	65.6	74	14.3	8.4


Average Detector:

Modulation and Bitrate	Measured field strength (dBμV/m)		Limit	Margin	
	2390 MHz	2483.5 MHz	dB	dB	
802.11b, 11 Mbps	35.2	43.0	54	18.9	11.1
802.11g, 6 Mbps	36.7	40.2	54	17.9	14.5
802.11n, MCS0	40.6	39.1	54	14.6	16.1


Values above are the maximum values for each modulation type.

Average detector values were measured with Average detector and trace averaging over 1000 sweeps. The measured values are corrected for duty cycle.


See attached plots




Lower Band Edge, Peak, 2412 MHz, 802.11b, 1Mbps, (Max: Ant 0, HP)




Lower Band Edge, Average, 2412 MHz, 802.11b, 1Mbps, (Max: Ant 0, HP)



Lower Band Edge, Peak, 2417 MHz, 802.11g, 6Mbps, (Max: Ant 0, HP)




Lower Band Edge, Average, 2417 MHz, 802.11g, 6Mbps, (Max: Ant 0, HP)



Lower Band Edge, Peak, 2412 MHz, 802.11n, MCS0, (Max: Ant 0, HP)



Lower Band Edge, Average, 2412 MHz, 802.11n, MCS0, (Max: Ant 0, HP)




Upper Band Edge, Peak, 2462 MHz, 802.11b, 1Mbps, (Max: Ant 0, HP)




Upper Band Edge, Average, 2462 MHz, 802.11b, 1Mbps, (Max: Ant 0, HP)




Upper Band Edge, Peak, 2457 MHz, 802.11g, 6Mbps, (Max: Ant 0, HP)



Upper Band Edge, Average, 2457 MHz, 802.11g, 6Mbps, (Max: Ant 0, HP)



Upper Band Edge, Peak, 2462 MHz, 802.11n, MCS0, (Max: Ant 0, HP)



Upper Band Edge, Average, 2462 MHz, 802.11n, MCS0, (Max: Ant 0, HP)

3.3 Radiated Emissions, 30 – 1000 MHz.

FCC 15.205, 15.209

ISED RSS-GEN, Issue 4, Clause 8.9

Test Results: Complies

Measurement Data:

Radiated emission 30 – 1000 MHz.

Detector: Quasi-Peak

Measuring distance 3m

Tested with all connections active


Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
43.831	38.40	40.00	1.60	1000.0	120.000	110.0	V	208	-27.1
57.103	37.98	40.00	2.02	1000.0	120.000	100.0	V	216	-28.7
74.853	38.14	40.00	1.86	1000.0	120.000	110.0	V	182	-28.3
118.001	38.83	43.50	4.67	1000.0	120.000	100.0	V	147	-26.0
173.248	34.44	43.50	9.06	1000.0	120.000	113.0	H	242	-23.2
270.336	39.27	46.00	6.73	1000.0	120.000	100.0	H	318	-23.5
285.840	34.31	46.00	11.69	1000.0	120.000	100.0	H	230	-22.9

See attached plots.


Requirements/Limit

FCC	Part 15.209 @ frequencies defined in §15.205	
ISED	RSS-GEN Issue 4, Clause 8.9 @ frequencies defined in 8.10	
	Radiated emission limit @3 meters	
Frequency (MHz)	Quasi Peak (μV/m)	Quasi Peak (dBμV/m)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Full Spectrum



Full Spectrum



3.4 Radiated Emissions, 1-25 GHz

FCC 15.205, 15.209

ISED RSS-GEN, Issue 4, Clause 8.9

Test Results: Complies

Measurement Data:

Radiated Emissions, 1-25 GHz

Measuring distance: 3m (1 – 8.5 GHz)
1m (8 – 25 GHz)

A pre-scan was performed above 18 GHz and no spurious emissions were detected.

Radiated Emissions in Restricted Bands						
Carrier Modulation	Carrier Freq MHz	Measured Freq MHz	Measured value Peak dBμV/m @3m	Measured value AV dBμV/m @3m	Limit (dBμV/m)	Verdict
Any*	Any	2777	57.0	36.1	74/54	Complies
Any*	Any	4160	57.7	37.2	74/54	Complies

* Not an emission from the radio


Only harmonics that fall in the restricted bands (ref. §15.205) have been checked.

Antenna factor, amplifier gain and cable loss are included in Spectrum Analyzer "Transducer factor".

See attached plots.


Requirements/Limit

FCC	Part 15.209 @ frequencies defined in §15.205	
ISED	RSS-GEN Issue 4, clause 8.9 @ frequencies defined in clause 8.10	
	Radiated emission limit @3 meters	
Frequency (MHz)	AV (dBμV/m)	Peak (dBμV/m)
Above 1 GHz	54.0	74.0




Date: 6.MAR.2017 09:23:28

Radiated Emissions, 1000 -2390 MHz, 2412MHz, HP, 802.11b, 1Mb, Ant0




Date: 6.MAR.2017 09:21:38

Radiated Emissions, 1000 -2390 MHz, 2412MHz, VP, 802.11b, 1Mb, Ant0




Date: 6.MAR.2017 09:27:41

Radiated Emissions, 1000 -2390 MHz, 2412MHz, HP, 802.11b, 1Mb, Ant1




Date: 6.MAR.2017 09:25:50


Radiated Emissions, 1000 -2390 MHz, 2412MHz, VP, 802.11b, 1Mb, Ant1




Radiated Emissions, 1000 -2390 MHz, 2412MHz, HP, 802.11n, MCS0, MIMO




Radiated Emissions, 1000 -2390 MHz, 2412MHz, VP, 802.11n, MCS0, MIMO




Radiated Emissions, 2500 -3200 MHz, 2462MHz, HP, 802.11b, 6Mbps, Ant0




Radiated Emissions, 2500 -3200 MHz, 2462MHz, VP, 802.11b, 6Mbps, Ant0




Radiated Emissions, 2500 -3200 MHz, 2472MHz, HP, 802.11b, 6Mbps, Ant1




Radiated Emissions, 2500 -3200 MHz, 2462MHz, VP, 802.11b, 6Mbps, Ant1




Radiated Emissions, 2500 -3200 MHz, 2462MHz, HP, 802.11n, MCS0, MIMO




Radiated Emissions, 2500 -3200 MHz, 2462MHz, VP, 802.11n, MCS0, MIMO



Radiated Emissions, 3000 -8500 MHz, 2442MHz, HP, 802.11b, 6Mbps, Ant0




Radiated Emissions, 3000 -8500 MHz, 2442MHz, VP, 802.11b, 6Mbps, Ant0




Radiated Emissions, 3000 -8500 MHz, 2442MHz, HP, 802.11b, 6Mbps, Ant1

(Measured with LCD panel Off)




Radiated Emissions, 3000 -8500 MHz, 2442MHz, VP, 802.11b, 6Mbps, Ant1


(Measured with LCD panel Off)




Radiated Emissions, 3000 -8500 MHz, 2442MHz, HP, 802.11g, 6Mbps, Ant0




Radiated Emissions, 3000 -8500 MHz, 2442MHz, VP, 802.11g, 6Mbps, Ant0




Radiated Emissions, 3000 -8500 MHz, 2442MHz, HP, 802.11n, MCS0, MIMO




Radiated Emissions, 3000 -8500 MHz, 2442MHz, VP, 802.11n, MCS0, MIMO




Radiated Emissions, 8000 -12000 MHz, 2442MHz, HP, 802.11b, 6Mbps, Ant0, @1m




Radiated Emissions, 8000 -12000 MHz, 2442MHz, VP, 802.11b, 6Mbps, Ant0, @1m




Radiated Emissions, 8000 -12000 MHz, 2442MHz, HP, 802.11b, 6Mbps, Ant1, @1m




Radiated Emissions, 8000 -12000 MHz, 2442MHz, VP, 802.11b, 6Mbps, Ant1, @1m




Radiated Emissions, 8000 -12000 MHz, 2442MHz, HP, 802.11n, MCS0, MIMO, @1m




Radiated Emissions, 8000 -12000 MHz, 2442MHz, VP, 802.11n, MCS0, MIMO, @1m




Radiated Emissions, 12000 -18000 MHz, 2442MHz, HP, 802.11b, 6Mbps, Ant0, @1m




Radiated Emissions, 12000 -18000 MHz, 2442MHz, VP, 802.11b, 6Mbps, Ant0, @1m




Radiated Emissions, 12000 -18000 MHz, 2442MHz, HP, 802.11b, 6Mbps, Ant1, @1m




Radiated Emissions, 12000 -18000 MHz, 2442MHz, VP, 802.11b, 6Mbps, Ant1, @1m



Radiated Emissions, 12000 -18000 MHz, 2442MHz, HP, 802.11n, MCS0, MIMO, @1m




Radiated Emissions, 12000 -18000 MHz, 2442MHz, VP, 802.11n, MCS0, MIMO, @1m




Date: 2.MAR.2017 15:38:00

Pre-scan, 18000 -25000 MHz, 2442MHz, 802.11b, 6Mbps, Ant0 (@ ≈10cm)




Date: 2.MAR.2017 15:39:15

Pre-scan, 18000 -25000 MHz, 2442MHz, 802.11b, 6Mbps, Ant1 (@ ≈10cm)




Date: 2.MAR.2017 15:43:46

Pre-scan, 18000 -25000 MHz, 2442MHz, 802.11g, 6Mbps, Ant0 (@ ≈10cm)




Date: 2.MAR.2017 15:45:11

Pre-scan, 18000 -25000 MHz, 2442MHz, 802.11g, 6Mbps, Ant1 (@ ≈10cm)




Date: 2.MAR.2017 15:41:46


Pre-scan, 18000 -25000 MHz, 2442MHz, 802.11n, MCS0, MIMO (@ ≈10cm)




Radiated Emissions Pk, 2777MHz, 2442MHz (Max: HP)
(Same for all RF-modulations and frequencies)




Radiated Emissions Av, 2777MHz, 2442MHz (Max: HP)
(Same for all RF-modulations and frequencies)




Radiated Emissions Pk, 2971MHz, 2442MHz (Max: HP)
(Same for all RF-modulations and frequencies)




Radiated Emissions Av, 2971MHz, 2442MHz (Max: HP)
(Same for all RF-modulations and frequencies)



Radiated Emissions Pk, 4158MHz, 2442MHz (Max: HP)
(Same for all RF-modulations and frequencies)



Radiated Emissions Av, 4158MHz, 2442MHz (Max: HP)
(Same for all RF-modulations and frequencies)



Radiated Emissions Pk, 5460MHz, 2442MHz (Max: HP)
(Same for all RF-modulations and frequencies)

4 Measurement Uncertainty

Measurement Uncertainty Values		
Test Item		Uncertainty
Output Power		±0.5 dB
Power Spectral Density		±0.5 dB
Out of Band Emissions, Conducted	< 3.6 GHz	±0.6 dB
	> 3.6 GHz	±0.9 dB
Spurious Emissions, Radiated	< 1 GHz	±2.5 dB
	> 1 GHz	±2.2 dB
Emission Bandwidth		±4 %
Power Line Conducted Emissions		+2.9 / -4.1 dB
Spectrum Mask Measurements	Frequency	±5 %
	Amplitude	±1.0 dB
Frequency Error		±0.6 ppm
Temperature Uncertainty		±1 °C

All uncertainty values are expanded standard uncertainty to give a confidence level of 95%, based on coverage factor k=2

5 LIST OF TEST EQUIPMENT


To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Test Laboratory.

No.	Model	Description	Manufacturer	Asset no.	Cal. date	Cal. Due
1	FSW26	Spectrum Analyzer	Rohde & Schwarz	LR 1640	2017.01	2018.01
2	ESU40	Measuring Receiver	Rohde & Schwarz	LR 1639	2016.12	2017.12
3	6HC3000/18000	Highpass Filter	Trilithic	LR 1614	Cal b4 use	
4	317	Preamplifier	Sonoma Instrument	LR 1687	2016.05	2017.05
5	8449A	Pre-amplifier	Hewlett Packard	LR 1322	2016.10	2017.10
6	6812B	AC Power Source	Agilent	LR 1515	Cal b4 use	
7	3115	Horn Antenna	EMCO	LR 1330	2016.10	2021.10
8	PM7320X	Antenna Horn	Sivers Lab	LR 102	2009.01	2019.01
9	DBF-520-20	Antenna Horn	Systron Donner	LR 100	2009.01	2019.01
10	638	Antenna Horn	Narda	LR 098	2010.06	2020.06
11	HK116	Biconical Antenna	Rohde & Schwarz	LR 1260	2013.12	2018.12
12	HL223	LogPeriod Antenna	Rohde & Schwarz	LR 1261	2013.12	2018.12
13	Model 87 V	Multimeter	Fluke	LR 1597	2016.10	2017.10
14	ESCI3	Measuring receiver	Rohde & Schwarz	N-4259	2015.08	2017.08
15	ESH3-Z2	Pulse Limiter	Rohde & Schwarz	LR 1074	2016.05	2017.05
16	ESH3-Z5	Two-Line V-Network	Rohde & Schwarz	N-3403	2015.07	2017.07


Test Software List			
Description	Manufacturer	Model	Version
EMC Software for Conducted tests	Rohde & Schwarz	EMC32	9.26.00

6 BLOCK DIAGRAM

6.1 Power Line Conducted Emission



6.2 Test Site Radiated Emission



The EUT is supplied with a stand for floor standing use, all tests were performed with the EUT mounted on this stand. No turntable was used for any of the tests.

For frequencies above 1 GHz the ground plane between the EUT and the measuring antenna was covered by absorbers.

Revision history

Version	Date	Comment	Sign
1.0	2017.04.12	First edition	FS