

Power reduction mechanism verification

According to the May 2017 TCBC Workshop, Demonstration of proper functioning of the detection and triggering mechanisms is required to support the corresponding RF exposure conditions. The verification is through a base station simulator is used to establish a conducted RF connection and monitor output power under different operating conditions related to the power reduction mechanisms. Detail of power reduction mechanisms referring to Operational Description

1. Power Verification Procedure

The power verification was performed according to the following procedure:

1. A base station simulator was used to establish a conducted RF connection and the output power was monitored. The power measurements were confirmed to be within expected tolerances for all states before and after a power reduction mechanism was triggered.
2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

General Note:

This device uses different Exposure Condition Index (DSI) to configure different time averaged power levels based on certain exposure scenarios as the following table:

Exposure Condition	Measure Distance	DSI	Ant No.	EUT Flip State	Trigger conditions
Head	touch&tilt 15deg	DSI 2	All ant	Flip Open	Earpiece On
Body worn	5 mm	DSI 3	All ant	Flip Open	Sensor On
Extremity	0mm	DSI 5	Ant2,Ant3,Ant4,Ant5, Ant6,Ant7,Ant8	Flip Open	Sensor On
Extremity	0mm	DSI 6	Ant0,Ant1,Ant2,Ant4,Ant7,Ant8	Flip Open	Sensor On
Hotspot	5 mm	DSI 7	All ant	Flip Open	Hotspot on
Extremity	0mm	DSI 9	Ant0,Ant1	Flip Open	Sensor On
Body worn	5 mm	DSI 10	All ant (Handheld except Ant2,Ant4,Ant7,Ant8)	Flip Close	Sensor On
Hotspot	5 mm	DSI 11	All ant	Flip Close	Hotspot on
Extremity	0mm	DSI 10	All ant (Handheld except Ant2,Ant4,Ant7,Ant8)	Flip Close	Sensor On
Extremity	0mm	DSI 12	Ant2,Ant4,Ant7,Ant8	Flip Close	Sensor On
Body Worn / Extremity / Sensor Off	Sensor Trigger Distance -1mm	DSI 4	All ant	Flip Open/Flip Close	Sensor Off

1. Select the bands with the largest power reduction for power verification :
 - a. Establish voice call and audio routed through the earpiece to monitor output power under head transmitting power states.
 - LTE Band 25/2 is set at 'highest BW, 1RB, RB Offset = 0, QPSK'.
 - b. Establish data connection monitor hotspot power state.
 - <Flip Open >
 - LTE Band 25/2 is set at 'highest BW, 1RB, RB Offset = 0, QPSK'.
 - <Flip Close >
 - LTE Band 48 is set at 'highest BW, 1RB, RB Offset = 0, QPSK'.
 - c. Establish data connection monitor body worn power state.
 - <Flip Open >
 - LTE Band 7 is set at 'highest BW, 1RB, RB Offset = 0, QPSK'.
 - Body Detect mechanism was performed for the in-hand and on a stationary object (placed on a table)
 - <Flip Close >
 - LTE Band 7 is set at 'highest BW, 1RB, RB Offset = 0, QPSK'.
 - Body Detect mechanism was performed for the in-hand and on a stationary object (placed on a table)
 - d. Establish data connection monitor extremity power state.
 - LTE Band 7 is set at 'highest BW, 1RB, RB Offset = 0, QPSK'.
 - Body Detect mechanism was performed for the in-hand and on a stationary object (placed on a table).
2. In this power validation purpose is to demonstrate of proper functioning of the detection and triggering mechanisms to support the corresponding RF exposure conditions.
3. Verification performed for one technology/Band to demonstrate that the power reduction applies for same technology/band and call origination.

2. Verification output Power Results

Head exposure conditions

Ear acoustic output Status:		OFF		ON	
Power state		WWAN DSI4		WWAN DSI2	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM1900 (GPRS 3 TX slots)	Ant 2	25.02	25.8	22.25	23.3
WCDMA II	Ant 2	23.55	24	18.02	18.9
LTE Band 41(PC2)	Ant 3	26.05	27	17.57	18.4
FR1 N7	Ant 2	23.31	24	16.33	17

Hotspot exposure condition

<Flip Open >

Flip Open Hotspot output Status:		OFF		ON	
Power state		WWAN DSI4		WWAN DSI7	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM1900 (GPRS 3 TX slots)	Ant 2	25.02	25.8	21.71	23
WCDMA II	Ant 2	23.55	24	19.02	19.7
LTE Band 41(PC2)	Ant 3	26.05	27	18.08	19.2
FR1 N25	Ant 2	23.17	24	16.61	17.5

<Flip Close >

Flip Close Hotspot output Status:		OFF		ON	
Power state		WWAN DSI4		WWAN DSI11	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM1900 (GPRS 3 TX slots)	Ant 2	25.02	25.8	22.11	23.1
WCDMA II	Ant 2	23.55	24	18.72	19.5
LTE Band 41	Ant 3	26.05	27	19.43	20.5
FR1 N25	Ant 2	23.17	24	16.61	17.5

Body worn exposure condition

<Flip Open >

Flip Open Sensor output Status:		OFF		ON	
Power state		WWAN DSI4		WWAN DSI3	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM1900 (GPRS 3 TX slots)	Ant 2	25.02	25.8	24.11	25.3
WCDMA II	Ant 2	23.55	24	21.24	22.1
LTE Band 41(PC2)	Ant 3	26.05	27	21.48	22.4
FR1 N7	Ant 3	22.87	24	18.41	19.5

<Flip Close >

Flip Close Sensor output Status:		OFF		ON	
Power state		WWAN DSI4		WWAN DSI10	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
WCDMA II	Ant 2	23.55	24	22.01	22.5
LTE Band 41(PC2)	Ant 3	26.05	27	22.54	23.6
FR1 N41(PC3)	Ant 2	26.16	27	19.36	20

Extremity exposure condition

<Flip Open >

Flip Open Sensor output Status:		OFF		ON	
Power state		WWAN DSI4		WWAN DSI5	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
LTE Band 7	Ant 3	22.87	24	19.04	20.5
FR1 N7	Ant 3	22.87	24	20.44	21.5

Flip Open Sensor output Status:		OFF		ON	
Power state		WWAN DSI4		WWAN DSI6	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
LTE Band 7	Ant 2	23.3	24	22.02	22.7
FR1 N7	Ant 1	23.18	24	22.7	23.5



Flip Open Sensor output Status:		OFF		ON	
Power state		WWAN DSI4		WWAN DSI9	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
LTE Band 7	Ant 1	23.15	24	22.07	23.1
FR1 N7	Ant 1	23.18	24	22.7	23.5

3. Angle Verification Results

The angle verification procedure was performed according to the following procedure:

1. For licensed modes, the device state index on the device UI was monitored to determine the triggering state.
2. The device was opened and closed to determine the angle at which the Hall sensor mechanism triggers, per the FCC TCB Workshop Slides from November 2019. The triggering conditions of the angles were sufficient such that all possible user scenarios with the device in open/closed condition are in the different power state, the angle Verification data as following tables.

[illegible]