FCC §15.247 (i) & §1.1307 (b) (3) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation					
RF Source frequency (MHz)	Threshold ERP (watts)				
0.3-1.34	1,920 R ² .				
1.34-30	3,450 R ² /f ² .				
30-300	3.83 R ² .				
300-1,500	0.0128 R ² f.				
1,500-100,000	19.2R ² .				

Ris the minimum separation distance in meters f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^{a} \frac{P_i}{P_{th,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$

Report No.: SZNS220711-31250E-RFB

Mode	Frequency (MHz)	Tune up conducted power	Antenna Gain		ERP		Evaluation Distance	ERP Limit
		(dBm)	(dBi)	(dBd)	(dBm)	(W)	(m)	(W)
BT	2402-2480	0	2.0	-0.15	-0.15	0.0010	0.2	0.768
BLE	2402-2480	-4.0	2.0	-0.15	-4.15	0.0004	0.2	0.768
Wi-Fi	2412-2462	21.0	1.0	-1.15	19.85	0.0966	0.2	0.768

Report No.: SZNS220711-31250E-RFB

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.

2. The BT/BLE can transmit at the same time with the Wi-Fi.

Simultaneous transmitting consideration (worst case):

The ratio=ERP $_{\rm BT}$ /limit+ERP $_{\rm Wi-Fi}$ /limit=0.0010/0.768+0.0966/0.768=0.127 \leq 1.0, so simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.