RF Exposure Evaluation

Limits

KDB 447498 D01 General RF Exposure Guidance v06

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)						
(A) Limits for Occupational/Controlled Exposures										
0.3–3.0	614	1.63	*(100)	6						
3.0–30	1842/f	4.89/f	*(900/f²)	6						
30–300 61.4		0.163	1.0	6						
300–1500			f/300	6						
1500–100,000			5	6						
(B) Limits for General Population/Uncontrolled Exposure										
0.3–1.34	614	1.63	*(100)	30						
1.34–30	824/f	2.19/f	*(180/f²)	30						
30–300	27.5	0.073	0.2	30						
300–1500			f/1500	30						
1500–100,000			1.0	30						

Limits for Maximum Permissible Exposure (MPE)

f = frequency in MHz

Friis transmission formula: Pd = (Pout*G)/(4*pi*r²)

Where

Pd = power density in mW/cm², Pout = output power to antenna in mW;

G = gain of antenna in linear scale, Pi = 3.1416;

 \mathbf{R} = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

EIRP=EMeas+20log(dMeas)-104.7

EIRP is the equivalent isotropically radiated power, in dBm

EMeas is the field strength of the emission at the measurement distance, in dB μ V/m

dMeas is the measurement distance, in m

Test Result of RF Exposure Evaluation

For BLE

Field strength (dBuV/m)	EIRP (dBm)	Max tune-up (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
84.79	-10.37	0.0918	0.00002	1.0	PASS

Remark: antenna gain= -0.58dBi