

## FCC TEST REPORT

For

Shenzhen KVD Communication Equipment Limited

GSM/WCDMA Smartphone

Model No.: X30

Additional Model No.: /

Prepared for : Shenzhen KVD Communication Equipment Limited  
Address : Lenovo R&D Center 2F-B, South First Road, High-tech Park,  
Nanshan District, Shenzhen, Guangdong, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an  
District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : Jul 03, 2017  
Number of tested samples : 1  
Serial number : Prototype  
Date of Test : Jul 03, 2017~Jul 12, 2017  
Date of Report : Jul 12, 2017

## FCC TEST REPORT

### FCC CFR 47 PART 15 C(15.247)

**Report Reference No.** ..... : **LCS170801024AE**

**Date of Issue** ..... : Jul 12, 2017

**Testing Laboratory Name**..... : **Shenzhen LCS Compliance Testing Laboratory Ltd.**

**Address** ..... : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,  
Bao'an District, Shenzhen, Guangdong, China

**Testing Location/ Procedure** ..... : Full application of Harmonised standards ☒  
Partial application of Harmonised standards ☐  
Other standard testing method ☐

**Applicant's Name**..... : **Shenzhen KVD Communication Equipment Limited**

**Address** ..... : Lenovo R&D Center 2F-B, South First Road, High-tech Park,  
Nanshan District, Shenzhen, Guangdong, China

#### Test Specification

**Standard**..... : FCC CFR 47 PART 15 C(15.247)

**Test Report Form No.** ..... : LCSEMC-1.0

**TRF Originator** ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

**Master TRF** ..... : Dated 2011-03

#### Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**EUT Description.** ..... : **GSM/WCDMA Smartphone**

**Trade Mark**..... : DOOGEE

**Model/ Type reference** ..... : X30

**Ratings** ..... : DC 3.8V by Li-ion Battery(3360mAh)  
Charging parameter: Input: 100~240V AC, 50/60Hz, 0.2A;  
Adapter output:DC 5V, 1000mA

**Result** ..... : **Positive**

**Compiled by:**



Calvin Weng/ Administrators

**Supervised by:**



Dick Su/ Technique principal

**Approved by:**



Gavin Liang/ Manager

**FCC -- TEST REPORT**

<b>Test Report No. :</b>	<b>LCS170801024AE</b>	<u>Jul 12, 2017</u> Date of issue
--------------------------	-----------------------	--------------------------------------

EUT.....	: GSM/WCDMA Smartphone
Type / Model.....	: X30
<b>Applicant.....</b>	<b>: Shenzhen KVD Communication Equipment Limited</b>
Address.....	: Lenovo R&D Center 2F-B, South First Road, High-tech Park, Nanshan District, Shenzhen, Guangdong, China
Telephone.....	:
Fax.....	:
<b>Manufacturer.....</b>	<b>: Shenzhen KVD Communication Equipment Limited</b>
Address.....	: A, 3rd floor, Building A2, Silicon valley Digital Industrial Park, 22nd of Dafu industrial area, Aobei Community, Guanlan town, Longhua District, shenzhen 518000, China
Telephone.....	:
Fax.....	:
<b>Factory.....</b>	<b>: Shenzhen KVD Communication Equipment Limited</b>
Address.....	: A, 3rd floor, Building A2, Silicon valley Digital Industrial Park, 22nd of Dafu industrial area, Aobei Community, Guanlan town, Longhua District, shenzhen 518000, China
Telephone.....	:
Fax.....	:

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

**Revision History**

Revision	Issue Date	Revisions	Revised By
000	Jul 12, 2017	Initial Issue	Gavin Liang

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>6</b>
1.1. DESCRIPTION OF DEVICE (EUT) .....	6
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS .....	6
1.3. EXTERNAL I/O CABLE .....	6
1.4. DESCRIPTION OF TEST FACILITY .....	7
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY .....	7
1.6. MEASUREMENT UNCERTAINTY .....	7
1.7. DESCRIPTION OF TEST MODES .....	8
<b>2. TEST METHODOLOGY .....</b>	<b>9</b>
2.1. EUT CONFIGURATION .....	9
2.2. EUT EXERCISE .....	9
2.3. GENERAL TEST PROCEDURES .....	9
<b>3. SYSTEM TEST CONFIGURATION.....</b>	<b>10</b>
3.1. JUSTIFICATION .....	10
3.2. EUT EXERCISE SOFTWARE.....	10
3.3. SPECIAL ACCESSORIES .....	10
3.4. BLOCK DIAGRAM/SCHEMATICS.....	10
3.5. EQUIPMENT MODIFICATIONS .....	10
3.6. TEST SETUP .....	10
<b>4. SUMMARY OF TEST RESULTS.....</b>	<b>11</b>
<b>5. TEST RESULT.....</b>	<b>12</b>
5.1. ON TIME AND DUTY CYCLE .....	12
5.2. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT.....	14
5.3. POWER SPECTRAL DENSITY MEASUREMENT .....	16
5.4. 6 dB SPECTRUM BANDWIDTH MEASUREMENT .....	21
5.5. RADIATED EMISSIONS MEASUREMENT.....	26
5.6. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGES TEST.....	45
5.7. POWER LINE CONDUCTED EMISSIONS .....	56
5.8. ANTENNA REQUIREMENTS .....	59
<b>6. LIST OF MEASURING EQUIPMENTS .....</b>	<b>60</b>
<b>7. TEST SETUP PHOTOGRAPHS OF EUT.....</b>	<b>61</b>
<b>8. EXTERIOR PHOTOGRAPHS OF THE EUT.....</b>	<b>61</b>
<b>9. INTERIOR PHOTOGRAPHS OF THE EUT .....</b>	<b>61</b>

# 1. GENERAL INFORMATION

## 1.1. Description of Device (EUT)

Name of EUT	GSM/WCDMA Smartphone
Model Number	X30
Modulation Type	GMSK for GSM/GPRS, 8-PSK for EDGE, QPSK for UMTS
Antenna Gain	0 dBi (max.) For GSM 850, GSM 900, DCS 1800, PCS 1900; 0 dBi (max.) For WCDMA Band II, V; -1 dBi (max.) For BT and WLAN
Hardware version	HCT-W178MB-A2
Software version	DOOGEE-X30-Android7.0-20170622
GSM/EDGE/GPRS Operation Frequency Band	GSM850/PCS1900/GPRS850/GPRS1900/EDGE850/EDGE1900
UMTS Operation Frequency Band	UMTS FDD Band II/V
LTE Operation Frequency Band	Not Supported
GSM/EDGE/GPRS	Supported GSM/GPRS/EDGE
GSM Release Version	R99
GSM/EDGE/GPRS Power Class	GSM850:Power Class 4/ PCS1900:Power Class 1
GPRS/EDGE Multislot Class	GPRS/EDGE: Multi-slot Class 12
GPRS operation mode	Class B
WCDMA Release Version	R99
HSDPA Release Version	Release 9
HSUPA Release Version	Release 6
DC-HSUPA Release Version	Not Supported
LTE Release Version	Not Supported
LTE/UMTS Power Class	Class 3
WLAN FCC Modulation Type	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20/40: OFDM (64QAM, 16QAM, QPSK,BPSK)
WLAN FCC Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz IEEE 802.11n HT40:2422-2452MHz
Antenna Type	PIFA Antenna
BT Modulation Type	GFSK,8-DPSK, $\pi$ /4DQPSK(BT V4.1)
Extreme temp. Tolerance	-30°C to +50°C
GPS function	Support and only RX
NFC Function	Not Supported
Extreme vol. Limits	3.40VDC to 4.35VDC (nominal: 3.80VDC)

## 1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
Shenzhen HuaJin Electronics Co., Ltd.	Power Adapter	HJ-0501000E1-US	---	FCC VoC

## 1.3. External I/O Cable

I/O Port Description	Quantity	Cable
USB	1	1m, unshielded cable
Earphone	1	N/A

#### 1.4. Description of Test Facility

CNAS Registration Number. is L4595.

FCC Registration Number. is 899208.

Industry Canada Registration Number. is 9642A-1.

ESMD Registration Number. is ARCB0108.

UL Registration Number. is 100571-492.

TUV SUD Registration Number. is SCN1081.

TUV RH Registration Number. is UA 50296516-001

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

#### 1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

#### 1.6. Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Radiation Uncertainty	:	9KHz~30MHz	±3.10dB	(1)
		30MHz~200MHz	±2.96dB	(1)
		200MHz~1000MHz	±3.10dB	(1)
		1GHz~26.5GHz	±3.80dB	(1)
		26.5GHz~40GHz	±3.90dB	(1)
Conduction Uncertainty	:	150kHz~30MHz	±1.63dB	(1)
Power disturbance	:	30MHz~300MHz	±1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 1.7. Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power that was determined to be IEEE 802.11b mode (Mid Channel).

AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/50Hz modes, recorded worst case;

AC conducted emission pre-test at both at power adapter and power from PC modes, recorded worst case;

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power that was determined to be IEEE 802.11b mode (Mid Channel).

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

IEEE 802.11b Mode: 1 Mbps, DSSS.

IEEE 802.11g Mode: 6 Mbps, OFDM.

IEEE 802.11n Mode HT20: MCS0, OFDM.

IEEE 802.11n Mode HT40: MCS0, OFDM.

BT LE: 1Mbps, GFSK.

### Channel List & Frequency

#### IEEE 802.11b/g/n HT20

Frequency Band	Channel No.	Frequency(MHz)	Channel No.	Frequency(MHz)
2412~2462MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	--	--

#### IEEE 802.11n HT40

Frequency Band	Channel No.	Frequency(MHz)	Channel No.	Frequency(MHz)
2412~2462MHz	--	--	7	2442
	--	--	8	2447
	3	2422	9	2452
	4	2427	--	--
	5	2432	--	--
	6	2437	--	--

#### Bluetooth V4.1(DTS)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2402	21	2442
2	2404	---	---
3	2406	---	---
---	---	38	2476
---	---	39	2478
19	2438	40	2480
20	2440		



## 2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

### 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB558074 D01 DTS Meas. Guidance v04 and KDB 662911 are required to be used for this kind of FCC 15.247 digital modulation device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### 2.3. General Test Procedures

#### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

### 3. SYSTEM TEST CONFIGURATION

#### 3.1. Justification

The system was configured for testing in a continuous transmits condition.

#### 3.2. EUT Exercise Software

The sample is controlled by using dialing engineering code (\*##3646633##) to control sample change channel, modulation and so on;

#### 3.3. Special Accessories

No.	Equipment	Manufacturer	Model No.	Serial No.	Length	shielded/ unshielded	Notes
1	PC	Lenovo	Ideapad	A131101550	/	/	DOC
2	Power adapter	Lenovo	CPA-A090	36200414	1.00m	unshielded	DOC

#### 3.4. Block Diagram/Schematics

Please refer to the related document

#### 3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### 3.6. Test Setup

Please refer to the test setup photo.

## 4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart C		
FCC Rules	Description of Test	Result
§15.247(b)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	6dB Bandwidth	Compliant
§15.247(a)	Occupied Bandwidth	Compliant
§15.205, §15.209, §15.247(d)	Radiated and Conducted Spurious Emissions	Compliant
§15.207(a)	Conducted Emissions	Compliant
§15.203	Antenna Requirements	Compliant
§15.247(i)§2.1093	RF Exposure	Compliant

## 5. TEST RESULT

### 5.1. On Time and Duty Cycle

#### 5.1.1. Standard Applicable

None; for reporting purpose only.


#### 5.1.2. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of the spectrum analyzer.

#### 5.1.3. Test Procedures

1. Set the centre frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=8MHz, VBW=50MHz, Sweep time=5ms;
3. Detector = peak;
4. Trace mode = Single hold.

#### 5.1.4. Test Setup Layout





#### 5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



#### 5.1.6. Test result

Mode	On Time B (ms)	Period (ms)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW(KHz)
BT LE	5	5	1	100	0	0.010
IEEE 802.11b	5	5	1	100	0	0.010
IEEE 802.11g	5	5	1	100	0	0.010
IEEE 802.11n-HT20	5	5	1	100	0	0.010
IEEE 802.11n-HT40	5	5	1	100	0	0.010



## On Time and Duty Cycle



## IEEE 802.11b



## IEEE 802.11n-HT20



## BT LE

## 5.2. Maximum Conducted Output Power Measurement

### 5.2.1. Standard Applicable

According to §15.247(b): For systems using digital modulation in the 2400-2483.5 MHz and 5725-5850 MHz band, the limit for maximum peak conducted output power is 30dBm. The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter peak output power.

### 5.2.2. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of the power meter.

### 5.2.3. Test Procedures

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power, 9.1.2 the maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

According to KDB558074 D01 DTS Measurement Guidance Section 9.2 Maximum average conducted output power, 9.2.3.1 Method AVGPM (Measurement using an RF average power meter)

(a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.


- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
- 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

(b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.

(c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

(d) Adjust the measurement in dBm by adding  $10\log(1/x)$ , where x is the duty cycle to the measurement result.

### 5.2.4. Test Setup Layout



### 5.2.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 5.2.6. Test Result of Maximum Conducted Output Power

Temperature	25℃	Humidity	46%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n & BT LE

Test Mode	Channel	Frequency (MHz)	Measured Peak Output Power (dBm)	Measured Average Output Power (dBm)	Limits (dBm)	Verdict
IEEE 802.11b	1	2412	15.11	13.30	30	PASS
	6	2437	<b>15.39</b>	<b>13.61</b>		
	11	2462	15.25	13.25		
IEEE 802.11g	1	2412	14.81	13.00	30	PASS
	6	2437	15.14	13.42		
	11	2462	15.09	13.28		
IEEE 802.11n HT20	1	2412	14.63	12.88	30	PASS
	6	2437	14.95	13.13		
	11	2462	14.47	12.71		
IEEE 802.11n HT40	3	2422	13.92	12.02	30	PASS
	6	2437	14.23	12.39		
	9	2452	14.49	12.79		
BT – LE	0	2402	-5.783	-5.979	30	PASS
	19	2440	-4.816	-4.851		
	39	2480	-4.648	-4.783		

## Remark:

1. Measured output power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
4. Average power is for report only;

### 5.3. Power Spectral Density Measurement

#### 5.3.1. Standard Applicable

According to §15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


#### 5.3.2. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of Spectrum Analyzer.

#### 5.3.3. Test Procedures

1. The transmitter was connected directly to a Spectrum Analyzer.
2. The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
3. Set the RBW = 3 KHz~100 KHz.
4. Set the VBW  $\geq 3 \times$  RBW
5. Set the span to 1.5 times the DTS channel bandwidth.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.

#### 5.3.4. Test Setup Layout



#### 5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 5.3.6. Test Result of Power Spectral Density

Temperature	25°C	Humidity	46%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n & BT LE



Test Mode	Channel	Frequency (MHz)	Measured Peak Power Spectral Density (dBm/3KHz)	Limits (dBm/3KHz)	Verdict
IEEE 802.11b	1	2412	-8.677	8	PASS
	6	2437	-8.407		
	11	2462	-8.531		
IEEE 802.11g	1	2412	-15.296	8	PASS
	6	2437	-16.073		
	11	2462	-15.162		
IEEE 802.11n HT20	1	2412	-15.137	8	PASS
	6	2437	-15.550		
	11	2462	-15.573		
IEEE 802.11n HT40	3	2422	-16.996	8	PASS
	6	2437	-18.160		
	9	2452	-18.261		


Test Mode	Channel	Frequency (MHz)	Measured Peak Power Spectral Density (dBm/3KHz)	Limits (dBm/3KHz)	Verdict
BT – LE	0	2402	-12.765	8	PASS
	19	2440	-11.876		
	39	2480	-11.707		

**Remark:**


1. Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
4. Please refer to following plots;

## Power Spectral Density


## IEEE 802.11b




## IEEE 802.11g




## Channel 1 / 2412 MHz




## Channel 1 / 2412 MHz



## Channel 6 / 2437 MHz



## Channel 6 / 2437 MHz



## Channel 11 / 2462 MHz




## Channel 11 / 2462 MHz




## Power Spectral Density


## IEEE 802.11n HT20




## IEEE 802.11n HT40




## Channel 1 / 2412 MHz




## Channel 3 / 2422 MHz



## Channel 6 / 2437 MHz



## Channel 6 / 2437 MHz



## Channel 11 / 2462 MHz




## Channel 9 / 2452 MHz




## Power Spectral Density


BT – LE



BT – LE



Channel 0 / 2402 MHz



Channel 19 / 2440 MHz

Channel 39 / 2480 MHz

## 5.4. 6 dB Spectrum Bandwidth Measurement

### 5.4.1. Standard Applicable

According to §15.247(a) (2): For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 KHz.

### 5.4.2. Measuring Instruments and Setting


Please refer to section 6 of equipment's list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> RBW
Detector	Peak
Trace	Max Hold
Sweep Time	100ms

### 5.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth and the video bandwidth were set according to KDB558074.
3. Measured the spectrum width with power higher than 6dB below carrier.

### 5.4.4. Test Setup Layout



### 5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 5.4.6. Test Result of 6dB Spectrum Bandwidth

Temperature	25℃	Humidity	46%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n & BT LE

Test Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limits (MHz)	Verdict
IEEE 802.11b	1	2412	8.886	0.500	PASS
	6	2437	8.884		
	11	2462	8.851		
IEEE 802.11g	1	2412	16.39	0.500	PASS
	6	2437	16.39		
	11	2462	16.37		
IEEE 802.11n HT20	1	2412	17.59	0.500	PASS
	6	2437	17.59		
	11	2462	17.58		
IEEE 802.11n HT40	3	2422	36.08	0.500	PASS
	6	2437	36.09		
	9	2452	36.09		
BT - LE	0	2402	0.6557	0.500	PASS
	19	2440	0.6625		
	39	2480	0.6636		


**Remark:**

1. Measured 6dB Bandwidth at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
4. Please refer to following plots;




## 6 dB Bandwidth


## IEEE 802.11b




## IEEE 802.11g




## Channel 1 / 2412 MHz




## Channel 1 / 2412 MHz



## Channel 6 / 2437 MHz



## Channel 6 / 2437 MHz



## Channel 11 / 2462 MHz




## Channel 11 / 2462 MHz




## 6 dB Bandwidth


## IEEE 802.11n HT20




## IEEE 802.11n HT40




## Channel 1 / 2412 MHz




## Channel 3 / 2422 MHz



## Channel 6 / 2437 MHz



## Channel 6 / 2437 MHz



## Channel 11 / 2462 MHz




## Channel 9 / 2452 MHz






## 6 dB Bandwidth


BT – LE



BT – LE



Channel 0 / 2402 MHz



Channel 19 / 2440 MHz

Channel 39 / 2480 MHz

## 5.5. Radiated Emissions Measurement

### 5.5.1. Standard Applicable

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 5.5.2. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 <sup>th</sup> carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

### 5.5.3. Test Procedures

#### 1) Sequence of testing 9 kHz to 30 MHz

##### **Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

##### **Premeasurement:**

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

##### **Final measurement:**

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

### 3) Sequence of testing 1 GHz to 18 GHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

#### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

#### 4) Sequence of testing above 18 GHz

**Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.


**Premeasurement:**

- The antenna is moved spherical over the EUT in different polarizations of the antenna.


**Final measurement:**

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


## 5.5.4. Test Setup Layout



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB);  
 Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

## 5.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 5.5.6. Results of Radiated Emissions (9 KHz~30MHz)

Temperature	25℃	Humidity	46%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n & BT LE

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log$  (specific distance / test distance) (dB);


Limit line = specific limits (dBuV) + distance extrapolation factor.

## 5.5.7. Results of Radiated Emissions (30MHz~1GHz)

Temperature	25℃	Humidity	46%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b (Mid CH)

**Test result for IEEE 802.11b (Mid Channel)**

Horizontal:



	Freq MHz	Reading dBuV	CabLos dB	Antfac dB/m	Measured dBuV/m	Limit dBuV/m	Over dB	Remark
1	30.32	11.73	0.39	12.33	24.45	40.00	-15.55	QP
2	54.83	10.37	0.46	13.03	23.86	40.00	-16.14	QP
3	88.03	8.37	0.68	11.27	20.32	43.50	-23.18	QP
4	189.74	9.84	0.86	10.54	21.24	43.50	-22.26	QP
5	242.53	20.77	0.90	12.08	33.75	46.00	-12.25	QP
6	793.40	12.72	1.73	19.98	34.43	46.00	-11.57	QP


Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20dB below the official limit are not reported



Vertical:



	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	30.00	18.17	0.39	12.33	30.89	40.00	-9.11	QP
2	53.88	14.28	0.46	13.07	27.81	40.00	-12.19	QP
3	86.81	8.43	0.47	10.88	19.78	40.00	-20.22	QP
4	185.14	11.71	0.70	10.13	22.54	43.50	-20.96	QP
5	242.53	19.38	0.90	12.08	32.36	46.00	-13.64	QP
6	552.88	5.61	1.46	17.57	24.64	46.00	-21.36	QP


Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20dB below the official limit are not reported

Temperature	25°C	Humidity	46%
Test Engineer	Jayden Zhuo	Configurations	BLE(High CH)

Horizontal:




	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	30.32	9.73	0.39	12.33	22.45	40.00	-17.55	QP
2	54.83	6.37	0.46	13.03	19.86	40.00	-20.14	QP
3	92.14	4.31	0.56	12.30	17.17	43.50	-26.33	QP
4	189.74	8.84	0.86	10.54	20.24	43.50	-23.26	QP
5	242.53	21.77	0.90	12.08	34.75	46.00	-11.25	QP
6	649.66	9.76	1.58	18.63	29.97	46.00	-16.03	QP
7	793.40	10.72	1.73	19.98	32.43	46.00	-13.57	QP

Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20dB below the official limit are not reported

Vertical:



	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	30.00	18.17	0.39	12.33	30.89	40.00	-9.11	QP
2	53.88	15.28	0.46	13.07	28.81	40.00	-11.19	QP
3	86.81	7.43	0.47	10.88	18.78	40.00	-21.22	QP
4	185.14	11.71	0.70	10.13	22.54	43.50	-20.96	QP
5	242.53	20.38	0.90	12.08	33.36	46.00	-12.64	QP
6	744.87	7.15	1.61	19.37	28.13	46.00	-17.87	QP

Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20db below the official limit are not reported

Note:

1). Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11b(Mid channel)&BLE (High Channel)). Emission level (dBuV/m) = 20 log Emission level (uV/m).

2). Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 5.5.8. Results for Radiated Emissions (Above 1GHz)

IEEE 802.11b

Channel 1 / 2412MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	55.14	33.06	35.14	3.98	57.04	74.00	-16.96	Peak	Horizontal
4824.00	39.63	33.06	35.14	3.98	41.53	54.00	-12.47	Average	Horizontal
4824.00	59.22	33.06	35.14	3.98	61.12	74.00	-12.88	Peak	Vertical
4824.00	43.71	33.06	35.14	3.98	45.61	54.00	-8.39	Average	Vertical

Channel 6 / 2437MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	54.58	33.16	35.15	3.96	56.55	74.00	-17.45	Peak	Horizontal
4874.00	40.55	33.16	35.15	3.96	42.52	54.00	-11.48	Average	Horizontal
4874.00	60.03	33.16	35.15	3.96	62.00	74.00	-12.00	Peak	Vertical
4874.00	41.57	33.16	35.15	3.96	43.54	54.00	-10.46	Average	Vertical

Channel 11 / 2462MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	55.19	33.26	35.14	3.98	57.29	74.00	-16.71	Peak	Horizontal
4924.00	39.42	33.26	35.14	3.98	41.52	54.00	-12.48	Average	Horizontal
4924.00	60.88	33.26	35.14	3.98	62.98	74.00	-11.02	Peak	Vertical
4924.00	41.93	33.26	35.14	3.98	44.03	54.00	-9.97	Average	Vertical

## IEEE 802.11g

## Channel 1 / 2412MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	53.94	33.06	35.14	3.98	55.84	74.00	-18.16	Peak	Horizontal
4824.00	39.73	33.06	35.14	3.98	41.63	54.00	-12.37	Average	Horizontal
4824.00	60.59	33.06	35.14	3.98	62.49	74.00	-11.51	Peak	Vertical
4824.00	42.80	33.06	35.14	3.98	44.70	54.00	-9.30	Average	Vertical

## Channel 6 / 2437MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	55.68	33.16	35.15	3.96	57.65	74.00	-16.35	Peak	Horizontal
4874.00	37.72	33.16	35.15	3.96	39.69	54.00	-14.31	Average	Horizontal
4874.00	60.54	33.16	35.15	3.96	62.51	74.00	-11.49	Peak	Vertical
4874.00	40.57	33.16	35.15	3.96	42.54	54.00	-11.46	Average	Vertical

## Channel 11 / 2462MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	56.86	33.26	35.14	3.98	58.96	74.00	-15.04	Peak	Horizontal
4924.00	40.16	33.26	35.14	3.98	42.26	54.00	-11.74	Average	Horizontal
4924.00	60.32	33.26	35.14	3.98	62.42	74.00	-11.58	Peak	Vertical
4924.00	43.51	33.26	35.14	3.98	45.61	54.00	-8.39	Average	Vertical

## IEEE 802.11n HT20

## Channel 1 / 2412MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	48.86	33.06	35.14	3.98	50.76	74.00	-23.24	Peak	Horizontal
4824.00	34.46	33.06	35.14	3.98	36.36	54.00	-17.64	Average	Horizontal
4824.00	53.46	33.06	35.14	3.98	55.36	74.00	-18.64	Peak	Vertical
4824.00	39.16	33.06	35.14	3.98	41.06	54.00	-12.94	Average	Vertical

## Channel 6 / 2437MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	49.72	33.16	35.15	3.96	51.69	74.00	-22.31	Peak	Horizontal
4874.00	34.21	33.16	35.15	3.96	36.18	54.00	-17.82	Average	Horizontal
4874.00	54.20	33.16	35.15	3.96	56.17	74.00	-17.83	Peak	Vertical
4874.00	36.28	33.16	35.15	3.96	38.25	54.00	-15.75	Average	Vertical

## Channel 11 / 2462MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	49.45	33.26	35.14	3.98	51.55	74.00	-22.45	Peak	Horizontal
4924.00	33.34	33.26	35.14	3.98	35.44	54.00	-18.56	Average	Horizontal
4924.00	53.30	33.26	35.14	3.98	55.40	74.00	-18.60	Peak	Vertical
4924.00	38.75	33.26	35.14	3.98	40.85	54.00	-13.15	Average	Vertical

## IEEE 802.11n HT40

## Channel 3 / 2422 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4844.00	49.11	33.06	35.14	3.98	51.01	74.00	-22.99	Peak	Horizontal
4844.00	34.46	33.06	35.14	3.98	36.36	54.00	-17.64	Average	Horizontal
4844.00	55.29	33.06	35.14	3.98	57.19	74.00	-16.81	Peak	Vertical
4844.00	39.26	33.06	35.14	3.98	41.16	54.00	-12.84	Average	Vertical

## Channel 6 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	51.78	33.16	35.15	3.96	53.75	74.00	-20.25	Peak	Horizontal
4874.00	33.57	33.16	35.15	3.96	35.54	54.00	-18.46	Average	Horizontal
4874.00	54.27	33.16	35.15	3.96	56.24	74.00	-17.76	Peak	Vertical
4874.00	36.29	33.16	35.15	3.96	38.26	54.00	-15.74	Average	Vertical

## Channel 9 / 2452 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4904.00	50.60	33.26	35.14	3.98	52.70	74.00	-21.30	Peak	Horizontal
4904.00	34.18	33.26	35.14	3.98	36.28	54.00	-17.72	Average	Horizontal
4904.00	56.91	33.26	35.14	3.98	59.01	74.00	-14.99	Peak	Vertical
4904.00	37.76	33.26	35.14	3.98	39.86	54.00	-14.14	Average	Vertical

**BT LE****Channel 0 / 2402MHz**

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4804.00	49.63	33.06	35.04	3.94	51.59	74.00	-22.41	Peak	Horizontal
4804.00	33.36	33.06	35.04	3.94	35.32	54.00	-18.68	Average	Horizontal
4804.00	50.13	33.06	35.04	3.94	52.09	74.00	-21.91	Peak	Vertical
4804.00	35.02	33.06	35.04	3.94	36.98	54.00	-17.02	Average	Vertical

**Channel 19 / 2440MHz**

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4880.00	49.24	33.16	35.15	3.96	51.21	74.00	-22.79	Peak	Horizontal
4880.00	33.23	33.16	35.15	3.96	35.20	54.00	-18.80	Average	Horizontal
4880.00	51.03	33.16	35.15	3.96	53.00	74.00	-21.00	Peak	Vertical
4880.00	36.35	33.16	35.15	3.96	38.32	54.00	-15.68	Average	Vertical

**Channel 39 / 2480MHz**

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4960.00	47.65	33.26	35.14	3.98	49.75	74.00	-24.25	Peak	Horizontal
4960.00	31.71	33.26	35.14	3.98	33.81	54.00	-20.19	Average	Horizontal
4960.00	50.16	33.26	35.14	3.98	52.26	74.00	-21.74	Peak	Vertical
4960.00	36.38	33.26	35.14	3.98	38.48	54.00	-15.52	Average	Vertical

**Notes:**

1. Measuring frequencies from 9 KHz~10<sup>th</sup> harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
2. Radiated emissions measured in frequency range from 9 KHz~10<sup>th</sup> harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20 13.5Mbps at IEEE 802.11n HT40

## Results of Restricted Bands Test (Radiated)

According to C63.10:2013 Clause 11.12.2.2, for conducted measurements above 1000 MHz, EIRP shall be computed as specified in 11.12.2.2, and then field strength shall be computed as follows (see 11.12.2.2e):

1)  $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{m}]) + 104.77$ , where E is field strength and d is distance at which the field strength limit is specified in the applicable requirements.

2)  $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2$ , for  $d = 3 \text{ m}$ .

Then the radiated field strength E can be calculated as

$$E = \text{EIRP}[\text{dBm}] + 95.2$$

=Antenna port power+Antenna gain( or 2dBi, which is greater)+95.2

And note if the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater.

Add the appropriate maximum ground reflection factor to the EIRP (6 dB for frequencies < 30 MHz; 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive; and 0 dB for frequencies > 1000 MHz).

If all peak measurement results satisfy the average limit, then average measurements are not required.

802.11b						
Freq. MHz	Reading Level dBm	Antenna Gain dBi	Calculated E dBuV/m	Limit dBuV/m	Margin dB	Remark
2310.000	-40.962	-1.00	56.24	74.00	-17.76	Peak
2310.000	-52.852	-1.00	44.35	54.00	-9.65	Average
2390.000	-37.991	-1.00	59.21	74.00	-14.79	Peak
2390.000	-52.370	-1.00	44.83	54.00	-9.17	Average
2483.500	-40.598	-1.00	56.60	74.00	-17.40	Peak
2483.500	-51.738	-1.00	45.46	54.00	-8.54	Average
2500.000	-41.084	-1.00	56.12	74.00	-17.88	Peak
2500.000	-51.941	-1.00	45.26	54.00	-8.74	Average

802.11g						
Freq. MHz	Reading Level dBm	Antenna Gain dBi	Calculated E dBuV/m	Limit dBuV/m	Margin dB	Remark
2310.000	-42.639	-1.00	54.56	74.00	-19.44	Peak
2310.000	-52.825	-1.00	44.38	54.00	-9.63	Average
2390.000	-39.557	-1.00	57.64	74.00	-16.36	Peak
2390.000	-51.420	-1.00	45.78	54.00	-8.22	Average
2483.500	-33.094	-1.00	64.11	74.00	-9.89	Peak
2483.500	-49.451	-1.00	47.75	54.00	-6.25	Average
2500.000	-39.483	-1.00	57.72	74.00	-16.28	Peak
2500.000	-51.341	-1.00	45.86	54.00	-8.14	Average




802.11n(HT20)						
Freq. MHz	Reading Level dBm	Antenna Gain dBi	Calculated E dBuV/m	Limit dBuV/m	Margin dB	Remark
2310.000	-40.403	-1.00	56.80	74.00	-17.20	Peak
2310.000	-52.797	-1.00	44.40	54.00	-9.60	Average
2390.000	-36.923	-1.00	60.28	74.00	-13.72	Peak
2390.000	-50.165	-1.00	47.04	54.00	-6.97	Average
2483.500	-32.136	-1.00	65.06	74.00	-8.94	Peak
2483.500	-48.468	-1.00	48.73	54.00	-5.27	Average
2500.000	-38.074	-1.00	59.13	74.00	-14.87	Peak
2500.000	-51.150	-1.00	46.05	54.00	-7.95	Average

802.11n(HT40)						
Freq. MHz	Reading Level dBm	Antenna Gain dBi	Calculated E dBuV/m	Limit dBuV/m	Margin dB	Remark
2310.000	-39.840	-1.00	57.36	74.00	-16.64	Peak
2310.000	-52.819	-1.00	44.38	54.00	-9.62	Average
2390.000	-32.215	-1.00	64.99	74.00	-9.02	Peak
2390.000	-49.036	-1.00	48.16	54.00	-5.84	Average
2483.500	-25.925	-1.00	71.28	74.00	-2.72	Peak
2483.500	-44.699	-1.00	52.50	54.00	-1.50	Average
2500.000	-31.511	-1.00	65.69	74.00	-8.31	Peak
2500.000	-46.060	-1.00	51.14	54.00	-2.86	Average


BT LE						
Freq. MHz	Reading Level dBm	Antenna Gain dBi	Calculated E dBuV/m	Limit dBuV/m	Margin dB	Remark
2310.000	-51.306	-1.000	45.894	74.000	-28.106	Peak
2390.000	-51.111	-1.000	46.089	74.000	-27.911	Peak
2483.500	-42.481	-1.000	54.719	74.000	-19.281	Peak
2500.000	-50.721	-1.000	46.479	74.000	-27.521	Peak

## Test plot of Restricted Bands-conducted




802.11b-Low channel(Peak)

802.11b-Low channel(Average)



802.11b-High channel(Peak)



802.11b-High channel(Average)



802.11g-Low channel(Peak)



802.11g-Low channel(Average)

## Test plot of Restricted Bands





802.11g-High channel(Peak)

802.11g-High channel(Average)



802.11n(HT20)-Low channel(Peak)


802.11n(HT20)-Low channel(Average)




802.11n(HT20)-High channel(Peak)

802.11n(HT20)-High channel(Average)


## Test plot of Restricted Bands




802.11n(HT40)-Low channel(Peak)



802.11n(HT40)-Low channel(Average)




802.11n(HT40)-High channel(Peak)




802.11n(HT40)-High channel(Average)

## Test plot of Restricted Bands



BT LE-Low channel(Peak)



BT LE-High channel(Peak)

## 5.6. Conducted Spurious Emissions and Band Edges Test

### 5.6.1. Standard Applicable

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 5.6.2. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Detector	Peak
Attenuation	Auto
RB / VB (Emission in restricted band)	100KHz/300KHz
RB / VB (Emission in non-restricted band)	100KHz/300KHz

### 5.6.3. Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz

The spectrum from 9 KHz to 26.5GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

### 5.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 5.4.4.

### 5.6.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

### 5.6.6. Test Results of Conducted Spurious Emissions

Temperature	25℃	Humidity	46%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n & BT LE





Test Mode	Channel	Frequency (MHz)	Spurious RF Conducted Emission (dBc)	Limits (dBc)	Verdict
IEEE 802.11b	1	2412	<-20	-20	PASS
	6	2437	<-20		
	11	2462	<-20		
IEEE 802.11g	1	2412	<-20	-20	PASS
	6	2437	<-20		
	11	2462	<-20		
IEEE 802.11n HT20	1	2412	<-20	-20	PASS
	6	2437	<-20		
	11	2462	<-20		
IEEE 802.11n HT40	3	2412	<-20	-20	PASS
	6	2437	<-20		
	9	2452	<-20		
BT – LE	0	2402	<-20	-20	PASS
	19	2440	<-20		
	39	2480	<-20		

**Remark:**

1. Measured RF conducted spurious emission at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40; “---“means that the fundamental frequency not for 15.209 limits requirement.
4. Please refer to following plots;



## RF Conducted Spurious Emission

## IEEE 802.11b





## Reference Peak Value

## 9 KHz – 26.5 GHz



## Reference Peak Value

## 9 KHz – 26.5 GHz





## Reference Peak Value

## 9 KHz – 26.5 GHz



## RF Conducted Spurious Emission

## IEEE 802.11g





## Reference Peak Value

## 9 KHz – 26.5 GHz



## Reference Peak Value

## 9 KHz – 26.5 GHz





## Reference Peak Value

## 9 KHz – 26.5 GHz





## RF Conducted Spurious Emission

## IEEE 802.11n HT20





## Reference Peak Value

## 9 KHz – 26.5 GHz



## Reference Peak Value

## 9 KHz – 26.5 GHz




## Reference Peak Value


## 9 KHz – 26.5 GHz

## RF Conducted Spurious Emission


## IEEE 802.11n HT40




## Reference Peak Value




## 9 KHz – 26.5 GHz




## Reference Peak Value



## 9 KHz – 26.5 GHz





## Reference Peak Value



## 9 KHz – 26.5 GHz



## RF Conducted Spurious Emission

## BT LE





## Reference Peak Value

## 9 KHz – 26.5 GHz



## Reference Peak Value

## 9 KHz – 26.5 GHz





## Reference Peak Value

## 9 KHz – 26.5 GHz





## Band-edge measurements for conducted emissions

## IEEE 802.11b



## Reference Peak Value



## Channel 1 / 2412 MHz



## Reference Peak Value

## Channel 11 / 2462 MHz

## IEEE 802.11g




## Reference Peak Value


## Channel 1 / 2412 MHz

## Band-edge measurements for conducted emissions

## IEEE 802.11g




Reference Peak Value




Channel 11 / 2462 MHz


## IEEE 802.11n HT20




Reference Peak Value



Channel 1 / 2412 MHz




Reference Peak Value




Channel 11 / 2462 MHz

## Band-edge measurements for conducted emissions


## IEEE 802.11n HT40




## Reference Peak Value



## Channel 3 / 2422 MHz



## Reference Peak Value




## Channel 9 / 2452 MHz




## Band-edge measurements for conducted emissions

## BT - LE



## Reference Peak Value

## Channel 0 / 2402 MHz



## Reference Peak Value

## Channel 39 / 2480 MHz

## 5.7. Power line conducted emissions


### 5.7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

\* Decreasing linearly with the logarithm of the frequency

### 5.7.2 Block Diagram of Test Setup



### 5.7.3 Test Results


**PASS.**

The test data please refer to following page.



**AC Conducted Emission of power adapter @ AC 240V/50Hz @ IEEE 802.11b (worst case)**


Line:



	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.55	24.38	9.63	0.04	10.00	44.05	56.00	-11.95	QP
2	0.55	15.52	9.63	0.04	10.00	35.19	46.00	-10.81	Average
3	1.02	23.81	9.63	0.05	10.00	43.49	56.00	-12.51	QP
4	1.02	7.31	9.63	0.05	10.00	26.99	46.00	-19.01	Average
5	1.53	24.62	9.64	0.05	10.00	44.31	56.00	-11.69	QP
6	1.53	8.75	9.64	0.05	10.00	28.44	46.00	-17.56	Average
7	1.83	23.69	9.64	0.05	10.00	43.38	56.00	-12.62	QP
8	1.83	7.93	9.64	0.05	10.00	27.62	46.00	-18.38	Average
9	2.08	22.78	9.64	0.05	10.00	42.47	56.00	-13.53	QP
10	2.08	6.09	9.64	0.05	10.00	25.78	46.00	-20.22	Average
11	8.24	24.13	9.68	0.07	10.00	43.88	60.00	-16.12	QP
12	8.24	11.37	9.68	0.07	10.00	31.12	50.00	-18.88	Average

Remarks: 1. Measured = Reading + LISNFac + Cable Loss + Aux2 Fac.  
 2. The emission levels that are 20dB below the official limit are not reported.

Neutral:




	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.15	24.80	9.70	0.02	10.00	44.52	66.00	-21.48	QP
2	0.15	7.54	9.70	0.02	10.00	27.26	55.99	-28.73	Average
3	0.18	22.33	9.63	0.02	10.00	41.98	64.42	-22.44	QP
4	0.18	6.24	9.63	0.02	10.00	25.89	54.41	-28.52	Average
5	0.48	22.96	9.62	0.04	10.00	42.62	56.36	-13.74	QP
6	0.48	10.40	9.62	0.04	10.00	30.06	46.36	-16.30	Average
7	0.55	24.12	9.62	0.04	10.00	43.78	56.00	-12.22	QP
8	0.55	9.26	9.62	0.04	10.00	28.92	46.00	-17.08	Average
9	1.59	22.45	9.63	0.05	10.00	42.13	56.00	-13.87	QP
10	1.59	4.13	9.63	0.05	10.00	23.81	46.00	-22.19	Average
11	8.28	22.08	9.70	0.07	10.00	41.85	60.00	-18.15	QP
12	8.28	5.59	9.70	0.07	10.00	25.36	50.00	-24.64	Average

Remarks: 1. Measured = Reading + LISNFac + Cable Loss + Aux2 Fac.  
 2. The emission levels that are 20dB below the official limit are not reported.

**AC Conducted Emission of power adapter @ AC 240V/50Hz @ BLE (worst case)**


Line:



	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.15	24.98	9.57	0.02	10.00	44.57	66.00	-21.43	QP
2	0.15	8.48	9.57	0.02	10.00	28.07	55.99	-27.92	Average
3	0.55	23.52	9.63	0.04	10.00	43.19	56.00	-12.81	QP
4	0.55	14.91	9.63	0.04	10.00	34.58	46.00	-11.42	Average
5	1.02	24.01	9.63	0.05	10.00	43.69	56.00	-12.31	QP
6	1.02	9.62	9.63	0.05	10.00	29.30	46.00	-16.70	Average
7	1.53	24.17	9.64	0.05	10.00	43.86	56.00	-12.14	QP
8	1.53	8.88	9.64	0.05	10.00	28.57	46.00	-17.43	Average
9	2.04	23.04	9.64	0.05	10.00	42.73	56.00	-13.27	QP
10	2.05	6.83	9.64	0.05	10.00	26.52	46.00	-19.48	Average
11	8.46	24.32	9.69	0.08	10.00	44.09	60.00	-15.91	QP
12	8.46	10.49	9.69	0.08	10.00	30.26	50.00	-19.74	Average

Remarks: 1. Measured = Reading + LISNFac + Cable Loss + Aux2 Fac.  
 2. The emission levels that are 20dB below the official limit are not reported.

Neutral:



	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dB	dBuV	dBuV	dB
1	0.19	23.37	9.61	0.02	10.00	43.00	64.02	-21.02	QP
2	0.19	7.23	9.61	0.02	10.00	26.86	54.02	-27.16	Average
3	0.55	23.67	9.62	0.04	10.00	43.33	56.00	-12.67	QP
4	0.55	11.92	9.62	0.04	10.00	31.58	46.00	-14.42	Average
5	1.11	22.85	9.63	0.05	10.00	42.53	56.00	-13.47	QP
6	1.11	5.10	9.63	0.05	10.00	24.78	46.00	-21.22	Average
7	1.59	21.36	9.63	0.05	10.00	41.04	56.00	-14.96	QP
8	1.59	5.89	9.63	0.05	10.00	25.57	46.00	-20.43	Average
9	7.77	22.10	9.70	0.07	10.00	41.87	60.00	-18.13	QP
10	7.77	6.28	9.70	0.07	10.00	26.05	50.00	-23.95	Average
11	16.05	19.06	9.75	0.11	10.00	38.92	60.00	-21.08	QP
12	16.06	1.48	9.75	0.11	10.00	21.34	50.00	-28.66	Average

Remarks: 1. Measured = Reading + LISNFac + Cable Loss + Aux2 Fac.  
 2. The emission levels that are 20dB below the official limit are not reported.

\*\*\*Note: Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11b@240VAC, BLE@240VAC).

## 5.8 Antenna Requirements

### 5.8.1 Standard Applicable

According to antenna requirement of §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### 5.8.2 Antenna Connected Construction

#### 5.8.2.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 5.8.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is -1dBi, and the antenna is a PIFA antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.  
The WLAN and BT share same antenna;

#### 5.8.2.3. Results: Compliance.

## 6. LIST OF MEASURING EQUIPMENTS

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	Power Sensor	R&S	NRV-Z51	100458	2017-06-18	2018-06-17
2	Power Sensor	R&S	NRV-Z32	10057	2017-06-18	2018-06-17
3	Power Meter	R&S	NRVS	100444	2017-06-18	2018-06-17
4	DC Filter	MPE	23872C	N/A	2017-06-18	2018-06-17
5	RF Cable	Harbour Industries	1452	N/A	2017-06-18	2018-06-17
6	SMA Connector	Harbour Industries	9625	N/A	2017-06-18	2018-06-17
7	Spectrum Analyzer	Agilent	N9020A	MY50510140	2016-10-27	2017-10-26
8	Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	2017-06-18	2018-06-17
9	RF Cable	Hubersuhne	SucofleX304	FP2RX2	2017-06-18	2018-06-17
10	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2017-06-18	2018-06-17
11	Amplifier	SCHAFFNER	COA9231A	18667	2017-04-18	2018-04-17
12	Amplifier	Agilent	8449B	3008A02120	2017-04-18	2018-04-17
13	Amplifier	MITEQ	AMF-6F-260400	9121372	2017-04-18	2018-04-17
14	Loop Antenna	R&S	HFH2-Z2	860004/001	2017-04-18	2018-04-17
15	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2017-04-18	2018-04-17
16	Horn Antenna	EMCO	3115	6741	2017-04-18	2018-04-17
17	Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	2017-04-18	2018-04-17
18	RF Cable-R03m	Jye Bao	RG142	CB021	2017-06-18	2018-06-17
19	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2017-06-18	2018-06-17
20	EMI Test Receiver	R&S	ESCI	101142	2017-06-18	2018-06-17
21	Artificial Mains	R&S	ENV216	101288	2017-06-18	2018-06-17
22	EMI Test Software	AUDIX	E3	N/A	2017-06-18	2018-06-17

## **7. TEST SETUP PHOTOGRAPHS OF EUT**

Please refer to separate file for test setup photos.

## **8. EXTERIOR PHOTOGRAPHS OF THE EUT**

Please refer to separate file for exterior photos of EUT.

## **9. INTERIOR PHOTOGRAPHS OF THE EUT**

Please refer to separate file for interior photos of EUT.

-----THE END OF REPORT-----