

# RF Exposure evaluation

FCC ID: 2AZQ8-SC1

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

## 1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

## 2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 4. Antenna Information

SC1 can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
BT	/	PIFA antenna	2.42dBi for 2400-2500MHz;	
2.4GWIFI	/	PIFA antenna	2.31dBi for 2400-2500MHz for ANT 1 2.43dBi for 2400-2500MHz for ANT 2	
5.2GWIFI	/	PIFA antenna	2.37dBi for 5180-5240MHz for ANT 1 2.49dBi for 5180-5240MHz for ANT 2	
5.8GWIFI		PIFA antenna	2.37dBi for 5745-5825MHz for ANT 1 2.49dBi for 5745-5825MHz for ANT 2	

### 5. Manufacturing Tolerance

BT GFSK(Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	1.0	1.0	1.0
Tolerance ±(dB)	1.0	1.0	1.0
π /4DQPSK (Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	1.0	1.0	1.0
Tolerance ±(dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	1.0	1.0	1.0
Tolerance ±(dB)	1.0	1.0	1.0

BLE GFSK(Peak)			
Channel	Channel 00	Channel 19	Channel 39
Target (dBm)	3.0	4.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

WIFI(Peak) ANT1

	Max Tune-up
Target (dBm)	14.0
Tolerance $\pm$ (dB)	1.0

WIFI(Peak) ANT2

	Max Tune-up
Target (dBm)	14.0
Tolerance $\pm$ (dB)	1.0

[5.2GHz WLAN] ANT 1

	Max Tune-up
Target (dBm)	12.0
Tolerance $\pm$ (dB)	1.0

[5.2GHz WLAN] ANT 2

	Max Tune-up
Target (dBm)	12.0
Tolerance $\pm$ (dB)	1.0

[5.8GHz WLAN] ANT1

	Max Tune-up
Target (dBm)	12.0
Tolerance $\pm$ (dB)	1.0

[5.8GHz WLAN] ANT2

	Max Tune-up
Target (dBm)	12.0
Tolerance $\pm$ (dB)	1.0

## 6. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r=20\text{cm}$ , as well as the gain of the used antenna is refer to section, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
BT	2.0	1.5849	2.42	1.7458	0.0006	1.0000
BLE	5.0	3.1623	2.42	1.7458	0.0011	1.0000
2.4GWIFI ANT1	15.0	31.6228	2.31	1.7022	0.0107	1.0000
5.2GWIFI ANT1	13.0	19.9526	2.37	1.7258	0.0069	1.0000
5.8GWIFI ANT1	13.0	19.9526	2.49	1.7742	0.0070	1.0000

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
2.4GWIFI ANT2	15.0	31.6228	2.31	1.7022	0.0107	1.0000
5.2GWIFI ANT2	13.0	19.9526	2.37	1.7258	0.0069	1.0000
5.8GWIFI ANT2	13.0	19.9526	2.49	1.7742	0.0070	1.0000

*Remark:*

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

## 7. simultaneous MPE Result

2.4GWIFI ANT1 MPE (Ratio)	2.4GWIFI ANT2 MPE (Ratio)	BLE MPE (Ratio)	simultaneous MPE (Ratio)	MPE Limits (Ratio)
0.0107	0.0107	0.0011	0.0225	1.0000

## 8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----