

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: Z63-P101201

EUT Specification

EUT	Automatic Feeder (Video Version)					
Model Number	P101201					
Series Model	P101XXX ("X" represent "0-9" or "A-Z")					
Model Difference	Note: All models are identical except model name and grain					
	bucket size.					
Rating	Input: USB-C (DC 5V/1A)/3pcs 1# batteries (D battery)					
Frequency band	I ⊠BT: 2.402GHz ~ 2.480GHz					
(Operating)	WLAN: 2.412GHz ~ 2.462GHz					
	WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz					
	WLAN: 5.745GHz ~ 5825GHz					
Device category	□Portable (<20cm separation)					
	⊠Mobile (>20cm separation)					
Exposure classification	Occupational/Controlled exposure (S = 5mW/cm2)					
	General Population/Uncontrolled exposure					
	(S=1mW/cm2)					
Antenna diversity	⊠Single antenna					
	☐Multiple antennas					
	□Tx diversity					
	□Rx diversity					
	Tx/Rx diversity					
Max. output power (peak	BLE: 4.49 dBm					
power)	IEEE 802.11b: 16.83 dBm					
	IEEE 802.11g: 16.67 dBm					
	IEEE 802.11n-HT20: 16.09 dBm					
	IEEE 802.11n-HT40: 15.63 dBm					
Antenna gain (Max)	BT: 3.57 dBi					
	2.4GHz WIFI: 3.55 dBi					
Evaluation applied	MPE Evaluation					
	□SAR Evaluation					



Frequency	Electric Field	Magnetic Field	Power	Average			
Range(MHz)	Strength(V/m)	Strength(A/m)	h(A/m) Density(mW/cm²)				
(A) Limits for Occupational/Control Exposures							
300-1500			F/300	6			
1500-100000			5	6			
(B) Limits for General Population/Uncontrol Exposures							
300-1500		F/1500		6			
1500-100000			1	30			

Limits for Maximum Permissible Exposure(MPE)

Friis transmission formula: Pd=(Pout*G)\(4*pi*R2)

Where

Pd= Power density in mW/cm², Pout=output power to antenna in Mw

G= gain of antenna in linear scale, Pi=3.1416

R= distance between observation point and center of the radiator in cm=20cm Pd the limit of MPE, 1mW/cm2. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation

$$\sum_{k=1}^{c} \frac{Evaluated_{k}}{Exposure \ Limit_{k}} \leq 1$$

Evaluated_k: the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k: either the general population/uncontrolled maximum permissible exposure (MPE) or specific Absorption rate (SAR) limit for each fixed, mobile, or portable RF source k.



Measurement Result

Operati on Mode	Channe I Freque ncy (MHz)	Max Measur ed Power (dBm)	Tune up toleran ce (dBm)	Max tune up conduc ted power (dBm)	Outp ut Peak pow er (mW)	Ant Gai n (dB i)	Ant. Gain (numer ic)	Power densit y at 20cm (mW/ cm2)	Powe r densi ty Limit s (mW/ cm2)
BLE (1Mbps)	2420	4.49	4±1	5	3.16 2	3.5 7	2.275	0.0014 31	1
2.4GHz WIFI (802.11 b)	2412	16.83	17±1	18	63.0 96	3.5 5	2.265	0.0284 26	1

Maximum Simultaneous transmission MPE Ratio for Bluetooth & 2.4G WIFI

Maximum MPE ratio (Bluetooth)	Maximum MPE ratio (2.4G WIFI)	∑ MPE ratios	Limit	Results
0.001431	0.028426	0.029857	1.000	Pass

The Product unsupported at the same time to Transmitting. According to KDB 447498, and no simultaneous SAR measurement is required.

