


# FCC Test Report

Equipment : 11ac Dual Band Concurrent Wall-mount AP  
Brand Name : EDIMAX  
Model No. : EW-7679WAC / GAP-679WAC / WAP1750 /  
WAP1750H / WAP1750S /  
WAP1750L / WAP1750i  
FCC ID : NDD9576791401  
Standard : 47 CFR FCC Part 15.247  
Operating Band : 2400 MHz – 2483.5 MHz  
FCC Classification : DTS  
Applicant : EDIMAX TECHNOLOGY CO., LTD.  
Manufacturer : No.3, Wu-Chuan 3rd Road,  
Wu-Ku Industrial Park,  
New Taipei City, Taiwan

The product sample received on Apr. 23, 2014 and completely tested on May 02, 2014. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

  
Wayne Hsu / Assistant Manager



## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Accessories And Support Equipment.....	7
1.3	Testing Applied Standards .....	7
1.4	Testing Location Information.....	8
1.5	Measurement Uncertainty .....	8
<b>2</b>	<b>TEST CONFIGURATION OF EUT .....</b>	<b>9</b>
2.1	The Worst Case Modulation Configuration .....	9
2.2	The Worst Case Power Setting Parameter.....	9
2.3	The Worst Case Measurement Configuration.....	10
2.4	Test Setup Diagram .....	11
<b>3</b>	<b>TRANSMITTER TEST RESULT .....</b>	<b>13</b>
3.1	AC Power-line Conducted Emissions .....	13
3.2	6dB Bandwidth .....	16
3.3	RF Output Power.....	18
3.4	Power Spectral Density .....	23
3.5	Transmitter Bandedge Emissions .....	25
3.6	Transmitter Unwanted Emissions.....	28
<b>4</b>	<b>TEST EQUIPMENT AND CALIBRATION DATA .....</b>	<b>57</b>

### **APPENDIX A. TEST PHOTOS**

### **APPENDIX B. PHOTOGRAPHS OF EUT**

## Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.3	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 0.439744MHz 35.82 (Margin 11.25dB) - AV 47.59 (Margin 9.48dB) - QP	FCC 15.207	Complied
3.2	15.247(a)	6dB Bandwidth	6dB Bandwidth Unit [MHz] 20M: 6.63 / 40M: 34.48	≥500kHz	Complied
3.3	15.247(b)	RF Output Power (Maximum Peak Conducted Output Power)	Power [dBm]: 28.26	Power [dBm]:30	Complied
3.4	15.247(d)	Power Spectral Density	PSD [dBm/100kHz]: -3.10	PSD [dBm/3kHz]:8	Complied
3.5	15.247(c)	Transmitter Radiated Bandedge Emissions	Non-Restricted Bands: 2400.00MHz: 28.72dB Restricted Bands [dBuV/m at 3m]: 2390.00MHz 72.52 (Margin 1.48dB) - PK 52.99 (Margin 1.01dB) - AV	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied
3.6	15.247(c)	Transmitter Radiated Unwanted Emissions	[dBuV/m at 3m]: 7311MHz 65.16 (Margin 8.84dB) - PK 52.89 (Margin 1.11dB) - AV	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied



SPORTON INTERNATIONAL INC.  
TEL : 886-3-327-3456  
FAX : 886-3-327-0973

# 1 General Description

## 1.1 Information

This equipment contains two kinds of exterior features. For more detail and other information, please refer to user manual.

### 1.1.1 Multiple list

No.	Brand Name	Model Name
1	Edimax	EW-7679WAC,GAP-679WAC, WAP1750, WAP1750H, WAP1750S, WAP1750L,WAP1750i
2	Comtrend	WAP-5872u
3	Sophos	AP 100
4	4ipnet	EAP760,EAP767
5	SMAX	SWA1750H

### 1.1.2 RF General Information

RF General Information						
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	RF Output Power (dBm)	Co-location
2400-2483.5	b	2412-2462	1-11 [11]	1	25.40	Yes
2400-2483.5	g	2412-2462	1-11 [11]	1	27.73	Yes
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	3	28.26	Yes
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	3	24.37	Yes
Note 1: RF output power specifies that Maximum Peak Conducted Output Power. Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation. Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation. Note 4: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other. (i.e., EUT has simultaneously co-transmitting that operating 2.4GHz and 5GHz.)						

**1.1.3 Antenna Information**

Antenna Category	
<input type="checkbox"/>	Integral antenna (antenna permanently attached)
<input type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
<input checked="" type="checkbox"/>	External antenna (dedicated antennas)
<input checked="" type="checkbox"/>	Single power level with corresponding antenna(s).
<input type="checkbox"/>	Multiple power level and corresponding antenna(s).

Antenna General Information			
No.	Ant. Cat.	Ant. Type	Gain (dBi)
1	External	DIPOLE	2.4

Remark: 11b/g only include 1TX and Port1 to emission. IEEE 802.11n has the CDD function.

**1.1.4 Type of EUT**

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input type="checkbox"/> Production ; <input type="checkbox"/> Pre-Production ; <input checked="" type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.:
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.:
<input type="checkbox"/>	Other:

**1.1.5 Test Signal Duty Cycle**

Operated Mode for Worst Duty Cycle	
<input type="checkbox"/>	Operated normally mode for worst duty cycle
<input checked="" type="checkbox"/>	Operated test mode for worst duty cycle
Test Signal Duty Cycle (x)	Power Duty Factor [dB] – (10 log 1/x)
<input checked="" type="checkbox"/> 100.00% - IEEE 802.11b	0.00
<input checked="" type="checkbox"/> 99.30% - IEEE 802.11g	0.03
<input checked="" type="checkbox"/> 96.01% - IEEE 802.11n (HT20)	0.18
<input checked="" type="checkbox"/> 96.29% - IEEE 802.11n (HT40)	0.16

### 1.1.6 EUT Operational Condition

<b>Supply Voltage</b>	<input checked="" type="checkbox"/> AC mains	<input type="checkbox"/> DC	<input type="checkbox"/> System
<b>Type of DC Source</b>	<input type="checkbox"/> Internal DC supply	<input checked="" type="checkbox"/> External DC from PoE	<input checked="" type="checkbox"/> External DC adapter

## 1.2 Accessories And Support Equipment

Accessories				
AC Adapter 1	Brand Name	APD	Model Name	WA30B12
	Power Rating	I/P: 100-240Vac 0.8A ; O/P: 12V $\overline{\text{---}}$ 2.5A		
	Power cord	1.8m, non-shielded cable, w/o ferrite core		
AC Adapter 2	Brand Name	APD	Model Name	DA-48T12
	Power Rating	I/P: 100-240Vac 1.2A ; O/P: 12V $\overline{\text{---}}$ 4A		
	Power Cord	AC: 1.4m, non-shielded cable, w/o ferrite core DC: 1.5m, non-shielded cable, with one ferrite core		

Note: Regarding to more detail and other information, please refer to user manual.

Support Equipment - AC Conduction and Radiated Emission				
Remote				
No.	Equipment	Brand Name	Model Name	FCC ID
1	PoE	Acelink	PI-1000PT	DoC

Support Equipment - RF Conducted				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	Dell	E5520	-

## 1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2009
- ♦ FCC KDB 558074
- ♦ FCC KDB 662911

## 1.4 Testing Location Information

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.	
		TEL : 886-3-327-3456 FAX : 886-3-327-0973	
Test Condition	Test Site No.	Test Engineer	Test Environment
AC Conduction	CO04-HY	Zeus	24.4°C / 53%
RF Conducted	TH06-HY	Wei	24.2°C / 63%
Radiated Emission	03CH03-HY	Leo	24.4°C / 53%

## 1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty		
Test Item		Uncertainty
AC power-line conducted emissions		±2.26 dB
Emission bandwidth, 6dB bandwidth		±1.42 %
RF output power, conducted		±0.63 dB
Power density, conducted		±0.81 dB
Unwanted emissions, conducted	9 – 150 kHz	±0.38 dB
	0.15 – 30 MHz	±0.42 dB
	30 – 1000 MHz	±0.51 dB
	1 – 18 GHz	±0.67 dB
	18 – 40 GHz	±0.83 dB
	40 – 200 GHz	N/A
All emissions, radiated	9 – 150 kHz	±2.49 dB
	0.15 – 30 MHz	±2.28 dB
	30 – 1000 MHz	±2.56 dB
	1 – 18 GHz	±3.59 dB
	18 – 40 GHz	±3.82 dB
	40 – 200 GHz	N/A
Temperature		±0.8 °C
Humidity		±3 %
DC and low frequency voltages		±3 %
Time		±1.42 %
Duty Cycle		±1.42 %



## 2 Test Configuration of EUT

### 2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing			
Modulation Mode	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS	Worst Data Rate / MCS
11b,1-11Mbps	1	1-11 Mbps	1 Mbps
11g,6-54Mbps	1	6-54 Mbps	6 Mbps
HT20,M0-23	3	MCS 0-23	M 0
HT40,M0-23	3	MCS 0-23	M 0




### 2.2 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter (2400-2483.5MHz band)							
Test Software Version	DOS						
Modulation Mode	N <sub>TX</sub>	Test Frequency (MHz)					
		NCB: 20MHz			NCB: 40MHz		
		2412	2437	2462	2422	2437	2452
11b	1	24	22.5	21	-	-	-
11g	1	17	25	17	-	-	-
HT-20	3	14	19	14	-	-	-
HT-40	3	-	-	-	9.5	15	14


## 2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	AC power-line conducted emissions
<b>Condition</b>	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
<b>Operating Mode</b>	Operating Mode Description
1	EUT with adapter 1
2	EUT with adapter 2
3	EUT with PoE
Operating mode 1 was the worst case and it was recorded in this test report.	


The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	RF Output Power, Power Spectral Density, 6 dB Bandwidth
<b>Test Condition</b>	Conducted measurement at transmit chains
<b>Modulation Mode</b>	11b, 11g, HT20, HT40

The Worst Case Mode for Following Conformance Tests			
<b>Tests Item</b>	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions		
<b>Test Condition</b>	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
<b>User Position</b>	<input type="checkbox"/> EUT will be placed in fixed position.		
	<input checked="" type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed three orthogonal planes. The worst plane is Z.		
	<input type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes.		
<b>Operating Mode &lt; 1GHz</b>	<input checked="" type="checkbox"/> 1. EUT with adapter 1		
	<input checked="" type="checkbox"/> 2. EUT with adapter 2		
	<input checked="" type="checkbox"/> 3. EUT with PoE		
	For operating mode 3 was the worst case and it was recorded in this test report.		
<b>Operating Mode &gt; 1GHz</b>	<input checked="" type="checkbox"/> 2. EUT with adapter 2		
<b>Modulation Mode</b>	11b, 11g, HT20, HT40		
<b>Orthogonal Planes of EUT</b>	<b>X Plane</b>	<b>Y Plane</b>	<b>Z Plane</b>
			


## 2.4 Test Setup Diagram



**Test Setup Diagram - Radiated Emission mode 3 (Below 1GHz)**



**Test Setup Diagram - Radiated Emission mode 2 (Above 1GHz)**



### 3 Transmitter Test Result

### 3.1 AC Power-line Conducted Emissions

### 3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.


### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


### 3.1.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.

### 3.1.4 Test Setup




### 3.1.5 Test Result of AC Power-line Conducted Emissions



**AC Power-line Conducted Emissions Result**

Operating Mode	1	Power Phase	Line
Operating Function	EUT with adatper 1		



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.1924150	46.35	-17.58	63.93	45.84	0.03	0.48	QP
2	0.1924150	37.93	-16.00	53.93	37.42	0.03	0.48	Average
3	0.2575110	36.75	-14.76	51.51	36.18	0.03	0.54	Average
4	0.2575110	47.03	-14.48	61.51	46.46	0.03	0.54	QP
5	0.4305230	46.71	-10.53	57.24	46.06	0.03	0.62	QP
6	0.4305230	35.36	-11.88	47.24	34.71	0.03	0.62	Average
7	0.5916410	40.61	-15.39	56.00	39.89	0.04	0.68	QP
8	0.5916410	29.16	-16.84	46.00	28.44	0.04	0.68	Average
9	1.080	40.21	-15.79	56.00	39.35	0.06	0.80	QP
10	1.080	28.89	-17.11	46.00	28.03	0.06	0.80	Average
11	1.540	38.27	-17.73	56.00	37.40	0.07	0.80	QP
12	1.540	28.91	-17.09	46.00	28.04	0.07	0.80	Average

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

## 3.2 6dB Bandwidth

### 3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
<b>Systems using digital modulation techniques:</b>	
<input checked="" type="checkbox"/>	6 dB bandwidth $\geq$ 500 kHz.


### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.2.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input checked="" type="checkbox"/>	For conducted measurement.
<input checked="" type="checkbox"/>	The EUT supports single transmit chain and measurements performance of this transmit chain port 1.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/>	Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1.
<input checked="" type="checkbox"/>	Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.


### 3.2.4 Test Setup





### 3.2.5 Test Result of Emission Bandwidth

Emission Bandwidth Result								
Condition			Emission Bandwidth (MHz)					
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	99% Bandwidth			6dB Bandwidth		
			Chain Port 1	Chain Port 2	Chain Port 3	Chain Port 1	Chain Port 2	Chain Port 3
11b	1	2412	12.02	-	-	7.05	-	-
11b	1	2437	11.93	-	-	6.63	-	-
11b	1	2462	11.67	-	-	7.09	-	-
11g	1	2412	16.46	-	-	16.53	-	-
11g	1	2437	17.07	-	-	16.50	-	-
11g	1	2462	16.46	-	-	16.48	-	-
HT20	3	2412	17.69	17.61	17.69	17.73	17.05	17.73
HT20	3	2437	17.67	17.70	17.64	17.55	17.74	17.58
HT20	3	2462	17.72	17.63	17.70	17.73	17.64	17.64
HT40	3	2422	36.14	36.18	36.26	36.00	36.36	36.40
HT40	3	2437	36.10	36.10	36.14	34.68	34.76	35.32
HT40	3	2452	36.26	36.18	36.18	35.68	34.48	36.16
Limit			N/A			≥500 kHz		
Result			Complied					
Note 1: N <sub>TX</sub> = Number of Transmit Chains								



### 3.3 RF Output Power

#### 3.3.1 RF Output Power Limit

RF Output Power Limit	
<b>Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit</b>	
<input checked="" type="checkbox"/> 2400-2483.5 MHz Band:	
<input checked="" type="checkbox"/>	If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
<input type="checkbox"/>	Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
<input type="checkbox"/>	Smart antenna system (SAS):
<input type="checkbox"/>	Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
<input type="checkbox"/>	Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
<input type="checkbox"/>	Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
<b>e.i.r.p. Power Limit:</b>	
<input checked="" type="checkbox"/> 2400-2483.5 MHz Band	
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
<input type="checkbox"/>	Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm
<input type="checkbox"/>	Smart antenna system (SAS)
<input type="checkbox"/>	Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
<input type="checkbox"/>	Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
<input type="checkbox"/>	Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
$P_{Out}$ = maximum peak conducted output power or maximum conducted output power in dBm, $G_{TX}$ = the maximum transmitting antenna directional gain in dBi. $P_{eirp}$ = e.i.r.p. Power in dBm.	


#### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.3.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Maximum Peak Conducted Output Power
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.1.1 Option 1 (RBW ≥ EBW method).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 9.1.2 Option 2 (integrated band power method).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.1.3 Option 2 (peak power meter for VBW ≥ DTS BW)
<input checked="" type="checkbox"/>	Maximum Conducted Output Power
	[duty cycle ≥ 98% or external video / power trigger]
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2.2.2 Method AVGSA-1 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2.2.3 Method AVGSA-1 Alt. (slow sweep speed)
	duty cycle < 98% and average over on/off periods with duty factor
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2.2.4 Method AVGSA-2 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2.2.5 Method AVGSA-2 Alt. (slow sweep speed)
	RF power meter and average over on/off periods with duty factor or gated trigger
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2.3 Method AVGPM (using an RF average power meter).
<input checked="" type="checkbox"/>	For conducted measurement.
<input checked="" type="checkbox"/>	The EUT supports single transmit chain and measurements performance on this transmit chain port 1.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
<input checked="" type="checkbox"/>	If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$

### 3.3.4 Test Setup



### 3.3.5 Directional Gain for Power Measurement

Directional Gain (DG) Result					
Transmit Chains No.		1	2	3	-
Maximum $G_{ANT}$ (dBi)		2.4	2.4	2.4	-
Modulation Mode	DG (dBi)	$N_{TX}$	$N_{SS}$ (Min.)	STBC	Array Gain (dB)
11b,1-11Mbps	2.4	1	1	-	-
11g,6-54Mbps	2.4	1	1	-	-
HT20,M0-23	2.4	3	1/2/3	-	0
HT40,M0-23	2.4	3	1/2/3	-	0
<p>Note 1: For all transmitter outputs with equal antenna gains, directional gain is to be computed as follows:  Any transmit signals are correlated, Directional Gain = <math>G_{ANT} + 10 \log(N_{TX})</math>  All transmit signals are completely uncorrelated, Directional Gain = <math>G_{ANT}</math></p> <p>Note 2: For all transmitter outputs with unequal antenna gains, directional gain is to be computed as follows:  Any transmit signals are correlated, Directional Gain = <math>10 \log[(10^{G_{1/20}} + \dots + 10^{G_{N/20}})^2 / N_{TX}]</math>  All transmit signals are completely uncorrelated, Directional Gain = <math>10 \log[(10^{G_{1/10}} + \dots + 10^{G_{N/10}}) / N_{TX}]</math></p> <p>Note 3: For Spatial Multiplexing, Directional Gain (DG) = <math>G_{ANT} + 10 \log(N_{TX}/N_{SS})</math>,  where <math>N_{SS}</math> = the number of independent spatial streams data.</p> <p>Note 4: For CDD transmissions, directional gain is calculated as power measurements:  Directional Gain (DG) = <math>G_{ANT} + \text{Array Gain}</math>, where Array Gain is as follows:  Array Gain = 0 dB (i.e., no array gain) for <math>N_{TX} \leq 4</math>;  Array Gain = 0 dB (i.e., no array gain) for channel widths <math>\geq 40</math> MHz for any <math>N_{TX}</math>;</p>					

### 3.3.6 Test Result of Maximum Peak Conducted Output Power


Maximum Peak Conducted Output Power Result										
Condition			RF Output Power (dBm)							
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Chain Port 1	Chain Port 2	Chain Port 3	Sum Chain	Power Limit	DG (dBi)	EIRP Power	EIRP Limit
11b	1	2412	25.40	-	-	25.40	30.00	2.4	27.80	36.00
11b	1	2437	24.48	-	-	24.48	30.00	2.4	26.88	36.00
11b	1	2462	23.25	-	-	23.25	30.00	2.4	25.65	36.00
11g	1	2412	20.63	-	-	20.63	30.00	2.4	23.03	36.00
11g	1	2437	27.73	-	-	27.73	30.00	2.4	30.13	36.00
11g	1	2462	21.28	-	-	21.28	30.00	2.4	23.68	36.00
HT20	3	2412	18.58	18.24	18.94	23.37	30.00	2.4	25.77	36.00
HT20	3	2437	23.92	23.52	22.98	28.26	30.00	2.4	30.66	36.00
HT20	3	2462	18.41	19.34	19.13	23.75	30.00	2.4	26.15	36.00
HT40	3	2422	13.85	14.21	14.80	19.08	30.00	2.4	21.48	36.00
HT40	3	2437	19.40	19.75	19.65	24.37	30.00	2.4	26.77	36.00
HT40	3	2452	17.82	18.27	18.13	22.85	30.00	2.4	25.25	36.00
Result			Complied							
Note : IEEE 802.11 n have the CDD function, so the array gain is 0.										

### 3.3.7 Test Result of Maximum Conducted Output Power

Maximum Conducted Output Power Result										
Condition			RF Output Power (dBm)							
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Chain Port 1	Chain Port 2	Chain Port 3	Sum Chain	Power Limit	DG (dBi)	EIRP Power	EIRP Limit
11b	1	2412	22.46	-	-	22.46	30.00	2.4	24.86	36.00
11b	1	2437	21.55	-	-	21.55	30.00	2.4	23.95	36.00
11b	1	2462	20.05	-	-	20.05	30.00	2.4	22.45	36.00
11g	1	2412	15.75	-	-	15.75	30.00	2.4	18.15	36.00
11g	1	2437	22.78	-	-	22.78	30.00	2.4	25.18	36.00
11g	1	2462	16.18	-	-	16.18	30.00	2.4	18.58	36.00
HT20	3	2412	13.17	12.82	13.54	17.95	30.00	2.4	20.35	36.00
HT20	3	2437	18.62	18.01	17.73	22.90	30.00	2.4	25.30	36.00
HT20	3	2462	13.05	13.81	13.69	18.30	30.00	2.4	20.70	36.00
HT40	3	2422	8.34	8.69	9.25	13.55	30.00	2.4	15.95	36.00
HT40	3	2437	13.84	14.24	14.11	18.84	30.00	2.4	21.24	36.00
HT40	3	2452	12.61	12.84	12.64	17.47	30.00	2.4	19.87	36.00
Result			Complied							
Note : IEEE 802.11 n have the CDD function, so the array gain is 0.										

## 2400-2483.5MHz - Worst RF Output Power Plots

11g [Port 1]



Note 1: RF Output Power Plots w/o Duty Factor

### 3.4 Power Spectral Density

#### 3.4.1 Power Spectral Density Limit

Power Spectral Density Limit	
<input checked="" type="checkbox"/>	Power Spectral Density (PSD) $\leq$ 8 dBm/3kHz


#### 3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.4.3 Test Procedures


Test Method	
<input checked="" type="checkbox"/>	Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 10.2 Method PKPSD (RBW=3-100kHz;detector=peak).. [duty cycle $\geq$ 98% or external video / power trigger]
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 10.3 Method AVGPS-1 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 10.4 Method AVGPS-1 Alt. (slow sweep speed) duty cycle < 98% and average over on/off periods with duty factor
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 10.5 Method AVGPS-2 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 10.6 Method AVGPS-2 Alt. (slow sweep speed)
<input checked="" type="checkbox"/>	For conducted measurement.
<input checked="" type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain port 1.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below:
<input checked="" type="checkbox"/>	Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the N <sub>TX</sub> output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input type="checkbox"/>	Option 2: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.

### 3.4.4 Test Setup



### 3.4.5 Test Result of Power Spectral Density


Power Spectral Density Result				
Condition			Power Spectral Density	
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Sum Chain (dBm/100kHz)	PSD Limit (dBm/3kHz)
11b	1	2412	-3.86	8
11b	1	2437	-3.10	8
11b	1	2462	-4.29	8
11g	1	2412	-14.20	8
11g	1	2437	-7.45	8
11g	1	2462	-13.82	8
HT20	3	2412	-9.47	8
HT20	3	2437	-5.12	8
HT20	3	2462	-10.05	8
HT40	3	2422	-16.23	8
HT40	3	2437	-10.95	8
HT40	3	2452	-11.43	8
Result			Complied	





### 3.5 Transmitter Bandedge Emissions

#### 3.5.1 Transmitter Radiated Bandedge Emissions Limit




#### 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.5.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	The average emission levels shall be measured in [duty cycle $\geq 98$ or duty factor].
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.2.2 bandedge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq 98\%$ )
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced VBW $\geq 1/T$ ).
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW $\geq 1/T$ , where T is pulse time.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/>	For the transmitter bandedge emissions shall be measured using following options below:
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 13.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.2 for band-edge testing and the test distance is 3m.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.3 for marker-delta method for band-edge measurements.
<input checked="" type="checkbox"/>	For radiated measurement, refer as FCC KDB 558074, clause 12.2.7.

### 3.5.4 Test Setup



### 3.5.5 Transmitter Radiated Bandedge Emissions

2400-2483.5MHz Transmitter Radiated Bandedge Emissions (Non-restricted Band)								
Modulation	N <sub>TX</sub>	Test Freq. (MHz)	In-band PSD [i] (dBuV/100kHz)	Freq. (MHz)	Out-band PSD [o] (dBuV/100kHz)	[i] – [o] (dB)	Limit (dB)	Pol.
11b	1	2412	111.52	2399.94	68.37	43.15	20	V
11b	1	2462	109.69	2521.90	51.43	58.26	20	V
11g	1	2412	101.90	2400.00	73.18	28.72	20	V
11g	1	2462	100.88	2510.60	51.49	49.39	20	V
HT20	3	2412	105.97	2400.00	74.62	31.35	20	V
HT20	3	2462	107.92	2519.90	52.19	55.73	20	V
HT40	3	2422	100.87	2400.00	70.30	30.57	20	V
HT40	3	2452	103.66	2507.12	51.86	51.80	20	V

Note 1: Measurement worst emissions of receive antenna polarization

2400-2483.5MHz Transmitter Radiated Bandedge Emissions (Restricted Band)										
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Measure Distance (m)	Freq. (MHz) PK	Level (dBuV/m) PK	Limit (dBuV/m) PK	Freq. (MHz) AV	Level (dBuV/m) AV	Limit (dBuV/m) AV	Pol.
11b	1	2412	3	2371.26	64.31	74	2389.07	51.66	54	V
11b	1	2462	3	2499.50	62.26	74	2500.00	47.73	54	V
11g	1	2412	3	2390.00	71.50	74	2390.00	51.09	54	V
11g	1	2462	3	2483.50	69.84	74	2483.50	48.20	54	V
HT20	3	2412	3	2390.00	70.59	74	2390.00	51.74	54	V
HT20	3	2462	3	2484.20	70.15	74	2483.50	50.59	54	V
HT40	3	2422	3	2389.46	72.52	74	2390.00	52.99	54	V
HT40	3	2452	3	2483.60	69.85	74	2483.50	52.17	54	V

Note 1: Measurement worst emissions of receive antenna polarization.

### 3.6 Transmitter Unwanted Emissions

#### 3.6.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

#### 3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

### 3.6.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input checked="" type="checkbox"/>	Measurements in the frequency range 10 GHz - 18GHz are typically made at a closer distance 1m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input checked="" type="checkbox"/>	Measurements in the frequency range above 18 GHz - 25GHz are typically made at a closer distance 0.5m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input checked="" type="checkbox"/>	The average emission levels shall be measured in [duty cycle $\geq$ 98 or duty factor].
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq$ 98%)
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced VBW $\geq$ 1/T).
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW $\geq$ 1/T, where T is pulse time.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 12.2.3 measurement procedure Quasi-Peak limit.
<input checked="" type="checkbox"/>	For radiated measurement, refer as FCC KDB 558074, clause 12.2.7.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1 GHz and test distance is 3m.


### 3.6.4 Test Setup

#### Transmitter Radiated Unwanted Emissions Below 1GHz



Magnetic field tests shall be performed in the frequency range of 9 kHz to 30 MHz using a calibrated loop antenna. Electric field tests shall be performed in the frequency range of 30 MHz to 1000 MHz using a calibrated bi-log antenna.

#### Transmitter Radiated Unwanted Emissions Above 1GHz




Electric field tests shall be performed in the frequency range of 1 GHz to 10th harmonic of highest fundamental frequency or 40 GHz using a calibrated horn antenna.

### 3.6.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


### 3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)





**Transmitter Radiated Unwanted Emissions (Below 1GHz)**

Operating Mode	3	Polarization	H
Operating Function	EUT with PoE		



	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp		Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @	30.000	28.26	-11.74	40.00	36.20	18.85	0.82	27.61 Peak	---	---
2	226.910	27.92	-18.08	46.00	42.14	10.21	2.48	26.91 Peak	---	---
3	299.660	27.74	-18.26	46.00	38.26	13.23	2.90	26.65 Peak	---	---
4 @	664.380	33.93	-12.07	46.00	38.72	18.76	4.41	27.96 Peak	---	---
5 @	741.980	34.57	-11.43	46.00	38.25	19.56	4.64	27.88 Peak	---	---
6 @	901.060	39.33	-6.67	46.00	41.16	20.53	5.19	27.55 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)



### 3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	11b	Test Freq. (MHz)	2412
N <sub>TX</sub>	1	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Rnt Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	51.10	-22.90	74.00	44.73	33.09	5.71	32.43	Peak	---	---
2	4824.000	42.31	-11.69	54.00	35.94	33.09	5.71	32.43	Average	---	---
3	7236.000	55.27			44.81	35.88	7.23	32.65	Peak	---	---
4	9648.000	56.69			42.66	38.34	8.79	33.10	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (113.78 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	11b	<b>Test Freq. (MHz)</b>	2412
<b>N<sub>TX</sub></b>	1	<b>Polarization</b>	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	52.37	-21.63	74.00	46.00	33.09	5.71	32.43	Peak	---	---
2	4824.000	45.30	-8.70	54.00	38.93	33.09	5.71	32.43	Average	---	---
3	7236.000	57.88			47.42	35.88	7.23	32.65	Peak	---	---
4	9648.000	56.88			42.85	38.34	8.79	33.10	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (113.78 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	11b	<b>Test Freq. (MHz)</b>	2437
<b>N<sub>TX</sub></b>	1	<b>Polarization</b>	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	51.41	-22.59	74.00	44.93	33.18	5.72	32.42	Peak	---	---
2	4874.000	41.14	-12.86	54.00	34.66	33.18	5.72	32.42	Average	---	---
3	7311.000	46.15	-7.85	54.00	35.49	36.04	7.28	32.66	Average	---	---
4	7311.000	56.59	-17.41	74.00	45.93	36.04	7.28	32.66	Peak	---	---
5	9748.000	55.20			40.94	38.57	8.77	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (113.46 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

### Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11b	Test Freq. (MHz)	2437
N <sub>TX</sub>	1	Polarization	H



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	4874.000	46.88	-7.12	54.00	40.40	33.18	5.72	32.42	Average	---	---
2	4874.000	53.28	-20.72	74.00	46.80	33.18	5.72	32.42	Peak	---	---
3 @	7311.000	49.40	-4.60	54.00	38.74	36.04	7.28	32.66	Average	---	---
4	7311.000	61.24	-12.76	74.00	50.58	36.04	7.28	32.66	Peak	---	---
5	9748.000	59.83			45.57	38.57	8.77	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (113.46 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11b	Test Freq. (MHz)	2462
N <sub>TX</sub>	1	Polarization	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4924.000	46.81	-27.19	74.00	40.20	33.28	5.74	32.41	Peak	---	---
2	4924.000	38.10	-15.90	54.00	31.49	33.28	5.74	32.41	Average	---	---
3	7386.000	44.04	-9.96	54.00	33.14	36.25	7.34	32.69	Average	---	---
4	7386.000	53.11	-20.89	74.00	42.21	36.25	7.34	32.69	Peak	---	---
5	9848.000	55.43			41.01	38.76	8.74	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (112.78 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	11b	<b>Test Freq. (MHz)</b>	2462
<b>N<sub>TX</sub></b>	1	<b>Polarization</b>	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4924.000	43.00	-11.00	54.00	36.39	33.28	5.74	32.41	Average	---	---
2	4924.000	51.35	-22.65	74.00	44.74	33.28	5.74	32.41	Peak	---	---
3	7386.000	51.75	-2.25	54.00	40.85	36.25	7.34	32.69	Average	---	---
4	7386.000	61.88	-12.12	74.00	50.98	36.25	7.34	32.69	Peak	---	---
5	9848.000	58.91			44.49	38.76	8.74	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (112.78 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	11g	<b>Test Freq. (MHz)</b>	2412
<b>N<sub>TX</sub></b>	1	<b>Polarization</b>	V



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	46.82	-27.18	74.00	40.45	33.09	5.71	32.43	Peak	---	---
2	4824.000	35.11	-18.89	54.00	28.74	33.09	5.71	32.43	Average	---	---
3	7236.000	51.21			40.75	35.88	7.23	32.65	Peak	---	---
4	9648.000	54.64			40.61	38.34	8.79	33.10	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (109.76 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	11g	<b>Test Freq. (MHz)</b>	2412
<b>N<sub>TX</sub></b>	1	<b>Polarization</b>	H



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	47.94	-26.06	74.00	41.57	33.09	5.71	32.43	Peak	---	---
2	4824.000	35.39	-18.61	54.00	29.02	33.09	5.71	32.43	Average	---	---
3	7236.000	51.27			40.81	35.88	7.23	32.65	Peak	---	---
4	9648.000	56.42			42.39	38.34	8.79	33.10	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (109.76 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



### Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11g	Test Freq. (MHz)	2437
N <sub>TX</sub>	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	48.65	-25.35	74.00	42.17	33.18	5.72	32.42	Peak	---	---
2	4874.000	37.49	-16.51	54.00	31.01	33.18	5.72	32.42	Average	---	---
3	7311.000	47.83	-6.17	54.00	37.17	36.04	7.28	32.66	Average	---	---
4	7311.000	60.51	-13.49	74.00	49.85	36.04	7.28	32.66	Peak	---	---
5	9748.000	55.09			40.83	38.57	8.77	33.08	Peak	---	---

- Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (117.81 dBuV/m).  
 Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

### Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11g	Test Freq. (MHz)	2437
N <sub>TX</sub>	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	54.88	-19.12	74.00	48.40	33.18	5.72	32.42	Peak	---	---
2	4874.000	44.35	-9.65	54.00	37.87	33.18	5.72	32.42	Average	---	---
3	7311.000	65.16	-8.84	74.00	54.50	36.04	7.28	32.66	Peak	---	---
4	7311.000	52.89	-1.11	54.00	42.23	36.04	7.28	32.66	Average	---	---
5	9748.000	56.22			41.96	38.57	8.77	33.08	Peak	---	---

- Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (117.81 dBuV/m).  
 Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	11g	<b>Test Freq. (MHz)</b>	2462
<b>N<sub>TX</sub></b>	1	<b>Polarization</b>	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4924.000	46.44	-27.56	74.00	39.83	33.28	5.74	32.41	Peak	---	---
2	4924.000	34.41	-19.59	54.00	27.80	33.28	5.74	32.41	Average	---	---
3	7386.000	39.66	-14.34	54.00	28.76	36.25	7.34	32.69	Average	---	---
4	7386.000	51.29	-22.71	74.00	40.39	36.25	7.34	32.69	Peak	---	---
5	9848.000	54.95			40.53	38.76	8.74	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (109.11 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	11g	<b>Test Freq. (MHz)</b>	2462
<b>N<sub>TX</sub></b>	1	<b>Polarization</b>	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4924.000	46.54	-27.46	74.00	39.93	33.28	5.74	32.41	Peak	---	---
2	4924.000	34.77	-19.23	54.00	28.16	33.28	5.74	32.41	Average	---	---
3	7386.000	40.08	-13.92	54.00	29.18	36.25	7.34	32.69	Average	---	---
4	7386.000	53.81	-20.19	74.00	42.91	36.25	7.34	32.69	Peak	---	---
5	9848.000	54.40			39.98	38.76	8.74	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (109.11 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	HT20	<b>Test Freq. (MHz)</b>	2412
<b>N<sub>TX</sub></b>	3	<b>Polarization</b>	V



	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp		Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4824.000	47.26	-26.74	74.00	40.89	33.09	5.71	32.43	Peak	---
2	4824.000	34.42	-19.58	54.00	28.05	33.09	5.71	32.43	Average	---
3	7236.000	51.21			40.75	35.88	7.23	32.65	Peak	---
4	9648.000	54.94			40.91	38.34	8.79	33.10	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (113.36 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	HT20	<b>Test Freq. (MHz)</b>	2412
<b>N<sub>TX</sub></b>	3	<b>Polarization</b>	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	47.88	-26.12	74.00	41.51	33.09	5.71	32.43	Peak	---	---
2	4824.000	35.01	-18.99	54.00	28.64	33.09	5.71	32.43	Average	---	---
3	7236.000	52.40			41.94	35.88	7.23	32.65	Peak	---	---
4	9648.000	55.34			41.31	38.34	8.79	33.10	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (113.36 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

### Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2437
N <sub>TX</sub>	3	Polarization	V



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	54.31	-19.69	74.00	47.83	33.18	5.72	32.42	Peak	---	---
2	4874.000	40.43	-13.57	54.00	33.95	33.18	5.72	32.42	Average	---	---
3	7311.000	58.54	-15.46	74.00	47.88	36.04	7.28	32.66	Peak	---	---
4	7311.000	43.04	-10.96	54.00	32.38	36.04	7.28	32.66	Average	---	---
5	9748.000	54.10			39.84	38.57	8.77	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (119.96 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2437
N <sub>TX</sub>	3	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	53.18	-20.82	74.00	46.70	33.18	5.72	32.42	Peak	---	---
2	4874.000	39.61	-14.39	54.00	33.13	33.18	5.72	32.42	Average	---	---
3	7311.000	45.34	-8.66	54.00	34.68	36.04	7.28	32.66	Average	---	---
4	7311.000	61.67	-12.33	74.00	51.01	36.04	7.28	32.66	Peak	---	---
5	9748.000	55.14			40.88	38.57	8.77	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level 119.96 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	HT20	<b>Test Freq. (MHz)</b>	2462
<b>N<sub>TX</sub></b>	3	<b>Polarization</b>	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4924.000	48.90	-25.10	74.00	42.29	33.28	5.74	32.41	Peak	---	---
2	4924.000	37.60	-16.40	54.00	30.99	33.28	5.74	32.41	Average	---	---
3	7386.000	40.02	-13.98	54.00	29.12	36.25	7.34	32.69	Average	---	---
4	7386.000	50.80	-23.20	74.00	39.90	36.25	7.34	32.69	Peak	---	---
5	9848.000	54.82			40.40	38.76	8.74	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (115.90 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	HT20	<b>Test Freq. (MHz)</b>	2462
<b>N<sub>TX</sub></b>	3	<b>Polarization</b>	H



	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp		Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4924.000	46.52	-27.48	74.00	39.91	33.28	5.74	32.41	Peak	---	---
2	4924.000	35.91	-18.09	54.00	29.30	33.28	5.74	32.41	Average	---	---
3	7386.000	50.98	-23.02	74.00	40.08	36.25	7.34	32.69	Peak	---	---
4	7386.000	40.13	-13.87	54.00	29.23	36.25	7.34	32.69	Average	---	---
5	9848.000	55.00			40.58	38.76	8.74	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (115.90 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	HT40	<b>Test Freq. (MHz)</b>	2422
<b>N<sub>TX</sub></b>	3	<b>Polarization</b>	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	Remark	Rnt Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4844.000	46.67	-27.33	74.00	40.26	33.12	5.72	32.43 Peak	---	---
2	4844.000	33.70	-20.30	54.00	27.29	33.12	5.72	32.43 Average	---	---
3	7266.000	52.47	-21.53	74.00	41.92	35.96	7.25	32.66 Peak	---	---
4	7266.000	38.04	-15.96	54.00	27.49	35.96	7.25	32.66 Average	---	---
5	9688.000	55.79			41.68	38.42	8.78	33.09 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (109.05 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

### Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	2422
N <sub>TX</sub>	3	Polarization	H



	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp		Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4844.000	33.55	-20.45	54.00	27.14	33.12	5.72	32.43	Average	---	---
2	4844.000	46.78	-27.22	74.00	40.37	33.12	5.72	32.43	Peak	---	---
3	7266.000	37.91	-16.09	54.00	27.36	35.96	7.25	32.66	Average	---	---
4	7266.000	51.39	-22.61	74.00	40.84	35.96	7.25	32.66	Peak	---	---
5	9688.000	55.81			41.70	38.42	8.78	33.09	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (109.05 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	HT40	<b>Test Freq. (MHz)</b>	2437
<b>N<sub>TX</sub></b>	3	<b>Polarization</b>	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	36.01	-17.99	54.00	29.53	33.18	5.72	32.42	Average	---	---
2	4874.000	48.77	-25.23	74.00	42.29	33.18	5.72	32.42	Peak	---	---
3	7311.000	37.98	-16.02	54.00	27.32	36.04	7.28	32.66	Average	---	---
4	7311.000	51.38	-22.62	74.00	40.72	36.04	7.28	32.66	Peak	---	---
5	9748.000	56.46			42.20	38.57	8.77	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (112.69 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	HT40	<b>Test Freq. (MHz)</b>	2437
<b>N<sub>TX</sub></b>	3	<b>Polarization</b>	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	47.05	-26.95	74.00	40.57	33.18	5.72	32.42	Peak	---	---
2	4874.000	34.30	-19.70	54.00	27.82	33.18	5.72	32.42	Average	---	---
3	7311.000	51.79	-22.21	74.00	41.13	36.04	7.28	32.66	Peak	---	---
4	7311.000	38.34	-15.66	54.00	27.68	36.04	7.28	32.66	Average	---	---
5	9748.000	55.85			41.59	38.57	8.77	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (112.69 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	HT40	<b>Test Freq. (MHz)</b>	2452
<b>N<sub>TX</sub></b>	3	<b>Polarization</b>	V



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4904.000	47.69	-26.31	74.00	41.14	33.24	5.73	32.42	Peak	---	---
2	4904.000	35.08	-18.92	54.00	28.53	33.24	5.73	32.42	Average	---	---
3	7356.000	51.57	-22.43	74.00	40.77	36.17	7.31	32.68	Peak	---	---
4	7356.000	38.17	-15.83	54.00	27.37	36.17	7.31	32.68	Average	---	---
5	9808.000	55.97			41.62	38.68	8.75	33.08	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (109.04 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

<b>Modulation Mode</b>	HT40	<b>Test Freq. (MHz)</b>	2452
<b>N<sub>TX</sub></b>	3	<b>Polarization</b>	H



	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp		Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4904.000	33.80	-20.20	54.00	27.25	33.24	5.73	32.42	Average	---
2	4904.000	47.21	-26.79	74.00	40.66	33.24	5.73	32.42	Peak	---
3	7356.000	38.17	-15.83	54.00	27.37	36.17	7.31	32.68	Average	---
4	7356.000	51.77	-22.23	74.00	40.97	36.17	7.31	32.68	Peak	---
5	9808.000	55.87			41.52	38.68	8.75	33.08	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (109.04 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## 4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Mar. 26, 2014	AC Conduction
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	Jan. 21, 2014	AC Conduction
RF Cable-CON	HUBER+SUHNER	RG213/U	7.61183201e+012	9kHz ~ 30MHz	Oct. 30, 2013	AC Conduction
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	AC Conduction

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSV 40	101013	9KHz~40GHz	Jan. 25, 2014	RF Conducted
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Jun. 27, 2013	RF Conducted
AC Power Source	G.W	APS-9102	EL920581	AC 0V ~ 300V	Jul. 16, 2013	RF Conducted
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	-20 ~ 100℃	Nov. 21, 2013	RF Conducted
RF Cable-2m	HUBER+SUHNER	SUCOFLEX_104	SN 345673/4	30MHz ~ 26.5GHz	Dec. 02, 2013	RF Conducted
RF Cable-0.5m	HUBER+SUHNER	SUCOFLEX_103	10715/4 10716/4	30MHz ~ 26.5GHz	Dec. 02, 2013	RF Conducted

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz ~ 1GHz 3m	Nov. 30, 2013	Radiated Emission
Amplifier	HP	8447D	2944A08033	10kHz ~ 1.3GHz	May 03, 2013	Radiated Emission
Amplifier	Agilent	8449B	3008A02120	1GHz ~ 26.5GHz	Aug. 20, 2013	Radiated Emission
Spectrum	R&S	FSP40	100004	9kHz ~ 40GHz	Mar. 27, 2014	Radiated Emission
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30MHz ~ 1GHz	Sep. 21, 2013	Radiated Emission
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 31, 2013	Radiated Emission
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz ~ 40GHz	Jan. 10, 2014	Radiated Emission
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz ~ 1GHz	Nov. 16, 2013	Radiated Emission
RF Cable-high	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz ~ 40GHz	Dec. 11, 2013	Radiated Emission
Turn Table	EM Electronics	EM Electronics	060615	0 ~ 360 degree	N/A	Radiated Emission
Antenna Mast	MF	MF-7802	MF780208179	1 ~ 4 m	N/A	Radiated Emission

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	TESEQ	HLA 6120	31244	9kHz ~ 30MHz	Dec. 02, 2012	Radiated Emission

Note: Calibration Interval of instruments listed above is two year.